Type-model Processo	r MHz	Memory	Screen	Disk	CD or DVD drive	Comm Bay	Preload	Available	
2662-41U Pentium® 2662-61U Pentium I 2662-62U Pentium I 2662-64U Pentium I 2662-65U Pentium I 2662-66U Pentium I 2662-67U Pentium I 2662-6MU Pentium I 2662-6NU Pentium I 2662-6HU Pentium I	600 700 700 700 700 700 700 700 700 700	64MB 128MB 128MB 128MB 128MB 128MB 128MB 128MB 128MB 128MB	12.1" SVGA 12.1" XGA 12.1" XGA 12.1" XGA 12.1" XGA 12.1" XGA 12.1" XGA 12.1" XGA 12.1" XGA	10GB 20GB 20GB 20GB 20GB 20GB 20GB 20GB 2	option via UltraBase X2 or Dock	modem modem Intel® eth/mod Intel eth/mod 3Com® eth/mo 3Com eth/mo Intel eth/mod Intel eth/mod	98 SE 2000 98 SE 2000 98 SE 2000 od 98 SE d 2000 98 SE, Office 2000 SB 2000, Office XP SB	Apr 2001 Apr 2001	
Processor Intel® Mobile Pentium® III 600MHz with Intel SpeedStep™ technology and 100MHz system bus							WINDOWS 98 PRELO		
L2 cache								- Microsoft® Windows® 98 Second Edition	
Memory							- Some: Microsoft Office 2000 Small Business (Word, Excel, Outlook, Publisher, Small Business Tools) • ThinkPad Utilities • ThinkPad Assistant™ • Universal Manageability Srvs (web) • ConfigSafe® • IBM Update Connector™.15 • Access ThinkPad II • PC-Doctor™ • SystemSoft Card Wizard Lotus SmartSuite Millennium and Lotus Notes Client 5.0 license		
Diskette drive CD or DVD-ROM UltraBay™ 2000	None standard / 3.5" 1.44MB integrated in optional UltraBase X2 media slice None standard / optional CD or DVD-ROM removable from optional UltraBase X2 Modular bay for interchangeable devices / support for UltraBay™ 2000 devices in optional UltraBase X2 media slice or ThinkPad Dock								
Disk	10GB* or 20GB / user upgradeable / S.M.A.R.T. / ATA-66								
Graphics controller Graphics - external	12.1" (308mm) SVGA (800x600) TFT color / Active Matrix / 125 nits or 12.1" (308mm) XGA (1024x768) TFT color / Active Matrix / 150 nits ATI™ Rage™ Mobility M / AGP 2X / 4MB SGRAM / DDC2B External SVGA to 1024x768x16.7 million colors at 75Hz and up to 1600x1200								
Keyboard Standard-size ²⁶ keys / 97% size of T Series / pitch: 18.5mm / stroke: 2.5mm /							♦ Some: Office 2000 Small Bus CD		
ThinkLight™ UltraPort™	ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar Illuminates the keyboard to improve visibility in low-light conditions UltraPort connector on top of display for options such as digital UltraPort Camera						♦ Disk-to-Disk Recovery (in hidden Service Partition)		
Dimensions ³ Travel weight ² Case material Battery - type Battery - life ¹⁰	4xx: 11" x 8.9" x .94"-1.1"; 279mm x 227mm x 23.8-27.9mm Others: 11" x 8.9" x .98"-1.2"; 279mm x 227mm x 24.9-30.5mm 4xx: 3.1 lbs Others: 3.5 lbs Titanium Composite in the top cover for enhanced strength ⁴ 4xx: Lithium Ion 4-cell / intelligent 4xx: 2.8 hrs 61U/62U: 4.9 hrs Others: 4.8 hrs						WINDOWS 2000 PRELOAD ^{14, 27} Microsoft Windows 2000 Professional Some: Microsoft Office 2000 or XP Small Business ²⁸ The Market Profession Pro		
Architecture					(EIDE with Ultra DMA/33 or PIO M	ode 4	ThinkPad UtilitiesThinkPad Assistant		
Port replicator Media slice	support, ISA Bridge, USB) / Ricoh® RŜC476II CardBus controller for PC Card and Compact Flash / AGP 2X for graphics / PCI 2.1 / 32-bit / 33MHz (EIDE, CardBus, audio, USB, ext expansion) / PC97338 Super I/O / ISA (diskette, serial, parallel, infrared, ext exp) Optional ThinkPad Port Replicator Optional UltraBase X2 media slice (see right side)						Universal Manageability Srvs (web) ConfigSafe IBM Update Connector Access ThinkPad II PC-Doctor SystemSoft Card Wizard Lotus SmartSuite Millennium and Lotus Notes Client 5.0 license Some: Office 2000 Small Bus CD Some: Office XP Small Bus CD Disk-to-Disk Recovery (in hidden Service Partition)		
Docking Station Compact Flash slot PC Card Std slot Ports	Optional ThinkPad Dock (includes Ültrabay 2000 and half-size PCI slot) Compact Flash slot / 1 CF+ Type II / supports optional IBM Microdrive [™] One Type II / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video Two USB (Version 1.1) / external DB-15 monitor / RJ-11 (modem) / RJ-45 (ethernet) / no serial, parallel, keyboard, mouse or infrared ports None								
Video out Communicatns Bay Modem	Communications Bay with Mini PCI IIIb slot / customer accessible Some: 56K ⁶ V.90 Mini PCI modem card / Lucent [®] chip set Some: IBM 10/100 Ethernet Mini PCI Adapter with 56K Modem (3Com						ULTRABASE X2 MEDIA SLICE OPTION		
Ethernet/modem	ethernet chipset / 3Com modem chip set) Some: Intel PRO/100 SP Mobile Combo Adapter / Mini PCI ethernet with 56K modem / Intel 82550EY ethernet chipset / Lucent modem chipset					Left bay of UltraBase X2 supports most Ultrabay 2000 options: optional CD-ROM, CD-RW, DVD-ROM, LS-120 SuperDisk, Zip 250MB, CD-RW/DVD Combo optional HDD adapter; for 2nd disk			
Audio support	PCI audio / SoundBlaster Pro™ support / CS4281 with CS4297A AC97 codec / mono speaker / 0.5 watt / volume up, down, mute buttons / internal microphone / input jack (3.5 mm) / output jack (3.5 mm) / line in jack Power-on password / dual hard disk password / supervisor pwrd / security keyhole								
Security	3 year	- EasySe	rv™,19 onsite p	ickup a	nd delivery courier service	,	UltraBase X2 right bay conta		
Limited warranty*,12 Service options ²²	Optiona	al service	upgrades pro	ovide up	o to three ýears of onsite or depot re hase (including warranty period)	pair service	 standard diskette drive (no removable))L	
Communication Bay -IBM 10/100 EtherJu -56K Modem by 3Cc -Intel Pro/100 SP Mi -56K modem	et Mini Pom ni PCI A hangeal ay 2000 20) Ultrabay Ultrabay 2000 D 2000 oo Ultrab y ss LAN I	CI Adapter wood access Drive aBay 2000 Drive 2000 Drive bay 2000 I	er with 09N977 with 06P380 sories 27L344 0 27L345 ive 05K923 08K956 00N825 19K448 Drive 08K957	- 64 - 12 - 25 - 10 01 - 20 - 32 8 - Se 8 - Se 11 - 10 33 - Uli 39 - Th 100 - Th 101 - Th 104 - IB	MB SO DIMM 100MHz NP SDRAM 8MB SO DIMM 100MHz NP SDRAM 8MB SO DIMM 100MHz NP SDRAM 6MB SO DIMM 100MHz NP SDRAM 6MB HDD GB HD GB HDD GB HD GB HDD GB HD GB	M 20L0255 M 33L3069 08K9510 27L3439 08K9511	Other features • stereo speakers (1 watt) • security keyhole, UltraBas • Serial and parallel ports • Keyboard / mouse port 72 watt AC Adapter PC 99-compliant CIM and DMI 2.0-compliant Wired for Management (Wfl Local and remote asset man ment via the IBM Univers Manageability solutions IBM PC Lifecycle Care ²¹ Personalized Web-based si International Warranty Serv 24 hour x 7 day ¹⁸ toll-free ha	VI) 2.0 nage al upport ice ¹⁷	
* For a copy of IBM's S		A - 6 1 to-14 -		- Po	rtable DVD-ROM Drive	22P5282	support during the warrar	nty	