


# **OVERVIEW**



1. Smart card reader *	7. Side docking connector
2. USB 3.2 Gen 1 (Always On)	8. USB 3.2 Gen 1
3. Ethernet (RJ-45)	9. HDMI 2.0
4. Kensington Security Slot	10. Headphone / microphone combo jack (3.5mm)
5. USB-C 3.2 Gen 2	11. microSD card reader
6. USB-C 3.2 Gen 2	

## Notes:

- Ports with \* are only available on selected models
- Optional nano-SIM card slot on the rear side (not shown on the sample product above)
- The combination of 5, 6, and 7 is side docking connector



## **PERFORMANCE**

## **Processor**

### **Processor Family**

AMD Ryzen™ 5 / 7 Processor

#### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
AMD Ryzen 5 PRO 5650U	6	12	2.3GHz	4.2GHz	3MB L2 / 16MB L3	DDR4-3200	AMD Radeon™ Graphics
AMD Ryzen 7 PRO 5850U	8	16	1.9GHz	4.4GHz	4MB L2 / 16MB L3	DDR4-3200	AMD Radeon Graphics

## **Operating System**

## Operating System\*\*

- Windows® 11 Pro 64
- Windows 11 Home 64
- Windows 11 Home 64 Single Language
- Windows 11 DG Windows 10 Pro 64
- Windows 10 Pro 64
- Windows 10 Home 64
- Windows 10 Home 64 Single Language
- Fedora Linux
- Ubuntu Linux LTS
- No operating system

## **Graphics**

## **Graphics**

Graphics	Туре	Memory	Connector	Max Resolution	Key Features	Remark
AMD Radeon Graphics	Integrated	Shared	-	-	DirectX® 12	-

## **Monitor Support**

## **Monitor Support**

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and USB-C®)

- HDMI supports up to 4096x2160@60Hz
- USB-C supports up to 5120x2880@60Hz, DP mode via USB-C to DP dongle

## **Chipset**

#### Chipset

AMD SoC (System on Chip) platform

## Memory

#### Max Memory[1]

Up to 48GB (16GB soldered + 32GB SO-DIMM) DDR4-3200

#### **Memory Slots**

One memory soldered to systemboard, one DDR4 SO-DIMM slot, dual-channel capable

### **Memory Type**

DDR4-3200 non-ECC

#### Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

## **Storage**

Storage Support[1]

## ThinkPad P14s Gen 2 (AMD)



One drive, up to 2TB M.2 2280 SSD

#### **Storage Slot**

One M.2 2280 PCIe® Gen 3x4 slot, supports M.2 2242/2280 SSD

## Storage Type\*\*[2]

Disk Type	Interface	RPM	Offering	Security
M.2 2242 SSD	PCIe NVMe®, PCIe 3.0 x4	-	-	-
M.2 2280 SSD	PCIe NVMe, PCIe 4.0 x4 Performance	-	-	Opal2
M.2 2280 SSD	PCIe NVMe, PCIe x4	-	-	Opal2

#### Notes:

- 1. The storage capacity supported is based on the test results with current Lenovo storage offerings. The system may support larger storage as the technology develops.
- 2. PCIe x4 SSD may be PCIe 3.0 x4 or PCIe 4.0 x4 as substitution.

## **Removable Storage**

#### **Card Reader**

MicroSD card reader

### Multi-Media

#### **Audio Chip**

High Definition (HD) Audio, Realtek® ALC3287 codec

#### **Speakers**

Stereo speakers, 2W x2, Dolby® Audio™

#### Microphone

- · Dual array microphone, near-field
- · No microphone

#### Camera\*\*

- HD 720p, with privacy shutter, fixed focus
- IR & HD 720p hybrid, with privacy shutter, fixed focus
- No camera

### **Battery**

### **Battery**

Integrated Li-Polymer 50Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

## Max Battery Life[1]

MobileMark® 2018: 12.5 hr JEITA 2.0: 15.8 hr (idle, 150 nits)

## Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

## **Power Adapter**

## Power Adapter\*\*[1][2]

- 45W USB-C (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 45W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C slim (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- No power adapter

### Notes:



- 1. AC adapter offerings depend on the country.
- 2. No power adapter is for special bid only.

## **DESIGN**

## **Display**

## Display\*\*[1]

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	Key Features
14.0"	FHD (1920x1080)	None	IPS	300 nits	Anti- glare	16:9	700:1	45% NTSC	170°	DC dimming
14.0"	FHD (1920x1080)	None	IPS	400 nits	Anti- glare	16:9	800:1	72% NTSC	170°	Low power
14.0"	FHD (1920x1080)	Multi- touch	IPS	300 nits	Anti- glare	16:9	700:1	45% NTSC	170°	DC dimming
14.0"	FHD (1920x1080)	Multi- touch	IPS	500 nits	Anti- glare	16:9	1000:1	72% NTSC	170°	ThinkPad® Privacy Guard, DC dimming
14.0"	UHD (3840x2160)	None	IPS	500 nits	Anti- glare	16:9	1500:1	100% DCI-P3	170°	Dolby Vision™, DisplayHDR™ 400, DC dimming, X-Rite® FCC

### **Color Calibration**

- X-Rite Pantone® factory color calibration (UHD display)
- No color calibration

#### **Touchscreen**

- On-cell touch, supports 10-point touch
- Non-touch

#### Notes

1. California Electronic Waste Recycling Fee
In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product.
For more information, go to https://www.calrecycle.ca.gov/Electronics/Consumer

## **Input Device**

### Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls

## **Keyboard Backlight**

- · LED backlight
- Non-backlight

#### UltraNav™

TrackPoint® pointing device and Mylar® surface multi-touch touchpad

## **Mechanical**<sup>®</sup>

## Dimensions (WxDxH)

329 x 227 x 17.9 mm (12.95 x 8.94 x 0.70 inches)

## Weight

Models	Weight			
FHD Low Power / Privacy Guard models	1.46 kg (3.22 lbs)			
FHD touch models	1.55 kg (3.41 lbs)			
HD / FHD non-touch models	1.55 kg (3.41 lbs)			
UHD models	1.46 kg (3.23 lbs)			

## Case Color\*\*

Black

## ThinkPad P14s Gen 2 (AMD)



· Storm grey

#### Case Material\*\*

- Aluminium (top), PC + ABS / Talc15 + magnesium alloy (keyboard cover), PA / 50% GF (bottom)
- PPS / 50% GF (top), PC + ABS / Talc15 + magnesium alloy (keyboard cover), PA / 50% GF (bottom)

#### Notes:

1. The system dimensions and weight vary depending on configurations.

## CONNECTIVITY

## **Network**

#### **Ethernet**

Gigabit Ethernet, Realtek RTL8111H, supports Wake-on-LAN

### WLAN + Bluetooth®\*\*[1][2]

- Wi-Fi® 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1
- Mediatek Wi-Fi 6 MT7921, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1
- Realtek Wi-Fi 6 RTL8852AE, 802.11ax Dual Band 2x2 Wi-Fi + Bluetooth 5.1
- Qualcomm® QCNFA765, Wi-Fi 6E, 802.11ax Dual Band 2x2 Wi-Fi + Bluetooth 5.1, M.2 Card
- Intel® Wi-Fi 6 AX200, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1

#### WWAN\*\*

- Wireless WAN upgradable to 4G (with antenna ready)
- Quectel EM120R-GL, 4G LTE CAT12, M.2 card
- Quectel EM120R-GL, 4G LTE CAT12, M.2 card, with embedded eSIM functionality
- · No support

#### SIM Card

- Gemalto eSIM card (physical)
- No SIM card inbox

## NFC

- Near Field Communication
- No support

### Notes:

- 1. Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitation
- 2. Intel AX200 and Mediatek MT7921 are for special bid only.
  Intel Wi-Fi 6 full features might be limited by country-level restrictions.

## Ports<sup>[1]</sup>

## **Standard Ports**

- 2x USB 3.2 Gen 1 (one Always On)
- 2x USB-C 3.2 Gen 1 (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4)
- 1x HDMI 2.0
- 1x microSD card reader
- 1x Ethernet (RJ-45)
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Side docking connector

## Optional Ports\*\*\*

- 1x Smart card reader
- 1x Nano-SIM card slot (WWAN support models)

#### Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s



## **Docking**

## **Docking**

Various docking solutions supported via side docking connector, Thunderbolt or USB-C. For more compatible docking solutions, please visit <u>Docking for ThinkPad P14s Gen 2 (AMD)</u>

### **Monitor Cable**

## Monitor Cable\*\*\*

- Lenovo HDMI to VGA Monitor Adapter
- Lenovo USB-C to VGA Adapter
- Lenovo USB-C to DisplayPort Adapter
- No monitor cable

## **SECURITY & PRIVACY**

## **Security**

#### **Security Chip**

Discrete TPM 2.0, TCG certified

### **Physical Locks**

Kensington® Security Slot™, 3 x 7 mm

#### **Smart Card Reader**

- · Smart card reader
- · No smart card reader

## **Fingerprint Reader**

- Touch style fingerprint reader on palm rest, match-on-chip
- · No fingerprint reader

### **BIOS Security**

- Power-on password
- · Supervisor password
- NVMe password
- · Self-healing BIOS

### **Other Security**

- (Optional) Camera privacy shutter
- (Optional) IR camera for Windows Hello
- (Optional) Privacy Guard with Privacy Alert

## **MANAGEABILITY**

## **System Management**

## **System Management**

AMD Pro Manageability

# **SERVICE**

## Warranty

# Base Warranty\*\*[1]

- 1-year depot service
- 1-year depot with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) depot service
- · 3-year (1-yr battery) limited onsite service
- No base warranty

## Notes:

1. More information of warranty policy, please access https://pcsupport.lenovo.com/warranty



## **ENVIRONMENTAL**

## **Operating Environment**

### Temperature[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping packaging: -20 °C (-4 °F) to 60 °C (140 °F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

#### Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Altitude

Maximum altitude (without pressurization): 2438 m (8,000 ft)

#### Notes:

1. When you charge the battery, its temperature must be no lower than  $10^{\circ}\text{C}$  (50°F).

# **CERTIFICATIONS**

### **Green Certifications**

#### **Green Certifications**

- EPEAT™ Gold
- ENERGY STAR® 8.0
- RoHS compliant

### Other Certifications

#### Mil-Spec Test

MIL-STD-810H military test passed

#### **ISV Certifications**

#### ISV Certifications

Please visit www.thinkworkstations.com/isv-certifications/

- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Feature with \*\*\* means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
  responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
  WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
  OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
  disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
  you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.











