IBM® ThinkPad®:	765L 13.3" XGA TFT	
Processor type Processor upgrade L2 cache Removable diskette External FDD port Removable CD-ROM	**Pentium® MMX 166/66 MHz** (P55CLM) / 64 bit to L2 cache / 64 bit to memory None **256 KB** / write-back / direct mapped / 10 ns / synchronous pipelined burst 3.5" 1.44 MB ○ / use in UltraBay or attach externally via rear ext FDD port External FDD port (requires FDD External Attachment Kit 66G3618) None / **can upgrade to 4 x or 6 x or 8 x CD-ROM into UltraBay**	**WINDOWS 95 PRELOAD** - Microsoft Windows 95 OSR2 (FAT16) - Online User's Guide - ThinkPad Features - Diskette Factory 1. Lotus Organizer 2. CompuServ for Windows
Type - model (code) Preload (see side) Avail / withdrawn date Remv disk - size / ms Disk controller	9547-U9J **Windows 95 OSR2** June 1997 / July 1998 **3.0 GB** / 12 ms ○ / DMA Mode 2 or PIO Mode 4 (C: is 1.99 GB, D: is 885 MB) EIDE / busmaster / PCI 2.1 / supports two internal disks / SMART	3. Puma TranXit™ 4. NetFinity for Windows 95 5. Triton CoSession™ Host 6. IntelliLink Connect 7. IBM AntiVirus 8. IBM Internet Connection Services with
Display - size and type Display - techology	**13.3 inch XGA color / 640 x 480, 800 x 600 or 1024 x 768 / 65,536 siml colors** **Black Matrix TFT - active matrix** / 100 to 1 contrast ratio	Netscape Navigator web browser 9. Registration Mailer
Graphics - controller Graph - arch/data path Graphics - features Graphics - external	Trident™ CYBER9385 / 64 bit SVGA accelerator / **2 MB EDO DRAM** / 70 ns PCI 2.1 / 32 bit / DCI, DirectDraw, EnDIVE support Simultaneous LCD and CRT / 180 degree tilt External SVGA to 1280 x 1024 w/ 256 colors or 1024 x 768 w/ 65,536 colors	10. ThinkPad on the NET 11. America Online - Lotus SmartSuite 96 CD-ROM - Recovery CD-ROM with boot diskette - Windows 95 CD-ROM (no installation)
Memory - std / max Memory - sockets avail Memory - features	**32 MB** / 104 MB 1 socket available (1 socket uses 16 MB) 70 ns / non-parity / 3.3 volt / EDO / supports JEDEC 144 pin SO-DIMMs 8 MB in system; 8 MB on memory module with 2 SO-DIMM sockets Memory module under disk (not removable) and accessible by opening keyboard If use 64 MB SO-DIMM, the 8 MB on memory module is disabled via switch	
Keyboard / # of keys Keyboard slope Pointing / palm rest	Full size alp/num / 85 (8 Fn key functions) **Automated tilt up keyboard** (5.5 degrees) **TrackPoint III**™ / integrated palm rest / ext keyboard support (with option cable)	
Dimensions Weight	11.7 x 9.3 x 2.23" (243 cubic inches) 7.4 pounds (3.34 kg)	
Battery - type Battery - life (1 batt) Charge time - on / off	Lithium Ion / intelligent *(optional NiMH battery supported)* 2.1 hours (4.2 hours with 2 batteries) 2 to 3 hrs / 1.5 to 2.5 hrs	
Architecture Docking Station Port replicator PC Card Standard slots Serial / parallel ports Other features	ISA (audio, diskette, serial, parallel, infrared, ext expansion) PCI 2.1 / 32 bit / 33 MHz (EIDE, graphics, CardBus, ext expansion) Intel Mobile Triton 82430MX PCIset / TI PCI1130 for CardBus **SelectaDock I and II and III** Port Replicator I and II / **SelectaDock Base Model I** 2 Type I or 2 Type II or 1 Type III / **CardBus 32 bit PCI** / PCMCIA 2.1 compatible One 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional) APM-aware BIOS / AC Adapter 4 pin 3 prong (56 watts) / Selectable boot	ThinkPad 765L supported batteries: - 760 NiMH Battery (black) 41H9720 - Li-Ion Battery Pack II (gray) 29H9329 - Travel Quick Charger 85G1522 - Car Battery Adapter 49G2167
Video in/out MPEG decoder DSP function Data/fax modem Audio support Jacks Telephone Infrared ports	None None None None **16 bit audio chip / 20 voice MIDI FM synthesis / ESS1688** Int stereo speakers / .5 watt / slide volume control / internal microphone Input jack (3.5 mm) / output jack (3.5 mm) None **Infrared ports (front and back) /** IrDA 1.0 compatible / up to 115 kbs	*Liftable (pop-up) keyboard* **to access and remove diskette drive, 1st/2nd disk, and 1st/2nd battery, and other UltraBay options** ThinkPad 760 supported disks: - (360/750/755 IDE disks not supported) - 720 MB HDD II EIDE 12.5 mm 29H9383 - 810 MB HDD II EIDE 12.5 mm 29H9313 - 1.08 GB HDD II EIDE 12.5 mm 29H9319
Security	Power-on password / Hard disk password / Supervisor password / Locking device keyhole (Kensington™ cable lock) / Security latch for keyboard and DIMMS (requires Kensington) / PC Card lock / Personalization / Security Plate	- 1.2 GB (1.96"+ models) 17 mm 29H9325 - 1.4 GB HDD 3L EIDE 12.5 mm 69H8412 - 2.1 GB (1.96"+ models) 17 mm 69H8414
Warranty Service options	**3 year** - ThinkPad EasyServ (depot repair service) or carry-in On-site, M-F, 8-5, next bus day (71 cities) / Warranty extension to 5 years	- 3.0 GB (1.96"+ models) 17 mm 45H8789 - 5.1 GB (1.96"+ models) 17 mm 00K7902

The left bay (UltraBay™) supports:
① 2nd disk (requires Second HDD Adapter)
② 2nd battery
③ Standard diskette drive
④ 2.88 MB diskette drive
⑤ CD-ROM
 	
Maximum internal disk capacity on 765L is 10.2 GB with two 5.1 GB disks
 	
Easy-Setup is entered by holding F1 when turning on.
 	
810 MB = DMA Mode 2 or PIO Mode 4
1.08 GB = DMA Mode 2 or PIO Mode 4
1.2 GB   = DMA Mode 1 or PIO Mode 3
1.35 GB = DMA Mode 2 or PIO Mode 4
2.1 GB   = DMA Mode 2 or PIO Mode 4
3.0 GB   = DMA Mode 2 or PIO Mode 4
5.1 GB   = Ultra DMA/33 or PIO Mode 4
	- Second HDD Adapter 29H9333
	- IDE Conversion Card (for Dock II) 46H5994
	- **SelectaDock I** **3547001**
	- **SelectaDock II** **3547002**
	- **SelectaDock III** **3547003**
	- Port Replicator I (w/ PCMCIA slots) 66G3510
	- Port Replicator II 66G3520
	- **SelectaDock Base Model I** **39H7405**
	- 2.88 MB diskette 66G0108
	- FDD External Attachment Kit 66G3618
	- 56 watt AC Adapter (4 pin; 3 prong) 12J2456
	- **6 x CD-ROM** (UltraBay) **85G1957**
	- **8 x CD-ROM** (UltraBay) **45H8786**
	- **8-20 x CD-ROM** (UltraBay) **00K7903**
	- **8 MB SO DIMM 3.3v NP EDO 64 bit** **92G7340**
	- **16 MB SO DIMM 3.3v NP EDO 64 bit** **92G7341**
	- **16 MB SO DIMM NP EDO 64 bit (new)** **01K1124**
	- **32 MB SO DIMM 3.3v NP EDO 64 bit** **92G7342**
	- **64 MB SO DIMM 3.3v NP EDO 64 bit** **76H0268**
	- PCMCIA 33.6 Kbps modem w/ XJACK 55H6759
	- 56K PC Card Modem Kit 04K0052
		FEATURES OF 765 MODELS
		Quick Setup Guide (single page)
		LCD indicator panel
		Plug and Play 1.0a
		Discharge battery via mouse click
		Non-disruptive battery exchange
		Standby, suspend, safe suspend,and
		  hibernation modes
		US EPA Energy Star compliant
		Personalized nameplate in indention
		Personalization screen at startup
		International Warranty Service
		IBM System Care Program
		**24 hour / 7 day telephone, bulletin
		  board, fax, electronic, and Internet
		  (http://www.pc.ibm.com) support**
		IBM and dealer warranty/service
		Online Housecall (remote diagnostics)

ThinkPad EasyServ™: customer calls 1-800-772-2227, courier service picks up ThinkPad at any location, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround).
○ = Removable