

IBM ThinkPad 760LD - withdrawn

IBM® ThinkPad®: ≈ 760LD 10.4" TFT color - CD-ROM		ThinkPad 760LD strengths: <ul style="list-style-type: none"> Removable, 4 x speed, 5.25" CD-ROM Automated tilt up keyboard / palm rest space UltraBay: 2nd disk, 2nd battery, diskette Two high speed infrared ports Integrated audio / speakers / microphone 16.7 million simultaneous color LCD 	
Processor type Processor upgrade L2 cache Removable diskette Removable CD-ROM	Pentium® 90/60 MHz (P54LM) / 64 bit to L2 cache / 32 bit to memory to Pentium 120/60 MHz 256 KB / write-through / direct mapped / 10 ns / synchronous / soldered 3.5" 1.44 MB ○ / use in UltraBay or attach externally to FDD attach port 5.25" CD-ROM ○ / 4 x speed / multi-session / XA / play with eject button EIDE / PIO Mode 3 (ATAPI)		
Price Type - model (part) Preload (see side) Avail / withdrawn date Remv disk - size / ms	9547-U31(9547U31) SelectaSystem Feb 96 / Oct 96 810 MB / 12 ms / EIDE ○ / PIO Mode 4	9547-U3A (9547U3A) Windows 95 Feb 96 / Oct 96	Pallete of 24 systems 9547-U3R (9547U3R) Blank Feb 96 / Oct 96
Display - diagonal size Display - type Display - technology	10.4 inch VGA color / 640 x 480 / 16.7 million simultaneous colors Black Matrix TFT - active matrix / 100 to 1 contrast ratio		The left bay (UltraBay™) supports: ① 2nd disk ② 2nd battery ③ std diskette drive ④ std CD-ROM ⑤ 2.88 MB diskette (option) ⑥ PCMCIA Cartridge (option) ⑦ IBM Wireless Modem ARDIS (option) ⑧ IBM Wireless Modem for Cellular/ CDPD (option)
Graphics - controller Graphics - external Graph - arch/data path	Tridentä CYBER9320 with 1 MB DRAM External SVGA to 1024 x 768 w/ 256 colors up to 75 Hz VL-Bus 2.0 local bus / 32 bit / Simultaneous LCD and CRT / 180 degree tilt		
Memory - std / max Memory - upgrade	8 MB / 64 MB 70 ns / non-parity / 3.3 volt / fast page 2 sockets for two JEDEC 88 pin EDO SO DIMMs of 8 or 16 MB (acts like fast page)		
Keyboard / # of keys Keyboard slope Pointing / palm rest Ext keyboard support	Full size alp/num / 85 (8 Fn key functions) Automated tilt up keyboard (5.5 degrees) TrackPoint III™ / integrated palm rest Yes (with option cable)		
Dimensions Weight (with CD-ROM)	11.7 x 8.3 x 1.96" (190 cubic inches) 7.11 pounds		
Battery - type Battery - life (1 batt) Battery - life (2 batt) Charge time - on / off	NiMH / intelligent 3 hours 6 hours 1.7 hrs / 1.2 hrs	<i>Optional</i> <i>Lithium Ion</i>	Liftable (pop-up) keyboard to access and remove CD-ROM, diskette drive, 1st/2nd disk, and 1st/2nd battery Exceeds MPC2 standard
Architecture Docking Station Port replicator PCMCIA™ 2.1 slots Serial / parallel ports Other features	ISA (EIDE, audio, PCMCIA, diskette, serial, parallel, ext expansion) VL-Bus 2.0 / 32 bit / 33 Mhz (graphics) Dock I and II Port Replicator I and II 2 Type I or 2 Type II or 1 Type III One 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional) APM-aware BIOS / Universal adapter (40 watts) / Selectable boot		
Motion video accel MPEG decoder DSP function Data/fax modem Audio support	None None None None 16 bit audio chip / 18 voice MIDI FM synthesis / ESS1688 Int stereo speakers / .5 watt / slide volume control / internal microphone Input jack (3.5 mm) / Output jack (3.5 mm)		
Jacks Telephone Infrared ports	None None Infrared ports (front and back) / IrDA 1.0 compatible / up to 115 kbs		
Security	Power-on password / Hard disk password / Supervisor password / Locking device keyhole (Kensington™ MicroSaver™ cable lock) / Security latch for keyboard and DIMMS (requires Kensington) / PC Card lock		
Preinstalled software Warranty	Choice of two preload configurations (listed to right) 3 year - ThinkPad EasyServ (optional Overnight Repair Option) or carry-in		
Differences between 760L/LD and 760C/CD:		Compatible in ThinkPad 760 family:	
760L/LD Pentium 90/60 MHz All 10.4" TFT VGA 640 x 480 LCD 16.7 mil colors on LCD None None None None 18 voice FM synthesis NiMH battery Type is 9547	760C/CD Pentium 120/60 or 90/60 10.4" or 12.1" TFT SVGA 800 x 600 LCD 65,536 colors on LCD 760CD: Enh. Vid Card 760CD: MPEG decoder Mwave DSP 28.8 modem / DSVD 32 voice wavetable syn. Li-Ion battery Type is 9546	- Disks: (360/750/755 IDE disks not supported) 720 MB HDD II EIDE 12.5 mm 29H9383 810 MB HDD II EIDE 12.5 mm 29H9313 1.08 GB HDD II EIDE 12.5 mm 29H9319 1.2 GB HDD II (LD/CD only) 17 mm 29H9325 - Second HDD Adapter 29H9333 - Dock I (1 slot / 1 bay) 3545001 - Dock II (2 slot / 2 bay) 3546001 - Port Replicator I (w/ PCMCIA) 66G3510 - Port Replicator II 66G3520 - 2.88 MB diskette 66G0108 - PCMCIA Cartridge 84G1301 - 760 NiMH Battery (black) 41H9720 - Li-Ion Battery Pack II (gray) 29H9329 - Travel Quick Charger 85G1522 - FDD External Attachment Kit 66G3618 - Pentium 120/60 MHz upgrade 29H9340 - Car Battery Adapter 49G2167 - ThinkPad AC Adapter (50 watts) 66G3541 - 8 MB SO DIMM 3.3v non-parity EDO 92G7315 - 16 MB SO DIMM 3.3v non-parity EDO 92G7316 - ThinkPad headset 85G1301	
All 760 systems support the NiMH or Li-Ion battery in both battery bay and UltraBay. Maximum internal disk capacity on 760LD is 2.4 GB with two 1.2 GB disks.		Easy-Setup is entered by holding F1 when turning on.	
		FEATURES OF 760 MODELS Product Map; LCD indicator panel Plug and Play 1.0a Discharge battery via mouse click Non-disruptive battery exchange Standby, suspend, and hibernation modes US EPA Energy Star compliant Personalized nameplate in indentation Personalization screen at startup International Warranty Service 24 hour / 7 day telephone, bulletin board, fax, electronic, and Internet (http://www.pc.ibm.com) support IBM and dealer warranty/service Online Housecall (remote diagnostics)	

ThinkPad EasyServ™: customer calls 1-800-772-2227, courier service picks up ThinkPad at any location, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround). Overnight repair option in US available for \$99.
○ = Removable

All trademarks are the property of their respective owners
No warranties are expressed or implied in this summary
(760LD) Compiled by Roger Dodson, IBM. October 1996