

# IBM ThinkPad 760L - withdrawn

<b>IBM® ThinkPad®:</b> ≈ 760L 10.4" TFT color				<b>ThinkPad 760L strengths:</b> ⬢ Automated tilt up keyboard / palm rest space ⬢ UltraBay: 2nd disk, 2nd battery, diskette ⬢ Two high speed infrared ports ⬢ Integrated audio / speakers / microphone ⬢ 16.7 million simultaneous color LCD																																															
Processor type <b>Pentium® (P54LM)</b> / 64 bit to L2 cache / 32 bit to memory Processor speed <b>90/60 MHz</b> Processor upgrade    to Pentium 120/60 MHz L2 cache    256 KB / write-through / direct mapped / 10 ns / synchronous / soldered Removable diskette    Internal 3.5" 1.44 MB ○ / no rear connector for diskette drive Removable CD-ROM    None (diskette bay is called UltraBay™) - cannot install an int CD-ROM				Differences between 760L and 760LD:																																															
<table><tr><td>Price</td><td></td><td></td><td></td><td>Palette of 24 systems</td></tr><tr><td>Type - model</td><td>9547-U01</td><td>9547-U0A</td><td></td><td>9547-U0R</td></tr><tr><td>Preload (see side)</td><td>SelectaSys</td><td>Windows 95</td><td></td><td>Blank</td></tr><tr><td>Part number</td><td>9547U01</td><td>9547U0A</td><td></td><td>9547U0R</td></tr><tr><td>Avail / withdrawn date</td><td>Feb 96 / Oct 96</td><td>Feb 96 / Oct 96</td><td></td><td>Feb 96 / Oct 96</td></tr><tr><td>Remv disk - size / ms</td><td><b>810 MB</b> / 13 ms / EIDE○</td><td></td><td></td><td></td></tr></table>				Price				Palette of 24 systems	Type - model	9547-U01	9547-U0A		9547-U0R	Preload (see side)	SelectaSys	Windows 95		Blank	Part number	9547U01	9547U0A		9547U0R	Avail / withdrawn date	Feb 96 / Oct 96	Feb 96 / Oct 96		Feb 96 / Oct 96	Remv disk - size / ms	<b>810 MB</b> / 13 ms / EIDE○				<table><tr><td><b>760L</b></td><td><b>760LD</b></td></tr><tr><td>No internal CD-ROM</td><td>Removable CD-ROM</td></tr><tr><td>1.74" height</td><td>1.96" height</td></tr><tr><td>6.5 lbs / 169 cu in</td><td>7.11 lbs / 190 cu in</td></tr><tr><td>Supports 12 mm disks</td><td>Supports 1.2 GB disks</td></tr><tr><td>2.16 GB max capacity</td><td>2.4 GB max capacity</td></tr><tr><td>No ext FDD port</td><td>Ext. FDD port on back</td></tr><tr><td>Price</td><td>Price</td></tr></table>		<b>760L</b>	<b>760LD</b>	No internal CD-ROM	Removable CD-ROM	1.74" height	1.96" height	6.5 lbs / 169 cu in	7.11 lbs / 190 cu in	Supports 12 mm disks	Supports 1.2 GB disks	2.16 GB max capacity	2.4 GB max capacity	No ext FDD port	Ext. FDD port on back	Price	Price
Price				Palette of 24 systems																																															
Type - model	9547-U01	9547-U0A		9547-U0R																																															
Preload (see side)	SelectaSys	Windows 95		Blank																																															
Part number	9547U01	9547U0A		9547U0R																																															
Avail / withdrawn date	Feb 96 / Oct 96	Feb 96 / Oct 96		Feb 96 / Oct 96																																															
Remv disk - size / ms	<b>810 MB</b> / 13 ms / EIDE○																																																		
<b>760L</b>	<b>760LD</b>																																																		
No internal CD-ROM	Removable CD-ROM																																																		
1.74" height	1.96" height																																																		
6.5 lbs / 169 cu in	7.11 lbs / 190 cu in																																																		
Supports 12 mm disks	Supports 1.2 GB disks																																																		
2.16 GB max capacity	2.4 GB max capacity																																																		
No ext FDD port	Ext. FDD port on back																																																		
Price	Price																																																		
Display - diagonal size <b>10.4 inch</b> Display - type <b>VGA color / 640 x 480 / 16.7 million simultaneous colors</b> Display - technology <b>Black Matrix TFT - active matrix</b> / 100 to 1 contrast ratio				<b>SELECTASYSTEM PRELOAD</b> <ul style="list-style-type: none"><li>- IBM DOS 7.0</li><li>- Windows 3.11</li><li>- OS/2 Warp 3.0 (dual boot) w/ selected BonusPak</li><li>- IBM PC Card Director™ 3.0</li><li>- Online Users Guide</li><li>- ThinkPad Features Program</li><li>- Diskette Factory</li><li>1. Triton CoSession™ Host</li><li>2. PRODIGY®</li><li>3. SofNet FaxWorks™</li><li>4. Video For Windows™ 1.1 Runtime</li><li>5. Puma TranXit™</li><li>6. CompuServ for Windows</li><li>7. NetFinity for Windows and OS/2</li></ul> <b>WINDOWS 95 PRELOAD</b> <ul style="list-style-type: none"><li>- Microsoft Windows 95</li><li>- Online User's Guide</li><li>- ThinkPad Features Program</li><li>- Diskette Factory</li><li>1. Triton CoSession™ Host</li><li>2. PRODIGY®</li><li>3. SofNet FaxWorks™</li><li>4. Puma TranXit™</li><li>5. CompuServ for Windows</li><li>9. NetFinity for Windows 95</li></ul>																																															
Graphics - controller    Trident™ CYBER9320 with 1 MB DRAM Graphics - external    External SVGA to 1024 x 768 w/ 256 colors up to 75 Hz Graph - arch/data path    VL-Bus 2.0 local bus / 32 bit / Simultaneous LCD/CRT / 180 degree tilt																																																			
Memory - std / max <b>8 MB</b> / 64 MB    70 ns / non-parity / 3.3 volt / fast page Mem - upgrade    2 sockets for two JEDEC 88 pin EDO SO DIMMs of 8 or 16 MB (acts like fast page)				<b>FEATURES OF 760 MODELS</b> Product Map; <b>LCD indicator panel</b> LCD of remaining battery life LCD icons for two batteries Plug and Play 1.0a Discharge battery via mouse click Non-disruptive battery exchange Standby, suspend, and hibernation modes US EPA Energy Star compliant Personalized nameplate in indentation Personalization screen at startup <b>International Warranty Service</b> <b>24 hour / 7 day telephone, bulletin board, fax, electronic, and Internet</b> <b>(http://www.pc.ibm.com) support</b> <b>IBM and dealer warranty/service</b> <b>Online Housecall (remote diagnostics)</b>																																															
Keyboard / # of keys    Full size alp/num / 85 (8 Fn key functions) Keyboard slope <b>Automoted tilt up keyboard</b> (5.5 degrees) Pointing / palm rest <b>TrackPoint III™ / integrated palm rest</b> Ext keyboard support    Yes (with option cable) <b>Liftable (pop-up) keyboard to access and remove diskette drive, 1st/2nd disk, and 1st/2nd battery</b>																																																			
Dimensions (cubic in)    11.7 x 8.3 x 1.74" (169) Weight (with battery)    6.51 pounds Battery - type    NiMH / intelligent / <i>Optional Lithium Ion</i> Battery - life (1 batt)    3 hours Battery - life (2 batt)    6 hours Charge time - on / off    1.7 hrs / 1.2 hrs																																																			
Architecture    ISA (EIDE, audio, PCMCIA, diskette, serial, parallel, 240 pin ext expansion) VL-Bus 2.0 / 32 bit / 33 MHz (graphics) Docking Station    Dock I and II Port replicator    Port Replicator I and II PCMCIA™ 2.1 slots    2 Type I or 2 Type II or 1 Type III Serial / parallel ports    One 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional) Other features    APM-aware BIOS / Universal AC adapter (35 watts) / Selectable boot																																																			
Motion video accel    None MPEG decoder    None DSP function    None Data/fax modem    None Audio support <b>16 bit audio chip / 18 voice MIDI FM synthesis / ESS1688</b> <b>Int stereo speakers / .5 watt / slide volume control / internal microphone</b> Input jack (3.5 mm) / output jack (3.5 mm) <b>Infrared ports (front and back) / IrDA 1.0 compatible / up to 115 kbs</b> <b>None</b>																																																			
Audio in/out jacks    Input jack (3.5 mm) / output jack (3.5 mm) Infrared ports <b>Infrared ports (front and back) / IrDA 1.0 compatible / up to 115 kbs</b> Telephone <b>None</b>																																																			
Security    Power-on password / Hard disk password / Supervisor password / Locking device keyhole (Kensington™ MicroSaver™ cable lock) / Security latch for keyboard and DIMMS (requires Kensington) / PC Card lock																																																			
Preinstalled software    Choice of two preloaded configurations (listed to right) Warranty <b>3 year</b> - ThinkPad EasyServ (optional Overnight Repair Option) or carry-in																																																			
<table><tr><td>The left bay (UltraBayä) supports: ① 2nd disk ② 2nd battery ③ std diskette drive ④ 2.88 MB diskette drive (option) ⑤ PCMCIA Cartridge (option) ⑥ IBM Wireless Modem for ARDIS (option) ⑦ IBM Wireless Modem for Cellular/CDPD (option)  Easy-Setup is entered by holding F1 when turning on.  All 760 systems support the NiMH or Li-Ion battery in both battery bay and UltraBay.  Maximum internal disk capacity on 760L is 2.16 GB with two 1.08 GB disks.</td><td>Compatible in ThinkPad 760 family: - Disks: (360/750/755 IDE disks not supported) 720 MB HDD II EIDE    12.5 mm 29H9383 810 MB HDD II EIDE    12.5 mm 29H9313 1.08 GB HDD II EIDE    12.5 mm 29H9319 1.2 GB HDD II (LD/CD only) 17 mm 29H9325 - Second HDD Adapter    29H9333 - Dock I (1 slot / 1 bay)    3545001 - Dock II (2 slot / 2 bay)    3546001 - Port Replicator I (w/ PCMCIA)    66G3510 - Port Replicator II    66G3520 - 2.88 MB diskette    66G0108 - PCMCIA Cartridge    84G1301 - <b>760 NiMH Battery (black)</b>    <b>41H9720</b> - <b>Li-Ion Battery Pack II (gray)</b>    <b>29H9329</b> - Travel Quick Charger    85G1522 - FDD External Attachment Kit    66G3618 - <b>Pentium 120/60 MHz upgrade</b>    <b>29H9340</b> - Car Battery Adapter    49G2167 - ThinkPad AC Adapter (50 watts)    66G3541 - 8 MB SO DIMM 3.3v non-parity EDO    92G7315 - 16 MB SO DIMM 3.3v non-parity EDO    92G7316 - ThinkPad headset    85G1301</td></tr></table>				The left bay (UltraBayä) supports: ① 2nd disk ② 2nd battery ③ std diskette drive ④ 2.88 MB diskette drive (option) ⑤ PCMCIA Cartridge (option) ⑥ IBM Wireless Modem for ARDIS (option) ⑦ IBM Wireless Modem for Cellular/CDPD (option)  Easy-Setup is entered by holding F1 when turning on.  All 760 systems support the NiMH or Li-Ion battery in both battery bay and UltraBay.  Maximum internal disk capacity on 760L is 2.16 GB with two 1.08 GB disks.	Compatible in ThinkPad 760 family: - Disks: (360/750/755 IDE disks not supported) 720 MB HDD II EIDE    12.5 mm 29H9383 810 MB HDD II EIDE    12.5 mm 29H9313 1.08 GB HDD II EIDE    12.5 mm 29H9319 1.2 GB HDD II (LD/CD only) 17 mm 29H9325 - Second HDD Adapter    29H9333 - Dock I (1 slot / 1 bay)    3545001 - Dock II (2 slot / 2 bay)    3546001 - Port Replicator I (w/ PCMCIA)    66G3510 - Port Replicator II    66G3520 - 2.88 MB diskette    66G0108 - PCMCIA Cartridge    84G1301 - <b>760 NiMH Battery (black)</b> <b>41H9720</b> - <b>Li-Ion Battery Pack II (gray)</b> <b>29H9329</b> - Travel Quick Charger    85G1522 - FDD External Attachment Kit    66G3618 - <b>Pentium 120/60 MHz upgrade</b> <b>29H9340</b> - Car Battery Adapter    49G2167 - ThinkPad AC Adapter (50 watts)    66G3541 - 8 MB SO DIMM 3.3v non-parity EDO    92G7315 - 16 MB SO DIMM 3.3v non-parity EDO    92G7316 - ThinkPad headset    85G1301																																														
The left bay (UltraBayä) supports: ① 2nd disk ② 2nd battery ③ std diskette drive ④ 2.88 MB diskette drive (option) ⑤ PCMCIA Cartridge (option) ⑥ IBM Wireless Modem for ARDIS (option) ⑦ IBM Wireless Modem for Cellular/CDPD (option)  Easy-Setup is entered by holding F1 when turning on.  All 760 systems support the NiMH or Li-Ion battery in both battery bay and UltraBay.  Maximum internal disk capacity on 760L is 2.16 GB with two 1.08 GB disks.	Compatible in ThinkPad 760 family: - Disks: (360/750/755 IDE disks not supported) 720 MB HDD II EIDE    12.5 mm 29H9383 810 MB HDD II EIDE    12.5 mm 29H9313 1.08 GB HDD II EIDE    12.5 mm 29H9319 1.2 GB HDD II (LD/CD only) 17 mm 29H9325 - Second HDD Adapter    29H9333 - Dock I (1 slot / 1 bay)    3545001 - Dock II (2 slot / 2 bay)    3546001 - Port Replicator I (w/ PCMCIA)    66G3510 - Port Replicator II    66G3520 - 2.88 MB diskette    66G0108 - PCMCIA Cartridge    84G1301 - <b>760 NiMH Battery (black)</b> <b>41H9720</b> - <b>Li-Ion Battery Pack II (gray)</b> <b>29H9329</b> - Travel Quick Charger    85G1522 - FDD External Attachment Kit    66G3618 - <b>Pentium 120/60 MHz upgrade</b> <b>29H9340</b> - Car Battery Adapter    49G2167 - ThinkPad AC Adapter (50 watts)    66G3541 - 8 MB SO DIMM 3.3v non-parity EDO    92G7315 - 16 MB SO DIMM 3.3v non-parity EDO    92G7316 - ThinkPad headset    85G1301																																																		

**ThinkPad EasyServ™:** customer calls 1-800-772-2227, courier service picks up ThinkPad at any location, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround). Overnight repair option in US available for \$99.  
○ = Removable

All trademarks are the property of their respective owners  
No warranties are expressed or implied in this summary  
(760L) Compiled by Roger Dodson, IBM. October 1996