



IBM ThinkPad 760ELD - withdrawn

IBM® ThinkPad®:  760ELD			
12.1" TFT color - CD-ROM			
Processor type	Pentium® 100/66 (P54LM) / 64 bit to L2 cache / 64 bit to memory		
Processor upgrade	to Pentium 133/66 MHz which includes 256 KB L2 cache		
L2 cache	None (not separately upgradeable)		
Removable diskette	3.5" 1.44 MB  / use in UltraBay or attach externally via rear ext FDD port		
External FDD port	External FDD port (requires FDD External Attachment Kit 66G3618)		
Removable CD-ROM	5.25" CD-ROM  / 4 x speed / multi-session / XA / play with eject button		
	EIDE / PIO Mode 3 (ATAPI) / in UltraBay which supports several devices		
Price			
Type - model	9547-U3F		
Preload (see side)	Windows 95		
Avail / withdrawn date	May 1996 / 1997		
Remv disk - size / ms	810 MB / 13 ms  / DMA Mode 2 or PIO Mode 4		
Disk controller	Enhanced IDE / busmaster / PCI 2.1 / supports two internal disks		
Display - size and type	12.1 inch SVGA color / 640 x 480 or 800 x 600 / 65,536 simultaneous colors		
Display - technology	Black Matrix TFT - active matrix / 100 to 1 contrast ratio		
Graphics - controller	Trident™ CYBER9320 / 32 bit SVGA accelerator / 1 MB EDO DRAM / 70 ns		
Graph - arch/data path	PCI 2.1 / 32 bit		
Graphics - features	Simultaneous LCD and CRT / 180 degree tilt		
Graphics - external	External SVGA to 1024 x 768 with 256 colors		
Memory - std / max	8 MB / 72 MB 70 ns / non-parity / 3.3 volt / EDO		
Memory - upgrade	2 sockets for two JEDEC 144 pin EDO SO DIMMs of 8, 16, 32 MB		
Keyboard / # of keys	Full size alp/num / 85 (8 Fn key functions)		
Keyboard slope	Automated tilt up keyboard (5.5 degrees)		
Pointing / palm rest	TrackPoint III™ / integrated palm rest / ext keyboard support (w/ option cable)		
Dimensions	11.7 x 8.3 x 2.14" (208 cubic inches)		
Weight (with CD-ROM)	7.28 pounds (3.30 kg)		
Battery - type	Lithium Ion / intelligent	Liftable (pop-up) keyboard to access and remove CD-ROM, diskette drive, 1st/2nd disk, and 1st/2nd battery	
Battery - life (1 batt)	3.2 hours		
Battery - life (2 batt)	6.4 hours		
Charge time - on / off	2 to 3 hrs / 1.5 to 2.5 hrs		
Architecture	ISA (audio, diskette, serial, parallel, infrared, ext expansion) PCI 2.1 / 32 bit / 33 Mhz (EIDE, graphics, CardBus, ext expansion)		
Docking Station	Dock I and II / SelectaDock I, II and III		
Port replicator	Port Replicator I and II / SelectaDock Base Model I		
PC Card Standard slots	2 Type I or 2 Type II or 1 Type III / CardBus 32 bit PCI / PCMCIA 2.1 compatible		
Serial / parallel ports	One 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)		
Other features	APM-aware BIOS / Slim AC Adapter 2 prong (35 watts) / Selectable boot		
Video in/out	None		
MPEG decoder	None		
DSP function	None		
Data/fax modem	None		
Audio support	16 bit audio chip / 20 voice MIDI FM synthesis / ESS1688 Int stereo speakers / .5 watt / slide volume control / internal microphone Input jack (3.5 mm) / Output jack (3.5 mm)		
Jacks	None		
Telephone	None		
Infrared ports	Infrared ports (front and back) / IrDA 1.0 compatible / up to 115 kbs		
Security	Power-on password / Hard disk password / Supervisor password / Locking device keyhole (Kensington™ cable lock) / Security latch for keyboard and DIMMS (requires Kensington) / PC Card lock / Personalization / Security Plate		
Preinstalled software	Windows 95 with applications (listed on right)		
Warranty	3 year - ThinkPad EasyServ (optional Overnight Repair Option) or carry-in		
The left bay (UltraBay™) supports:		Compatible in ThinkPad 760ELD family:	
① 2nd disk		- Second HDD Adapter 29H9333	
② 2nd battery		- Dock I (1 slot / 1 bay) 3545001	
③ std diskette drive		- Dock II (2 slot / 2 bay) 3546001	
④ CD-ROM		- IDE Conversion Card (for Dock I/II) 46H5994	
⑤ 2.88 MB diskette (option)		- SelectaDock I 3547001	
⑥ PCMCIA Cartridge (option)		- Port Replicator I (w/ PCMCIA slots) 66G3510	
⑦ IBM Wireless Modem ARDIS (option)		- Port Replicator II 66G3520	
⑧ IBM Wireless Modem for Cellular/ CDPD (option)		- SelectaDock Base Model I 39H7405	
		- 2.88 MB diskette drive 66G0108	
		- PCMCIA Cartridge (one Type III) 84G1301	
		- FDD External Attachment Kit 66G3618	
		- Pentium 133/66 MHz/L2 upgrade 46H5991	
		- 4 x CD-ROM (UltraBay) 39H7413	
		- 6 x CD-ROM (UltraBay) 85G1957	
		- 8 x CD-ROM (UltraBay) 45H8786	
		- 8-20 x CD-ROM (UltraBay) 00K7903	
		- 8 MB SO DIMM 3.3v NP EDO 64 bit 92G7340	
		- 16 MB SO DIMM 3.3v NP EDO 64 bit 92G7341	
		- 32 MB SO DIMM 3.3v NP EDO 64 bit 92G7342	
All 760 systems support the NiMH or Li-Ion battery in both battery bay and UltraBay.			
Maximum internal disk capacity on 760ELD is 2.4 GB with two 1.2 GB disks.			
		WINDOWS 95 PRELOAD - Microsoft Windows 95 - Online User's Guide - ThinkPad Features - PC Card Director 4.0 - Diskette Factory 1. Triton CoSession™ Host; 2. PRODIGY® 3. SofNet FaxWorks™ Fax 4. Puma TranXit™ 5. Compuserp for Windows 6. NetFinity for Windows 95 - Lotus SmartSuite 96 CD-ROM	
		Easy-Setup is entered by holding F1 when turning on. 810 MB = DMA Mode 2 or PIO Mode 4 1.08 GB = DMA Mode 2 or PIO Mode 4 1.2 GB = DMA Mode 1 or PIO Mode 3 ThinkPad 760 ELD supported disks: - (360/750/755 IDE disks not supported) - 720 MB HDD II EIDE 12.5 mm 29H9383 - 810 MB HDD II EIDE 12.5 mm 29H9313 - 1.08 GB HDD II EIDE 12.5 mm 29H9319 - 1.2 GB (1.96"+ models) 17 mm 29H9325 - 1.4 GB HDD 3L EIDE 12.5 mm 69H8412 - 2.1 GB (1.96"+ models) 17 mm 69H8414 - 3.0 GB (1.96"+ models) 17 mm 45H8789 - 5.1 GB (1.96" or higher models) 00K7902	
		ThinkPad 760E supported batteries: - 760 NiMH Battery (black) 41H9720 - Li-Ion Battery Pack II (gray) 29H9329 - Travel Quick Charger 85G1522 - Car Battery Adapter 49G2167	
		FEATURES OF 760 MODELS Setup Pointer (single page) LCD indicator panel Plug and Play 1.0a Discharge battery via mouse click Non-disruptive battery exchange Standby, suspend, safe suspend, and hibernation modes US EPA Energy Star compliant Personalized nameplate in indentation Personalization screen at startup International Warranty Service 24 hour / 7 day telephone, bulletin board, fax, electronic, and Internet (http://www.pc.ibm.com) support IBM and dealer warranty/service Online Housecall (remote diagnostics)	

ThinkPad EasyServ™: customer calls 1-800-772-2227, courier service picks up ThinkPad at any location, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround). Overnight repair option in US available for \$99.
○ = Removable

All trademarks are the property of their respective owners
No warranties are expressed or implied in this summary
(760ELD) Compiled by Roger Dodson, IBM. December 1997