

| Type-model   | Processor   | Speed   | Memory <sup>11</sup>  | Screen    | Disk GB <sup>8</sup> | Optical   | Mini PCI Comm Bay wireless/modem | CDC modem | Ethernet on planar | Security Chip | Preload | Small business software  | Workhorse (W) or Global (G) model | Avail date |
|--|---|---------|---|-----------|----------------------|-----------|----------------------------------|-----------|--------------------|---------------|---------|--|-----------------------------------|------------|
| 2656-25U   | Celeron™  | 1.06    | 128MB   | 13.3" XGA | 20G                  | CD-ROM    | Open                             | Modem     | 10/100             |               | XP Home |  |                                   | Feb 2002   |
| 2656-A5U   | Celeron   | 1.06    | 128MB   | 13.3" XGA | 20G                  | CD-ROM    | Open                             | Modem     | 10/100             |               | XP Pro  |  |                                   | Feb 2002   |
| 2656-AFU   | Celeron   | 1.06    | 128MB   | 13.3" XGA | 20G                  | CD-ROM    | Wi-Fi <sup>32</sup> /mod         | None      | 10/100             |               | XP Pro  |  |                                   | Feb 2002   |
| 2656-AKU   | Celeron   | 1.06    | 128MB   | 13.3" XGA | 20G                  | CD-ROM    | Open                             | Modem     | 10/100             |               | XP Pro  | Office XP SB <sup>18</sup>   |                                   | Feb 2002   |
| 2656-AGU   | Celeron   | 1.06    | 128MB   | 14.1" XGA | 20G                  | CD-ROM    | Wi-Fi/mod                        | None      | 10/100             |               | XP Pro  |  |                                   | Aug 2002   |
| 2656-HHU   | Pentium® III-M  | 1.00    | 128MB   | 14.1" XGA | 20G                  | DVD-ROM   | Open                             | Modem     | 10/100             |               | XP Pro  |  | G                                 | Mar 2002   |
| 2656-3FU   | Pentium III-M   | 1.13    | 128MB   | 13.3" XGA | 20G                  | CD-RW     | Wi-Fi/mod                        | None      | 10/100             |               | XP Home |  |                                   | Feb 2002   |
| 2656-BFU   | Pentium III-M   | 1.13    | 128MB   | 13.3" XGA | 20G                  | CD-RW     | Wi-Fi/mod                        | None      | 10/100             |               | XP Pro  |  |                                   | Feb 2002   |
| 2656-E5U   | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 30G                  | DVD-ROM   | Open                             | Modem     | 10/100             |               | XP Pro  |  | W G                               | Feb 2002   |
| 2656-E6U   | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 30G                  | CD-RW     | Open                             | Modem     | 10/100             | Yes           | XP Pro  |  |                                   | Feb 2002   |
| 2656-EFU   | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 30G                  | DVD-ROM   | Wi-Fi/mod                        | None      | 10/100             |               | XP Pro  |  | W G                               | Feb 2002   |
| 2656-HFU   | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 40G                  | DVD/CD-RW | Wi-Fi/mod                        | None      | 10/100             | Yes           | XP Pro  |  |                                   | Feb 2002   |
| 2656-EHU   | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 30G                  | DVD-ROM   | Wi-Fi/mod                        | None      | 10/100             |               | XP Pro  | Office XP SB   |                                   | Feb 2002   |
| 2656-HGU   | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 40G                  | DVD/CD-RW | Wi-Fi/mod                        | None      | 10/100             | Yes           | XP Pro  | Office XP SB   |                                   | Feb 2002   |
| Positioning Processor  | Best blend of portability and essential features; two-spindle system<br><b>Intel® Mobile Celeron™ 1.06GHz with 133MHz frontside bus or Intel Mobile Pentium® III-M 1.0 or 1.13GHz</b> with Speedstep™ technology <sup>1</sup> with 133MHz frontside bus<br><i>Celeron: 256KB / at processor speed; Pentium III: 512 KB / at processor speed</i><br><b>128MB</b> standard / 1GB max <sup>7</sup> / SDRAM / non-parity / 133MHz / PC133 / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available |         |   |           |                      |           |                                  |           |                    |               |         | <b>SOFTWARE<sup>14</sup></b>   |                                   |            |
| L2 cache   |   |         |   |           |                      |           |                                  |           |                    |               |         | <b>Windows XP Home models</b>  |                                   |            |
| Memory   |   |         |   |           |                      |           |                                  |           |                    |               |         | - Microsoft® Windows® XP Home <sup>20</sup><br>✦ Disk-to-Disk Recovery (in hidden Service Partition)   |                                   |            |
| Diskette drive   | None standard / use optional Ultrabay™-based or USB-based diskette drive  |         |   |           |                      |           |                                  |           |                    |               |         | <b>Windows XP Pro models</b>   |                                   |            |
| CD-ROM   | <i>Some:</i> CD-ROM / 24X-10X <sup>9</sup> speed / bootable / removable   |         |   |           |                      |           |                                  |           |                    |               |         | - Microsoft® Windows® XP Professional <sup>20</sup>  |                                   |            |
| CD-RW  | <i>Some:</i> CD-RW / 8X/4X/24X Max <sup>9</sup> / removable   |         |   |           |                      |           |                                  |           |                    |               |         | ✦ Disk-to-Disk Recovery (in hidden Service Partition)  |                                   |            |
| DVD-ROM  | <i>Some:</i> DVD-ROM / 8X-3.3X <sup>9</sup> speed / removable   |         |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |
| DVD-ROM/CD-RW  | <i>Some:</i> DVD-ROM/CD-RW combo / 8X/8X/24X/8X <sup>21</sup> speed / removable   |         |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |
| Ultrabay 2000  | One modular bay for interchangeable devices (right side) / <b>Ultrabay™ Plus-compatible</b>   |         |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |
| Disk   | <b>20, 30, or 40GB<sup>8</sup></b> (4200 rpm) / upgradable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay   |         |   |           |                      |           |                                  |           |                    |               |         | <b>INCLUDED SOFTWARE<sup>14</sup> (all)</b>  |                                   |            |
| Display  | <i>Some:</i> <b>13.3"</b> (337.8mm) <b>XGA (1024x768) TFT color</b> / Active Matrix<br><i>Some:</i> <b>14.1"</b> (358.1mm) <b>XGA (1024x768) TFT color</b> / Active Matrix  |         |   |           |                      |           |                                  |           |                    |               |         | <b>Preloaded</b>   |                                   |            |
| Graphics controller  | <b>Intel 830MG Integrated Direct AGP 3D</b> / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB <sup>11</sup> of system memory for graphics  |         |   |           |                      |           |                                  |           |                    |               |         | • Access ThinkPad  |                                   |            |
| Graphics - external  | External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200  |         |   |           |                      |           |                                  |           |                    |               |         | - Access Connections<br>- Access Help<br>- Access Support  |                                   |            |
| Keyboard   | 87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar <sup>13</sup> / pitch: 19mm; stroke: 2.7mm   |         |   |           |                      |           |                                  |           |                    |               |         | • Adobe® Acrobat   |                                   |            |
| ThinkLight™  | Illuminates the keyboard to improve visibility in low-light conditions / no UltraPort™  |         |   |           |                      |           |                                  |           |                    |               |         | • InterVideo WinDVD (DVD models)   |                                   |            |
| Dimensions <sup>3</sup>  | 12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm  |         |   |           |                      |           |                                  |           |                    |               |         | • Norton AntiVirus   |                                   |            |
| Approximate weight <sup>2</sup>  | w/ battery and: <i>CD-ROM:</i> 5.8 lbs; <i>DVD:</i> 5.8 lbs; <i>CD-RW:</i> 6.1 lbs; <i>DVD/CD-RW:</i> 6.1 lbs   |         |   |           |                      |           |                                  |           |                    |               |         | • PC-Doctor™   |                                   |            |
| Case material  | <i>Color:</i> Black; <i>All:</i> ABS plastic  |         |   |           |                      |           |                                  |           |                    |               |         | • ThinkPad Utilities   |                                   |            |
| Battery - type   | Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus   |         |   |           |                      |           |                                  |           |                    |               |         | • IBM Update Connector™ <sup>15</sup>  |                                   |            |
| Battery - life <sup>10</sup>   | <i>Celeron models:</i> 2.4 to 2.6 hrs; <i>Pentium III models:</i> 2.9 to 3.1 hrs  |         |   |           |                      |           |                                  |           |                    |               |         | • Veritas RecordNOW (CD-RW mod)  |                                   |            |
| Architecture   | <b>Intel 830MG</b> chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus, Mini PCI) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared)  |         |   |           |                      |           |                                  |           |                    |               |         | <b>Downloadable</b>  |                                   |            |
| Port Replicator  | Optional <b>ThinkPad Port Replicator</b> (no ThinkPad Dock support)   |         |   |           |                      |           |                                  |           |                    |               |         | • IBM Rapid Restore™ PC  |                                   |            |
| PC Card Std slots  | One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door   |         |   |           |                      |           |                                  |           |                    |               |         | • IBM Data Transfer  |                                   |            |
| Ports  | Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port   |         |   |           |                      |           |                                  |           |                    |               |         | • Veritas RecordNOW (CD-RW mod)  |                                   |            |
| Video out  | S-video out port (TV out) / one industry standard connector   |         |   |           |                      |           |                                  |           |                    |               |         | <b>License</b>   |                                   |            |
| Mini PCI   | One Mini PCI type III slot (Communications Bay) / not customer upgradable   |         |   |           |                      |           |                                  |           |                    |               |         | - Lotus® SmartSuite® Millennium and Lotus Notes® Client 5.0  |                                   |            |
| Wi-Fi <sup>32</sup> /modem   | <i>Some:</i> Mini PCI Wi-Fi <sup>32</sup> wireless <sup>4</sup> , Intel® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K <sup>6</sup> V.90 (V.92-designed <sup>29</sup> ) modem combo, Lucent® chipset   |         |   |           |                      |           |                                  |           |                    |               |         | <b>Microsoft Office XP Small Business<sup>28</sup> Models</b>  |                                   |            |
| CDC  | One Communications Daughter Card (CDC) socket (open or modem) / not accessible  |         |   |           |                      |           |                                  |           |                    |               |         | - Microsoft Office XP Small Business <sup>18</sup> (Word, Excel, Outlook, Publisher, Small Business Tools)   |                                   |            |
| Modem  | <i>Some:</i> 56K <sup>6</sup> V.90 (V.92-designed <sup>29</sup> ) CDC modem card / Lucent® chip set   |         |   |           |                      |           |                                  |           |                    |               |         | ✦ Office XP Small Business CD  |                                   |            |
| Ethernet   | 10/100 ethernet on planar / Intel® 82562ET chipset  |         |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |
| Audio support  | Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)   |         |   |           |                      |           |                                  |           |                    |               |         | <b>Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series</b> |                                   |            |
| Security   | Power-on password / hard disk password / supervisor password / security keyhole<br><i>Some:</i> <b>IBM Embedded Security Subsystem<sup>33</sup></b> / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security <sup>16</sup>  |         |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |
| Limited warranty <sup>12</sup>   | <b>1 year - EasyServ™.</b> onsite pickup and delivery / service upgrades <sup>22</sup> available  |         |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |
| 64 MB SO DIMM  | 133MHz NP SDRAM   | 19K4650 | USB Portable Diskette Drive   | 05K9276   |                      |           |                                  |           |                    |               |         |  |                                   |            |
| 128 MB SO DIMM   | 133MHz NP SDRAM   | 19K4652 | ThinkPad R30/R31 Li-Ion Battery   | 02K6821   |                      |           |                                  |           |                    |               |         |  |                                   |            |
| 256 MB SO DIMM   | 133MHz NP SDRAM   | 19K4654 | ThinkPad 72W AC Adapter   | 02K6699   |                      |           |                                  |           |                    |               |         |  |                                   |            |
| 512 MB SO DIMM   | 133MHz NP SDRAM   | 19K4656 | ThinkPad Port Replicator  | 02K8667   |                      |           |                                  |           |                    |               |         |  |                                   |            |
| SuperDisk (LS-240)   | Ultrabay 2000   | 08K9616 | Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices) | 19K4480   |                      |           |                                  |           |                    |               |         |  |                                   |            |
| Zip 250MB  | Ultrabay 2000 Drive   | 00N8253 | 20GB Hard Disk 9.5mm (4200 rpm)   | 08K9686   |                      |           |                                  |           |                    |               |         |  |                                   |            |
| 24X-10X CD-ROM   | Ultrabay 2000 Drive   | 05K9233 | 40GB HS Hard Disk 9.5mm (5400 rpm)  | 08K9816   |                      |           |                                  |           |                    |               |         |  |                                   |            |
| 8X/4X/24X Max CD-RW  | Ultrabay 2000   | 22P9101 | IBM Optical 3-Button Travel Wheel Mouse                                   | 31P7410   |                      |           |                                  |           |                    |               |         |  |                                   |            |
| Ultralight 8X Max DVD  | Ultrabay 2000   | 22P9102 | ServicePac®, 22 1yr IOR 9x5 NBD   | 30L9188   |                      |           |                                  |           |                    |               |         |  |                                   |            |
| CD-RW/DVD Combo III  | Ultrabay 2000   | 22P6980 | ServicePac 2yr IOR 9x5 NBD  | 30L9189   |                      |           |                                  |           |                    |               |         |  |                                   |            |
| Second HDD Adapter   | for Ultrabay 2000   | 08K6068 | ServicePac 3yr IOR 9x5 NBD  | 30L9195   |                      |           |                                  |           |                    |               |         |  |                                   |            |
| IBM ThinkPad Ultrabay Plus Carrier   |   | 22P5737 | ServicePac 2yr P&L P/U Depot  | 30L9191   |                      |           |                                  |           |                    |               |         |  |                                   |            |
| IBM ThinkPad Ultrabay Plus c500 Cradle   |   | 22P5738 | ServicePac 3yr P&L P/U Depot  | 30L9192   |                      |           |                                  |           |                    |               |         |  |                                   |            |
| ThinkPad Ultrabay Plus Numeric Keypad  |   | 22P7330 |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |
| Other options at <a href="http://ibm.com/pc/us/accessories">ibm.com/pc/us/accessories</a>  |   |         |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |
| Universal 72 watt AC adapter   |   |         |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |
| PC 2001-compliant  |   |         |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |
| CIM and DMI 2.0-compliant  |   |         |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |
| IBM ImageUltra™ Services available   |   |         |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |
| IBM Rapid Restore PC available to protect software image and data                          |   |         |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |
| Setup Guide, Service and Trouble-shooting Guide, Windows manual                            |   |         |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |
| International Warranty Service <sup>17</sup>   |   |         |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |
| 24 hour x 7 day <sup>18</sup> toll-free hardware support during the warranty <sup>12</sup> |   |         |   |           |                      |           |                                  |           |                    |               |         |  |                                   |            |

See footnotes for important warranty information

US models announced January 22, March 19, or August 13, 2002

US models withdrawn effective July 2002, January 2003, or July 2003

(R31) © IBM Corp. July 2003

| Type-model                          | Processor   | Speed   | Memory <sup>11</sup>  | Screen    | Disk GB <sup>8</sup> | Optical   | Mini PCI Comm Bay wireless/modem | CDC modem | Ethernet on planar | Security Chip  | Preload      | Small business software   | Workhorse (W) or Global (G) model | Avail date |
|-------------------------------------|---|---------|---|-----------|----------------------|-----------|----------------------------------|-----------|--------------------|--|--------------|---|-----------------------------------|------------|
| 2656-F5U                            | Pentium® III-M  | 1.13    | 128MB   | 14.1" XGA | 30G                  | DVD-ROM   | Open                             | Modem     | 10/100             |  | XP Pro       |   |                                   | Apr 2002   |
| 2656-H4U                            | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 30G                  | CD-RW     | Open                             | Modem     | 10/100             | Yes  | XP Pro       |   |                                   | Apr 2002   |
| 2656-H8U                            | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 40G                  | DVD/CD-RW | Wi-Fi <sup>32</sup> /mod         | None      | 10/100             | Yes  | XP Pro       |   |                                   | Apr 2002   |
| 2656-FGU                            | Pentium III-M   | 1.13    | 256MB   | 14.1" XGA | 30G                  | DVD-ROM   | Open                             | Modem     | 10/100             |  | XP Pro       |   |                                   | Apr 2002   |
| 2656-M4U                            | Pentium III-M   | 1.0     | 128MB   | 14.1" XGA | 20G                  | DVD-ROM   | Open                             | Modem     | 10/100             |  | XP Pro       |   |                                   | Apr 2002   |
| 2656-H6U                            | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 30G                  | DVD-ROM   | Wi-Fi/mod                        | None      | 10/100             |  | XP Pro       | Office XP SB <sup>18</sup>  |                                   | Apr 2002   |
| 2656-H9U                            | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 40G                  | DVD/CD-RW | Wi-Fi/mod                        | None      | 10/100             | Yes  | XP Pro       | Office XP SB  |                                   | Apr 2002   |
| 2656-H5U                            | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 30G                  | CD-RW     | Open                             | Modem     | 10/100             | Yes  | Windows 2000 |   |                                   | Apr 2002   |
| 2656-H7U                            | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 40G                  | DVD/CD-RW | Wi-Fi/mod                        | None      | 10/100             | Yes  | Windows 2000 |   |                                   | Apr 2002   |
| 2656-F4U                            | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 30G                  | DVD-ROM   | Open                             | Modem     | 10/100             |  | Windows 2000 |   |                                   | Apr 2002   |
| 2656-FEU                            | Pentium III-M   | 1.13    | 256MB   | 14.1" XGA | 30G                  | DVD-ROM   | Open                             | Modem     | 10/100             |  | Windows 2000 |   |                                   | Apr 2002   |
| 2656-L4U                            | Pentium III-M   | 1.0     | 128MB   | 14.1" XGA | 20G                  | DVD-ROM   | Open                             | Modem     | 10/100             |  | Windows 2000 |   |                                   | Apr 2002   |
| Positioning TAA-compliant Processor | Best blend of portability and essential features; two-spindle system<br>Trade Act Agreement-compliant<br>Intel® Mobile Pentium® III-M 1.0 or 1.13GHz with Speedstep™ technology <sup>1</sup> with 133MHz Front Side Bus   |         |   |           |                      |           |                                  |           |                    |  |              | SOFTWARE <sup>14</sup>  |                                   |            |
| L2 cache                            | 512 KB / at processor speed / ECC   |         |   |           |                      |           |                                  |           |                    |  |              | Windows XP Pro models   |                                   |            |
| Memory                              | 128 or 256MB standard / 1GB max <sup>7</sup> / SDRAM / non-parity / 133MHz / PC133 / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available  |         |   |           |                      |           |                                  |           |                    |  |              | - Microsoft® Windows® XP Professional <sup>20</sup><br>✦ Disk-to-Disk Recovery (in hidden Service Partition)  |                                   |            |
| Diskette drive                      | None standard / use optional Ultrabay™-based or USB-based diskette drive  |         |   |           |                      |           |                                  |           |                    |  |              | Windows 2000 models   |                                   |            |
| CD-RW                               | Some: CD-RW / 8X/4X/24X Max <sup>9</sup> / removable  |         |   |           |                      |           |                                  |           |                    |  |              | - Microsoft Windows 2000 Professional <sup>20</sup>   |                                   |            |
| DVD-ROM                             | Some: DVD-ROM / 8X-3.3X speed / removable   |         |   |           |                      |           |                                  |           |                    |  |              | - ConfigSafe®   |                                   |            |
| DVD-ROM/CD-RW                       | Some: DVD-ROM/CD-RW combo / 8X/8X/24X/8X <sup>21</sup> speed / removable  |         |   |           |                      |           |                                  |           |                    |  |              | ✦ Disk-to-Disk Recovery (in hidden Service Partition)   |                                   |            |
| Ultrabay 2000                       | One modular bay for interchangeable devices (right side) / Ultrabay™ Plus-compatible  |         |   |           |                      |           |                                  |           |                    |  |              | INCLUDED SOFTWARE <sup>14</sup> (all)   |                                   |            |
| Disk                                | 20, 30, or 40GB <sup>8</sup> (4200 rpm) / upgradeable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay  |         |   |           |                      |           |                                  |           |                    |  |              | Preloaded   |                                   |            |
| Display                             | 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix  |         |   |           |                      |           |                                  |           |                    |  |              | • Access ThinkPad   |                                   |            |
| Graphics controller                 | Intel 830MG Integrated Direct AGP 3D / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB <sup>11</sup> of system memory for graphics   |         |   |           |                      |           |                                  |           |                    |  |              | - Access Connections  |                                   |            |
| Graphics - external                 | External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200  |         |   |           |                      |           |                                  |           |                    |  |              | - Access Help   |                                   |            |
| Keyboard                            | 87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar <sup>13</sup> / pitch: 19mm; stroke: 2.7mm   |         |   |           |                      |           |                                  |           |                    |  |              | - Access Support  |                                   |            |
| ThinkLight™ UltraPort™              | Illuminates the keyboard to improve visibility in low-light conditions<br>None  |         |   |           |                      |           |                                  |           |                    |  |              | • Adobe® Acrobat  |                                   |            |
| Dimensions <sup>3</sup>             | 12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm  |         |   |           |                      |           |                                  |           |                    |  |              | • InterVideo WinDVD (DVD models)  |                                   |            |
| Approximate weight <sup>2</sup>     | w/ battery and: DVD-ROM: 5.8 lbs; CD-RW: 6.1 lbs; DVD/CD-RW: 6.1 lbs  |         |   |           |                      |           |                                  |           |                    |  |              | • Norton AntiVirus  |                                   |            |
| Case material                       | Color: black; All: ABS plastic  |         |   |           |                      |           |                                  |           |                    |  |              | • PC-Doctor™  |                                   |            |
| Battery - type                      | Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus   |         |   |           |                      |           |                                  |           |                    |  |              | • ThinkPad Utilities  |                                   |            |
| Battery - life <sup>10</sup>        | 802.11b models: 2.9 hrs; Others: 3.1 hrs  |         |   |           |                      |           |                                  |           |                    |  |              | • IBM Update Connector™ <sup>15</sup>   |                                   |            |
| Architecture                        | Intel 830MG chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus, Mini PCI) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared) |         |   |           |                      |           |                                  |           |                    |  |              | • Veritas RecordNOW (CD-RW mod)   |                                   |            |
| Port Replicator                     | Optional ThinkPad Port Replicator (no ThinkPad Dock support)  |         |   |           |                      |           |                                  |           |                    |  |              | Downloadable  |                                   |            |
| PC Card Std slots                   | One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video   |         |   |           |                      |           |                                  |           |                    |  |              | • IBM Rapid Restore™ PC   |                                   |            |
| Ports                               | Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port   |         |   |           |                      |           |                                  |           |                    |  |              | • IBM Data Transfer   |                                   |            |
| Video out                           | S-video out port (TV out) / one industry standard connector   |         |   |           |                      |           |                                  |           |                    |  |              | • IBM Director Agent  |                                   |            |
| Mini PCI                            | One Mini PCI type III slot (Communications Bay) / not customer upgradeable  |         |   |           |                      |           |                                  |           |                    |  |              | • IBM Client Security Software (for security chip)  |                                   |            |
| Wi-Fi <sup>32</sup> /modem          | Some: Mini PCI Wi-Fi <sup>32</sup> wireless <sup>4</sup> , Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K <sup>6</sup> V.90 (V.92-designed <sup>29</sup> ) modem combo, Lucent® chipset   |         |   |           |                      |           |                                  |           |                    |  |              | License   |                                   |            |
| CDC                                 | One Communications Daughter Card (CDC) socket (open or modem) / not accessible  |         |   |           |                      |           |                                  |           |                    |  |              | - Lotus® SmartSuite® Millennium and Lotus Notes® Client 5.0   |                                   |            |
| Modem                               | Some: 56K <sup>6</sup> V.90 (V.92-designed <sup>29</sup> ) CDC modem card / Lucent® chip set  |         |   |           |                      |           |                                  |           |                    |  |              | Microsoft Office XP Small Business <sup>18</sup> Models (H6U and H9U)   |                                   |            |
| Ethernet                            | 10/100 ethernet on planar / Intel® 82562ET chipset  |         |   |           |                      |           |                                  |           |                    |  |              | - Microsoft Office XP Small Business <sup>28</sup> (Word, Excel, Outlook, Publisher, Small Business Tools)  |                                   |            |
| Audio support                       | Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)   |         |   |           |                      |           |                                  |           |                    |  |              | ✦ Office XP Small Business CD   |                                   |            |
| Security                            | Power-on password / hard disk password / supervisor password / security keyhole<br>Some: IBM Embedded Security Subsystem <sup>33</sup> / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security <sup>16</sup>   |         |   |           |                      |           |                                  |           |                    |  |              | Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series |                                   |            |
| Limited warranty <sup>12</sup>      | 1 year - EasyServ™ <sup>19</sup> onsite pickup and delivery / warranty service upgrades <sup>22</sup>   |         |   |           |                      |           |                                  |           |                    |  |              | Universal 72 watt AC adapter  |                                   |            |
| 64 MB SO DIMM                       | 133MHz NP SDRAM   | 19K4650 | USB Portable Diskette Drive   |           |                      |           |                                  |           | 05K9276            | PC 2001-compliant  |              |   |                                   |            |
| 128 MB SO DIMM                      | 133MHz NP SDRAM   | 19K4652 | ThinkPad R30/R31 Li-Ion Battery   |           |                      |           |                                  |           | 02K6821            | CIM and DMI 2.0-compliant  |              |   |                                   |            |
| 256 MB SO DIMM                      | 133MHz NP SDRAM   | 19K4654 | ThinkPad 72W AC Adapter   |           |                      |           |                                  |           | 02K6699            | IBM ImageUltra Services available  |              |   |                                   |            |
| 512 MB SO DIMM                      | 133MHz NP SDRAM   | 19K4656 | ThinkPad Port Replicator  |           |                      |           |                                  |           | 02K8667            | IBM Rapid Restore PC available to protect software image and data                          |              |   |                                   |            |
| SuperDisk (LS-240)                  | Ultrabay 2000   | 08K9616 | Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices) |           |                      |           |                                  |           | 19K4480            | Personalized Web-based support <sup>31</sup>   |              |   |                                   |            |
| Zip 250MB                           | Ultrabay 2000 Drive   | 00N8253 | 20GB HDD  |           |                      |           |                                  |           | 08K9686            | Setup Guide, Service and Trouble-shooting Guide, Windows manual                            |              |   |                                   |            |
| 24X-10X CD-ROM                      | Ultrabay 2000 Drive   | 05K9233 | 40GB HDD  |           |                      |           |                                  |           | 08K9687            | International Warranty Service <sup>17</sup>   |              |   |                                   |            |
| 8X/4X/24X Max                       | CD-RW Ultrabay 2000   | 22P9101 | 60GB HS Hard Disk 9.5mm (5400 rpm)  |           |                      |           |                                  |           | 08K9688            | 24 hour x 7 day <sup>18</sup> toll-free hardware support during the warranty <sup>12</sup> |              |   |                                   |            |
| Ultralight 8X                       | Max DVD Ultrabay 2000   | 22P9102 | ServicePac <sup>22</sup> 1yr IOR 9x5 NBD                                  |           |                      |           |                                  |           | 30L9188            |  |              |   |                                   |            |
| CD-RW/DVD Combo II                  | Ultrabay 2000   | 08K9701 | ServicePac 2yr IOR 9x5 NBD  |           |                      |           |                                  |           | 30L9189            |  |              |   |                                   |            |
| Second HDD Adapter                  | for Ultrabay 2000   | 08K6068 | ServicePac 3yr IOR 9x5 NBD  |           |                      |           |                                  |           | 30L9195            |  |              |   |                                   |            |
| IBM ThinkPad                        | Ultrabay Plus Carrier   | 22P5737 | ServicePac 2yr P&L P/U Depot  |           |                      |           |                                  |           | 30L9191            |  |              |   |                                   |            |
| IBM ThinkPad                        | Ultrabay Plus c500 Cradle   | 22P5738 | ServicePac 3yr P&L P/U Depot  |           |                      |           |                                  |           | 30L9192            |  |              |   |                                   |            |
| ThinkPad                            | Ultrabay Plus Numeric Keypad  | 22P7330 |   |           |                      |           |                                  |           |                    |  |              |   |                                   |            |

See footnotes for important warranty information

US models announced April 2, 2002

US models withdrawn effective October 2002

(R31TAA) © IBM Corp. October 2002



| Type-model | Processor      | GHz  | Memory <sup>11</sup> | Screen    | Disk              | Optical | Mini PCI<br>Comm Bay | CDC<br>Modem | Ethernet<br>on planar | Security<br>Chip | Preload        | Workhorse (W)<br>or Global (G)<br>model | Avail<br>date |
|------------|----------------|------|----------------------|-----------|-------------------|---------|----------------------|--------------|-----------------------|------------------|----------------|---|---------------|
| 2657-F4U   | Pentium® III-M | 1.13 | 128MB                | 14.1" XGA | 30GB <sup>8</sup> | DVD-ROM | Open                 | Modem        | 10/100                | No               | Windows® 2000  |   | Apr 2002      |
| 2657-FEU   | Pentium III-M  | 1.13 | 256MB                | 14.1" XGA | 30GB              | DVD-ROM | Open                 | Modem        | 10/100                | No               | Windows 2000   |   | Apr 2002      |
| 2657-F5U   | Pentium III-M  | 1.13 | 128MB                | 14.1" XGA | 30GB              | DVD-ROM | Open                 | Modem        | 10/100                | No               | Windows XP Pro |   | Apr 2002      |
| 2657-FGU   | Pentium III-M  | 1.13 | 256MB                | 14.1" XGA | 30GB              | DVD-ROM | Open                 | Modem        | 10/100                | No               | Windows XP Pro |   | Apr 2002      |

- 2657 models have a 3 year limited warranty (other 2656 ThinkPad R31 systems have a 1 year limited warranty)
- Trade Act Agreement (TAA)-compliant models

|   |  |         |   |  |  |
|---|--|---------|---|--|--|
| Positioning<br>TAA-compliant<br>Processor   | Best blend of portability and essential features; two-spindle system<br><b>Trade Act Agreement-compliant</b><br><b>Intel® Mobile Pentium® III Processor-M 1.13GHz</b> with Speedstep™ technology <sup>1</sup> with 133MHz Front Side Bus   |         |   | <b>SOFTWARE<sup>14</sup></b>   |  |
| L2 cache<br>Memory  | 512 KB / at processor speed<br>128MB or 256MB standard / 1GB maximum <sup>7</sup> / SDRAM / non-parity / 133MHz / PC133 / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available  |         |   | <b>Windows XP Pro models</b><br>- Microsoft® Windows® XP Professional <sup>20</sup><br>✧ Disk-to-Disk Recovery (in hidden Service Partition)   |  |
| Diskette drive<br>CD-RW<br>Ultrabay 2000<br>Disk  | None standard / use optional Ultrabay™-based or USB-based diskette drive<br>DVD-ROM / 8X-3.3X <sup>9</sup> speed / removable<br>One modular bay for interchangeable devices (right side) / <b>Ultrabay™ Plus</b> -compatible<br>30GB <sup>8</sup> (4200 rpm) / upgradeable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay  |         |   | <b>Windows 2000 models</b><br>- Microsoft Windows 2000 Professional <sup>20</sup><br>- ConfigSafe®<br>✧ Disk-to-Disk Recovery (in hidden Service Partition)  |  |
| Display   | 14.1" (358.1mm) <b>XGA (1024x768) TFT color</b> / Active Matrix  |         |   | <b>INCLUDED SOFTWARE<sup>14</sup> (all)</b>  |  |
| Graphics controller   | Intel 830MG Integrated Direct AGP 3D / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB <sup>11</sup> of system memory for graphics  |         |   | <b>Preloaded</b>   |  |
| Graphics - external   | External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200   |         |   | <ul style="list-style-type: none"><li>• Access ThinkPad<ul style="list-style-type: none"><li>- Access Connections</li><li>- Access Help</li><li>- Access Support</li></ul></li><li>• Adobe® Acrobat</li><li>• InterVideo WinDVD (DVD models)</li><li>• Norton AntiVirus</li><li>• PC-Doctor™</li><li>• ThinkPad Utilities</li><li>• IBM Update Connector™<sup>15</sup></li></ul> |  |
| Keyboard  | 87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar <sup>13</sup> / pitch: 19mm; stroke: 2.7mm  |         |   | <b>Downloadable</b>  |  |
| ThinkLight™<br>UltraPort™   | Illuminates the keyboard to improve visibility in low-light conditions<br>None   |         |   | <ul style="list-style-type: none"><li>• IBM Rapid Restore™ PC</li><li>• IBM Data Transfer</li><li>• IBM Director Agent</li><li>• IBM Client Security Software (for security chip)</li></ul>  |  |
| Dimensions <sup>3</sup><br>Approximate weight <sup>2</sup><br>Case material<br>Battery - type<br>Battery - life <sup>10</sup> | 12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm<br>w/ battery and DVD: 5.8 lbs (2.6 kg)<br>Color: black; All: ABS plastic<br>Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus<br>2.5 to 3.1 hrs  |         |   | <b>License</b><br>- Lotus® SmartSuite® Millennium and Lotus Notes® Client 5.0  |  |
| Architecture  | Intel 830MG chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus, Mini PCI) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared)  |         |   | <b>Ultrabay Plus</b> integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series   |  |
| Port Replicator<br>PC Card Std slots<br>Ports   | Optional <b>ThinkPad Port Replicator</b> (no ThinkPad Dock support)<br>One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video<br>Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port  |         |   | Other options at <a href="http://ibm.com/pc/us/accessories">ibm.com/pc/us/accessories</a>  |  |
| Video out<br>Mini PCI<br>Wi-Fi <sup>32</sup> wireless<br>CDC<br>Modem<br>Bluetooth™<br>Ethernet<br>Audio support              | S-video out port (TV out) / one industry standard connector<br>One Mini PCI type III slot (Communications Bay) / not customer upgradeable<br>None<br>One Communications Daughter Card (CDC) socket / not accessible<br>56K <sup>6</sup> V.90 (V.92-designed <sup>29</sup> ) CDC modem card / Lucent® chip set<br>None<br>10/100 ethernet on planar / Intel® 82562ET chipset<br>Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm) |         |   |  |  |
| Security  | Power-on password / hard disk password / supervisor password / security keyhole  |         |   |  |  |
| Limited warranty <sup>12</sup>  | 3 years/1 year battery - EasyServ™ <sup>19</sup> onsite pickup and delivery / warranty service upgrades <sup>22</sup>  |         |   |  |  |
| 64 MB SO DIMM   | 133MHz NP SDRAM  | 19K4650 | USB Portable Diskette Drive   | 05K9276  | Universal 72 watt AC adapter<br>PC 2001-compliant<br>CIM and DMI 2.0-compliant<br>IBM ImageUltra Services available<br>IBM Rapid Restore PC available to protect software image and data<br>Personalized Web-based support <sup>31</sup><br>Setup Guide, Service and Troubleshooting Guide, Windows manual<br>International Warranty Service <sup>17</sup><br>24 hour x 7 day <sup>18</sup> toll-free hardware support during the warranty <sup>12</sup> |
| 128 MB SO DIMM  | 133MHz NP SDRAM  | 19K4652 | ThinkPad Removable Diskette Drive   | 08K9603  |  |
| 256 MB SO DIMM  | 133MHz NP SDRAM  | 19K4654 | ThinkPad R30/R31 Li-Ion Battery   | 02K6821  |  |
| 512 MB SO DIMM  | 133MHz NP SDRAM  | 19K4656 | ThinkPad 72W AC Adapter   | 02K6699  |  |
| IBM 32MB USB Memory Key   |  | 22P5296 | ThinkPad Port Replicator  | 02K8667  |  |
| SuperDisk (LS-240) UltraBay 2000  |  | 08K9616 | Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices) | 19K4480  |  |
| Zip 250MB Ultrabay 2000 Drive   |  | 00N8253 | 20GB HDD  | 08K9686  |  |
| 24X-10X CD-ROM Ultrabay 2000 Drive  |  | 05K9233 | 40GB HDD  | 08K9687  |  |
| 8X/4X/24X Max CD-RW Ultrabay 2000   |  | 22P9101 | 60GB HS Hard Disk 9.5mm (5400 rpm)  | 08K9688  |  |
| Ultralight 8X Max DVD Ultrabay 2000   |  | 22P9102 | IBM USB 2.0 Portable CD-RW Drive  | 22P5297  |  |
| CD-RW/DVD Combo II Ultrabay 2000  |  | 08K9701 | ThinkPad Portable 20GB Hard Disk Drive                                    | 10K0177  |  |
| Second HDD Adapter for Ultrabay 2000  |  | 08K6068 | IBM 1GB Microdrive  | 07N5574  |  |
| IBM ThinkPad Ultrabay Plus Carrier  |  | 22P5737 | IBM USB Mobile Mouse  | 33L3243  |  |
| IBM ThinkPad Ultrabay Plus c500 Cradle  |  | 22P5738 | ServicePac®, 22 2yr IOR 9x5 NBD   | 30L9190  |  |
| ThinkPad Ultrabay Plus Numeric Keypad   |  | 22P7330 | ServicePac 3yr IOR 9x5 NBD  | 30L9197  |  |
| Other options at <a href="http://ibm.com/pc/us/accessories">ibm.com/pc/us/accessories</a>                                     |  |         |   |  |  |

See footnotes for important warranty information  
 US models announced April 2, 2002  
 US models withdrawn effective October 2002

(R31TAA3) © IBM Corp. October 2002

| Type-model  | Processor   | GHz     | Memory <sup>11</sup>  | Screen    | Disk              | Optical   | Mini PCI<br>Comm Bay     | CDC<br>Modem | Ethernet<br>on<br>planar | Security<br>Chip | Preload  | Workhorse (W)<br>or Global (G)<br>model | Avail<br>date |
|---|---|---------|---|-----------|-------------------|-----------|--------------------------|--------------|--------------------------|------------------|--|---|---------------|
| 2656-A4U  | Celeron™  | 1.06    | 128MB   | 13.3" XGA | 20GB <sup>8</sup> | CD-ROM    | Open                     | Modem        | 10/100                   |                  | Windows® 2000  |   | Feb 2002      |
| 2656-AEU  | Celeron   | 1.06    | 128MB   | 13.3" XGA | 20GB              | CD-ROM    | Wi-Fi <sup>32</sup> /mod | None         | 10/100                   |                  | Windows 2000   |   | Feb 2002      |
| 2656-FFU  | Pentium® III-M  | 1.00    | 128MB   | 14.1" XGA | 20GB              | DVD-ROM   | Open                     | Modem        | 10/100                   |                  | Windows 2000   | G                                       | Mar 2002      |
| 2656-BEU  | Pentium III-M   | 1.13    | 128MB   | 13.3" XGA | 20GB              | CD-RW     | Wi-Fi/modem              | None         | 10/100                   |                  | Windows 2000   |   | Feb 2002      |
| 2656-EEU  | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 30GB              | DVD-ROM   | Wi-Fi/modem              | None         | 10/100                   |                  | Windows 2000   | W G                                     | Feb 2002      |
| 2656-E4U  | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 30GB              | DVD-ROM   | Open                     | Modem        | 10/100                   |                  | Windows 2000   | W G                                     | Feb 2002      |
| 2656-E7U  | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 30GB              | CD-RW     | Open                     | Modem        | 10/100                   | Yes              | Windows 2000   |   | Feb 2002      |
| 2656-HEU  | Pentium III-M   | 1.13    | 128MB   | 14.1" XGA | 40GB              | DVD/CD-RW | Wi-Fi/modem              | None         | 10/100                   | Yes              | Windows 2000   |   | Feb 2002      |
| Positioning<br>Processor                          | <i>Best blend of portability and essential features; two-spindle system</i><br><b>Intel® Mobile Celeron™ 1.06GHz with 133MHz Front Side Bus</b> or<br><b>Intel Mobile Pentium™ III-M 1.0 or 1.13GHz</b> with Speedstep™ technology <sup>1</sup> with 133MHz Front Side Bus<br><i>Celeron: 256KB / at processor speed; Pentium III: 512 KB / at processor speed</i><br><b>128MB<sup>9</sup> standard / 1GB maximum / SDRAM / non-parity / 133MHz / PC133 / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available</b> |         |   |           |                   |           |                          |              |                          |                  | <b>SOFTWARE<sup>14</sup></b>   |   |               |
| L2 cache  |   |         |   |           |                   |           |                          |              |                          |                  | <b>Windows 2000 models</b>   |   |               |
| Memory  |   |         |   |           |                   |           |                          |              |                          |                  | - Microsoft Windows 2000 Professional <sup>20</sup><br>- ConfigSafe®<br>◆ Disk-to-Disk Recovery (in hidden Service Partition)  |   |               |
| Diskette drive                                    | None standard / use optional Ultrabay™-based or USB-based diskette drive  |         |   |           |                   |           |                          |              |                          |                  | <b>INCLUDED SOFTWARE<sup>14</sup></b>  |   |               |
| CD-ROM  | <i>Some: CD-ROM / 24X-10X<sup>9</sup> speed / bootable / removable</i>  |         |   |           |                   |           |                          |              |                          |                  | <b>Preloaded</b>   |   |               |
| CD-RW   | <i>Some: CD-RW / 8X/4X/24X Max<sup>9</sup> / removable</i>  |         |   |           |                   |           |                          |              |                          |                  | • Access ThinkPad  |   |               |
| DVD-ROM   | <i>Some: DVD-ROM / 8X-3.3X<sup>9</sup> speed / removable</i>  |         |   |           |                   |           |                          |              |                          |                  | - Access Connections   |   |               |
| DVD-ROM/CD-RW                                     | <i>Some: DVD-ROM/CD-RW combo / 8X/8X/24X/8X<sup>21</sup> speed / removable</i>  |         |   |           |                   |           |                          |              |                          |                  | - Access Help  |   |               |
| Ultrabay 2000                                     | One modular bay for interchangeable devices (right side) / <b>Ultrabay™ Plus-compatible</b>   |         |   |           |                   |           |                          |              |                          |                  | - Access Support   |   |               |
| Disk  | <b>20, 30, or 40GB<sup>8</sup> (4200 rpm) / upgradeable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay</b>  |         |   |           |                   |           |                          |              |                          |                  | • Adobe® Acrobat   |   |               |
| Display   | <i>Some: 13.3" (337.8mm) XGA (1024x768) TFT color / Active Matrix</i><br><i>Some: 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix</i>  |         |   |           |                   |           |                          |              |                          |                  | • InterVideo WinDVD (DVD models)   |   |               |
| Graphics controller                               | <b>Intel 830MG Integrated Direct AGP 3D / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB<sup>11</sup> of system memory for graphics</b>   |         |   |           |                   |           |                          |              |                          |                  | • Norton AntiVirus   |   |               |
| Graphics - external                               | External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200  |         |   |           |                   |           |                          |              |                          |                  | • PC-Doctor™   |   |               |
| Keyboard  | 87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar <sup>13</sup> / pitch: 19mm; stroke: 2.7mm   |         |   |           |                   |           |                          |              |                          |                  | • ThinkPad Utilities   |   |               |
| ThinkLight™<br>UltraPort™                         | Illuminates the keyboard to improve visibility in low-light conditions<br>None  |         |   |           |                   |           |                          |              |                          |                  | • IBM Update Connector™ <sup>15</sup>  |   |               |
| Dimensions <sup>3</sup>                           | 12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm  |         |   |           |                   |           |                          |              |                          |                  | • Veritas RecordNOW (CD-RW mod)  |   |               |
| Approximate weight <sup>2</sup>                   | w/ battery and: <i>CD-ROM: 5.8 lbs; DVD: 5.8 lbs; CD-RW with 13.3": 6.0 lbs; CD-RW with 14.1": 6.1 lbs; DVD/CD-RW: 6.1 lbs</i>  |         |   |           |                   |           |                          |              |                          |                  | <b>Downloadable</b>  |   |               |
| Case material                                     | Color: black; All: ABS plastic  |         |   |           |                   |           |                          |              |                          |                  | • IBM Rapid Restore™ PC  |   |               |
| Battery - type                                    | Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus   |         |   |           |                   |           |                          |              |                          |                  | • IBM Data Transfer  |   |               |
| Battery - life <sup>10</sup>                      | <i>Celeron models: 2.4 to 2.6 hrs; Pentium III models: 2.9 to 3.1 hrs</i>   |         |   |           |                   |           |                          |              |                          |                  | • Universal Manageability Services™  |   |               |
| Architecture                                      | <b>Intel 830MG chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus, Mini PCI) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared)</b>  |         |   |           |                   |           |                          |              |                          |                  | • IBM Client Security Software (for security chip)   |   |               |
| Port Replicator                                   | Optional <b>ThinkPad Port Replicator</b> (no ThinkPad Dock support)   |         |   |           |                   |           |                          |              |                          |                  | <b>License</b>   |   |               |
| PC Card Std slots                                 | One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video   |         |   |           |                   |           |                          |              |                          |                  | - Lotus® SmartSuite® Millennium and Lotus Notes® Client 5.0  |   |               |
| Ports   | Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port   |         |   |           |                   |           |                          |              |                          |                  | <b>Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series</b> |   |               |
| Video out   | S-video out port (TV out) / one industry standard connector   |         |   |           |                   |           |                          |              |                          |                  |  |   |               |
| Mini PCI  | One Mini PCI type III slot (Communications Bay) / not customer upgradeable  |         |   |           |                   |           |                          |              |                          |                  |  |   |               |
| Wi-Fi <sup>32</sup> /modem                        | <i>Some: Mini PCI Wi-Fi<sup>32</sup> wireless<sup>4</sup>, Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K<sup>6</sup> V.90 (V.92-designed<sup>29</sup>) modem combo, Lucent® chipset</i>  |         |   |           |                   |           |                          |              |                          |                  |  |   |               |
| CDC   | One Communications Daughter Card (CDC) socket (open or modem) / not accessible  |         |   |           |                   |           |                          |              |                          |                  |  |   |               |
| Modem   | <i>Some: 56K<sup>6</sup> V.90 (V.92-designed<sup>29</sup>) CDC modem card / Lucent® chip set</i>  |         |   |           |                   |           |                          |              |                          |                  |  |   |               |
| Bluetooth™  | None  |         |   |           |                   |           |                          |              |                          |                  |  |   |               |
| Ethernet  | 10/100 ethernet on planar / Intel® 82562ET chipset  |         |   |           |                   |           |                          |              |                          |                  |  |   |               |
| Audio support                                     | Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)   |         |   |           |                   |           |                          |              |                          |                  |  |   |               |
| Security  | Power-on password / hard disk password / supervisor password / security keyhole<br><i>Some: IBM Embedded Security Subsystem<sup>33</sup> / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security<sup>16</sup></i>  |         |   |           |                   |           |                          |              |                          |                  |  |   |               |
| Limited warranty <sup>12</sup>                    | <b>1 year - EasyServ™<sup>19</sup> onsite pickup and delivery / service upgrades<sup>22</sup> available</b>   |         |   |           |                   |           |                          |              |                          |                  |  |   |               |
| 64 MB SO DIMM                                     | 133MHz NP SDRAM   | 19K4650 | USB Portable Diskette Drive   | 05K9276   |                   |           |                          |              |                          |                  |  |   |               |
| 128 MB SO DIMM                                    | 133MHz NP SDRAM   | 19K4652 | ThinkPad Removable Diskette Drive   | 08K9603   |                   |           |                          |              |                          |                  |  |   |               |
| 256 MB SO DIMM                                    | 133MHz NP SDRAM   | 19K4654 | ThinkPad R30/R31 Li-Ion Battery   | 02K6821   |                   |           |                          |              |                          |                  |  |   |               |
| 512 MB SO DIMM                                    | 133MHz NP SDRAM   | 19K4656 | ThinkPad 72W AC Adapter   | 02K6699   |                   |           |                          |              |                          |                  |  |   |               |
| IBM 32MB USB Memory Key                           |   | 22P5296 | ThinkPad Port Replicator  | 02K8667   |                   |           |                          |              |                          |                  |  |   |               |
| SuperDisk (LS-240) UltraBay 2000                  |   | 08K9616 | Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices) | 19K4480   |                   |           |                          |              |                          |                  |  |   |               |
| Zip 250MB Ultrabay 2000 Drive                     |   | 00N8253 | 20GB Hard Disk 9.5mm (4200 rpm)   | 08K9686   |                   |           |                          |              |                          |                  |  |   |               |
| 24X-10X CD-ROM Ultrabay 2000 Drive                |   | 05K9233 | 40GB HS Hard Disk 9.5mm (5400 rpm)  | 08K9816   |                   |           |                          |              |                          |                  |  |   |               |
| 8X/4X/24X Max CD-RW Ultrabay 2000                 |   | 22P9101 | 60GB HS Hard Disk 12.5mm (5400 rpm)                                       | 08K9688   |                   |           |                          |              |                          |                  |  |   |               |
| Ultralight 8X Max DVD Ultrabay 2000               |   | 22P9102 | ServicePac® <sup>21</sup> 1yr IOR 9x5 NBD                                 | 30L9188   |                   |           |                          |              |                          |                  |  |   |               |
| CD-RW/DVD Combo III Ultrabay 2000                 |   | 22P6980 | ServicePac 2yr IOR 9x5 NBD  | 30L9189   |                   |           |                          |              |                          |                  |  |   |               |
| Second HDD Adapter for Ultrabay 2000              |   | 08K6068 | ServicePac 3yr IOR 9x5 NBD  | 30L9195   |                   |           |                          |              |                          |                  |  |   |               |
| IBM ThinkPad Ultrabay Plus Carrier                |   | 22P5737 | ServicePac 2yr P&L P/U Depot  | 30L9191   |                   |           |                          |              |                          |                  |  |   |               |
| IBM ThinkPad Ultrabay Plus c500 Cradle            |   | 22P5738 | ServicePac 3yr P&L P/U Dmpot  | 30L9192   |                   |           |                          |              |                          |                  |  |   |               |
| ThinkPad Ultrabay Plus Numeric Keypad             |   | 22P7330 |   |           |                   |           |                          |              |                          |                  |  |   |               |
| Other options at <b>ibm.com/pc/us/accessories</b> |   |         |   |           |                   |           |                          |              |                          |                  |  |   |               |

See footnotes for important warranty information  
 US models announced January 22 or March 19, 2002  
 US models withdrawn effective July 2002 or January 2003

| Type-model | Processor      | Speed | Memory <sup>11</sup> | Screen    | Disk                    | Optical                    | Mini PCI<br>Comm Bay | Ethernet<br>on planar | Security<br>Chip | Preload         | Limited<br>warranty | Avail<br>date |
|------------|----------------|-------|----------------------|-----------|-------------------------|----------------------------|----------------------|-----------------------|------------------|-----------------|---------------------|---------------|
| 2656-99U   | Pentium® III-M | 1.06  | 128MB                | 13.3" XGA | 20GB <sup>8</sup> CD-RW | Wi-Fi <sup>32</sup> /modem | None                 | 10/100                | No               | Windows® XP Pro | 1 yr                | Apr 2002      |
| 2656-88U   | Pentium III-M  | 1.06  | 128MB                | 14.1" XGA | 30GB DVD/CD-RW          | Wi-Fi/modem                | None                 | 10/100                | No               | Windows XP Pro  | 1 yr                | Apr 2002      |
| 2656-77U   | Pentium III-M  | 1.06  | 128MB                | 14.1" XGA | 20GB CD-RW              | Wi-Fi/modem                | None                 | 10/100                | No               | Windows XP Pro  | 1 yr                | Aug 2002      |
| 2657-99U   | Pentium III-M  | 1.06  | 128MB                | 13.3" XGA | 20GB CD-RW              | Wi-Fi/modem                | None                 | 10/100                | No               | Windows XP Pro  | 3 yr                | Apr 2002      |
| 2657-88U   | Pentium III-M  | 1.06  | 128MB                | 14.1" XGA | 30GB DVD/CD-RW          | Wi-Fi/modem                | None                 | 10/100                | No               | Windows XP Pro  | 3 yr                | Apr 2002      |
| 2657-77U   | Pentium III-M  | 1.06  | 128MB                | 14.1" XGA | 20GB CD-RW              | Wi-Fi/modem                | None                 | 10/100                | No               | Windows XP Pro  | 3 yr                | Aug 2002      |

These educational models of the ThinkPad R31 notebook must be sold only to qualified education customers. Qualified institution/customer is a public or private K-12 (or higher) accredited school organized and operated exclusively for educational purposes for use by Qualified Students and/or Qualified Teachers.

This model for education is for sale direct from IBM or through an Authorized Education Reseller. The model or models for education are not available for resale to any other organization or individual.

|  |  |         |   |   |
|--|--|---------|---|---|
| Positioning Processor  | Best blend of portability and essential features; two-spindle system<br><b>Intel® Mobile Pentium® III-M 1.06GHz</b> with Speedstep™ technology <sup>1</sup> with 133MHz frontside bus  |         |   | <b>SOFTWARE<sup>14</sup></b><br><b>Windows XP Pro models</b><br>- Microsoft® Windows® XP Professional <sup>20</sup><br>✧ Disk-to-Disk Recovery (in hidden Service Partition)<br><br><b>INCLUDED SOFTWARE<sup>14</sup> (all)</b><br><b>Preloaded</b><br>• Access ThinkPad<br>- Access Connections<br>- Access Help<br>- Access Support<br>• Adobe® Acrobat<br>• InterVideo WinDVD (DVD models)<br>• Norton AntiVirus<br>• PC-Doctor™<br>• ThinkPad Utilities<br>• IBM Update Connector™.15<br>• Veritas RecordNOW<br><br><b>Downloadable</b><br>• IBM Rapid Restore™ PC<br>• IBM Data Transfer<br>• IBM Director Agen<br><br><b>License</b><br>- Lotus® SmartSuite® Millennium and Lotus Notes® Client 5.0 |
| L2 cache   | <b>512 KB</b> / at processor speed / ECC   |         |   |   |
| Memory   | <b>128MB</b> standard / 1GB max <sup>7</sup> / SDRAM / non-parity / 133MHz / PC133-compliant / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available   |         |   |   |
| Diskette drive   | None standard / use optional Ultrabay™-based or USB-based diskette drive   |         |   |   |
| CD-RW  | <i>Some:</i> CD-RW / 8X/4X/24X Max <sup>9</sup> / removable  |         |   |   |
| DVD-ROM/CD-RW  | <i>Some:</i> DVD-ROM/CD-RW combo / 8X/8X/24X/8X <sup>21</sup> speed / removable  |         |   |   |
| Ultrabay 2000  | One modular bay for interchangeable devices (right side) / <b>Ultrabay™ Plus</b> -compatible   |         |   |   |
| Disk   | <b>20</b> or <b>30GB<sup>8</sup></b> (4200 rpm) / upgradeable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay   |         |   |   |
| Display  | <i>Some:</i> <b>13.3"</b> (337.8mm) <b>XGA (1024x768) TFT color</b> / Active Matrix<br><i>Some:</i> <b>14.1"</b> (358.1mm) <b>XGA (1024x768) TFT color</b> / Active Matrix   |         |   |   |
| Graphics controller  | <b>Intel 830MG Integrated Direct AGP 3D</b> / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB <sup>11</sup> of system memory for graphics   |         |   |   |
| Graphics - external  | External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200   |         |   |   |
| Keyboard   | 87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar <sup>13</sup> / pitch: 19mm; stroke: 2.7mm  |         |   |   |
| ThinkLight™  | Illuminates the keyboard to improve visibility in low-light conditions   |         |   |   |
| UltraPort™   | None   |         |   |   |
| Dimensions <sup>3</sup>  | 12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm   |         |   |   |
| Approximate weight <sup>2</sup>  | w/ battery and: <b>13.3" TFT:</b> 6.0 lbs (2.7kg); <b>14.1" TFT:</b> 6.1 lbs (2.7kg)   |         |   |   |
| Case material  | <i>Color:</i> black; <i>All:</i> ABS plastic   |         |   |   |
| Battery - type   | Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus  |         |   |   |
| Battery - life <sup>10</sup>   | 2.9 hrs  |         |   |   |
| Architecture   | <b>Intel 830MG</b> chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus, Mini PCI) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared) |         |   |   |
| Port Replicator  | Optional <b>ThinkPad Port Replicator</b> (no ThinkPad Dock support)  |         |   |   |
| PC Card Std slots  | One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video  |         |   |   |
| Ports  | Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port  |         |   |   |
| Video out  | S-video out port (TV out) / one industry standard connector  |         |   |   |
| Mini PCI   | One Mini PCI type III slot (Communications Bay) / not customer upgradeable   |         |   |   |
| Wi-Fi <sup>32</sup> /modem   | Mini PCI Wi-Fi <sup>32</sup> wireless <sup>4</sup> , Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K <sup>6</sup> V.90 (V.92-designed <sup>29</sup> ) modem combo, Lucent® chipset  |         |   |   |
| CDC  | One Communications Daughter Card (CDC) socket / not accessible   |         |   |   |
| Open   | One Communications Daughter Card (CDC) socket open   |         |   |   |
| Ethernet   | 10/100 ethernet on planar / Intel® 82562ET chipset (physical layer)  |         |   |   |
| Audio support  | Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)  |         |   |   |
| Security   | Power-on password / hard disk password / supervisor password / security keyhole  |         |   |   |
| Limited warranty <sup>12</sup>   | 2656: <b>1 year</b> - EasyServ™.19 onsite pickup and delivery / service upgrades <sup>22</sup> available<br>2657: <b>3 years</b> /1 year battery - EasyServ onsite pickup and delivery / service upgrades available  |         |   |   |
| 64MB SO DIMM   | 133MHz NP SDRAM  | 19K4650 | USB Portable Diskette Drive   | 05K9276   |
| 128MB SO DIMM  | 133MHz NP SDRAM  | 19K4652 | ThinkPad R30/R31 Li-Ion Battery   | 02K6821   |
| 256MB SO DIMM  | 133MHz NP SDRAM  | 19K4654 | ThinkPad 72W AC Adapter   | 02K6699   |
| 512MB SO DIMM  | 133MHz NP SDRAM  | 19K4656 | ThinkPad Port Replicator  | 02K8667   |
| SuperDisk (LS-240)   | UltraBay 2000  | 08K9616 | Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices) | 19K4480   |
| Zip 250MB  | Ultrabay 2000 Drive  | 00N8253 | 20GB Hard Disk 9.5mm (4200 rpm)   | 08K9686   |
| 24X-10X CD-ROM   | Ultrabay 2000 Drive  | 05K9233 | 40GB HS Hard Disk 9.5mm (5400 rpm)  | 08K9816   |
| 8X/4X/24X Max  | CD-RW Ultrabay 2000  | 22P9101 | 60GB HS Hard Disk 12.5mm (5400 rpm)                                       | 08K9688   |
| Ultralight 8X  | Max DVD Ultrabay 2000  | 22P9102 | 2656: ServicePac®, 22 1yr IOR 9x5 NBD                                     | 30L9188   |
| CD-RW/DVD Combo  | III Ultrabay 2000  | 22P6980 | 2656: ServicePac 2yr IOR 9x5 NBD  | 30L9189   |
| Second HDD   | Adapter for Ultrabay 2000  | 08K6068 | 2656: ServicePac 3yr IOR 9x5 NBD  | 30L9195   |
| IBM ThinkPad   | Ultrabay Plus Carrier  | 22P5737 | 2656: ServicePac 2yr P&L P/U Depot  | 30L9191   |
| IBM ThinkPad   | Ultrabay Plus c500 Cradle  | 22P5738 | 2656: ServicePac 3yr P&L P/U Depot  | 30L9192   |
| ThinkPad   | Ultrabay Plus Numeric Keypad   | 22P7330 | 2657: ServicePac 2yr IOR 9x5 NBD  | 30L9190   |
| Other options at   | ibm.com/pc/us/accessories  |         | 2657: ServicePac 3yr IOR 9x5 NBD  | 30L9197   |
| Universal 72 watt AC adapter<br>PC 2001-compliant<br>CIM and DMI 2.0-compliant<br>IBM ImageUltra Services available<br>IBM Rapid Restore PC available to protect software image and data<br>Personalized Web-based support <sup>31</sup><br>Setup Guide, Service and Troubleshooting Guide, Windows manual<br>International Warranty Service <sup>17</sup><br>24 hour x 7 day <sup>18</sup> toll-free hardware support during the warranty <sup>12</sup> |  |         |   |   |

See footnotes for important warranty information  
US models announced April 30 or August 13, 2002  
US models withdrawn from marketing effective October 2002 or January 2003

(R31E) © IBM Corp. December 2002



| Type-model | Processor | Speed<br>GHz | Memory <sup>11</sup> | Screen    | Disk<br>GB <sup>8</sup> | Optical | Mini PCI<br>Comm Bay<br>wireless/modem | CDC<br>modem | Ethernet<br>on<br>planar | IEEE<br>1394 | Preload         | Workhorse (W)<br>or Global (G)<br>model | Avail<br>date |
|------------|-----------|--------------|----------------------|-----------|-------------------------|---------|--|--------------|--------------------------|--------------|-----------------|---|---------------|
| 2656-2GU   | Celeron®  | 1.13         | 128MB                | 13.3" XGA | 20GB                    | CD-ROM  | Open                                   | Modem        | 10/100                   |              | Windows® XP Pro | No                                      | Jun 2002      |
| 2656-1CU   | Celeron   | 1.13         | 128MB                | 14.1" XGA | 20GB                    | CD-ROM  | Open                                   | Modem        | 10/100                   |              | Windows XP Pro  | No                                      | Jun 2002      |
| 2656-2VU   | Celeron   | 1.13         | 128MB                | 13.3" XGA | 20GB                    | CD-ROM  | Wi-Fi <sup>32</sup> /modem             | Open         | 10/100                   | 1394         | Windows XP Pro  | No                                      | Jun 2002      |
| 2656-1FU   | Celeron   | 1.13         | 128MB                | 14.1" XGA | 20GB                    | CD-RW   | Open                                   | Modem        | 10/100                   |              | Windows XP Pro  | No                                      | Jun 2002      |
| 2656-1GU   | Celeron   | 1.13         | 128MB                | 14.1" XGA | 20GB                    | DVD     | Open                                   | Modem        | 10/100                   |              | Windows XP Home | No                                      | Jun 2002      |
| 2656-2HU   | Celeron   | 1.13         | 128MB                | 13.3" XGA | 20GB                    | CD-ROM  | Open                                   | Modem        | 10/100                   |              | Windows XP Home | No                                      | Jun 2002      |
| 2656-1BU   | Celeron   | 1.13         | 128MB                | 14.1" XGA | 20GB                    | CD-ROM  | Open                                   | Modem        | 10/100                   |              | Windows XP Home | No                                      | Aug 2002      |

|   |   |  |  |  |   |  |  |  |  |  |  |  |  |
|---|---|--|--|--|---|--|--|--|--|--|--|--|--|
| Positioning Processor<br>L2 cache<br>Memory   | <i>Best blend of portability and essential features; two-spindle system</i><br><b>Intel® Mobile Celeron® 1.13GHz with 133MHz frontside bus</b><br><b>256KB</b> <sup>7</sup> / at processor speed / ECC<br><b>128MB</b> standard / 1GB max <sup>7</sup> / SDRAM / non-parity / 133MHz / PC133 / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available  |  |  |  |   |  |  |  |  |  |  | <b>SOFTWARE<sup>14</sup></b><br><b>Windows XP Home models</b><br>- Microsoft® Windows® XP Home <sup>20</sup><br>⇨ Disk-to-Disk Recovery (in hidden Service Partition)  |  |
| Diskette drive<br>CD-ROM<br>CD-RW<br>DVD-ROM<br>Ultrabay 2000<br>Disk   | None standard / use optional Ultrabay™-based or USB-based diskette drive<br><i>Some:</i> CD-ROM / 24X-10X <sup>9</sup> speed / removable from Ultrabay 2000<br><i>Some:</i> CD-RW / 8X/4X/24X Max <sup>9</sup> / removable from Ultrabay 2000<br><i>Some:</i> DVD-ROM / 8X-3.3X Max <sup>9</sup> / removable from Ultrabay 2000<br>One modular bay for interchangeable devices (right side) / <b>Ultrabay™ Plus-compatible</b><br><b>20GB<sup>8</sup></b> (4200 rpm) / upgradeable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay |  |  |  |   |  |  |  |  |  |  | <b>Windows XP Pro models</b><br>- Microsoft® Windows® XP Professional <sup>20</sup><br>⇨ Disk-to-Disk Recovery (in hidden Service Partition)   |  |
| Display   | <i>Some:</i> <b>13.3"</b> (337.8mm) <b>XGA (1024x768) TFT color</b> / Active Matrix<br><i>Some:</i> <b>14.1"</b> (358.1mm) <b>XGA (1024x768) TFT color</b> / Active Matrix  |  |  |  |   |  |  |  |  |  |  | <b>INCLUDED SOFTWARE<sup>14</sup> (all)</b>  |  |
| Graphics controller   | <b>Intel 830MG Integrated Direct AGP 3D</b> / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB <sup>11</sup> of system memory for graphics  |  |  |  |   |  |  |  |  |  |  | <b>Preloaded</b><br>• Access ThinkPad<br>- Access Connections<br>- Access Help<br>- Access Support<br>• Adobe® Acrobat Reader<br>• InterVideo WinDVD (DVD models)<br>• Norton AntiVirus<br>• PC-Doctor™<br>• ThinkPad Utilities<br>• IBM Update Connector™ <sup>15</sup><br>• Veritas RecordNOW (CD-RW mod)  |  |
| Graphics - external   | External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200  |  |  |  |   |  |  |  |  |  |  |  |  |
| Keyboard  | 87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar <sup>13</sup> / pitch: 19mm; stroke: 2.7mm   |  |  |  |   |  |  |  |  |  |  |  |  |
| ThinkLight™<br>UltraPort™   | Illuminates the keyboard to improve visibility in low-light conditions<br>None  |  |  |  |   |  |  |  |  |  |  |  |  |
| Dimensions <sup>3</sup><br>Approximate weight <sup>2</sup><br>Case material<br>Battery - type<br>Battery - life <sup>10</sup>   | 12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm<br>w/ battery and: <i>CD-ROM:</i> 5.8lb (2.62kg); <i>DVD:</i> 5.75lb (2.61kg); <i>CD-RW:</i> 6.05lb (2.73kg)<br><i>Color:</i> black; <i>All:</i> ABS plastic<br>Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus<br><i>2VU:</i> 2.4 hrs; <i>Others:</i> 2.6 hrs   |  |  |  |   |  |  |  |  |  |  |  |  |
| Architecture  | <b>Intel 830MG</b> chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus, Mini PCI, TI TSB43AB22 IEEE 1394) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared)  |  |  |  |   |  |  |  |  |  |  | <b>Downloadable</b><br>• IBM Rapid Restore™ PC<br>• IBM Data Transfer<br>• IBM Director Agent  |  |
| Port Replicator<br>PC Card Std slots<br>Ports   | Optional <b>ThinkPad Port Replicator</b> (no ThinkPad Dock support)<br>One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video<br>Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / IEEE 1394 (4-pin) / no keyboard or mouse or serial port   |  |  |  |   |  |  |  |  |  |  | <b>License</b> (CD not included)<br>- Lotus® SmartSuite® Millennium and Lotus Notes® Stand Alone Client  |  |
| Video out<br>IEEE 1394 (FireWire)<br>Mini PCI<br>Wi-Fi <sup>32</sup> /modem   | S-video out port (TV out) / one industry standard connector<br><i>Some:</i> IEEE 1394 (FireWire) Port (4-pin)<br>One Mini PCI type III slot (Communications Bay) / not customer upgradeable<br><i>Some:</i> Mini PCI Wi-Fi <sup>32</sup> wireless <sup>4</sup> , Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K <sup>6</sup> V.90 (V.92-designed <sup>29</sup> ) modem combo, Lucent® chipset   |  |  |  |   |  |  |  |  |  |  |  |  |
| CDC<br>Modem<br>Ethernet<br>Audio support   | One Communications Daughter Card (CDC) socket (open or modem) / not accessible<br><i>Some:</i> 56K <sup>6</sup> V.90 (V.92-designed <sup>29</sup> ) CDC modem card / Lucent® chip set<br>10/100 ethernet on planar / Intel® 82562ET chipset<br>Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)  |  |  |  |   |  |  |  |  |  |  | <b>Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series</b> |  |
| Security  | Power-on password / hard disk password / supervisor password / security keyhole   |  |  |  |   |  |  |  |  |  |  |  |  |
| Limited warranty <sup>12</sup>  | <b>1 year</b> - EasyServ™ <sup>19</sup> onsite pickup and delivery / service upgrades <sup>22</sup> available   |  |  |  |   |  |  |  |  |  |  |  |  |
| 64 MB SO DIMM<br>128 MB SO DIMM<br>256 MB SO DIMM<br>512 MB SO DIMM<br>SuperDisk (LS-240)<br>Zip 250MB<br>24X-10X CD-ROM<br>8X/4X/24X Max CD-RW<br>Ultralight 8X Max DVD<br>CD-RW/DVD Combo III<br>Second HDD Adapter<br>IBM ThinkPad<br>IBM ThinkPad<br>ThinkPad<br>Portable Drive Bay 2000 (accepts 2000 media and storage devices)<br>ThinkPad Port Replicator | 133MHz NP SDRAM<br>133MHz NP SDRAM<br>133MHz NP SDRAM<br>133MHz NP SDRAM<br>UltraBay 2000<br>Ultrabay 2000 Drive<br>Ultrabay 2000 Drive<br>Max CD-RW Ultrabay 2000<br>Max DVD Ultrabay 2000<br>Combo III Ultrabay 2000<br>for Ultrabay 2000<br>Ultrabay Plus Carrier<br>Ultrabay Plus c500 Cradle<br>Ultrabay Plus Numeric Keypad<br>2000 (accepts Ultrabay media and storage devices)<br>Port Replicator   | 19K4650<br>19K4652<br>19K4654<br>19K4656<br>08K9616<br>00N8253<br>05K9233<br>22P9101<br>22P9102<br>22P6980<br>08K6068<br>22P5737<br>22P5738<br>22P7330<br>19K4480<br>02K8667 | IBM USB Portable Diskette Drive<br>IBM 128MB USB 2.0 Memory Key<br>TrackPoint Cap Collection<br>IBM USB 2.0 Portable CD-RW Drive<br>IBM ThinkPad USB 2.0 CardBus Adapter<br>IBM USB Serial Parallel Adapter<br>ThinkPad R30 Series Li-Ion Battery<br>ThinkPad 72W AC Adapter<br>20GB Hard Disk 9.5mm (4200 rpm)<br>40GB HS Hard Disk 9.5mm (5400 rpm)<br>60GB HS Hard Disk 12.5mm (5400 rpm)<br>ServicePac™ <sup>22</sup> 1yr IOR 9x5 NBD<br>ServicePac 2yr IOR 9x5 NBD<br>ServicePac 3yr IOR 9x5 NBD<br>ServicePac 2yr P&L P/U Depot<br>ServicePac 3yr P&L P/U Depot<br>Other options at <a href="http://ibm.com/pc/us/accessories">ibm.com/pc/us/accessories</a> | 05K9276<br>22P8998<br>73P2698<br>22P5297<br>33L3245<br>22P5298<br>02K6821<br>02K6699<br>08K9686<br>08K9816<br>08K9688<br>30L9188<br>30L9189<br>30L9195<br>30L9191<br>30L9192 | Universal 72 watt AC adapter<br>PC 2001-compliant<br>CIM and DMI 2.0-compliant<br>IBM ImageUltra Services available<br>IBM Rapid Restore PC available to protect software image and data<br>Personalized Web-based support <sup>31</sup><br>Proactive e-mail updates <sup>31</sup><br>Setup Guide, Service and Troubleshooting Guide, Windows manual<br>International Warranty Service <sup>17</sup><br>24x7 <sup>18</sup> toll-free support for warranty-related issues during the warranty period <sup>12</sup> |  |  |  |  |  |  |  |  |

See footnotes for important warranty information

US models announced June 4 or August 13, 2002

US models withdrawn from marketing effective October 2002 or January 2003

(R31J) © IBM Corp. December 2002

| Type-model  | Processor   | GHz             | Memory <sup>11</sup> | Screen                                    | Disk              | Optical | Mini PCI<br>Comm Bay  | CDC<br>Modem | Ethernet<br>on<br>planar | Security<br>Chip | Preload   | Workhorse (W)<br>or Global (G)<br>model | Avail<br>date |
|---|---|-----------------|----------------------|---|-------------------|---------|---|--------------|--------------------------|------------------|---|---|---------------|
| 2657-LLU  | Pentium®III-M   | 1.00            | 128MB                | 14.1" XGA                                 | 20GB <sup>8</sup> | DVD-ROM | Open  | Modem        | 10/100                   | No               | Windows® 2000   |   | Mar 2002      |
| 2657-MMU  | PentiumIII-M  | 1.00            | 128MB                | 14.1" XGA                                 | 20GB              | DVD-ROM | Open  | Modem        | 10/100                   | No               | Windows XP Pro  |   | Mar 2002      |
| 2657-E4U  | PentiumIII-M  | 1.13            | 128MB                | 14.1" XGA                                 | 30GB              | DVD-ROM | Open  | Modem        | 10/100                   | No               | Windows 2000  | W G                                     | Mar 2002      |
| 2657-J1U  | PentiumIII-M  | 1.13            | 256MB                | 14.1" XGA                                 | 30GB              | DVD-ROM | Open  | Modem        | 10/100                   | No               | Windows 2000  | W G                                     | Mar 2002      |
| 2657-E5U  | PentiumIII-M  | 1.13            | 128MB                | 14.1" XGA                                 | 30GB              | DVD-ROM | Open  | Modem        | 10/100                   | No               | Windows XP Pro  | W G                                     | Mar 2002      |
| 2657-J2U  | PentiumIII-M  | 1.13            | 256MB                | 14.1" XGA                                 | 30GB              | DVD-ROM | Open  | Modem        | 10/100                   | No               | Windows XP Pro  | W G                                     | Mar 2002      |
| 2657 models have a 3 year limited warranty (other 2656 ThinkPad R31 systems have a 1 year limited warranty) |   |                 |                      |   |                   |         |   |              |                          |                  |   |   |               |
| Positioning Processor   | Best blend of portability and essential features; two-spindle system<br>Intel® Mobile Pentium® III Processor-M 1.0 or 1.13GHz with Speedstep™ technology <sup>1</sup> with 133MHz Front Side Bus  |                 |                      |   |                   |         |   |              |                          |                  | SOFTWARE <sup>14</sup>  |   |               |
| L2 cache  | 512 KB / at processor speed   |                 |                      |   |                   |         |   |              |                          |                  | Windows XP Pro models   |   |               |
| Memory  | 128MB or 256MB standard / 1GB maximum <sup>7</sup> / SDRAM / non-parity / 133MHz / PC133 / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available  |                 |                      |   |                   |         |   |              |                          |                  | - Microsoft® Windows® XP Professional <sup>20</sup><br>✧ Disk-to-Disk Recovery (in hidden Service Partition)  |   |               |
| Diskette drive  | None standard / use optional Ultrabay™-based or USB-based diskette drive  |                 |                      |   |                   |         |   |              |                          |                  | Windows 2000 models   |   |               |
| DVD-ROM   | DVD-ROM / 8X-3.3X <sup>9</sup> speed / removable  |                 |                      |   |                   |         |   |              |                          |                  | - Microsoft Windows 2000 Professional <sup>20</sup>   |   |               |
| Ultrabay 2000   | One modular bay for interchangeable devices (right side) / Ultrabay™ Plus-compatible  |                 |                      |   |                   |         |   |              |                          |                  | - ConfigSafe®   |   |               |
| Disk  | 20, 30, or 40GB <sup>8</sup> (4200 rpm) / upgradable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay   |                 |                      |   |                   |         |   |              |                          |                  | ✧ Disk-to-Disk Recovery (in hidden Service Partition)   |   |               |
| Display   | 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix  |                 |                      |   |                   |         |   |              |                          |                  | INCLUDED SOFTWARE <sup>14</sup> (all)   |   |               |
| Graphics controller   | Intel 830MG Integrated Direct AGP 3D / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB <sup>11</sup> of system memory for graphics   |                 |                      |   |                   |         |   |              |                          |                  | Preloaded   |   |               |
| Graphics - external   | External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200  |                 |                      |   |                   |         |   |              |                          |                  | • Access ThinkPad   |   |               |
| Keyboard  | 87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar <sup>13</sup> / pitch: 19mm; stroke: 2.7mm   |                 |                      |   |                   |         |   |              |                          |                  | - Access Connections  |   |               |
| ThinkLight™   | Illuminates the keyboard to improve visibility in low-light conditions  |                 |                      |   |                   |         |   |              |                          |                  | - Access Help   |   |               |
| UltraPort™  | None  |                 |                      |   |                   |         |   |              |                          |                  | - Access Support  |   |               |
| Dimensions <sup>3</sup>   | 12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm  |                 |                      |   |                   |         |   |              |                          |                  | • Adobe® Acrobat  |   |               |
| Approximate weight <sup>2</sup>   | w/ battery and DVD: 5.8 lbs (2.6 kg)  |                 |                      |   |                   |         |   |              |                          |                  | • InterVideo WinDVD (DVD models)  |   |               |
| Case material   | Color: black; All: ABS plastic  |                 |                      |   |                   |         |   |              |                          |                  | • Norton AntiVirus  |   |               |
| Battery - type  | Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus   |                 |                      |   |                   |         |   |              |                          |                  | • PC-Doctor™  |   |               |
| Battery - life <sup>10</sup>  | 3.1 hrs   |                 |                      |   |                   |         |   |              |                          |                  | • ThinkPad Utilities  |   |               |
| Architecture  | Intel 830MG chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus, Mini PCI) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared) |                 |                      |   |                   |         |   |              |                          |                  | • IBM Update Connector™.15  |   |               |
| Port Replicator   | Optional ThinkPad Port Replicator (no ThinkPad Dock support)  |                 |                      |   |                   |         |   |              |                          |                  | • Veritas RecordNOW (CD-RW mod)   |   |               |
| PC Card Std slots   | One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1   |                 |                      |   |                   |         |   |              |                          |                  | Downloadable  |   |               |
| Ports   | Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port   |                 |                      |   |                   |         |   |              |                          |                  | • IBM Rapid Restore™ PC   |   |               |
| Video out   | S-video out port (TV out) / one industry standard connector   |                 |                      |   |                   |         |   |              |                          |                  | • IBM Data Transfer   |   |               |
| Mini PCI  | One Mini PCI type III slot (Communications Bay) / not customer upgradable   |                 |                      |   |                   |         |   |              |                          |                  | • IBM Director Agent  |   |               |
| Wi-Fi <sup>32</sup> wireless  | None  |                 |                      |   |                   |         |   |              |                          |                  | • IBM Client Security Software (for security chip)  |   |               |
| CDC   | One Communications Daughter Card (CDC) socket / not accessible  |                 |                      |   |                   |         |   |              |                          |                  | License   |   |               |
| Modem   | 56K <sup>6</sup> V.90 (V.92-designed <sup>29</sup> ) CDC modem card / Lucent® chip set  |                 |                      |   |                   |         |   |              |                          |                  | - Lotus® SmartSuite® Millennium and Lotus Notes® Client 5.0   |   |               |
| Bluetooth™  | None  |                 |                      |   |                   |         |   |              |                          |                  | Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series |   |               |
| Ethernet  | 10/100 ethernet on planar / Intel® 82562ET chipset  |                 |                      |   |                   |         |   |              |                          |                  |   |   |               |
| Audio support   | Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)   |                 |                      |   |                   |         |   |              |                          |                  |   |   |               |
| Security  | Power-on password / hard disk password / supervisor password / security keyhole   |                 |                      |   |                   |         |   |              |                          |                  |   |   |               |
| Limited warranty <sup>12</sup>  | 3 years/1 year battery - EasyServ™.19 onsite pickup and delivery  |                 |                      |   |                   |         |   |              |                          |                  |   |   |               |
| Service options   | Service upgrades <sup>22</sup> provide up to five years of onsite or depot repair service coverage from date of ThinkPad purchase (including warranty period)   |                 |                      |   |                   |         |   |              |                          |                  |   |   |               |
| 64 MB SO DIMM   |   | 133MHz NP SDRAM | 19K4650              | USB Portable Diskette Drive               |                   | 05K9276 | Universal 72 watt AC adapter                                      |              |                          |                  |   |   |               |
| 128 MB SO DIMM  |   | 133MHz NP SDRAM | 19K4652              | ThinkPad Removable Diskette Drive         |                   | 08K9603 | PC 2001-compliant   |              |                          |                  |   |   |               |
| 256 MB SO DIMM  |   | 133MHz NP SDRAM | 19K4654              | ThinkPad R30/R31 Li-Ion Battery           |                   | 02K6821 | CIM and DMI 2.0-compliant   |              |                          |                  |   |   |               |
| 512 MB SO DIMM  |   | 133MHz NP SDRAM | 19K4656              | ThinkPad 72W AC Adapter                   |                   | 02K6699 | IBM ImageUltra™ Services available                                |              |                          |                  |   |   |               |
| IBM 32MB USB Memory Key   |   |                 | 22P5296              | ThinkPad Port Replicator                  |                   | 02K8667 | IBM Rapid Restore PC available to protect software image and data |              |                          |                  |   |   |               |
| SuperDisk (LS-240) UltraBay 2000  |   |                 | 08K9616              | Portable Drive Bay 2000 (accepts Ultrabay |                   |         | Personalized Web-based support <sup>31</sup>                      |              |                          |                  |   |   |               |
| Zip 250MB Ultrabay 2000 Drive   |   |                 | 00N8253              | 2000 media and storage devices)           |                   | 19K4480 | Setup Guide, Service and Trouble-                                 |              |                          |                  |   |   |               |
| 24X-10X CD-ROM Ultrabay 2000 Drive  |   |                 | 05K9233              | 20GB Hard Disk 9.5mm (4200 rpm)           |                   | 08K9686 | shooting Guide, Windows manual                                    |              |                          |                  |   |   |               |
| 8X/4X/24X Max CD-RW Ultrabay 2000   |   |                 | 22P9101              | 40GB HS Hard Disk 9.5mm (5400 rpm)        |                   | 08K9816 | International Warranty Service <sup>17</sup>                      |              |                          |                  |   |   |               |
| Ultralight 8X Max DVD Ultrabay 2000   |   |                 | 22P9102              | 60GB HS Hard Disk 12.5mm (5400 rpm)       |                   | 08K9688 | 24 hour x 7 day <sup>18</sup> toll-free hardware                  |              |                          |                  |   |   |               |
| CD-RW/DVD Combo III Ultrabay 2000   |   |                 | 22P6980              | IBM USB 2.0 Portable CD-RW Driv           |                   | 22P5297 | support during the warranty <sup>12</sup>                         |              |                          |                  |   |   |               |
| Second HDD Adapter for Ultrabay 2000  |   |                 | 08K6068              | ThinkPad Portable 20GB Hard DiskDrive     |                   | 10K0177 |   |              |                          |                  |   |   |               |
| IBM ThinkPad Ultrabay Plus Carrier  |   |                 | 22P5737              | IBM 1GB Microdrive                        |                   | 07N5574 |   |              |                          |                  |   |   |               |
| IBM ThinkPad Ultrabay Plus c500 Cradle  |   |                 | 22P5738              | IBM Optical 3-Button Travel Wheel Mouse   |                   | 31P7410 |   |              |                          |                  |   |   |               |
| ThinkPad Ultrabay Plus Numeric Keypad   |   |                 | 22P7330              | ServicePac®.22 2yr IOR 9x5 NBD            |                   | 30L9190 |   |              |                          |                  |   |   |               |
| Other options at <a href="http://ibm.com/pc/us/accessories">ibm.com/pc/us/accessories</a>                   |   |                 |                      | ServicePac 3yr IOR 9x5 NBD                |                   | 30L9197 |   |              |                          |                  |   |   |               |

See footnotes for important warranty information

(R313) © IBM Corp. March 2003

US models announced March 5 or 19, 2002

US models withdrawn effective January 2003 or April 2003



| Type-model  | Processor   | Speed<br>GHz | Memory <sup>11</sup>                      | Screen    | Disk<br>GB <sup>8</sup> | Optical<br>in Ultrabay<br>2000 | Mini PCI<br>Comm Bay<br>wireless/modem | CDC<br>modem | Ethernet<br>on<br>planar | IEEE<br>1394 | Preload  | Workhorse (W)<br>or Global (G)<br>model | Avail<br>date |
|---|---|--------------|---|-----------|-------------------------|--------------------------------|--|--------------|--------------------------|--------------|--|---|---------------|
| 2656-L2U  | Celeron®  | 1.2          | 128MB                                     | 13.3" XGA | 20GB                    | CD-ROM                         | Open                                   | Modem        | 10/100                   |              | Windows® XP Pro  | No                                      | Sep 2002      |
| 2656-L6U  | Celeron   | 1.2          | 128MB                                     | 13.3" XGA | 20GB                    | CD-ROM                         | Wi-Fi <sup>32</sup> /modem             | Open         | 10/100                   | 1394         | Windows XP Pro   | No                                      | Sep 2002      |
| 2656-M2U  | Celeron   | 1.2          | 128MB                                     | 14.1" XGA | 20GB                    | CD-ROM                         | Open                                   | Modem        | 10/100                   |              | Windows XP Pro   | No                                      | Sep 2002      |
| 2656-NYU  | Celeron   | 1.2          | 128MB                                     | 14.1" XGA | 20GB                    | Combo III                      | Open                                   | Modem        | 10/100                   |              | Windows XP Pro   | No                                      | Sep 2002      |
| 2656-L1U  | Celeron   | 1.2          | 128MB                                     | 13.3" XGA | 20GB                    | CD-ROM                         | Open                                   | Modem        | 10/100                   |              | Windows XP Home  | No                                      | Sep 2002      |
| 2656-LBU  | Celeron   | 1.2          | 256MB                                     | 14.1" XGA | 30GB                    | None (open)                    | Open                                   | Modem        | 10/100                   |              | Windows XP Home  | No                                      | Sep 2002      |
| 2656-NAU  | Celeron   | 1.2          | 128MB                                     | 14.1" XGA | 20GB                    | DVD                            | Open                                   | Modem        | 10/100                   |              | Windows XP Home  | No                                      | Sep 2002      |
| Positioning<br>Processor<br>L2 cache<br>Memory  | <i>Best blend of portability and essential features; two-spindle system</i><br><b>Intel® Mobile Celeron® 1.20GHz with 133MHz frontside bus</b><br><b>256KB</b> / at processor speed / ECC<br><b>128MB</b> or <b>256MB</b> standard / 1GB max <sup>7</sup> / SDRAM / non-parity / 133MHz / PC133 / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available   |              |   |           |                         |                                |  |              |                          |              | <b>SOFTWARE<sup>14</sup></b><br><b>Windows XP Home models</b><br>- Microsoft® Windows® XP Home <sup>20</sup><br>✧ Disk-to-Disk Recovery (in hidden Service Partition)  |   |               |
| Diskette drive<br>CD-ROM<br>Combo<br>DVD-ROM<br>Ultrabay 2000<br>Disk                     | None standard / use optional Ultrabay™-based or USB-based diskette drive<br><i>Some:</i> CD-ROM / 24X-10X <sup>9</sup> speed / removable from Ultrabay 2000<br><i>Some:</i> DVD-ROM/CD-RW Combo III / 16X/10X/24X/8X <sup>21</sup> / removable from Ultrabay 2000<br><i>Some:</i> DVD-ROM / 8X-3.3X Max <sup>9</sup> / removable from Ultrabay 2000<br>One modular bay for interchangeable devices (right side) / <b>Ultrabay™ Plus</b> -compatible<br><b>20GB<sup>8</sup></b> (4200 rpm) or <b>30GB</b> (4200 rpm) / upgradable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay |              |   |           |                         |                                |  |              |                          |              | <b>Windows XP Pro models</b><br>- Microsoft® Windows® XP Professional <sup>20</sup><br>✧ Disk-to-Disk Recovery (in hidden Service Partition)   |   |               |
| Display   | <i>Some:</i> <b>13.3"</b> (337.8mm) <b>XGA (1024x768) TFT color</b> / Active Matrix<br><i>Some:</i> <b>14.1"</b> (358.1mm) <b>XGA (1024x768) TFT color</b> / Active Matrix  |              |   |           |                         |                                |  |              |                          |              | <b>INCLUDED SOFTWARE<sup>14</sup> (all)</b>  |   |               |
| Graphics controller   | <b>Intel 830MG Integrated Direct AGP 3D</b> / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB <sup>11</sup> of system memory for graphics  |              |   |           |                         |                                |  |              |                          |              |  |   |               |
| Graphics - external   | External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200  |              |   |           |                         |                                |  |              |                          |              |  |   |               |
| Keyboard  | 87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar <sup>13</sup> / pitch: 19mm; stroke: 2.7mm   |              |   |           |                         |                                |  |              |                          |              |  |   |               |
| ThinkLight™   | Illuminates the keyboard to improve visibility in low-light conditions / no UltraPort™  |              |   |           |                         |                                |  |              |                          |              |  |   |               |
| Dimensions <sup>3</sup><br>Approximate weight <sup>2</sup> w/ battery and:                | 12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm<br><i>CD-ROM:</i> 5.8 lb (2.62kg); <i>DVD:</i> 5.75 lb (2.61kg);<br><i>Combo:</i> 6.05 lb (2.73kg); <i>Open LBU:</i> 5.3 lb (2.41kg)   |              |   |           |                         |                                |  |              |                          |              |  |   |               |
| Case material<br>Battery - type<br>Battery - life <sup>10</sup>                           | <i>Color:</i> black; <i>All:</i> ABS plastic<br>Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus<br><i>Wireless L6U:</i> 2.4 hrs; <i>Others:</i> 2.6 hrs   |              |   |           |                         |                                |  |              |                          |              |  |   |               |
| Architecture  | <b>Intel 830MG</b> chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus, Mini PCI, TI TSB43AB22 IEEE 1394) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared)<br>Optional <b>ThinkPad Port Replicator</b> (no ThinkPad Dock support)<br>One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1  |              |   |           |                         |                                |  |              |                          |              |  |   |               |
| Port Replicator<br>PC Card Std slots<br>Ports   | Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / IEEE 1394 (4-pin) / no keyboard or mouse or serial port   |              |   |           |                         |                                |  |              |                          |              |  |   |               |
| Video out<br>IEEE 1394<br>Mini PCI<br>Wi-Fi <sup>32</sup> /modem                          | S-video out port (TV out) / one industry standard connector<br><i>Some:</i> IEEE 1394 (FireWire) Port (4-pin)<br>One Mini PCI type III slot (Communications Bay) / not customer upgradable<br><i>Some:</i> Mini PCI Wi-Fi <sup>32</sup> wireless <sup>4</sup> , Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K <sup>6</sup> V.90 (V.92-designed <sup>29</sup> ) modem combo, Lucent® chipset  |              |   |           |                         |                                |  |              |                          |              |  |   |               |
| CDC<br>Modem<br>Ethernet<br>Audio support   | One Communications Daughter Card (CDC) socket (open or modem) / not accessible<br><i>Some:</i> 56K <sup>6</sup> V.90 (V.92-designed <sup>29</sup> ) CDC modem card / Lucent® chip set<br>10/100 ethernet on planar / Intel® 82562ET chipset<br>Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)  |              |   |           |                         |                                |  |              |                          |              |  |   |               |
| Security  | Power-on password / hard disk password / supervisor password / security keyhole   |              |   |           |                         |                                |  |              |                          |              |  |   |               |
| Limited warranty <sup>12</sup>  | <b>1 year</b> - EasyServ™ <sup>19</sup> onsite pickup and delivery / service upgrades <sup>22</sup> available   |              |   |           |                         |                                |  |              |                          |              |  |   |               |
| 64 MB SO DIMM   | 133MHz NP SDRAM   | 19K4650      | IBM 128MB USB 2.0 Memory Key              | 22P8998   |                         |                                |  |              |                          |              |  |   |               |
| 128 MB SO DIMM  | 133MHz NP SDRAM   | 19K4652      | IBM USB 2.0 Portable CD-RW Drive          | 22P5297   |                         |                                |  |              |                          |              |  |   |               |
| 256 MB SO DIMM  | 133MHz NP SDRAM   | 19K4654      | IBM ThinkPad USB 2.0 CardBus Adapter      | 33L3245   |                         |                                |  |              |                          |              |  |   |               |
| 512 MB SO DIMM  | 133MHz NP SDRAM   | 19K4656      | IBM USB Serial Parallel Adapter           | 22P5298   |                         |                                |  |              |                          |              |  |   |               |
| ThinkPad Removable Diskette Drive   |   | 08K9603      | ThinkPad R30 Series Li-Ion Battery        | 02K6821   |                         |                                |  |              |                          |              |  |   |               |
| Zip 250MB Ultrabay 2000 Drive   |   | 00N8253      | ThinkPad 72W AC Adapter                   | 02K6699   |                         |                                |  |              |                          |              |  |   |               |
| 24X-10X CD-ROM Ultrabay 2000 Drive  |   | 05K9233      | 20GB Hard Disk Drive                      | 08K9686   |                         |                                |  |              |                          |              |  |   |               |
| Ultralight 8X Max DVD Ultrabay 2000   |   | 22P9102      | 40GB Hard Disk Drive                      | 08K9687   |                         |                                |  |              |                          |              |  |   |               |
| CD-RW/DVD Combo III Ultrabay 2000   |   | 22P6980      | 40GB HS Hard Disk 9.5mm (5400 rpm)        | 08K9816   |                         |                                |  |              |                          |              |  |   |               |
| Second HDD Adapter for Ultrabay 2000  |   | 08K6068      | 60GB HS Hard Disk 12.5mm (5400 rpm)*      | 08K9688   |                         |                                |  |              |                          |              |  |   |               |
| IBM ThinkPad Ultrabay Plus Carrier  |   | 22P5737      | ServicePac® <sup>22</sup> 1yr IOR 9x5 NBD | 30L9188   |                         |                                |  |              |                          |              |  |   |               |
| IBM ThinkPad Ultrabay Plus c500 Cradle  |   | 22P5738      | ServicePac 2yr IOR 9x5 NBD                | 30L9189   |                         |                                |  |              |                          |              |  |   |               |
| ThinkPad Ultrabay Plus Numeric Keypad   |   | 22P7330      | ServicePac 3yr IOR 9x5 NBD                | 30L9195   |                         |                                |  |              |                          |              |  |   |               |
| Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)                 |   | 19K4480      | ServicePac 4yr IOR 9x5 NBD                | 69P9194   |                         |                                |  |              |                          |              |  |   |               |
| ThinkPad Port Replicator  |   | 02K8667      | ServicePac 5yr IOR 9x5 NBD                | 69P9196   |                         |                                |  |              |                          |              |  |   |               |
| IBM High Rate Wireless LAN PC Card 128  |   | 09N9904      | ServicePac 2yr P&L P/U Depot              | 30L9191   |                         |                                |  |              |                          |              |  |   |               |
| IBM USB Portable Diskette Drive   |   | 05K9276      | ServicePac 3yr P&L P/U Depot              | 30L9192   |                         |                                |  |              |                          |              |  |   |               |
| Other options at <a href="http://ibm.com/pc/us/accessories">ibm.com/pc/us/accessories</a> |   |              |   |           |                         |                                |  |              |                          |              | Universal 72 watt AC adapter<br>PC 2001-compliant<br>CIM and DMI 2.0-compliant<br>ACPI 1.0b and 2.0-compliant<br>IBM ImageUltra™ Services available<br>IBM Rapid Restore PC available to protect software image and data<br>Personalized Web-based support <sup>31</sup><br>Proactive e-mail updates <sup>31</sup><br>Setup Guide, Service and Trouble-shooting Guide, Windows manual<br>International Warranty Service <sup>17</sup><br>24x7 <sup>18</sup> toll-free support for warranty-related issues during the warranty period <sup>12</sup> |   |               |