## **証 ThinkPad 365ED - withdrawn**

IBM® ThinkPad®:	≈ 365ED	
Processor upgrade	10.4" dual scan - CD-ROM  IBM 5x86c™ 100/33 MHz (Cyrix) / integrated math coprocessor  None	
Processor upgrade Memory cache Diskette (not internal) CD-ROM (not remove)	16 KB in 5x86c (write-back) / no L2 cache	
Price Type - model Preload (see side) Disk - capacity Disk - ms / interface Available date Withdrawn date	2625-W9G Windows 95 <b>540 MB</b> 13 ms / EIDE / PIO Mode 3 May 1996 October 1996	
Display - diagonal size Display - type Display - color Display - contrast	e 10.4" Dual scan VGA color / 640 x 480 256 simultaneous colors 30 to 1	
Graphics - controller Graphics - external Graph - arch/data path	Chips and Technologies™ 65545 with 1 MB DRAM External SVGA to 1024 x 768 w/ 256 colors up to 70 Hz VL-Bus 2.0 local bus / 32 bit / Simultaneous LCD and CRT / 180 degree tilt	
Memory - std / max Mem - upgrade	8 MB / 24 MB 70 ns / non-parity / 3.3 volt / fast page 1 socket for one JEDEC 72 pin SO DIMM of 4 or 16 MB	
Keyboard / # of keys Keyboard slope Pointing Ext keyboard support	Full size alp/num / 85 (8 Fn key functions) Yes (legs pop out) TrackPoint III™ Yes (with option cable or Port Replicator)	Liftable (pop-up) keyboard to access and remove battery (and upgrade memory and disk);
Dimensions (cubic in) Weight (with battery) Battery - type Battery - life Charge time - on / off	11.7 x 8.3 x 2.0" (194 cubic inches) 6.4 pounds NiMH/non-intelligent 2.3 hours 6 hrs / 2 hrs	
Architecture  Docking Station Port replicator PCMCIA™ 2.1 slots Serial / parallel ports Other features	ISA (audio, PCMCIA, diskette, serial, parallel, 240 pin external expansion) VL-Bus 2.0 / 32 bit / 25 MHz (graphics, disk) None Port Replicator and Charger (with built-in battery charger and palm rest) 2 Type I or 2 Type II or 1 Type III One 9 pin; 16550A / one (IEEE P1284, EPP, ECP, bidirectional) APM-aware BIOS / Universal AC adapter (35 watts) / Phoenix™ BIOS	
MPEG decoder Data/fax modem Audio support	None None 16 bit audio chip / 18 voice MIDI FM Synthesis / ESS1688 with OPL3 Internal speaker / .5 watt / dial volume control / internal microphone Input inch (stores) / microphone inch / output inch (stores)	
Audio in/out jacks Infrared ports	Input jack (stereo) / microphone jack / output jack (stereo) Joystick/MIDI port (includes Joystick/MIDI cable) Infrared port in back / IrDA 1.0 compatible / up to 115 Kbps	
Security	Power-on password / Supervisor password / Locking device keyhole (Kensington™ MicroSaver™ cable lock) / keyboard lock (requires Kensington)	
Preinstalled software Warranty	Windows 95 with utilities and applications (listed to right)  1 year - ThinkPad EasyServ (optional Overnight Repair Option) or carry-in	

ThinkPad 365 (CD-ROM models) strengths:

- **□** Entry-priced CD-ROM notebook
- Integrated audio, microphone, speaker
- Simultaneous external diskette
- Joystick/MIDI port
- Infrared port
- MPC2 compliant

## **WINDOWS 95 PRELOAD**

- Microsoft Windows 95
- Online Users Guide
- Diskette Factory
- PC Card Director 1.4 Triton CoSession™ Host
- Puma TranXit™
- NetFinity for Windows
- CompuServ™ for Windows

The Port Replicator and Charger provide cable management, a battery charger for an optional second battery, a palm rest when installed on the system, and has complete port replication.

The Port Replicator can charge a battery whether or not a ThinkPad is connected to it. When the ThinkPad is attached to the Port Replicator, it will attempt to recharge the battery in ThinkPad first (if there is one) before charging the battery in the Port Replicator.

Port Replicator and Charger connectors:

- Serial (RS-232, 9 pin)
- Parallel (EPP, ECP, 25 pin) External display (15 pin)
- Keyboard
- Mouse
- Diskette drive (26 pin)
- Game with MIDI support (15 pin)
- Audio in (3.5 mm)
- Audio out (3.5 mm)
- DC input connector
- Spare battery connector (to charge 2nd battery)

Options for ThinkPad 365:

- 4 MB SO DIMM 3.3v non-parity 72 pin 92G7287 16 MB SO DIMM 3.3v non-parity 72 pin 92G7293
- 810 MB EIDE HDD 13 ms Mode 4 1.08 GB EIDE HDD 13 ms Mode 4 42H4012
- 69H7956
- (old) 38H6303 - Port Replicator and Charger

85G6719

- replaced by 75H7529 - NiMH Battery Pack 38H6304
- Setup is entered by Ctrl + Alt + F11 from any

full-screen DOS prompt

Fn + F2 = Battery guage

- 35 watt AC Ádapter - 2 pin

Fn + F3 = StandbyFn + F4 = Suspend

Fn + F7 = LCD/CRT/Simultaneous

Fn + F8 = Reverse video Fn + F11 = PowermgmtFn + F12 = Hibernation

PgUp = Speaker enable PğDn = Speaker disable

System enters hibernation mode when keyboard is lifted up

Disk is not removable (like 755/760 systems), but it can be upgraded via a screwdriver

## **FEATURES OF 365 MODELS**

Product Map LED indicator panel Plug and Play 1.0a Non-disruptive battery exchange Doze, standby, suspend, safe suspend, and hibernation modes US EPA Energy Star compliant Personalized nameplate in indention Personalization screen at startup International Warranty Service 24 hour / 7 day telephone, bulletin board, fax, electronic, and Internet (http://www.pc.ibm.com) support IBM and dealer warranty/sérvice Online Housecall (remote diagnostics)

ThinkPad EasyServ™: customer calls IBM HelpCenter, courier service picks up ThinkPad at any location, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround).

All trademarks are the property of their respective owners No warranties are expressed or implied in this summary (365ED) Compiled by Roger Dodson, IBM. October 1996