## 国际 ThinkPad 755 - withdrawn

IBM® ThinkPad®:	>< 755Cs		>< 755C		ightarrow Traveling Multimedia		
	dual scan color		TFT color		preconfigured system		
Processor type Processor speed Memory cache Coprocessor socket Removable diskette	80486 DX2 ☐ to DX4 50/25 MHz 3.3 volt 8 KB internal (no L2) N/A (std in 486DX2) 3.5" 1.44 MB ○	InteIDX4 75/25 MHz 3.3 volt 16 KB internal (no L2) N/A (std in 486DX4) 3.5" 1.44 MB O	80486 DX2 ☐ to DX4 50/25 MHz 3.3 volt 8 KB internal (no L2) N/A (std in 486DX2) 3.5" 1.44 MB ○	InteIDX4 75/25 MHz 3.3 volt 16 KB internal (no L2) N/A (std in 486DX4) 3.5" 1.44 MB O	Included with the IBM		
Price (retail USD) Type - model all 9545 Removable disk - size Hard disk - speed ms Avail / withdrawn date	<b>170</b> 340 540 15	\$3,899 \$4,399 \$4,799 K0C K0E K0G 170 340 540 540 540 540 540 540 540 540 540 5	170 🗖 340 🗖 540 🗖	\$3,399 \$3,699 \$3,999 LOC LOE LOG 170 340 540 540 540 540 540 540 540 540 540 5			
Display - type Display - colors Display - techology Display - light source Display - size (diag) Display - contrast ratio	VGA color 256 colors 640x480 (pa STN - passive matrix LCD - Sidelit 9.5 inch Dual scan 20 to 1	llette of 4096 colors)	VGA color 256 colors 640x480 (pal TFT - active matrix LCD - Backlit 10.4 inch 100 to 1	lette of 262,144 colors)	- 755C Model LOG - DX4 75/25 with all features listed on left - 540 MB removable hard disk - 8 MB memory (4 MB std + 4 MB DIMM on		
Graphics - controller Graphics - vendor Graph - arch/data path	All: Western Digital / Ex	<ul> <li>II: WD90C24A or WD90C24A2 with 1 MB DRAM / Graphics WinMarks 4.0 = 4.3</li> <li>II: Western Digital / External SVGA to 1024 x 768 w/ 256 colors</li> <li>II: VL-Bus / 32 bit VESA local bus / Simultaneous LCD and CRT / 180 degree tilt</li> </ul>					
Memory - std / max Mem - sockets empty	All: 4 / 36 MB 70 ns  Memory upgraded via ① 1 open socket for IC memory card for 20 MB  Max or ② new DIMM technology for max of 36 MB with 4 or 16 MB  JEDEC 72 pin SO DIMMs on optional Memory Module Adapter.				_ modem (PCMCIA) - Dock I (Docking Station) - CD-ROM/XA - double		
Mem-options available All: 2, 4, 8, 16, 32 MB ICs or 4, 16 MB DIMMs that works on optional Memory Module Adapter					speed and Kodak Photo CD		
Keyboard / # of keys Fn key functions Keyboard slope Mouse/pointing Ext keyboard support	All: Full size alp/num/ 85 All: 8 (in any appl) All: Yes (legs pop out) All: TrackPoint II™ All: Yes (with option cab	Fn + F3 = Sta Fn + F4 = Sus Fn + F5 = Auc	andby Fn + F8, F spend Fn + F11 dio decrease Fn + F12	Fn + F7 = Ext display/LCD Fn + F8, F9, F10 = (reserved) Fn + F11 = Power mgmt asse Fn + F12 = Hibernation mode			
Dimensions Color Weight (with battery)	All: Black h bettery) 6.1 pounds Intelligent battery with a				7.00,		
Battery - type Batt - life (per battery) Charge time - on / off	Nickel hydride (smart) 4 to 8 hours 2 hrs / 1.5 hrs		Nickel hydride (smart) 3.1 to 8 hours	processor to allow accurate monitoring of battery condition and accurate fuel guage.	- Asymetrix MediaBlitz! (library of media clips) - LapLink™ V - Picture Factory™		
Architecture Docking Station Port replicator PCMCIA™ 2.1 slots Serial / parallel ports	All: AT bus (ISA) All: Yes (Dock I and II but All: Yes (2 types below) All: 2 Type I or 2 Type All: Yes (one 9 pin: 1655	elow) cellular moder and VCR play! Il or 1 Type III	can be removed ① to red m (CDPD), ③ to insert TV back), or ④ to add other th Port (FPP): non-DMA	Tuner (for on screen TV	ight, ② to insert   - TalkWorks™ ´ (for on screen TV - Sound Effects Library		
Other features	All: Yes (one 9 pin; 16550A) / Enhanced Parallel Port (EPP); non-DMA All: APM-aware BIOS / Hibernation mode / Wallmount A/C adapter (40 watts) / Selectable boot				ALL 755 MODELS Liftable (pop-up)		
Audio support Audio in/out jacks Security	All: Input jack supports r All: Power-on password	<ul> <li>III: 16 bit audio chip on planar / Crystal Semiconductor CS4248 / Internal speaker and microphone</li> <li>Input jack supports microphone / Output jack supports headphone or stereo speakers</li> <li>Power-on password / Hard disk password / Supervisor password (for hardware config changes) / Hardware security loop / PCMCIA card lock / (Security Base optional)</li> </ul>					
Preinstalled software		IBM DOS 6.3, Windows 3.1, Demo, and 8 applications: ① Lotus® cc:Mail, e-mail for					
Warranty	Flight Disk® 1.0, ® 7  All: 3 year - carry in or	Advantis <sup>®</sup> network, ② Lotus Organizer 1.12, ③ Lotus ScreenCam 1.0, ④ Official Airline Guide Flight Disk <sup>®</sup> 1.0, ⑤ Triton CoSessions <sup>™</sup> Host, ⑥ PRODIGY <sup>®</sup> , ⑦ America Online <sup>SM</sup> , ⑥ SofNet FaxWorks <sup>™</sup> 3.0  3 year - carry in or EasyServ (opt onsite \$40 yr)  The removed diskette drive can be used externally via the optional 'FDD External Kit' (includes cable and enclosure; \$135) to the Port Replicator Model I and II and Dock I.					
Dock I (Docking Station) \$685 The ThinkPad 755 family supports all of the Cellular Digital Packet Data (CDPD)							

SCSI-1 controller; two stereo speakers; One full-size 16 bit AT bus slot; 6.0 pounds; One bay (slim high 1") for 3.5" or 5.25" devices Can house removable disk from 360/750/755; Replication of ports on back of 360/750/755; Additional ports: SCSI, audio, speaker, video in, diskette, headphone jack; handle/palm rest; Dock II (Docking Station) SCSI-2 Fast controller; two stereo speakers;

Two full-size 16 bit AT bus slots; 17.6 pounds; Two 5.25" bays (1" high (SL) and 1.5" high HH); Two PCMCIÁ slòts (Typè II and III); Many ports including audio, diskette, SCSI; Plug and Play ready

## Port Replicator Model I \$299

2 Type I or 2 Type II or 1 Type III PCMCIA slots Provides cable management because all the cables attach to Replicator, not the ThinkPad Replication of Ports: mouse, keyboard, SVGA, parallel port, serial, diskette port, DC power

Port Replicator Model II Same as Model I except no PCMCIA slots options of the ThinkPad 750 family.

Compatible in 360, 750, and 755 family:

- Hard disks (170, 250, 340, 540, 810 MB)
- Batteries (see below)
- Dock I and Dock II
- Diskette drive - AC Adapter Port Replicator I
- Port Replicator II Quick Charger
- CDPD Mobile Module (not pen models)

ThinkPad IC memory for 700, 720, 750, and 755 are all compatible.

The 700 and 720 family hard disks, batteries, and docking station are NOT compatible with 750 or 755 family.

Battery compatibility: 360 750 755 84G2392 360 NiMH battery Ν

66G2846 750 NiMH battery Y = battery supported; N = not supported

Winstone 94 for 755C DX4 = 37.8

Mobile Communications Module \$1,999 Provides transmission of analog and digital data using a cellular telephone. Supported on all 360/750/755 (except 750P). 14.4 bps data/fax modem, AMPS cellular, and CDPD transceiver; wire or wireless.

## FEATURES OF ALL 750 and 755 FAMILY

Discharge battery via mouse click Quick Charger holds 2 batt; discharge button Battery life indicator

Non-disruptive battery exchange Standby / suspend / hibernation modes EasyPlaying (PC Card Director™) preinstalled and included on Utility Diskette (755 only) US EPA Energy Star compliant

Personalized nameplate in molded indention

International travelers warranty IBM or dealer warranty/service 30 day money back guarantee

24 hour / 7 day fax support 24 hour / 7 day bulletin board support 24 hour / 7 day telephone support

(755THINK) Compiled by Roger Dodson, IBM. December 1995

N Y

All trademarks are the property of their respective owners No warranties are expressed or implied in this summary