

Type-model	Processor	GHz	Memory	Screen	Disk	Ultrabay optical	Mini PCI	CDC Ethernet	CDC Mod/Blu	Security Chip	Preload	Small bus software	Workhorse or Global model	Avail date
2653-H3U	Pentium® 4-M	1.7	256MB	15" UXGA	60GB <sup>8</sup> DVD/CD-RW	Open		10/100	Modem	Yes	XP Pro		No	Mar 2002
2653-H4U	Pentium 4-M	1.7	256MB	15" UXGA	60GB DVD/CD-RW	Open		10/100	Modem	Yes	Windows® 2000		No	Mar 2002
2653-H5U	Pentium 4-M	1.7	256MB	15" UXGA	60GB DVD/CD-RW	Wi-Fi <sup>32</sup> /mod		10/100	Bluetooth	Yes	XP Pro		No	Mar 2002
2653-H6U	Pentium 4-M	1.7	256MB	15" UXGA	60GB DVD/CD-RW	Wi-Fi/mod		10/100	Bluetooth	Yes	Windows 2000		No	Mar 2002
2653-HTU	Pentium 4-M	1.7	256MB	15" UXGA	60GB DVD/CD-RW	Wi-Fi/mod		10/100	Bluetooth	Yes	XP Pro	Office XP SB <sup>28</sup>	No	Mar 2002
Positioning Processor	<i>High-performance desktop alternatives with exceptional versatility; three spindle</i>											<b>SOFTWARE<sup>14</sup></b>		
L2 cache	<b>Mobile Intel® Pentium® 4 Processor-M 1.7GHz</b> with enhanced Intel SpeedStep™ technology <sup>1</sup> and 400MHz frontside bus											<b>Windows XP Pro models</b>		
Memory	<b>512KB</b> / on die (at processor speed) / ECC											- Microsoft® Windows® XP Professional		
	<b>256MB</b> std / 1GB max <sup>7</sup> / <b>PC2100 266MHz<sup>30</sup> DDR-SDRAM</b> / non-parity / 2.5v / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available											✧ Disk-to-Disk Recovery (in hidden Service Partition)		
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive											<b>Windows 2000 models</b>		
DVD-ROM/CD-RW	Combo / 8X/8X/24X/8X <sup>21</sup> speed / bootable / removable from Ultrabay Plus											- Microsoft Windows 2000 Professional <sup>13</sup>		
Modular bays	<b>Two modular bays</b> for interchangeable devices / <b>Ultrabay 2000</b> (left side) and <b>Ultrabay Plus</b> (right side) / Ultrabay 2000 left bay empty at ship (uses Travel Bezel)											• ConfigSafe®		
Disk (removable)	<b>60GB<sup>8</sup></b> / high-speed 5400 rpm / upgradeable / S.M.A.R.T. / supports two additional disks with optional HDD adapter in each modular bay											✧ Disk-to-Disk Recovery (in hidden Service Partition)		
Display	<b>15.0"</b> (381mm) <b>UXGA-IPS (1600x1200) TFT color</b> / Active Matrix / 400:1 contrast / FlexView display with wide viewing angle and high density using in plane switching (IPS) technology											<b>INCLUDED SOFTWARE<sup>14</sup> (all)</b>		
Graphics controller	<b>ATI® Mobility™ FireGL™ 7800 / AGP 4X / 64MB</b> DDR-SDRAM 183MHz / supports OpenGL technology for 3D applications											<b>Preloaded</b>		
Graphics - external	External monitor support via analog DB-15 connector / up to 2048x1536x16.7M colors at 75Hz / DDC2B / supports external digital monitor <sup>5</sup> via the Digital Video Interface (DVI) port on either of the optional docking solutions											• Access ThinkPad		
Keyboard	87-key / Web navigation keys (6 total, 3 customizable) / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar / pitch: 19mm; stroke: 2.7mm											- Access Connections		
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions											- Access Help		
UltraPort™	UltraPort connector on top of display for options such as digital UltraPort Camera											- Access Support		
Case material	<i>Color: black; Top: ABS plastic; Bottom: glass-fiber reinforced plastic</i>											• Adobe Acrobat Reader		
Dimensions <sup>3</sup>	Approximately 13.0 x 10.7 x 1.8"; 329mm x 272.5mm x 45.8mm											• InterVideo™ Win DVD		
Approximate weight <sup>2</sup>	with battery and optical drive: 7.7 lb (3.49kg)											• MGI VideoWave 4		
Battery - type	Lithium Ion 6-cell 10.8V 4.0Ah / intelligent / supports 2nd battery in Ultrabay 2000											• PC-Doctor™		
Battery - life <sup>10</sup>	2.0 hours / universal 72 watt AC adapter (16Vdc 4.5A)											• ThinkPad Utilities		
Architecture	<b>Intel 845MP</b> chipset / 82845MP Memory Controller Hub (MCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB [Bluetooth], Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (Ricoh® R5C552 CardBus/1394 combo controller, Mini PCI, ext expansion) / LPC bus 33MHz (PC87392 Super I/O for diskette, serial, parallel, infrared)											• IBM Update Connector™ <sup>15</sup>		
Port replicator	Optional <b>ThinkPad Port Replicator</b>											• Veritas RecordNOW		
Docking Station	Optional <b>ThinkPad Dock</b> (includes Ultrabay 2000 and half-size PCI slot)											<b>Downloadable</b>		
PC Card Std slots	2 Type I, 2 Type II, or 1 Type III / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video											• IBM Rapid Restore™ PC		
Ports	Two USB (version 1.1) / one 9-pin serial / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / IEEE 1394 / no keyboard/mouse											• IBM Data Transfer		
Video in and out	S-video in and out ports / industry standard connectors / cable ships standard											• Client Security Software (models with security chip)		
IEEE 1394	IEEE 1394 FireWire port											• IBM Director Agent		
Mini PCI	One Mini PCI IIb slot (Communications Bay) / customer upgradeable											<b>License</b>		
Wi-Fi <sup>32</sup> /modem	<i>Some: Mini PCI Wi-Fi<sup>32</sup> wireless<sup>4</sup>, Intersil® Prism 2.5 chipset, dual antennas in display cover / 56K<sup>6</sup> V.90 (V.92-designed<sup>29</sup>) modem combo, Lucent® chipset</i>											- Lotus® SmartSuite® Millennium and Lotus Notes® Client 5.0		
CDC	Two Communications Daughter Card (CDC) sockets / customer accessible											<b>Office XP Small Business models only</b>		
Modem	<i>Some: 56K<sup>6</sup> V.90 (V.92-designed<sup>29</sup>) CDC modem card / Lucent® chip set</i>											- Microsoft Office XP Small Business <sup>28</sup> (Word, Excel, Outlook, Publisher, Small Business Tools)		
Ethernet	10/100 ethernet on CDC / Intel 82562ET chipset (physical layer)											✧ Office XP Small Business CD		
Bluetooth™	<i>Some: Bluetooth wireless technology / on CDC / power button on display</i>											<b>Ultrabay Plus integrated modular bay</b>		
Audio support	SoundBlaster Pro™-compatible / AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / mic input jack / output jack / line in jack											supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series		
Security	Power-on password / hard disk password / supervisor password / security keyhole /													
Security chip	<b>IBM Embedded Security Subsystem<sup>33</sup></b> / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security <sup>16</sup>													
Limited warranty <sup>12</sup>	<b>3 years/1 year battery</b> - EasyServ™ <sup>19</sup> onsite pickup and delivery courier service													
Service options	Service upgrades <sup>22</sup> provide up to three years of onsite or depot repair service coverage from date of ThinkPad purchase (including warranty period)													
128 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028	Ultrabay 2000 Li-Ion battery						02K6646	PC 2001-compliant					
256 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030	Multiple Li-Ion/NiMH Battery Charger						02K6719	ACPI 1.0b and 2.0 support					
512 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032	ThinkPad 72W AC Adapter						02K6699	CIM and DMI 2.0-compliant					
Second HDD Adapter for Ultrabay 2000	08K6068	ThinkPad Ultrabay Plus Carrier						22P5737	IBM ImageUltra Services available					
20GB Hard Disk Drive	08K9686	ThinkPad Ultrabay Plus c500 Cradle						22P5738	IBM Rapid Restore PC available to					
40GB Hard Disk Drive	08K9687	ThinkPad Ultrabay Plus Numeric Keypd						22P7330	protect software image and data					
60GB HS Hard Disk Drive (5400 rpm)	08K9688	ThinkPad Port Replicator						02K8667	Setup Guide, Service and Trouble-					
IBM USB Portable Diskette Drive	05K9276	ThinkPad Dock						263120U	shooting Guide, Windows manual					
ThinkPad Removable Diskette Drive	08K9603	IBM USB Keyboard w/ USB Ports						10K3849	Personalized Web-based support					
SuperDisk (LS-240) UltraBay 2000	08K9616	IBM USB Sleek Mouse						33L3244	International Warranty Service <sup>17</sup>					
Zip 250MB Ultrabay 2000 Drive	00N8253	IBM USB 32MB Memory Key						22P5296	24 hour x 7 day <sup>18</sup> toll-free hardware					
8X/4X/24X Max CD-RW Ultrabay 2000	22P9101	Portable Drive Bay 2000						19K4480	support during the warranty					
Ultralight 8X Max DVD Ultrabay 2000	22P9102	10/100 Enet/56K Mini PCI (3Com)						09N9774						
DVD/CD-RW Combo II Ultrabay 2000	08K9701	ServicePac®, <sup>22</sup> 2yr IOR 9x5 NBD						30L9190						
Travel Bezel for Ultrabay 2000	08K6070	ServicePac 3yr IOR 9x5 NBD						30L9197						
ThinkPad A30 Series Li-Ion Battery	02K6878	Other options at <a href="http://ibm.com/us/pc/accessories">ibm.com/us/pc/accessories</a>												

Type-model	Processor	GHz	Memory	Screen	Disk	Ultrabay optical	Mini PCI	CDC Ethernet	CDC Mod/Blu	Security Chip	Preload	Small bus software	Workhorse or Global model	Avail date
2653-N3U	Pentium® 4-M	1.8	256MB	15" UXGA	60GB <sup>8</sup> DVD/CD-RW	Open		10/100	Modem	Yes	XP Pro		No	Jun 2002
2653-N4U	Pentium 4-M	1.8	256MB	15" UXGA	60GB DVD/CD-RW	Open		10/100	Modem	Yes	Windows® 2000		No	Jun 2002
2653-N5U	Pentium 4-M	1.8	256MB	15" UXGA	60GB DVD/CD-RW	Wi-Fi <sup>32</sup> /mod		10/100	Bluetooth	Yes	XP Pro		No	Jun 2002
2653-N6U	Pentium 4-M	1.8	256MB	15" UXGA	60GB DVD/CD-RW	Wi-Fi/mod		10/100	Bluetooth	Yes	Windows 2000		No	Jun 2002
2653-NTU	Pentium 4-M	1.8	256MB	15" UXGA	60GB DVD/CD-RW	Wi-Fi/mod		10/100	Bluetooth	Yes	XP Pro	Office XP SB <sup>28</sup>	No	Jun 2002
Positioning Processor	High-performance desktop alternatives with exceptional versatility; three spindle Mobile Intel® Pentium® 4 Processor-M 1.8GHz with enhanced Intel SpeedStep™ technology <sup>1</sup> and 400MHz frontside bus											SOFTWARE <sup>14</sup> <b>Windows XP Pro models</b> - Microsoft® Windows® XP Professional ✧ Disk-to-Disk Recovery (in hidden Service Partition) <b>Windows 2000 models</b> - Microsoft Windows 2000 Professional <sup>13</sup> • ConfigSafe® ✧ Disk-to-Disk Recovery (in hidden Service Partition)		
L2 cache	512KB / on die (at processor speed) / ECC													
Memory	256MB std / 1GB max <sup>7</sup> / PC2100 DDR-SDRAM / 266MHz <sup>30</sup> / non-parity / 2.5v / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available													
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive													
DVD-ROM/CD-RW	Combo / 8X/8X/24X/8X <sup>21</sup> speed / bootable / removable from Ultrabay Plus													
Modular bays	Two modular bays for interchangeable devices / Ultrabay 2000 (left side) and Ultrabay Plus (right side) / Ultrabay 2000 left bay empty at ship (uses Travel Bezel)													
Disk (removable)	60GB <sup>8</sup> / high-speed 5400 rpm / upgradeable / S.M.A.R.T. / supports two additional disks with optional HDD adapter in each modular bay													
Display	15.0" (381mm) UXGA-IPS (1600x1200) TFT color / Active Matrix / 400:1 contrast / FlexView display with wide viewing angle and high density using in plane switching (IPS) technology													
Graphics controller	ATI® Mobility™ FireGL™ 7800 / AGP 4X / 64MB DDR-SDRAM 183MHz / supports OpenGL technology for 3D applications													
Graphics - external	External monitor support via analog DB-15 connector / up to 2048x1536x16.7M colors at 75Hz / DDC2B / supports external digital monitor <sup>5</sup> via the Digital Video Interface (DVI) port on either of the optional docking solutions													
Keyboard	87-key / Web navigation keys (6 total, 3 customizable) / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar <sup>13</sup> / pitch: 19mm; stroke: 2.7mm													
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions													
UltraPort™	UltraPort connector on top of display for options such as digital UltraPort Camera													
Case material	Color: black; Top: ABS plastic; Bottom: glass-fiber reinforced plastic													
Dimensions <sup>3</sup>	Approximately 13.0 x 10.7 x 1.8"; 329mm x 272.5mm x 45.8mm													
Approximate weight <sup>2</sup>	with battery and optical drive: 7.7 lb (3.49kg)													
Battery - type	Lithium Ion 6-cell 10.8V 4.0Ah / intelligent / supports 2nd battery in Ultrabay 2000													
Battery - life <sup>10</sup>	2.0 hours / universal 72 watt AC adapter (16Vdc 4.5A)													
Architecture	Intel 845MP chipset / 82845MP Memory Controller Hub (MCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB [Bluetooth], Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (Ricoh® R5C552 CardBus/1394 combo controller, Mini PCI, ext expansion) / LPC bus 33MHz (PC87392 Super I/O for diskette, serial, parallel, infrared)													
Port replicator	Optional ThinkPad Port Replicator													
Docking Station	Optional ThinkPad Dock (includes Ultrabay 2000 and half-size PCI slot)													
PC Card Std slots	2 Type I, 2 Type II, or 1 Type III / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video													
Ports	Two USB (version 1.1) / one 9-pin serial / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / IEEE 1394 / no keyboard/mouse													
Video in and out	S-video in and out ports / industry standard connectors / cable ships standard													
IEEE 1394	IEEE 1394 FireWire port													
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradeable													
Wi-Fi <sup>32</sup> /modem	Some: Mini PCI Wi-Fi <sup>32</sup> wireless <sup>3</sup> , Intersil® Prism 2.5 chipset, dual antennas in display cover / 56K <sup>6</sup> V.90 (V.92-designed <sup>29</sup> ) modem combo, Lucent® chipset													
CDC	Two Communications Daughter Card (CDC) sockets / customer accessible													
Modem	Some: 56K <sup>6</sup> V.90 (V.92-designed <sup>29</sup> ) CDC modem card / Lucent® chip set													
Ethernet	10/100 ethernet on CDC / Intel 82562ET chipset (physical layer)													
Bluetooth™	Some: Bluetooth wireless technology / on CDC / power button on display													
Audio support	SoundBlaster Pro™-compatible / AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / mic input jack / output jack / line in jack													
Security	Power-on password / hard disk password / supervisor password / security keyhole / IBM Embedded Security Subsystem <sup>33</sup> / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security <sup>16</sup>													
Limited warranty <sup>12</sup>	3 years/1 year battery - EasyServ™ <sup>19</sup> onsite pickup and delivery courier service													
Service options	Service upgrades <sup>22</sup> provide up to three years of onsite or depot repair service coverage from date of ThinkPad purchase (including warranty period)													
128 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028					Ultrabay 2000 Li-Ion battery					02K6646			
256 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030					Multiple Li-Ion/NiMH Battery Charger					02K6719			
512 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032					ThinkPad 72W AC Adapter					02K6699			
Second HDD Adapter for Ultrabay 2000	08K6068					ThinkPad Ultrabay Plus Carrier					22P5737			
20GB Hard Disk Drive	08K9686					ThinkPad Ultrabay Plus c500 Cradle					22P5738			
40GB Hard Disk Drive	08K9687					ThinkPad Ultrabay Plus Numeric Keydpd					22P7330			
60GB HS Hard Disk 9.5mm (5400 rpm)	08K9688					ThinkPad Port Replicator					02K8667			
IBM USB Portable Diskette Drive	05K9276					ThinkPad Dock					263120U			
ThinkPad Removable Diskette Drive	08K9603					IBM USB Keyboard w/ USB Ports					10K3849			
SuperDisk (LS-240) UltraBay 2000	08K9616					IBM USB Sleek Mouse					33L3244			
Zip 250MB Ultrabay 2000 Drive	00N8253					IBM 128MB USB 2.0 Memory Key					22P8998			
8X/4X/24X Max CD-RW Ultrabay 2000	22P9101					Portable Drive Bay 2000					19K4480			
Ultralight 8X Max DVD Ultrabay 2000	22P9102					10/100 Enet/56K Mini PCI (3Com)					09N9774			
DVD/CD-RW Combo II Ultrabay 2000	08K9701					ServicePac®, <sup>22</sup> 2yr IOR 9x5 NBD					30L9190			
Travel Bezel for Ultrabay 2000	08K6070					ServicePac 3yr IOR 9x5 NBD					30L9197			
ThinkPad A30 Series Li-Ion Battery	02K6878					Other options at <a href="http://ibm.com/us/pc/accessories">ibm.com/us/pc/accessories</a>								
PC 2001-compliant														
ACPI 1.0b and 2.0 support														
CIM and DMI 2.0-compliant														
IBM ImageUltra Services available														
IBM Rapid Restore PC available to protect software image and data														
Setup Guide, Service and Troubleshooting Guide, Windows manual														
Personalized Web-based support <sup>31</sup>														
Proactive e-mail updates <sup>31</sup>														
International Warranty Service <sup>17</sup>														
24x7 toll-free support <sup>18</sup> for warranty-related issues during the warranty period <sup>12</sup>														



Type-model	Processor	GHz	Memory	Screen	Disk	Ultrabay optical	Mini PCI	CDC ethernet mod/Blue	CDC Security chip	Preload	Small bus software	Workhorse or Global model	Avail date	
2653-R3U	Pentium® 4-M	2.0	256MB	15" UXGA	60 or 80GB* <sup>8</sup>	Combo	Open	10/100	Modem	Yes	XP Pro	No	Sep 2002	
2653-R4U	Pentium 4-M	2.0	256MB	15" UXGA	60 or 80GB*	Combo	Open	10/100	Modem	Yes	Windows® 2000	No	Sep 2002	
2653-R5U	Pentium 4-M	2.0	256MB	15" UXGA	60 or 80GB*	Combo	11b Wi-Fi <sup>32</sup> /mod	10/100	Bluetooth	Yes	XP Pro	No	Sep 2002	
2653-R6U	Pentium 4-M	2.0	256MB	15" UXGA	60 or 80GB*	Combo	11b Wi-Fi/mod	10/100	Bluetooth	Yes	Windows 2000	No	Sep 2002	
2653-R8U	Pentium® 4-M	2.0	256MB	15" UXGA	40GB	Combo	Open	10/100	Modem	Yes	XP Pro	No	Mar 2003	
2653-RBU	Pentium 4-M	2.0	256MB	15" UXGA	40GB	Combo	Open	10/100	Modem	Yes	Windows® 2000	No	Mar 2003	
2653-R9U	Pentium 4-M	2.0	256MB	15" UXGA	40GB	Combo	11b Wi-Fi <sup>32</sup> /mod	10/100	Bluetooth	Yes	XP Pro	No	Mar 2003	
2653-RCU	Pentium 4-M	2.0	256MB	15" UXGA	40GB	Combo	11b Wi-Fi/mod	10/100	Bluetooth	Yes	Windows 2000	No	Mar 2003	
2653-RTU	Pentium 4-M	2.0	256MB	15" UXGA	60 or 80GB*	Combo	11b Wi-Fi/mod	10/100	Bluetooth	Yes	XP Pro	Office XP SB <sup>28</sup>	No	Sep 2002
Positioning Processor	High-performance desktop alternatives with exceptional versatility; three spindle Mobile Intel® Pentium® 4 Processor-M 2.0GHz with enhanced Intel SpeedStep™ technology <sup>1</sup> and 400MHz system bus										SOFTWARE <sup>14</sup>			
L2 cache	512KB / on die (at processor speed) / ECC										Windows XP Pro models			
Memory	256MB std / 1GB max <sup>7</sup> / PC2100 DDR-SDRAM / 266MHz <sup>30</sup> / non-parity / 2.5v / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available										- Microsoft® Windows® XP Professional ✧ Disk-to-Disk Recovery (in hidden Service Partition)			
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive										Windows 2000 models			
Combo	DVD-ROM/CD-RW / 8X/16X/10X/24X <sup>21</sup> speed / removable from Ultrabay Plus										- Microsoft Windows 2000 Professional <sup>13</sup>			
Modular bays (both 12.7mm)	Two modular bays for interchangeable devices / Ultrabay 2000 (left side) and Ultrabay Plus (right side) / Ultrabay 2000 left bay empty at ship (uses Travel Bezel)										• ConfigSafe® ✧ Disk-to-Disk Recovery (in hidden Service Partition)			
Disk (removable)	40GB <sup>8</sup> (9.5mm, 5400 rpm), 60GB (12.5mm, 5400rpm), or 80GB (9.5mm, 4200rpm) / upgradable and removable / 12.5mm bay / supports two additional disks with optional HDD adapter in each modular bay										INCLUDED SOFTWARE <sup>14</sup> (all)			
Display	15.0" (381mm) UXGA-IPS (1600x1200) TFT color / Active Matrix / 400:1 contrast / FlexView display with wide viewing angle and high density using IPS technology										Preloaded			
Graphics controller	ATI® Mobility™ FireGL™ 7800 / AGP 4X / 64MB DDR-SDRAM 183MHz / supports OpenGL technology for 3D applications										• Access ThinkPad			
Graphics - external	External monitor support via analog DB-15 connector / up to 2048x1536x16.7M colors at 75Hz / DDC2B / supports external digital monitor via the Digital Video Interface (DVI) port on either of the optional docking solutions										- Access Connections - Access Help - Access Support			
Keyboard	87-key / Web navigation keys (6 total, 3 customizable) / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar <sup>13</sup> / pitch: 19mm; stroke: 2.7mm										• Adobe Acrobat Reader			
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions										• InterVideo™ Win DVD			
UltraPort™	UltraPort connector on top of display for options such as digital UltraPort Camera										• MGI VideoWave 4			
Case material	Color: black; Top: ABS plastic; Bottom: glass-fiber reinforced plastic										• PC-Doctor™			
Dimensions <sup>3</sup>	Approximately 13.0 x 10.7 x 1.8"; 329mm x 272.5mm x 45.8mm										• ThinkPad Utilities			
Approximate weight <sup>2</sup>	with battery and optical drive: 7.7 lb (3.49kg)										• IBM Update Connector™ <sup>15</sup>			
Battery - type	Lithium Ion 6-cell 10.8V 4.0Ah / intelligent / supports 2nd battery in Ultrabay 2000										• Veritas RecordNOW and DLA			
Battery - life <sup>10</sup>	2.0 hours / universal 72 watt AC adapter (16Vdc 4.5A)										Downloadable			
Architecture	Intel 845MP chipset / 82845MP Memory Controller Hub (MCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB [Bluetooth], Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (Ricoh® R5C552 CardBus/1394 combo controller, Mini PCI, ext expansion) / LPC bus 33MHz (PC87392 Super I/O for diskette, serial, parallel, infrared)										• IBM Rapid Restore™ PC			
Port replicator	Optional ThinkPad Port Replicator or Port Replicator II										• Software Delivery Assistant			
Docking Station	Optional ThinkPad Dock or Dock II (includes Ultrabay 2000 and half-size PCI slot)										• System Migration Assistant			
PC Card Std slots	2 Type I, 2 Type II, or 1 Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door										• IBM Director Agent			
Ports	Two USB (version 1.1) / one 9-pin serial / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / IEEE 1394 / no keyboard/mouse										• Client Security Software (security chip models)			
Video in and out	S-video in and out ports / industry standard connectors / cable ships standard										License (CD not included)			
IEEE 1394 (FireWire)	IEEE 1394 (FireWire) port (4-pin connector)										- Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client			
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable										Office XP Small Business models only (Model RTU)			
11b Wi-Fi <sup>32</sup> /mod	Some: Mini PCI 11b Wi-Fi <sup>32</sup> wireless <sup>4</sup> , Intersil® Prism 2.5 chipset, dual antennas in display cover / 56K <sup>6</sup> V.90 (V.92-designed <sup>29</sup> ) modem combo, Lucent® chipset										- Microsoft Office XP Small Business <sup>28</sup> (Word, Excel, Outlook, Publisher, Small Business Tools)			
CDC	Two Communications Daughter Card (CDC) sockets / customer accessible										✧ Office XP Small Business CD			
Modem	Some: 56K <sup>6</sup> V.90 (V.92-designed <sup>29</sup> ) CDC modem card / Lucent® chip set										Certified software			
Ethernet	10/100 ethernet on CDC / Intel 82562ET chipset (physical layer) / PXE / Wake on LAN®										- Visit <a href="http://ibm.com/pc/thinkpad/cert.html">ibm.com/pc/thinkpad/cert.html</a> for a complete list of applications certified to run on the ThinkPad A31p			
Bluetooth™	Some: Bluetooth wireless technology / on CDC / power button on display										PC 2001-compliant			
Audio support	SoundBlaster Pro™-compatible / AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / mic input jack / output jack / line in jack										ACPI 1.0b and 2.0 support			
Security	Power-on password / hard disk password / supervisor password / security keyhole / IBM Embedded Security Subsystem <sup>33</sup> / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security <sup>16</sup> / TCG-compliant										CIM and DMI 2.0-compliant			
Limited warranty <sup>12</sup>	3 years/1 year battery - EasyServ™ <sup>19</sup> onsite pickup and delivery courier service										IBM ImageUltra™ Services available			
128 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028					ThinkPad A30 Series Li-Ion Battery					IBM Rapid Restore PC available to protect software image and data			
256 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030					Ultrabay 2000 Li-Ion battery					Setup Guide, Service and Trouble-			
512 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032					Multiple Li-Ion/NiMH Battery Charger					shooting Guide, Windows manual			
Second HDD Adapter for Ultrabay 2000	08K6068					ThinkPad Port Replicator II					International Warranty Service <sup>17</sup>			
20GB Hard Disk Drive	08K9686					ThinkPad Mini Dock					24x7 toll-free support <sup>18</sup> for warranty-			
40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816					ThinkPad Dock					related issues during the warranty			
IBM 256MB USB 2.0 Memory Key	22P9025					ThinkPad Dock II					period <sup>12</sup>			
IBM USB Portable Diskette Drive	05K9276					IBM Optical Travel Wheel Mouse (black)								
ThinkPad Removable Diskette Drive	08K9603					ServicePac®, 22 2yr IOR 9x5 NBD								
Zip 250MB Ultrabay 2000 Drive	00N8253					ServicePac 3yr IOR 9x5 NBD								
DVD/CD-RW Combo IV Ultrabay 2000	22P6991					ServicePac 4yr IOR 9x5 NBD								
Travel Bezel for Ultrabay 2000	08K6070					ServicePac 5yr IOR 9x5 NBD								
Portable Drive Bay 2000	19K4480					ServicePac 4yr P&L P/U Depot								
IBM Portable USB 2.0 CD-RW Drive	2295297					ServicePac 5yr P&L P/U Depot								
ThinkPad 72W AC Adapter	02K6699					Other options at <a href="http://ibm.com/us/pc/accessories">ibm.com/us/pc/accessories</a>								

See footnotes for important warranty information

\*80GB for systems manufactured after May 2003

(A31PG) © IBM Corp. January 2004

US models announced on August 27, 2002 or March 12, 2003

US models withdrawn effective January 2004