

IBM ThinkPad® i Series 1512, 1552 - withdrawn

IBM® ThinkPad®		i Series 1512	i Series 1552		All-in-one design means the disk, diskette drive, and CD-ROM are all within the covers of the notebook
Processor type		Intel® Mobile Celeron™ 366MHz ¹ / 66MHz system bus			
L2 cache		128KB / onboard (full spd) / sync pipelined burst / ECC / write-back			
Diskette drive		Internal 3.5" 1.44MB / use simultaneously with CD-ROM / on right side			
CD-ROM		CD-ROM / 24X-10X ⁵ speed / CAV / ATAPI / bootable / not removable / on right side			
DVD		None available			
Audio Control Panel		Instant Audio (external CD player controls in front of palm rest to play music CDs for up to six hrs when system off/closed)			
Type - model		2611-512		2611-552	
UPC code		0-87944-4505433		0-87944-4505440	
Disk - size / ms		4.8GB ⁴ / 13ms read / 14ms write			
Disk controller		EIDE / PCI 2.1 / supports one internal disk / disk can not be removed or upgraded			
CD or DVD		24X-10X CD-ROM			
Avail / withdrawn date		July 1999 / September 1999			
Display (diagonal)		12.1" TFT / SVGA		14.1" TFT / XGA	
Display - size and type		12.1 inch (308mm) TFT color / Active Matrix		14.1 inch (358mm) TFT color / Active Matrix	
Display - technology		SVGA / 640x480 or 800x600 / 30ms / 120 nits 16.7 million simultaneous colors / 80 to 1 contrast		XGA / 640x480 or 800x600 or 1024x768 / 30ms / 130 nits 16.7 million simultaneous colors / 200 to 1 contrast	
Graphics - controller		NeoMagic™ MagicMedia256AV™ (NM2200) / Accelerated Graphics Port / AGP-1x / 128-bit engine, 256-bit memory interface / 2.5MB / SGRAM (embedded) / motion compensation / color space conversion / DDC2B			
Graphics - features		External SVGA to 1024x768x16.7 million colors at 85Hz and 1280x1024x256 colors			
Memory - std / max		64MB / 256MB ¹⁷			
Memory - features		SDRAM / non-parity / 66MHz / 3.3 volt / 64-bit 2 sockets for JEDEC 144-pin SO DIMMs / one socket used by std memory / sockets accessed from bottom via removing cover held by philips-head screws			
Keyboard		Full-size 85-key (10 Fn key functions) / keyboard slope with tilt feet Customizable color-coded ShortCut Keys / two Windows keys / palm rest			
Pointing		TrackPoint® / Press-to-Select / Release-to-Select / dragging / click pace / center button for scrolling (Internet Scroll Bar) or magnifying glass / spare caps			
Dimensions / weight ²		13.1 x 10.1 x 1.85" (245 cubic inches) / 1512: 7.4 lbs 1552: 7.7 lbs			
Battery - type / life ¹⁰		Li-Ion / non-intelligent / left side / 3.0 hrs			
Charge time - on / off		5.0 hrs on / 2.0 hrs off			
Architecture		ALI® Aladdin IV M1621 North Bridge / M1533 (EIDE, USB, PCI to ISA bdg) / AGP for graphics / O2® Micro 6833D1 PCMCIA controller / PCI 2.1 32-bit 33Mhz (EIDE, modem, PCMCIA, USB, audio) / ISA (diskette, serial, parallel, infrared) / NS PC97338			
Docking station		None			
Port replicator		ThinkPad i Series 1400 Port Replicator			
PCMCIA™ slots		2 Type I or 2 Type II or 1 Type III / CardBus 32-bit / Zoomed Video (upper slot) / PCMCIA 2.1 compatible / PC Card Standard 95			
USB / serial / parallel		One USB / one 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)			
Other features		APM-aware BIOS / Universal AC adapter, 3 prong, barrel, slim, 45 watts			
Video (TV) out		None			
MPEG decoder		None (software support for MPEG-1 in Windows 98)			
Data/fax modem		56K ³ V.90 / integrated in system / Lucent® 1644 / not voice-capable			
Audio		16-bit SoundBlaster Pro™ audio support / PCI / ES1946 / no full duplex support			
Speakers		Altec Lansing® SoundGuide stereo speakers w/ Dynamic Equalization Circuit™			
Audio features		Dial volume control (left side) / internal microphone			
Audio in/out jacks		Microphone jack (stereo) / headphone jack (stereo) / line-in jack			
Infrared ports		None			
Security		Power-on password / supervisor password / security keyhole			
Supported oper system		Windows 98 only			
Limited warranty ¹¹		1 year - ThinkPad EasyServ™.9 (door-to-door depot repair service) or carry-in			
Service options ¹⁵		On-site, M-F, 8-5, next bus day (72 cities) / serv up to 5 yrs from purch date			
The ThinkPad i Series 1400 Port Replicator provide cable management and I/O ports:		OPTIONS			
- Power jack		- 32MB SO DIMM 3.3v NP SDRAM 76H0294			
- Parallel connector		- 64MB SO DIMM 3.3v NP SDRAM 20L0241			
- Serial connector		- 128MB SO DIMM 3.3v NP SDRAM 01K1150			
- External mouse connector		- i Series 1400 Port Replicator 05K5591			
- External keyboard connector		- Li-Ion Battery 02K6576			
- External monitor connector		- 45 watt AC Adapr (barrel; 3 prong) 11J8702			
- Universal Serial Bus (USB) port		- Visit www.ibm.com/pc/us/accessories (U.S.) or www.ibm.com/pc/ca/accessories (CA)			
- Headphone jack		- ThinkPad Proven™ solutions ¹² (visit www.ibm.com/pc/us/thinkpad/proven)			
- Line-in jack		- Visit www.ibm.com/pc/us/thinkpad/iseries (U.S.) or www.ibm.com/pc/ca/thinkpad (CA)			
- Microphone jack					
Color depth	LCD	External Monitor			
Resolution	TFT	60Hz	75Hz	85Hz	
640x480	16M	16M	16M	16M	
800x600	16M	16M	16M	16M	
1024x768	16M	16M	16M	16M	
1280x1024	--	256	--	--	
WINDOWS 98 PRELOAD ¹⁶					
- Microsoft® Windows® 98					
• Office 2000 Small Business Edition					
- Microsoft Word 2000					
- Microsoft Excel 2000					
- Microsoft Outlook 2000					
- Microsoft Publisher 2000					
- Microsoft Small Business Tools					
• Online User's Guide					
• Easy Buttons Utility					
• IBM Owner Privileges					
• Marketing Screen Saver					
• Marketing Demo					
• Earthlink					
• Quicken 99					
• Tom Lehman Golf Pro 98					
• World Book Encyclopedia					
• Norton AntiVirus™ (OEM version)					
• Access ThinkPad					
• RingCentral Fax					
• America Online® ⁶⁶					
• ConfigSafe®					
• IBM Update Connector					
• PC-Doctor™ (system diagnostics)					
• IBM Global Network (IGN Dialer)					
• Netscape Communicator					
• ThinkPad on the Net					
✧ World Book Encyclopedia CD-ROM					
✧ Software Selections CD-ROM					
✧ Product Recovery CD-ROM					
4.8GB = DMA Mode 2 or PIO Mode 4 All disks are S.M.A.R.T. ⁸ compliant					
Pressing F1 during startup brings up BIOS Utility					
All models:					
- C: drive is FAT16 of 2GB					
- D: drive is FAT32 of remaining space					
FEATURES					
PC 98-compliant					
ACPI ready (APM enabled)					
Setup Guide, User's Reference, Windows 98 manual, and Quick Reference Card					
System Status Indicators					
Plug and Play 1.0a					
Light green mode, standby mode, and hibernation mode					
ENERGY STAR compliant					
International Warranty Service ¹¹					
24 hour / 7 day telephone ⁷ , bulletin board, fax, electronic, and Internet (www.ibm.com/pc/us) support					

ThinkPad EasyServ™: customer calls 1-800-772-2227, courier service picks up ThinkPad in most North American locations, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround). The customer may be asked certain diagnostic questions before a courier is sent.

All trademarks are the property of their respective owners
 No warranties are expressed or implied in this summary
 (1512) © IBM Corp. October 1999

IBM ThinkPad® i Series 1540, 1541, 1560 - withdrawn

IBM® ThinkPad®	i Series 1540		i Series 1541	i Series 1560	All-in-one design means the disk, diskette drive, and CD-ROM are all within the covers of the notebook
Processor type	Intel® Mobile Celeron™ 433 or 466MHz ¹ / 66MHz system bus				
L2 cache	128KB / at processor speed / sync pipelined burst / ECC / write-back				
Diskette drive	Internal 3.5" 1.44MB / use simultaneously with CD-ROM / on left side				
CD-ROM	CD-ROM / 24X-10X ⁵ speed / CAV / ATAPI / bootable / not removable / on right side				
DVD	None / no option available				
Audio Control Panel	Media Center with Instant Audio (external CD player controls in front to play music CDs when system off or closed)				
Type - model	2621-540	2621-541	2621-560		
UPC code	0-87944-51796-2	0-87944-52271-3	0-87944-51797-9		
Processor	Celeron 433MHz	Celeron 466MHz	Celeron 466MHz		
Disk - size / ms	4.8GB ⁴ / 13ms read	6.0GB / 12ms / ATA-66	6.4GB / 12ms read / 14ms write		
Disk controller	EIDE / PCI 2.1 / supports one internal disk / disk can not be removed or upgraded				
CD or DVD	24X-10X CD-ROM	24X-10X CD-ROM	24X-10X CD-ROM		
Avail / withdrawn date	October 1999 / March 2000	January 2000 / July 2000	October 1999 / April 2002		
Display (diagonal)	12.1" TFT / SVGA	12.1" TFT / SVGA	14.1" TFT / XGA		
Display - size and type	12.1 inch (308mm) TFT color / Active Matrix		14.1 inch (358mm) TFT color / Active Matrix		
Display - technology	SVGA / 640x480 or 800x600 / 30ms / 120 nits		XGA / 640x480 or 800x600 or 1024x768 / 30ms / 130 nits		
	16.7 million simultaneous colors / 80 to 1 contrast		16.7 million simultaneous colors / 200 to 1 contrast		
Graphics - controller	ATI™ Rage Mobility-M™ / Accelerated Graphics Port / AGP 2X / 64-bit graphics / 4MB SDRAM / motion compensation / multiple monitor support ²⁶ / DDC2B				
Graphics - features	External SVGA to 1024x768x16.7 million colors at 85Hz and 1280x1024x256 colors				
Memory - std / max	64MB / 256MB ¹⁷				WINDOWS 98 PRELOAD ¹⁶
Memory - features	SDRAM / non-parity / 66MHz / 3.3 volt / 64-bit data path / 2 sockets for JEDEC 144-pin SO DIMMs / one socket used by std memory / sockets accessed from bottom via removing cover held by phillips-head screws				
Keyboard	Full-size 85-key (multiple Fn key functions) / slope with tilt feet / palm rest / four customizable color-coded Easy Launch buttons ¹⁸ / two Windows keys				- Microsoft® Windows® 98 Second Edition • Office 2000 Small Business - Microsoft Word 2000 - Microsoft Excel 2000 - Microsoft Outlook 2000 - Microsoft Publisher 2000 - Microsoft Small Business Tools • Online User's Guide • Easy Buttons Utility • IBM Owner Privileges ¹³ • ThinkPad Utilities • Marketing Screen Saver • Marketing Demo • Earthlink • Quicken 99 • Norton AntiVirus™ (OEM version) ¹⁶ • Access ThinkPad • RingCentral • America Online ⁶⁶ • ConfigSafe® • IBM Update Connector ¹⁴ • PC-Doctor™ (system diagnostics) • IBM Global Network (IGN Dialer) • Netscape Communicator • ThinkPad on the Net ♦ Tom Lehman Golf Pro 98 CD-ROM ♦ World Book Encyclopedia CD-ROM ♦ Software Selections CD-ROM ♦ Product Recovery CD-ROM
Keyboard light	1560: ThinkLight™ / keyboard light (to work in low light) w/ power button				
Pointing	TrackPoint® / Press-to-Select / Release-to-Select / dragging / click pace / center button for scrolling (Internet Scroll Bar) or magnifying glass / spare cap				
Dimensions ¹⁹ / weight ²	1540/41: 12.9x10.6x1.59" front and 1.73" rear / 7.5 lbs 1560: 12.9x10.6x1.55" front and 1.69" rear / 7.65 lbs				
Battery - type	Li-Ion / intelligent / right side				
Battery - life ¹⁰	1540/41: 3.0 hrs		1560: 4.0 hrs		
Charge time - on / off	1540/41: 5.0 hrs on / 2.0 hrs off		1560: 4.0 hrs on / 3.1 hrs off		
Architecture	ALI® Aladdin IV M1621 North Bridge / M1533 (EIDE, USB, PCI to ISA bdg) / AGP for graphics / O2® Micro 6833 PCMCIA controller / PCI 2.1 32-bit 33Mhz (EIDE, modem, PCMCIA, USB, audio) / ISA (diskette, serial, parallel, infrared) / NS PC97338				
Docking station	None				
Port replicator	None				
PCMCIA™ slots	1 Type I or 1 Type II or 1 Type III / CardBus 32-bit / Zoomed Video				
USB / serial / parallel	One USB / one 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)				
Other features	ACPI power mgmt / Universal AC adapter, 3 prong, barrel, slim, 56 watts				
Video (TV) out	None				
MPEG decoder	None (software support for MPEG-1 in Windows 98)				
Data/fax modem	56K ³ V.90 / integrated in system / Lucent® 1646 / Mini PCI Type IIb / not voice-capable				
Audio	16-bit SoundBlaster Pro™ audio support / PCI / ES1946 / no full duplex support				
Speakers	Altec Lansing® SoundGuide stereo speakers w/ Dynamic Equalization Circuit™				
Audio features	Dial volume control (front side) / internal microphone				
Audio in/out jacks	Microphone jack (stereo) / headphone jack (stereo) / line-in jack (all left side)				
Infrared ports	None				
Security	Power-on password / supervisor password / security keyhole				
Limited warranty ^{*,11}	1 year - EasyServ™ ⁹ onsite pickup and delivery courier service				
Service options ¹⁵	On-site, M-F, 8-5, next bus day (72 cities) / serv up to 5 yrs from purch date				
Choose from seven optional color covers*: Mars Red Metallic, Terra Green Metallic, Eclipse Blue Metallic, Lunar Grey Metallic, Sirius Red, Andromeda Green, Polaris Blue Visit www.ibm.com/pc/us/thinkpad/series/cover.html for a complete list * Supplied by iBrands. Not manufactured or warranted by IBM.					
OPTIONS					
- 32MB SO DIMM 3.3v NP SDRAM 76H0294 - 64MB SO DIMM 3.3v NP SDRAM 20L0241 - 128MB SO DIMM 3.3v NP SDRAM 01K1150 - Li-Ion Battery 02K6603 - Ultrastim 56 watt AC Adapter (3 prong) 02K6545 - 10/100 EtherJet™ CardBus Adapter 34L1301 - MultiPort USB Hub 00N8215					
- Visit www.ibm.com/pc/us/accessories (U.S.) or www.ibm.com/pc/ca/accessories (CA)					
- ThinkPad Proven™ solutions ¹² (visit www.ibm.com/pc/us/thinkpad/proven)					
- Visit www.ibm.com/pc/us/thinkpad/series (U.S.) or www.ibm.com/pc/ca/thinkpad (CA)					
All models: - C: drive is FAT16 of 2GB - D: drive is FAT32 of remaining space					
Owner Privileges ¹³ program PC 98-compliant ACPI enabled Setup Guide, User's Reference, Windows 98 manual, and Quick Reference Card System Status Indicators Plug and Play 1.0a Standby mode and hibernation mode ENERGY STAR-compliant International Warranty Service ¹¹ IBM SystemXtra ³⁵ 24 hour / 7 day ⁷ telephone, bulletin board, electronic, and Internet (www.ibm.com/pc/us) support					
Color depth	LCD	External Monitor			
Resolution	TFT	60Hz	75Hz	85Hz	
640x480	16M	16M	16M	16M	
800x600	16M	16M	16M	16M	
1024x768	16M*	16M	16M	16M	
1280x1024	--	256	16K	16K	
1600x1200	--	64K	64K	64K	
* 14.1" model only					

ThinkPad EasyServ™: customer calls 1-800-772-2227, courier service picks up ThinkPad in most North American locations, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround). The customer may be asked certain diagnostic questions before a courier is sent.

* For a copy of IBM's Statement of Limited Warranty, call 1-800-772-2227
 No warranties are expressed or implied in this summary
 (1540) © IBM Corp. April 2002

IBM ThinkPad® i Series 1542, 1562, 1592 - withdrawn

IBM® ThinkPad®	i Series 1542		i Series 1562		i Series 1592		All-in-one design means the disk, diskette drive, and CD-ROM are all within the covers of the notebook																																																										
Processor type	Intel® Mobile Celeron™ 500MHz ¹ or Mobile Pentium III 500MHz / 100MHz system bus																																																																
L2 cache	Celeron: 128KB; Pentium III: 256KB; All: at processor speed / sync pipelined burst / ECC / write-back																																																																
Diskette drive	Internal 3.5" 1.44MB / on left side																																																																
CD-ROM	CD-ROM / 24X-10X ⁵ speed / CAV / ATAPI / bootable / not removable / on right side																																																																
DVD	None / no option available																																																																
Audio Control Panel	Media Center with Instant Audio (external CD player controls in front to play music CDs when system off or closed)																																																																
Type - model	2651-542		2651-562		2651-592																																																												
Processor	Celeron 500MHz		Pentium III 500MHz		Pentium III 500MHz																																																												
Disk - size / ms	12GB ⁴ / 12ms read / 14ms write / ATA-66 or PIO4 / S.M.A.R.T. ⁸																																																																
Disk controller	EIDE / supports one internal disk / disk can not be removed or upgraded / Ultra DMA/33 or PIO4																																																																
Avail / withdrawn date	April 2000 / October 2000																																																																
Display	12.1 inch (308mm) TFT color Active Matrix SVGA / 800x600 / 50ms / 120 nits 16.7 million colors / 150 to 1 contrast		14.1 inch (358mm) TFT color Active Matrix XGA / 1024x768 / 70 ms / 130 nits 16.7 million colors / 120 to 1 contrast		15.0 inch (381mm) TFT color Active Matrix XGA / 1024x768 / 80ms / 120 nits 16.7 million colors / 250 to 1 contrast																																																												
Graphics - controller	ATI™ Rage Mobility-M™ / Accelerated Graphics Port / AGP 2X / 64-bit graphics / 4MB SDRAM / motion compensation / multiple monitor support ²⁶ / DDC2B																																																																
Graphics - features	External SVGA to 1024x768x16.7 million colors at 85Hz and 1280x1024x256 colors																																																																
Memory - std / max	64MB / 256MB ¹⁷																																																																
Memory - features	SDRAM / non-parity / 100MHz / 3.3 volt / 64-bit data path / 2 sockets for JEDEC 144-pin SO DIMMs / one socket used by std memory / sockets accessed from bottom via removing cover held by phillips-head screws																																																																
Keyboard	Full-size 85-key (multiple Fn key functions) / slope with tilt feet / palm rest / four customizable color-coded Easy Launch buttons ¹⁸ / two Windows keys																																																																
Keyboard light	1562/92: ThinkLight™ / keyboard light (to work in low light) w/ power button																																																																
Pointing	TrackPoint® / Press-to-Select / Release-to-Select / dragging / click pace / center button for scrolling (Internet Scroll Bar) or magnifying glass / spare cap																																																																
Dimensions ¹⁹ / weight ²	1542: 12.9x10.6x1.59" front and 1.73" rear / 7.4 lbs 1562: 12.9x10.6x1.59" front and 1.73" rear / 7.6 lbs 1592: 12.9x10.6x1.73" front and 2.00" rear / 7.9 lbs																																																																
Battery - type	1542: NiMH / intelligent / right side		1562/92: Li-Ion / intelligent / right side																																																														
Battery - life ¹⁰	1542: 2.0 hrs		1562/92: 3.5 hrs																																																														
Charge time - on / off	1542: 2.5 hrs on / 2.1 hrs off		1562/92: 4.0 hrs on / 3.1 hrs off																																																														
Architecture	Intel 440BX AGPset / PIIX4M (EIDE, USB, PCI to ISA bdg) / AGP for graphics / TI1410 PCMCIA controller / PCI 2.1 32-bit 33Mhz (EIDE, modem, PCMCIA, USB, audio) / ISA (diskette, serial, parallel, infrared) / NS PC97338																																																																
Docking station	None																																																																
Port replicator	None																																																																
PCMCIA™ slots	1 Type I or 1 Type II or 1 Type III / CardBus 32-bit / Zoomed Video																																																																
USB / serial / parallel	One USB / one 9 pin; 16550A / one (IEEE P1284-A, EPP, ECP, bidirectional)																																																																
Other features	ACPI power mgmt / Universal AC adapter, 3 prong, barrel, slim, 56 watts																																																																
Video (TV) out	None																																																																
Data/fax modem	56K ³ V.90 / integrated in system / Lucent® 1646 / Mini PCI Type IIb / not voice-capable																																																																
Audio	16-bit SoundBlaster Pro™ audio support / PCI / ES1946 / full duplex support																																																																
Speakers	Altec Lansing® SoundGuide stereo speakers w/ Dynamic Equalization Circuit™																																																																
Audio features	Dial volume control (front side) / internal microphone																																																																
Audio in/out jacks	Microphone jack (stereo) / headphone jack (stereo) / line-in jack (all left side)																																																																
Infrared ports	None																																																																
Security	Power-on password / hard disk password / supervisor password / security keyhole																																																																
Limited warranty ¹¹	1 year - ThinkPad EasyServ™ ⁹ (door-to-door depot repair service) or carry-in																																																																
Service options ¹⁵	On-site, M-F, 8-5, next bus day (72 cities) / serv up to 5 yrs from purch date																																																																
Choose from seven optional color covers (12.1" and 14.0" models only ²⁰): Mars Red Metallic, Terra Green Metallic, Eclipse Blue Metallic, Lunar Grey Metallic, Sirius Red, Andromeda Green, Polaris Blue																																																																	
Visit www.ibm.com/pc/us/thinkpad/iseries/cover.html for a complete list																																																																	
<table><tr><th>Color depth</th><th>LCD</th><th colspan="3">External Monitor</th></tr><tr><th>Resolution</th><th>TFT</th><th>60Hz</th><th>75Hz</th><th>85Hz</th></tr><tr><td>640x480</td><td>16M</td><td>16M</td><td>16M</td><td>16M</td></tr><tr><td>800x600</td><td>16M</td><td>16M</td><td>16M</td><td>16M</td></tr><tr><td>1024x768</td><td>16M*</td><td>16M</td><td>16M</td><td>16M</td></tr><tr><td>1280x1024</td><td>--</td><td>256</td><td>16M</td><td>16M</td></tr><tr><td>1600x1200</td><td>--</td><td>256</td><td>256</td><td>--</td></tr></table>						Color depth	LCD	External Monitor			Resolution	TFT	60Hz	75Hz	85Hz	640x480	16M	16M	16M	16M	800x600	16M	16M	16M	16M	1024x768	16M*	16M	16M	16M	1280x1024	--	256	16M	16M	1600x1200	--	256	256	--																									
Color depth	LCD	External Monitor																																																															
Resolution	TFT	60Hz	75Hz	85Hz																																																													
640x480	16M	16M	16M	16M																																																													
800x600	16M	16M	16M	16M																																																													
1024x768	16M*	16M	16M	16M																																																													
1280x1024	--	256	16M	16M																																																													
1600x1200	--	256	256	--																																																													
* 14.1" and 15.0" models only																																																																	
<table><tr><th colspan="5">OPTIONS</th></tr><tr><td>- 32MB SO DIMM 100MHz NP SDRAM</td><td>20L0253</td><td colspan="3"></td></tr><tr><td>- 64MB SO DIMM 100MHz NP SDRAM</td><td>20L0254</td><td colspan="3"></td></tr><tr><td>- 128MB SO DIMM 100MHz NP SDRAM</td><td>20L0255</td><td colspan="3"></td></tr><tr><td>- Li-Ion Battery</td><td>02K6603</td><td colspan="3"></td></tr><tr><td>- Ultraslim 56 watt AC Adapter (3 prong)</td><td>02K6545</td><td colspan="3"></td></tr><tr><td>- 10/100 EtherJet™ CardBus Adapter</td><td>34L1301</td><td colspan="3"></td></tr><tr><td>- IBM MultiPort USB Hub</td><td>00N8215</td><td colspan="3"></td></tr><tr><td>- IBM Portable Drive Bay</td><td>37L1511</td><td colspan="3"></td></tr><tr><td colspan="5">- Visit www.ibm.com/pc/us/accessories (U.S.) or www.ibm.com/pc/ca/accessories (CA)</td></tr><tr><td colspan="5">- ThinkPad Proven™ solutions¹² (visit www.ibm.com/pc/us/thinkpad/proven)</td></tr><tr><td colspan="5">- Visit www.ibm.com/pc/us/thinkpad/iseries (U.S.) or www.ibm.com/pc/ca/thinkpad (CA)</td></tr></table>						OPTIONS					- 32MB SO DIMM 100MHz NP SDRAM	20L0253				- 64MB SO DIMM 100MHz NP SDRAM	20L0254				- 128MB SO DIMM 100MHz NP SDRAM	20L0255				- Li-Ion Battery	02K6603				- Ultraslim 56 watt AC Adapter (3 prong)	02K6545				- 10/100 EtherJet™ CardBus Adapter	34L1301				- IBM MultiPort USB Hub	00N8215				- IBM Portable Drive Bay	37L1511				- Visit www.ibm.com/pc/us/accessories (U.S.) or www.ibm.com/pc/ca/accessories (CA)					- ThinkPad Proven™ solutions ¹² (visit www.ibm.com/pc/us/thinkpad/proven)					- Visit www.ibm.com/pc/us/thinkpad/iseries (U.S.) or www.ibm.com/pc/ca/thinkpad (CA)				
OPTIONS																																																																	
- 32MB SO DIMM 100MHz NP SDRAM	20L0253																																																																
- 64MB SO DIMM 100MHz NP SDRAM	20L0254																																																																
- 128MB SO DIMM 100MHz NP SDRAM	20L0255																																																																
- Li-Ion Battery	02K6603																																																																
- Ultraslim 56 watt AC Adapter (3 prong)	02K6545																																																																
- 10/100 EtherJet™ CardBus Adapter	34L1301																																																																
- IBM MultiPort USB Hub	00N8215																																																																
- IBM Portable Drive Bay	37L1511																																																																
- Visit www.ibm.com/pc/us/accessories (U.S.) or www.ibm.com/pc/ca/accessories (CA)																																																																	
- ThinkPad Proven™ solutions ¹² (visit www.ibm.com/pc/us/thinkpad/proven)																																																																	
- Visit www.ibm.com/pc/us/thinkpad/iseries (U.S.) or www.ibm.com/pc/ca/thinkpad (CA)																																																																	
<table><tr><th colspan="5">OWNER PRIVILEGES¹³ program</th></tr><tr><td colspan="5">PC 98-compliant</td></tr><tr><td colspan="5">ACPI enabled</td></tr><tr><td colspan="5">Setup Guide, User's Reference, Windows manual, and Quick Reference Card</td></tr><tr><td colspan="5">System Status Indicators</td></tr><tr><td colspan="5">Plug and Play 1.0a</td></tr><tr><td colspan="5">Standby mode and hibernation mode</td></tr><tr><td colspan="5">ENERGY STAR-compliant</td></tr><tr><td colspan="5">International Warranty Service¹¹</td></tr><tr><td colspan="5">IBM SystemXtra^{®.35}</td></tr><tr><td colspan="5">24 hour / 7 day⁷ telephone, bulletin board, fax, electronic, and Internet (www.ibm.com/pc/us) support</td></tr></table>						OWNER PRIVILEGES ¹³ program					PC 98-compliant					ACPI enabled					Setup Guide, User's Reference, Windows manual, and Quick Reference Card					System Status Indicators					Plug and Play 1.0a					Standby mode and hibernation mode					ENERGY STAR-compliant					International Warranty Service ¹¹					IBM SystemXtra ^{®.35}					24 hour / 7 day ⁷ telephone, bulletin board, fax, electronic, and Internet (www.ibm.com/pc/us) support									
OWNER PRIVILEGES ¹³ program																																																																	
PC 98-compliant																																																																	
ACPI enabled																																																																	
Setup Guide, User's Reference, Windows manual, and Quick Reference Card																																																																	
System Status Indicators																																																																	
Plug and Play 1.0a																																																																	
Standby mode and hibernation mode																																																																	
ENERGY STAR-compliant																																																																	
International Warranty Service ¹¹																																																																	
IBM SystemXtra ^{®.35}																																																																	
24 hour / 7 day ⁷ telephone, bulletin board, fax, electronic, and Internet (www.ibm.com/pc/us) support																																																																	

ThinkPad EasyServ™: customer calls 1-800-772-2227, courier service picks up ThinkPad in most North American locations, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround). The customer may be asked certain diagnostic questions before a courier is sent.

All trademarks are the property of their respective owners
 No warranties are expressed or implied in this summary
 (1542) © IBM Corp. October 2000