


OVERVIEW



1. USB-C 3.2 Gen 1	7. Nano-SIM card slot *
2. USB-C 3.2 Gen 2	8. Ethernet (RJ-45)
3. Side docking connector	9. Smart card reader *
4. USB 3.2 Gen 1 (Always On)	10. Headphone / microphone combo jack (3.5mm)
5. HDMI 1.4b	11. USB 3.2 Gen 1
6. MicroSD card reader	12. Kensington Security Slot

- Notes:
- Ports with \* are only available on selected models
  - The combination of 2 and 3 is side docking connector

PERFORMANCE

Processor

Processor Family

Intel® Celeron® or 10th Generation Intel Core™ i3 / i5 / i7 Processor

Processor\*\*[1]

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
Celeron 5205U	2	2	1.9GHz	-	2MB	DDR4-2400	Intel UHD Graphics
Core i3-10110U	2	4	2.1GHz	4.1GHz	4MB	DDR4-2666	Intel UHD Graphics
Core i5-10210U	4	8	1.6GHz	4.2GHz	6MB	DDR4-2666	Intel UHD Graphics
Core i5-10310U	4	8	1.7GHz	4.4GHz	6MB	DDR4-2666	Intel UHD Graphics
Core i7-10510U	4	8	1.8GHz	4.9GHz	8MB	DDR4-2666	Intel UHD Graphics
Core i7-10610U	4	8	1.8GHz	4.9GHz	8MB	DDR4-2666	Intel UHD Graphics

Notes:

- 1. i7-10610U is NOT available in EMEA

Operating System

Operating System\*\*

- Windows® 10 Pro 64
- Windows 10 Home 64
- Ubuntu Linux
- No operating system

Graphics

Graphics\*\*[1]

Graphics	Type	Memory	Key Features
Intel UHD Graphics	Integrated	Shared	DirectX® 12
AMD Radeon™ 625	Discrete	2GB GDDR5	DirectX 12

Notes:

- 1. Discrete graphics is NOT available in EMEA.

Monitor Support

Monitor Support

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and USB-C)

- HDMI supports up to 4096x2160@24Hz
- USB-C supports up to 4096x2304@60Hz

Chipset

Chipset

Intel SoC (System on Chip) platform

Memory

Max Memory[1]

- Up to 64GB DDR4-2400
- Up to 64GB DDR4-2666

Memory Slots

Two DDR4 SO-DIMM slots, dual-channel capable

Memory Type\*\*[2]

- DDR4-2400
- DDR4-2666

- Notes:
- 1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.
  - 2. Installed memory is actually 3200MHz but run at 2400MHz or 2666MHz depending on the memory support capability of processor

Storage

Storage Support<sup>[1][2]</sup>

- HDD/SSD mode: up to two drives, 1x 2.5" HDD + 1x M.2 SSD
  - 2.5" HDD up to 2TB
  - M.2 2242 SSD up to 512GB
- One SSD mode: one drive, 1x M.2 SSD
  - M.2 2280 SSD up to 1TB
  - M.2 2242 SSD up to 512GB
  - Optional Intel Optane™ Memory integrated with SSD, M.2

Storage Slot<sup>[3]</sup>

- HDD/SSD mode: one 2.5" drive slot + one M.2 slot
  - One 2.5" drive slot, supports 2.5" SATA HDD
  - One M.2 2242 PCIe® Gen 3x2 slot, supports M.2 2242 SSD
- One SSD mode: one M.2 slot
  - One M.2 2280 PCIe Gen 3x4 slot, supports M.2 2242/2280 SSD

Storage Type

Disk Type	Interface	RPM	Security
2.5" SATA HDD	SATA 6Gb/s	5.4K	APS (Active Protection System™)
2.5" SATA HDD	SATA 6Gb/s	7.2K	APS (Active Protection System)
M.2 2242 SSD	PCIe NVMe®, PCIe 3.0 x2	-	-
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-	Opal2
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-	-
Intel Optane Memory with Solid State Storage, M.2 2280	PCIe NVMe, PCIe 3.0 x4	-	-

- Notes:
- 1. The storage capacity supported is based on the test results with current Lenovo storage offerings. The system may support larger storage as the technology develops.
  - 2. HDD/SSD mode is NOT available in EMEA
  - 3. System has one HDD slot or one M.2 2280 slot exclusively for storage

Removable Storage

Optical

None

Card Reader

MicroSD card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, Dolby® Audio™

Microphone<sup>[1]</sup>

Dual array microphone, far-field

Camera<sup>\*\*[2]</sup>

- 720p, with ThinkShutter, fixed focus
- IR & 720p hybrid, with ThinkShutter, fixed focus

Notes:

- 1. No microphone is for special bid only.
- 2. No camera is for special bid only.

Battery

Battery

Integrated Li-Polymer 45Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

Max Battery Life<sup>[1]</sup>

MobileMark® 2014: 11.6 hr  
MobileMark 2018: 8.56 hr  
JEITA 2.0: 10.8 hr

Notes:

- 1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter<sup>\*\*[1][2]</sup>

- 45W USB-C (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 45W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

- 1. AC adapter offerings depend on the country.
- 2. 45W USB-C AC adapter is NOT available in EMEA

DESIGN

Display

Display<sup>\*\*[1]</sup>

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	Key Features
15.6"	HD (1366x768)	None	TN	220 nits	Anti-glare	16:9	400:1	45% NTSC	90°	-
15.6"	FHD (1920x1080)	None	IPS	250 nits	Anti-glare	16:9	700:1	45% NTSC	170°	-
15.6"	FHD (1920x1080)	Multi-touch	IPS	300 nits	Anti-glare	16:9	700:1	45% NTSC	170°	-

Touchscreen

- On-cell touch, supports 10-point touch
- Non-touch

Notes:

- 1. California Electronic Waste Recycling Fee  
In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, go to <https://www.calrecycle.ca.gov/Electronics/Consumer>

Input Device

Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls, numeric keypad

Keyboard Backlight

- LED backlight
- Non-backlight

UltraNav™

TrackPoint® pointing device and Mylar® surface multi-touch touchpad

## Mechanical<sup>[1]</sup>

### Dimensions (WxDxH)

366.5 x 250 x 21 mm (14.43 x 9.84 x 0.83 inches)

### Weight

1.98 kg (4.37 lbs)

### Case Color

Black

### Case Material

PC + ABS (top), PC + ABS (bottom)

#### Notes:

1. The system dimensions and weight vary depending on configurations.

## CONNECTIVITY

### Network

#### Onboard Ethernet<sup>\*\*</sup>

- Gigabit Ethernet, Intel Ethernet Connection I219-LM (vPro models), 1x RJ-45, supports Wake-on-LAN
- Gigabit Ethernet, Intel Ethernet Connection I219-V (non-vPro models), 1x RJ-45, supports Wake-on-LAN

#### WLAN + Bluetooth<sup>\*\*[1][2]</sup>

- Wi-Fi® 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2, M.2 card
- Mediatek Wi-Fi 6 MT7921, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2, M.2 Card
- Realtek Wi-Fi 6 RTL8852AE, 802.11ax Dual Band 2x2 Wi-Fi + Bluetooth 5.2, M.2 card
- Intel Wi-Fi 6 AX200, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2, M.2 card
- No WLAN and Bluetooth

#### WWAN<sup>\*\*[3]</sup>

- Wireless WAN upgradable to 4G (with antenna ready)
- Integrated Mobile Broadband 4G LTE-A, CAT9, Fibocom L850-GL, M.2 card
- No support

#### SIM Card

- Gemalto eSIM
- No SIM card inbox

#### NFC

- Near Field Communication
- No support

#### Notes:

1. Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitation
2. Wi-Fi 6 full features might be limited by country-level restrictions.
3. For non-WWAN model, it means the model is NOT WWAN upgradable.  
WWAN is not supported on HDD models.

## Ports<sup>[1]</sup>

### Standard Ports

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 1x USB-C 3.2 Gen 1 (support data transfer, Power Delivery and DisplayPort™ 1.2)
- 1x USB-C 3.2 Gen 2 (support data transfer, Power Delivery and DisplayPort 1.2)
- 1x HDMI 1.4b
- 1x microSD card reader
- 1x Ethernet (RJ-45)
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Side docking connector

### Optional Ports<sup>\*\*\*</sup>

- 1x Smart card reader
- 1x Nano-SIM card slot (WWAN support models)

---

**Notes:**

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
  - USB 2.0: 480 Mbit/s;
  - USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
  - USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
  - USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
  - Thunderbolt™ 3/4: 40 Gbit/s;
  - FireWire 400: 400 Mbit/s;
  - FireWire 800: 800 Mbit/s

## Docking

### Docking

Various docking solutions supported via USB-C.

For more compatible docking solutions, please visit [Docking for ThinkPad® L15 Gen 1 \(Intel\)](#)

## Monitor Cable

### Monitor Cable\*\*\*

- Lenovo HDMI to VGA Monitor Adapter
- Lenovo USB-C to DisplayPort Adapter
- Lenovo USB-C to VGA Adapter
- No monitor cable

## SECURITY & PRIVACY

## Security

### Security Chip\*\*

- Discrete TPM 2.0, TCG certified
- Firmware TPM 2.0 integrated in chipset
- Disabled (in some regions)

### Physical Locks

Kensington® Security Slot

### Smart Card Reader

- Smart card reader
- No smart card reader

### Fingerprint Reader\*\*<sup>[1]</sup>

- Touch style fingerprint reader on palm rest, match-on-chip
- Touch style fingerprint reader on palm rest, match-on-host
- No fingerprint reader

### BIOS Security

- Power-on password
- Supervisor password
- Hard disk password
- Self-healing BIOS

### Other Security

- (Optional) ThinkShutter camera cover
- (Optional) IR camera for Windows Hello

---

**Notes:**

1. Preboot authentication is only available on the models with match-on-chip fingerprint reader.  
Match-on-chip fingerprint reader is for special bid only.

## MANAGEABILITY

## System Management

**System Management<sup>[1]</sup>**

- Intel vPro
- Non-vPro

## Notes:

1. Intel vPro offers a superset of DASH's defined capabilities.

**SERVICE****Warranty****Base Warranty<sup>\*\*[1]</sup>**

- 1-year depot service
- 1-year depot with 2-year system board service (Korea only)
- 1-year + 2-year depot service
- 1-year + 2-year limited onsite service
- 3-year (1-yr battery) depot service
- 3-year (1-yr battery) limited onsite service

## Notes:

1. More information of warranty policy, please access <https://pcsupport.lenovo.com/warranty>

**ENVIRONMENTAL****Operating Environment****Temperature<sup>[1]</sup>**

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F ) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

**Humidity**

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

**Altitude**

Maximum altitude (without pressurization): 3048 m (10,000 ft)

## Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F).

**CERTIFICATIONS****Green Certifications****Green Certifications**

- EPEAT™ Gold
- ENERGY STAR® 8.0
- TCO Certified
- RoHS compliant

**Other Certifications****Mil-Spec Test**

MIL-STD-810G military test passed

- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Feature with \*\*\* means that one or more offerings listed under the feature could be configured on selected models.

- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION “AS IS,” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



