

# IBM ThinkPad Power Series 850 - withdrawn

IBM® ThinkPad®: <b>≧ 850</b> PowerPC - TFT color - CD-ROM - Video Card		ThinkPad Power Series 850 strengths: ➤ <b>PowerPC performance</b> ➤ <b>Collaborative and conversational computing</b> ➤ <b>Removable, double speed, 5.25" CD-ROM</b> ➤ <b>Video card (acceleration, composite video)</b> ➤ <b>Optional top mounted video camera</b>						
Processor type	<b>Power PC 603e</b> / 100/66 MHz / 32 KB L1 cache							
L2 cache	256 KB / write back / direct mapped / 64 bit transfers							
Processor / L2 upgrade	None							
Removable diskette	Internal or external 3.5" 1.44 MB ○ / external diskette drive connector Can use diskette and CD-ROM simultaneously as diskette drive ships with an external case with cable							
Removable CD-ROM	<b>5.25" CD-ROM ○</b> / double speed / multi-session / XA / SCSI-2 / bootable The middle bay supports either the standard diskette drive or standard CD-ROM							
Type - model	6042-xxx (listed below)							
Available date	July 1995 or later (listed below)							
Disk controller	SCSI-2 Fast (for disk, CD-ROM) / external SCSI-2 50 pin connector							
Removable disk - size	<i>Choice:</i> <b>540 MB</b> 14 ms □ ○ / <b>810 MB</b> 14 ms □ ○ / <b>1.2 GB</b> 12 ms ○							
Display - type	<i>Choice:</i> Color 640 x 480 or Color 800 x 600 (listed below)							
Display - technology	<b>Black Matrix TFT - active matrix</b> / up to 65,536 simultaneous colors							
Display - diagonal size	10.4 inch / 100 to 1 contrast ratio for 640 x 480 / 110 to 1 for 800 x 600							
Graphics - controller	WD90C24A Rev C with 1 MB DRAM (called G10 Graphics Adapter)							
Graphics - vendor	Western Digital / External SVGA to 1024 x 768 w/ 256 colors (up to 75 Hz)							
Graph - arch/data path	PCI 2.0 / 32 bit / Simultaneous LCD and CRT / 180 degree tilt							
Video function	<b>Video acceleration / composite in/out</b> (called G10 Graphics with Motion Video)							
Video camera	<i>Option:</i> CCD camera on top of LCD / NTSC / white balance, iris, lens focus							
Memory - std / max	16 or 32 MB / 80 to 96 MB 70 ns / <b>parity</b> / 5 volt / 64 bit transfers							
Mem - sockets	Standard: 2 SO DIMMs in 2 SO DIMM sockets; available: 2 IC DRAM sockets							
Mem-options available	4, 8, 16, 32 MB IC DRAMs / must be installed in matched pairs							
Keyboard / # of keys	Full size alp/num / 84 (no Fn key)	Easy-Setup is entered by holding F1 when power on						
Keyboard slope	Yes (legs pop out) / <b>palm rest space</b>							
Mouse/pointing	<b>TrackPoint III™</b>							
Ext keyboard support	Yes (with option cable)							
Dimensions	11.7 x 10.2 x 2.4" (286 cubic inches)	<b>ALL 850 MODELS</b> <b>Liftable (pop-up) keyboard to access and remove CD-ROM, diskette drive, disk, and memory (Battery removed from side)</b>						
Color	Black							
Weight (with battery)	7.96 pounds (with CD-ROM)							
Battery - type	Nickel hydride (NiMH) / Intelligent							
Battery - life	2 to 5 hours							
Charge time - on / off	2 hrs / 1.5 hrs							
Architecture	PCI 2.0 / 32 bit / 33 MHz / 5 volt (SCSI, motion video) ISA (audio, PCMCIA, diskette, serial, parallel, 120-pin external expansion) VL-Bus 2.0 / 32 bit (graphics via PCI-to-VL Bridge)							
Docking Station	None							
Port replicator	None							
PCMCIA™ 2.1 slots	<b>2 Type I or 2 Type II or 1 Type III</b>							
Serial / parallel ports	One 9 pin; 16550A / Enhanced Parallel Port (EPP and IEEE 1284)							
Other features	Universal AC adapter, 50 watts, not wallmount / Drive Startup Sequence							
Data/fax modem	None (use PCMCIA) / voice-over-data using industry standard modems							
Audio support	<b>CD quality audio (44.1 kHz, 16 bit, stereo)</b> / Crystal Semiconductor™ CS4231 Internal stereo speakers (1 watt each) / dial volume control Internal microphone / IBM Personal Microphone (earphone and headset) Input jack / output jack / line in / line out (all 3.5 mm) None							
Audio in/out jacks								
Infrared ports	None							
Security	Power-on password / Supervisor password / Hardware security loop (locking lever) / Keyboard lock / Locking device keyhole (Kensington™ MicroSaver™ cable lock) / PCMCIA card lock							
Preinstalled software	<i>Choice:</i> none or select a supported operating system (listed below)							
Warranty	<b>3 year</b> - ThinkPad EasyServ							
Warranty options	ThinkPad EasyServ Overnight Repair Option							
<b>Type-Model</b>	<b>Part</b>	<b>Mem</b>	<b>Disk</b>	<b>LCD</b>	<b>Graphics</b>	<b>Op Sys</b>	<b>Price</b>	<b>Avail</b>
≧ 6042-9CD	29H8170	32 MB	1.2 GB	800x600	G10 w/ Motion	None	\$ 8,999	Aug 95
≧ 6042-9DD	29H8171	32 MB	1.2 GB	800x600	G10 w/ Motion	AIX	9,849	Aug 95
≧ 6042-9ED	29H8173	32 MB	1.2 GB	800x600	G10 w/ Motion	NT	9,299	Aug 95
≧ 6042-96D	29H8196	32 MB	810 MB	800x600	G10 w/ Motion	None	8,549	Jul 95
≧ 6042-97D	29H8197	32 MB	810 MB	800x600	G10 w/ Motion	AIX	9,399	Jul 95
≧ 6042-98D	29H8199	32 MB	810 MB	800x600	G10 w/ Motion	NT	8,849	Jul 95
≧ 6042-967	29H8175	32 MB	810 MB	640x480	G10 w/ Motion	None	8,149	Jul 95
≧ 6042-977	29H8176	32 MB	810 MB	640x480	G10 w/ Motion	AIX	8,999	Jul 95
≧ 6042-987	29H8178	32 MB	810 MB	640x480	G10 w/ Motion	NT	8,449	Jul 95
≧ 6042-906	29H8180	16 MB	540 MB	640x480	G10 w/ Motion	None	6,669	Jul 95
≧ 6042-926	29H8182	16 MB	540 MB	640x480	G10 w/ Motion	NT	6,999	Jul 95
Compatible in 820 and 850: ① Disks, ② CD-ROM, ③ AC Adapter								

Operating System Preloads: ① IBM AIX Version 4 for Clients 4.1.3 - Ultimedia Services Ver 2.1.2 - Insignia SoftWindows Ver 1.1 - Speech Dictation - Personal Conferencing for AIX on CD - Essentials! (catalogs and support) - Power, Performance, Potential multimedia presentation - CD-ROMs included: Program Pack, AIX backup, Pers Conferencing for AIX - Black 3 button mouse ② Microsoft Windows NT 3.51 Workstation - Essentials! (catalogs and support) - Power, Performance, Potential presenta - Compuserve WinCIM Power Series Ed - Introducing ThinkPad Power Series 850 - CD-ROMs included: Program Pack, NT backup ③ No preloaded operating system - CD-ROMs included: Program Pack, Personal Conferencing for AIX ④ IBM OS/2 Warp Connect (when available) ⑤ Solaris (when available)	
G10 Graphics with Motion Video provides: - <b>Acceleration</b> of motion video with scaling (no interpolation) of image. Video may be scaled up to full screen without frame rate degradation - <b>Composite in</b> (from camcorder, TV, VCR) for video capture (capture and digitize video), still image capture (capture and digitize still photo images), and overlay (view video on LCD without capturing it to disk). Uses NTSC or PAL - <b>Composite out</b> (to camcorder, TV, VCR) in NTSC. So can use TV as an external display or record the contents of the screen to VCR - ThinkPad 850 includes in/out RCA jacks on the back of the system	
Options for ThinkPad Power Series 850: - Disks: 540 MB SCSI-2 30H1388 810 MB SCSI-2 30H1392 1.2 GB SCSI-2 30H1467 - AC Adapter 50 watts 30H1403 - <b>Video Camera (NTSC)</b> <b>85G2715</b> - 850 NiMH Battery Pack 85G2671 - 850 Quick Charger 85G2662 - IBM Personal Microphone 12H1504 - 4 MB IC DRAM 70ns 5v parity 92G7238 - 8 MB IC DRAM 70ns 5v parity 92G7241 - 16 MB IC DRAM 70ns 5v parity 92G7234 - 32 MB IC DRAM 70ns 5v parity 92G7235	
<b>FEATURES OF 850 MODELS</b> Battery life and other indicators Non-disruptive battery exchange Suspend mode US EPA Energy Star compliant Personalized nameplate in molded indentation Compatible with PowerPC Reference Platform™ Specifications (PReP) v1.1 <b>3 year warranty</b> <b>International Warranty Service</b> <b>24 hour / 7 day telephone, bulletin board, fax, and electronic support</b> <b>IBM warranty/service</b> <b>30 day money back guarantee</b>	

**ThinkPad EasyServ™:** customer calls 1-800-772-2227, courier service picks up ThinkPad at any location, IBM repairs and mails back (no shipping charges, most shipping is overnight, 3 business day average turnaround). Overnight repair option in US available for \$99.  
□ = Upgradeable; ○ = Removable; ≧ = Withdrawn effective March 20, 1996

All trademarks are the property of their respective owners  
No warranties are expressed or implied in this summary  
(850) Compiled by Roger Dodson, IBM. February 1996