Type-model Processo	r MHz Mem Screen Disk	CD or DVD (	Communica Bay		WINDOWS 98 PRELOAD <sup>14</sup>
2647-21U Pentium I 2647-24U Pentium I 2647-64U Pentium I 2647-44U Pentium I 2647-44U Pentium I 2647-81U Pentium I 2647-852U Pentium I 2647-55U Pentium I 2647-95U Pentium I 2647-95U Pentium I 2647-95U Pentium I 2647-95U Pentium I 2647-86U Pentium I	1 650	GB 24X-10X CD   GB 24X-10X CD   GB 24X-10X CD   GB 24X-10X CD   GB 6X-2.3X DVD	modem Intel® eth/mod modem Intel® eth/mod modem Intel eth/mod modem SCom® eth/mod 3Com® eth/mod	98SE May 00 98SE May 00 2000 May 00 98SE May 00 98SE May 00 2000 May 00 2000 May 00 2000 Jun 00 2000 Jun 00 2000 Jun 00 100 July 00 98SE July 00 98SE July 00 2000 July 00 July 00 98SE July 00	- Microsoft® Windows® 98 Second Edition¹3  • ThinkPad Utilities • ThinkPad Assistant™ • ConfigSafe® • IBM Update Connector™.15 • Access ThinkPad II • PC-Doctor™ • Mediamatics DVD Express (if DVD) - Lotus® SmartSuite® Millennium and Lotus Notes® Client 5.0 license ♦ Software Selections CD-ROM ◆ Recovery CD-ROM (Windows 98 SE)
Processor Intel® Mobile Pentium® III 650, 700, or 750MHz <sup>1,24</sup> with Intel SpeedStep™ technology and 100MHz system bus					♦ Recovery CD-RÓM (Windows 95)
L2 cache Memory  Memory  L2 cache Memory  L2 cache Memory  L2 cache Memory  L2 cache Memory  Memory  L2 cache Memory  Mem					• WINDOWS 2000 PRELOAD <sup>14</sup> - Windows 2000 Professional <sup>13</sup> • ThinkPad Utilities • ThinkPad Assistant
Diskette drive CD-ROM DVD-ROM UltraBay 2000 Disk	3.5" 1.44MB (use in UltraBay 2000 or attach externally with optional cable via parallel port)  Some: CD-ROM / 24X-10X <sup>9</sup> speed / bootable / removable from Ultrabay™ 2000  Some: DVD-ROM / 6X-2.3X <sup>9</sup> speed / bootable / removable from Ultrabay 2000  Modular bay for interchangeable devices / on all A and T Series, ThinkPad Dock  6GB <sup>9</sup> or 12GB or 20GB / upgradeable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay 2000				ConfigSafe     IBM Update Connector     Access ThinkPad II     PC-Doctor     Mediamatics DVD Express (if DVD)     Lotus® SmartSuite® Millennium and Lotus Notes® Client 5.0 license
Display	13.3" (337.8mm) XGA (1024x768) TFT color / Active Matrix 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix				
Graphics controller Graphics - external	S3® Savage IX8 / <b>AGP 2X</b> / <b>8MB</b> SGRAM / 64-bit path to memory External SVGA to 1024x768x16.7 million colors at 85Hz and up to 1600x1200				LINUX PRELOAD <sup>14</sup>
Keyboard ThinkLight™ UltraPort™	<b>ThinkPad Button</b> / palm rest / TrackPoint®, Press-to-Select, Internet Scroll Bar Illuminates the keyboard to improve visibility in low-light conditions UltraPort connector on top of display for options such as digital Ultraport Camera				- Caldera® OpenLinux eDesktop™2.4 • Access ThinkPad II • StarOffice • Netscape Communicator
Dimensions <sup>3</sup> Approximate weight <sup>2</sup> Case material Battery - type Battery - life <sup>10</sup> Charge time <sup>10</sup> - on / off	<b>Titanium Composite</b> in the top and bottom covers for enhanced strength⁴ Lithium Ion 6-cell / intelligent / supports unique 2nd battery in Ultrabay 2000 4 hours (3.75 hours for Pentium III 750MHz models)				
Port replicator Docking Station PC Card Std slots Ports Other features Video out Communicatns Bay	Intel 440BX AGPset / Intel PIIX4M (EIDE with Ultra DMA/33 or PIO Mode 4 support, ISA Bridge, USB) / TI® PCI1450 for CardBus / AGP 2X for graphics / PCI 2.1 / 32-bit / 33MHz (EIDE, CardBus, audio, USB, ext expansion) / PC97338 Super I/O / ISA (diskette, serial, parallel, infrared, ext exp) ThinkPad Port Replicator ThinkPad Dock (includes Ultrabay 2000 and half-size PCI slot) 2 Type I, 2 Type II, or 1 Type III / CardBus 32-bit / PCMCIA 2.1 / Zoomed Video USB: One (Version 1.1) / Serial: one 9 pin / Parallel: one / keyboard / mouse / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) 72 watt AC Adapter S-video out / one industry standard connector / full MPEG-2 support / optional cable for S-video to composite conversion available Communications Bay with Mini PCI IIIb slot / customer accessible				
Modem Ethernet/modem Audio support Security	Some models: 56K <sup>6</sup> V.90 Mini PCI modem card / Lucent® chip set Some models: IBM 10/100 EtherJet™ Mini PCI Adapter with 56K Modem / Intel or 3Com ethernet chipset / Lucent modem chip set PCI audio / SoundBlaster Pro™ support / CS4624 with CS4297A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal microphone / input jack (3.5 mm) / output jack (3.5 mm) / line in jack Power-on password / hard disk password / supervisor password / security keyhole				PC 99-compliant CIM and DMI 2.0 compliant Wired for Management 2.0 Local and remote asset manage ment via the IBM Universal
Limited warranty <sup>12</sup> Service options	3 year - carry-in or ThinkPad EasyServ <sup>TM, 19</sup> depot repair service via courier Optional service upgrades provide up to three years of onsite or depot repair service coverage from date of ThinkPad purchase (including warranty period)				Manageability solutions     IBM PC Lifecycle Care provides     proactive life cycle management     and transition planning tools
56K Modem by 3Cc - IBM 10/100 EtherJo 56K Modem Ultrabay 2000 interci - 6X-2X DVD Ultraba - SuperDisk (LS-120) - 24X-10X CD-ROM - 4X/4X/20X CD-Rea - Zip 250MB Ultrabay - Ultrabay 2000 Li-lor - Travel Bezel for Ultr Wireless connectivit - IBM 802.11b Wirele	et Mini PCI Adapter with 09N9774 et Mini PCI Adapter with 08K3124 nangeable accessories y 2000 Drive 05K9232 UltraBay 2000 Drive 05K9233 d/Write Ultrabay 2000 oN8253 1 battery 02K6646 pabay 2000 0	- 64MB SO DIMM 1 - 128MB SO DIMM - 256MB SO DIMM - 6.0GB HDD - 12.0GB HDD - 18.0GB HDD - 20GB HDD - Second HDD Ada - Portable Drive Ba' - ThinkPad Port Re - ThinkPad Dock (A - ThinkPad T Serie - ThinkPad T Serie - ThinkPad Monitor - IBM Ultraport Can - RCA video convertions - 128M Ultraport Can - 128M Ultraport Can - RCA video convertions - 128M Ultraport Can - 128M Ultraport Can - 128M Ultraport Can - RCA video convertions - 128M Ultraport Can - 128M Ultrap	IOOMHz NP SDR 100MHz NP SDR 100MHz NP SDR 100MHz NP SDR 100MHz NP SDR 2000 eplicator (A and T A and T Series) is Battery C Adapter Stand mera II rsion cable	AM 20L0254 RAM 20L0255 RAM 33L3069 05K9237 05K9238 05K9239 27L3439 2000 08K6068 19K4480	ENERGY STAR compliant Setup Guide, User's Reference, Windows manual Asset ID™ wireless RF technology (via installing into disk cover) IBM is planning to announce Bluetooth™ wireless technology communications devices including a Bluetooth PC Card option and Bluetooth option for the ThinkPad UltraPort connector in the second half of 2000 Personalized Web-based support International Warranty Service¹ IBM SystemXtra®.20 24 hour x 7 day¹8 toll-free hardware support during the warranty