



Comp 512
Spring 2011

Beyond Regional Optimization

Global Data Flow Analysis with Applications

Copyright 2011, Keith D. Cooper & Linda Torczon, all rights reserved.

Students enrolled in Comp 512 at Rice University have explicit permission to make copies of these materials for their personal use.

Faculty from other educational institutions may use these materials for nonprofit educational purposes, provided this copyright notice is preserved.



Last Lecture


- Extended Basic Blocks
- Superlocal Value Numbering
 - > Treat each path as a single basic block
 - > Use a scoped hash table & SSA names to make it efficient
- Loop Unrolling as an example of a loop-based optimization



This Lecture

- Dominator Trees
 - Computing dominator information
 - Global data-flow analysis
- Dominator-based Value Numbering
 - Enhance the Superlocal Value Numbering algorithm so that it can cover more blocks
 - Not truly a global optimization, but a good application of dominators

Superlocal Value Numbering



With all the bells & whistles

- Find more redundancy
- Pay little additional cost
- Still does nothing for F & G

Superlocal techniques


- Some local methods extend cleanly to superlocal scopes
- VN does not back up
- If C adds to A, it's a problem



What About Larger Scopes?

We have not helped with F or G

- Multiple predecessors
- Must decide what facts hold in F and in G
 - For G, combine B & F?
 - Merging state is expensive
 - Fall back on what's known





Dominators

Definitions

In a flow graph, x dominates y if and only if every path from the entry of the control-flow graph to the node for y includes x

- By definition, x dominates x
- We associate a DOM set with each node
- $|\text{DOM}(x)| \geq 1$

Immediate dominator

- For any node x , there must be a y in $\text{DOM}(x)$ closest to x
→ Unless $x = n_0$, $x \neq \text{IDOM}(x)$
- We call this y the immediate dominator of x
- As a matter of notation, we write this as $\text{IDOM}(x)$

Original idea: R.T. Prosser. "Applications of Boolean matrices to the analysis of flow diagrams," *Proceedings of the Eastern Joint Computer Conference*, Spartan Books, New York, pages 133-138, 1959.



Dominators



Dominators have many uses in analysis & transformation

- Finding loops
- Building SSA form
- Making code motion decisions

Dominator sets

Block	Dom	IDom
A	A	-
B	A,B	A
C	A,C	A
D	A,C,D	C
E	A,C,E	C
F	A,C,F	C
G	A,G	A

Dominator tree




We'll look at how to compute dominators later



Dominators Can Improve Superlocal Value Numbering

We have not helped with F or G

- Multiple predecessors
 - For G, combine B & F?
 - Merging state is expensive
 - Fall back on what's known
- Can use table from $IDOM(x)$ to start x
 - Use C for F and A for G
 - Imposes a Dom-based application order



Leads to Dominator VN Technique (DVNT)

*



Dominator Value Numbering


The DVNT Algorithm

- Use superlocal algorithm on extended basic blocks
 - Retain use of scoped hash tables & SSA name space
- Start each node with table from its IDOM
 - DVNT generalizes the superlocal algorithm
- No values flow along back edges (i.e., around loops)
- Constant folding, algebraic identities as before

Larger scope leads to (*potentially*) better results

- LVN + SVN + good start for EBBs missed by SVN

Dominator Value Numbering



DVNT advantages

- Find more redundancy
- Little additional cost
- Retains *online* character

DVNT shortcomings

- Misses some opportunities
- No loop-carried CSEs or constants



Computing Dominators

Critical first step in SSA construction and in DVNT

- A node n dominates m iff n is on every path from n_0 to m
 - Every node dominates itself
 - n 's immediate dominator is its closest dominator, $IDom(n)^\dagger$

$$Dom(n_0) = \{ n_0 \}$$

$$Dom(n) = \{ n \} \cup \left(\bigcap_{p \in preds(n)} Dom(p) \right)$$

Initially, $Dom(n) = N$,
 $\forall n \neq n_0$.
Can do better.

Computing DOM

- These simultaneous set equations define a simple problem in data-flow analysis
- Equations have a unique fixed point solution
- An iterative fixed-point algorithm will solve them quickly

$^\dagger IDom(n) \neq n$, unless n is n_0 , by convention.



Round-robin Iterative Algorithm


```
DOM( $b_0$ )  $\leftarrow \emptyset$ 
for  $i \leftarrow 1$  to  $N$ 
    DOM( $b_i$ )  $\leftarrow \{ \text{all nodes in graph} \}$ 
change  $\leftarrow$  true
while (change)
    change  $\leftarrow$  false
    for  $i \leftarrow 0$  to  $N$ 
        TEMP  $\leftarrow \{ i \} \cup (\cap_{x \in \text{pred}(b)} \text{DOM}(x))$ 
        if DOM( $b_i$ )  $\neq$  TEMP then
            change  $\leftarrow$  true
            DOM( $b_i$ )  $\leftarrow$  TEMP
```

Termination

- Makes sweeps over the nodes
- Halts when some sweep produces no change



Example



Flow Graph

Progress of iterative solution for Dom


Iteration	DOM(<i>n</i>)							
	0	1	2	3	4	5	6	7
0	0	<i>N</i>	<i>N</i>	<i>N</i>	<i>N</i>	<i>N</i>	<i>N</i>	<i>N</i>
1	0	0,1	0,1,2	0,1,3	0,1,3,4	0,1,3,5	0,1,3,6	0,1,7
2	0	0,1	0,1,2	0,1,3	0,1,3,4	0,1,3,5	0,1,3,6	0,1,7

Results of iterative solution for Dom

	0	1	2	3	4	5	6	7
DOM	0	0,1	0,1,2	0,1,3	0,1,3,4	0,1,3,5	0,1,3,6	0,1,7
IDOM	0	0	1	1	3	3	3	1



Example



Dominance
Tree

Progress of iterative solution for DOM

Iteration	$\text{DOM}(n)$							
	0	1	2	3	4	5	6	7
0	0	N	N	N	N	N	N	N
1	0	0,1	0,1,2	0,1,3	0,1,3,4	0,1,3,5	0,1,3,6	0,1,7
2	0	0,1	0,1,2	0,1,3	0,1,3,4	0,1,3,5	0,1,3,6	0,1,7

Results of iterative solution for DOM

	0	1	2	3	4	5	6	7
DOM	0	0,1	0,1,2	0,1,3	0,1,3,4	0,1,3,5	0,1,3,6	0,1,7
IDOM	0	0	1	1	3	3	3	1

There are asymptotically faster algorithms.

With the right data structures, the iterative algorithm can be made extremely fast.

See Cooper, Harvey, & Kennedy, on the web site, or algorithm in Chapter 9 of EaC2e.



Aside on Data-Flow Analysis

The iterative DOM calculation is an example of data-flow analysis

- Data-flow analysis is a collection of techniques for *compile-time reasoning about the run-time flow of values*
- Data-flow analysis almost always operates on a graph
 - Problems are trivial in a basic block
 - Global problems use the control-flow graph (or derivative)
 - Interprocedural problems use call graph (or derivative)
- Data-flow problems are formulated as simultaneous equations
 - Sets attached to nodes and edges
 - One solution technique is the iterative algorithm
- Desired result is usually *meet over all paths (MOP) solution*
 - “What is true on every path from the entry node?”
 - “Can this event happen on any path from the entry node?”

Related to safety



Aside on Data-Flow Analysis

Why did the iterative algorithm work?

Termination

- The DOM sets are initialized to the (finite) set of nodes
- The DOM sets shrink monotonically
- The algorithm reaches a *fixed point* where they stop changing

Correctness

- We can prove that the fixed point solution is also the MOP
- That proof is beyond today's lecture, but we'll revisit it

Efficiency

- The round-robin algorithm is not particularly efficient
- Order in which we visit nodes is important for efficient solutions