

Name: Ariba Shuaib

Registration Number: 230201075

Department and batch: CS O4 (A)

Semester: 5th semester

LAB REPORT 8


WEB TECHNOLOGIES



Institute of Space and Technology

Submitted to: Miss Maryam

Home:



App.jsx:

```
import { Routes, Route, Link } from "react-router-dom";

import Counter from "./Counter.jsx";
import Form from "./Form.jsx";
import FetchPosts from "./FetchPosts.jsx";
import AxiosPosts from "./AxiosPosts.jsx";
import Login from "./Login.jsx";
import Dashboard from "./Dashboard.jsx";
import Profile from "./Profile.jsx";

function App() {
  return (
    <div style={{ padding: "20px" }}>
      <h1>Web Technologies Lab 8</h1>

      {/* Navigation Menu */}
      <nav style={{ marginBottom: "20px", padding: "10px", backgroundColor: "#f0f0f0" }}>
        <Link to="/" style={{ marginRight: "15px" }}>Home</Link> |
        <Link to="/counter" style={{ margin: "0 15px" }}>Counter</Link> |
        <Link to="/form" style={{ margin: "0 15px" }}>Form</Link> |
        <Link to="/fetch-posts" style={{ margin: "0 15px" }}>Fetch Posts</Link> |
        <Link to="/axios-posts" style={{ margin: "0 15px" }}>Axios Posts</Link> |
        <Link to="/login" style={{ margin: "0 15px" }}>Login</Link> |
        <Link to="/dashboard" style={{ margin: "0 15px" }}>Dashboard</Link> |
        <Link to="/profile" style={{ margin: "0 15px" }}>Profile</Link>
      </nav>
    </div>
  );
}

export default App;
```

```
<Link to="/fetch-posts" style={{ margin: "0 15px" }}>Fetch Posts</Link> |  
<Link to="/axios-posts" style={{ margin: "0 15px" }}>Axios Posts</Link> |  
<Link to="/login" style={{ margin: "0 15px" }}>Login</Link> |  
<Link to="/dashboard" style={{ margin: "0 15px" }}>Dashboard</Link> |  
<Link to="/profile" style={{ margin: "0 15px" }}>Profile</Link>  
</nav>  
  
<hr />  
  
<Routes>  
  <Route path="/" element={  
    <div>  
      <h2>Home Page</h2>  
      <p>Select a task from the navigation menu above.</p>  
      <p>Tasks completed:</p>  
      <ol>  
        <li>Counter with increment, decrement, reset</li>  
        <li>Form with name, email, validation</li>  
        <li>Routing for Login, Dashboard, Profile pages</li>  
        <li>Fetch and display posts from API</li>  
        <li>Convert API calls from fetch to axios</li>  
      </ol>  
    </div>  
  } />  
  <Route path="/counter" element={<Counter />} />  
  <Route path="/form" element={<Form />} />  
  <Route path="/fetch-posts" element={<FetchPosts />} />  
  <Route path="/axios-posts" element={<AxiosPosts />} />  
  <Route path="/login" element={<Login />} />  
  <Route path="/dashboard" element={<Dashboard />} />  
  <Route path="/profile" element={<Profile />} />  
</Routes>  
</div>  
);  
}  
  
export default App;
```

Task1: Create a counter with increment, decrement, and reset

```
import { useState } from "react";

function Counter() {
  const [count, setCount] = useState(0);

  const increment = () => setCount(count + 1);
  const decrement = () => setCount(count - 1);
  const reset = () => setCount(0);

  return (
    <div>
      <h2>Task 1: Counter</h2>
      <h3>Count: {count}</h3>
      <button onClick={increment} style={{ marginRight: "10px", padding: "8px 15px" }}>
        Increment (+)
      </button>
      <button onClick={decrement} style={{ marginRight: "10px", padding: "8px 15px" }}>
        Decrement (-)
      </button>
      <button onClick={reset} style={{ padding: "8px 15px", backgroundColor: "#ff6b6b", color: "white" }}>
        Reset
      </button>
      <p style={{ marginTop: "20px", color: "#666" }}>
        Click the buttons to change the counter value. Reset sets it back to 0.
      </p>
    </div>
  );
}

export default Counter;
```

Output:

The screenshot shows a web page titled "Web Technologies Lab 8". At the top, there is a navigation bar with links: Home, Counter, Form, Fetch Posts, Axios Posts, Login, Dashboard, and Profile. Below the navigation bar, the title "Task 1: Counter" is displayed. Underneath the title, the current count is shown as "Count: -6". There are three buttons below the count: "Increment (+)", "Decrement (-)", and a red "Reset" button. A note below the buttons says, "Click the buttons to change the counter value. Reset sets it back to 0."

Task 2: Build a form with name, email, and validation

```
import { useState } from "react";

function Form() {
  const [name, setName] = useState("");
  const [email, setEmail] = useState("");
  const [errors, setErrors] = useState({});

  const validateEmail = (email) => {
    const regex = /^[^@\s]+@[^\s@]+\.\w+$/;
    return regex.test(email);
  };

  const handleSubmit = (e) => {
    e.preventDefault();
    const newErrors = {};

    if (!name.trim()) {
      newErrors.name = "Name is required";
    }

    if (!email.trim()) {
      newErrors.email = "Email is required";
    } else if (!validateEmail(email)) {
      newErrors.email = "Please enter a valid email";
    }

    setErrors(newErrors);
  };
}
```

```
}

if (Object.keys(newErrors).length > 0) {
  setErrors(newErrors);
  return;
}

setErrors({});

alert(`Form submitted successfully!\n\nName: ${name}\nEmail: ${email}`);
setName("");
setEmail("");

};

return (
  <div>
    <h2>Task 2: Registration Form</h2>
    <form onSubmit={handleSubmit} style={{ maxWidth: "400px" }}>
      <div style={{ marginBottom: "15px" }}>
        <label htmlFor="name">Name:</label><br />
        <input
          type="text"
          id="name"
          value={name}
          onChange={(e) => setName(e.target.value)}
          style={{ width: "100%", padding: "8px", marginTop: "5px" }}
          placeholder="Enter your name"
        />
        {errors.name && <p style={{ color: "red", margin: "5px 0 0 0" }}>{errors.name}</p>}
      </div>

      <div style={{ marginBottom: "15px" }}>
        <label htmlFor="email">Email:</label><br />
        <input
          type="email"
          id="email"
          value={email}
          onChange={(e) => setEmail(e.target.value)}
          style={{ width: "100%", padding: "8px", marginTop: "5px" }}
          placeholder="Enter your email"
        />
        {errors.email && <p style={{ color: "red", margin: "5px 0 0 0" }}>{errors.email}</p>}
      </div>
    </form>
  </div>
)
```

```
<button
  type="submit"
  style={{
    padding: "10px 20px",
    backgroundColor: "#4CAF50",
    color: "white",
    border: "none",
    cursor: "pointer"
  }}
>
  Submit
</button>
</form>
</div>
);
}

export default Form;
```

Output:


Web Technologies Lab 8

[Home](#) | [Counter](#) | [Form](#) | [Fetch Posts](#) | [Axios Posts](#) | [Login](#) | [Dashboard](#) | [Profile](#)

Task 2: Registration Form

Name:

Email:



Task 3 — Implement routing for Login, Dashboard, and Profile pages

Login

```
import { useState } from "react";
import { useNavigate } from "react-router-dom";

function Login() {
  const [username, setUsername] = useState("");
  const [password, setPassword] = useState("");
  const [error, setError] = useState("");
  const navigate = useNavigate();

  const handleSubmit = (e) => {
    e.preventDefault();

    // Simple validation
    if (!username || !password) {
      setError("Both fields are required");
      return;
    }

    // Mock login - in real app, you'd call an API
    if (username === "admin" && password === "password") {
      setError("");
      alert("Login successful! Redirecting to dashboard...");
      navigate("/dashboard");
    } else {
      setError("Invalid credentials. Try admin/password");
    }
  };

  return (
    <div>
      <h2>Task 3: Login Page</h2>
      <form onSubmit={handleSubmit} style={{ maxWidth: "400px" }}>
        {error && <p style={{ color: "red", backgroundColor: "#ffe6e6", padding: "10px" }}>{error}</p>

          <div style={{ marginBottom: "15px" }}>
            <label htmlFor="username">Username:</label><br />
            <input
              type="text"
            </div>
      </form>
    </div>
  );
}
```

```
        id="username"
        value={username}
        onChange={(e) => setUsername(e.target.value)}
        style={{ width: "100%", padding: "8px", marginTop: "5px" }}
        placeholder="Enter username"
      />
    </div>

<div style={{ marginBottom: "15px" }}>
  <label htmlFor="password">Password:</label><br />
  <input
    type="password"
    id="password"
    value={password}
    onChange={(e) => setPassword(e.target.value)}
    style={{ width: "100%", padding: "8px", marginTop: "5px" }}
    placeholder="Enter password"
  />
</div>

<button
  type="submit"
  style={{
    padding: "10px 20px",
    backgroundColor: "#007bff",
    color: "white",
    border: "none",
    cursor: "pointer",
    marginRight: "10px"
  }}
>
  Login
</button>

<button
  type="button"
  onClick={() => navigate("/")}

  style={{
    padding: "10px 20px",
    backgroundColor: "#6c757d",
    color: "white",
    border: "none",
    cursor: "pointer"
  }}
>
```

```

        Back to Home
    </button>

    <p style={{ marginTop: "20px", color: "#666", fontSize: "0.9em" }}>
        Demo credentials: <strong>admin</strong> / <strong>password</strong>
    </p>
</form>
</div>
);
}

export default Login;

```

Output:

Task 3: Login Page

Username:

Password:

Demo credentials: **admin / password**

Dashboard

```

import { Link } from "react-router-dom";

function Dashboard() {
    return (
        <div>
            <h2>Task 3: Dashboard Page</h2>
            <div style={{{
                backgroundColor: "#e8f4fd",

```

```

        padding: "20px",
        borderRadius: "8px",
        margin: "20px 0"
    })>
    <h3>Welcome to your Dashboard!</h3>
    <p>This is a protected page that users can access after logging in.</p>

    <div style={{ marginTop: "20px" }}>
        <h4>Quick Stats:</h4>
        <ul>
            <li>Total Visits: 1,234</li>
            <li>Messages: 5</li>
            <li>Tasks Completed: 12</li>
        </ul>
    </div>

    <div style={{ marginTop: "20px" }}>
        <h4>Navigation:</h4>
        <Link to="/profile" style={{ marginRight: "15px" }}>Go to
Profile</Link>
        <Link to="/">Go to Home</Link>
    </div>
</div>
);
}

export default Dashboard;

```

Output:

Task 3: Dashboard Page

Welcome to your Dashboard!

This is a protected page that users can access after logging in.

Quick Stats:

- Total Visits: 1,234
- Messages: 5
- Tasks Completed: 12

Navigation:

[Go to Profile](#) [Go to Home](#)

Profile

```
import { useState } from "react";

function Profile() {
  const [user, setUser] = useState({
    name: "John Doe",
    email: "john.doe@example.com",
    bio: "Web developer and React enthusiast",
    location: "New York, USA"
  });

  const [isEditing, setIsEditing] = useState(false);
  const [tempUser, setTempUser] = useState({ ...user });

  const handleEdit = () => {
    setTempUser({ ...user });
    setIsEditing(true);
  };

  const handleSave = () => {
    setUser({ ...tempUser });
    setIsEditing(false);
    alert("Profile updated successfully!");
  };

  const handleCancel = () => {
    setIsEditing(false);
  };

  const handleChange = (e) => {
    setTempUser({
      ...tempUser,
      [e.target.name]: e.target.value
    });
  };

  return (
    <div>
      <h2>Task 3: Profile Page</h2>

      {!isEditing ? (
        <div style={{
```

```
        backgroundColor: "#f8f9fa",
        padding: "20px",
        borderRadius: "8px",
        maxWidth: "500px"
    }}>
    <h3>User Profile</h3>
    <p><strong>Name:</strong> {user.name}</p>
    <p><strong>Email:</strong> {user.email}</p>
    <p><strong>Bio:</strong> {user.bio}</p>
    <p><strong>Location:</strong> {user.location}</p>

    <button
        onClick={handleEdit}
        style={{
            padding: "10px 20px",
            backgroundColor: "#007bff",
            color: "white",
            border: "none",
            cursor: "pointer",
            marginTop: "15px"
        }}
    >
        Edit Profile
    </button>
</div>
) : (
    <div style={{
        backgroundColor: "#fff3cd",
        padding: "20px",
        borderRadius: "8px",
        maxWidth: "500px"
    }}>
        <h3>Edit Profile</h3>

        <div style={{ marginBottom: "15px" }}>
            <label htmlFor="name">Name:</label><br />
            <input
                type="text"
                id="name"
                name="name"
                value={tempUser.name}
                onChange={handleChange}
                style={{ width: "100%", padding: "8px", marginTop: "5px" }}
            />
        </div>
    </div>
```

```
<div style={{ marginBottom: "15px" }}>
  <label htmlFor="email">Email:</label><br />
  <input
    type="email"
    id="email"
    name="email"
    value={tempUser.email}
    onChange={handleChange}
    style={{ width: "100%", padding: "8px", marginTop: "5px" }}
  />
</div>

<div style={{ marginBottom: "15px" }}>
  <label htmlFor="bio">Bio:</label><br />
  <textarea
    id="bio"
    name="bio"
    value={tempUser.bio}
    onChange={handleChange}
    style={{ width: "100%", padding: "8px", marginTop: "5px", height: "100px" }}
  />
</div>

<div style={{ marginBottom: "20px" }}>
  <label htmlFor="location">Location:</label><br />
  <input
    type="text"
    id="location"
    name="location"
    value={tempUser.location}
    onChange={handleChange}
    style={{ width: "100%", padding: "8px", marginTop: "5px" }}
  />
</div>

<button
  onClick={handleSave}
  style={{
    padding: "10px 20px",
    backgroundColor: "#28a745",
    color: "white",
    border: "none",
    cursor: "pointer",
  }}>
```

```
        marginRight: "10px"
    }
  >
  Save
</button>

<button
  onClick={handleCancel}
  style={{
    padding: "10px 20px",
    backgroundColor: "#dc3545",
    color: "white",
    border: "none",
    cursor: "pointer"
  }}
  >
  Cancel
</button>
</div>
);
}

export default Profile;
```

Output:

Task 3: Profile Page

User Profile

Name: Ariba Shuaib

Email: ariba@example.com

Bio: Web developer and React enthusiast

Location: New York, USA

[Edit Profile](#)

Task 4 — Fetch and display posts from a public API

```
import { useEffect, useState } from "react";

function FetchPosts() {
  const [posts, setPosts] = useState([]);
  const [loading, setLoading] = useState(true);
  const [error, setError] = useState(null);

  useEffect(() => {
    setLoading(true);
    fetch("https://jsonplaceholder.typicode.com/posts")
      .then((response) => {
        if (!response.ok) {
          throw new Error("Failed to fetch posts");
        }
        return response.json();
      })
      .then((data) => {
        setPosts(data.slice(0, 10)); // Get first 10 posts
        setLoading(false);
      })
      .catch((err) => {
        setError(err.message);
        setLoading(false);
      });
  }, []);

  return (
    <div>
      <h2>Task 4: Fetch Posts from API</h2>
      <p>This uses the native JavaScript fetch() API</p>

      {loading && <p>Loading posts...</p>}
      {error && <p style={{ color: "red" }}>Error: {error}</p>}

      {!loading && !error && (
        <div>
          <p>Showing {posts.length} posts:</p>
          <div style={{ maxHeight: "400px", overflowY: "auto", border: "1px solid #ddd", padding: "10px" }}>
            {posts.map((post) => (
              <div key={post.id} style={{
                padding: "10px",
                marginBottom: "10px",
              }})
            )}
          </div>
        </div>
      )}
    </div>
  );
}
```

```

        backgroundColor: "#f9f9f9",
        borderLeft: "4px solid #007bff"
    }}>
    <h4 style={{ margin: "0 0 5px 0" }}>{post.title}</h4>
    <p style={{ margin: "0", color: "#666", fontSize: "0.9em" }}>
        {post.body.length > 100 ? post.body.substring(0, 100) + "..." :
post.body}
    </p>
    <small style={{ color: "#999" }}>Post ID: {post.id} | User ID:
{post.userId}</small>
    </div>
    ))
)
</div>
</div>
)
</div>
);
}

export default FetchPosts;

```

Output:

Web Technologies Lab 8

[Home](#) | [Counter](#) | [Form](#) | [Fetch Posts](#) | [Axios Posts](#) | [Login](#) | [Dashboard](#) | [Profile](#)

Task 4: Fetch Posts from API

This uses the native JavaScript `fetch()` API

Showing 10 posts:

sunt aut facere repellat provident occaecati excepturi optio reprehenderit quia et suscipit suscipit recusandae consequuntur expedita et cum reprehenderit molestiae ut ut quas... Post ID: 1 User ID: 1
qui est esse est rerum tempore vitae sequi sint nihil reprehenderit dolor beatae ea dolores neque fugiat blanditi... Post ID: 2 User ID: 1
ea molestias quasi exercitationem repellat qui ipsa sit aut et iusto sed quo iure voluptatem occaecati omnis eligendi aut ad voluptatem doloribus vel accusantium... Post ID: 3 User ID: 1
et num et est occaecati

Task 5 — Convert API calls from fetch to axios

```
import { useEffect, useState } from "react";
import axios from "axios";

function AxiosPosts() {
  const [posts, setPosts] = useState([]);
  const [loading, setLoading] = useState(true);
  const [error, setError] = useState(null);

  useEffect(() => {
    setLoading(true);
    axios.get("https://jsonplaceholder.typicode.com/posts")
      .then((response) => {
        setPosts(response.data.slice(0, 10)); // Get first 10 posts
        setLoading(false);
      })
      .catch((err) => {
        setError(err.message);
        setLoading(false);
      });
  }, []);

  return (
    <div>
      <h2>Task 5: Axios Posts from API</h2>
      <p>This uses the Axios library for HTTP requests</p>

      {loading && <p>Loading posts...</p>}
      {error && <p style={{ color: "red" }}>Error: {error}</p>}

      {!loading && !error && (
        <div>
          <p>Showing {posts.length} posts:</p>
          <div style={{ maxHeight: "400px", overflowY: "auto", border: "1px solid #ddd", padding: "10px" }}>
            {posts.map((post) => (
              <div key={post.id} style={{
                padding: "10px",
                marginBottom: "10px",
                backgroundColor: "#f0f8ff",
                borderLeft: "4px solid #28a745"
              }}>
                <h4 style={{ margin: "0 0 5px 0" }}>{post.title}</h4>
                <p style={{ margin: "0", color: "#666", fontSize: "0.9em" }}>

```

```
        {post.body.length > 100 ? post.body.substring(0, 100) + "..." : post.body}
    </p>
    <small style={{ color: "#999" }}>Post ID: {post.id} | User ID: {post.userId}</small>
    </div>
)}
```

```
</div>

<div style={{ marginTop: "20px", padding: "15px", backgroundColor: "#e7f3e7", borderRadius: "5px" }}>
    <h4>Axios vs Fetch Comparison:</h4>
    <ul>
        <li><strong>Axios:</strong> Automatically transforms JSON data, has built-in error handling</li>
        <li><strong>Fetch:</strong> Requires manual JSON parsing, needs extra error checking</li>
        <li><strong>Axios:</strong> Supports request/response interceptors</li>
        <li><strong>Fetch:</strong> Native browser API, no extra dependencies</li>
    </ul>
    </div>
)
</div>
);

}

export default AxiosPosts;
```

Output:

Web Technologies Lab 8

[Home](#) | [Counter](#) | [Form](#) | [Fetch Posts](#) | [Axios Posts](#) | [Login](#) | [Dashboard](#) | [Profile](#)

Task 5: Axios Posts from API

This uses the Axios library for HTTP requests

Showing 10 posts:

sunt aut facere repellat provident occaecati excepturi optio reprehenderit
quia et suscipit suscipit recusandae consequuntur expedita et cum reprehenderit molestiae ut ut quas...
Post ID: 1 User ID: 1
qui est esse
est rerum tempore vitae sequi sint nihil reprehenderit dolor beatae ea dolores neque fugiat blanditi...
Post ID: 2 User ID: 1
ea molestias quasi exercitationem repellat qui ipsa sit aut
et iusto sed quo iure voluptatem occaecati omnis eligendi aut ad voluptatem doloribus vel accusantiu...
Post ID: 3 User ID: 1
eum et est occaecati