

TENSORFLOW

CHEAT SHEET

for Deep Learning Model Building

Save for later reference



FEEDFORWARD NEURAL NETWORK

model = models.Sequential()
model.add(layers.Flatten(input_shape=(input_size,))) #
Adjust input_size based on your data

Add hidden layers model.add(layers.Dense(128, activation='relu')) model.add(layers.Dropout(0.2)) # Optional: Add dropout for regularization

Add output layer model.add(layers.Dense(output_size, activation='softmax')) # Adjust output_size based on your problem





CONVOLUTIONAL NEURAL NETWORK

```
model = models.Sequential()
model.add(layers.Conv2D(32, (3, 3), activation='relu',
input_shape=(img_height, img_width, channels)))
model.add(layers.MaxPooling2D((2, 2)))
```

Add more convolutional and pooling layers as needed

```
model.add(layers.Flatten())
model.add(layers.Dense(128, activation='relu'))
model.add(layers.Dense(output_size,
activation='softmax'))
```

```
model.compile(optimizer='adam',
loss='sparse_categorical_crossentropy',
metrics=['accuracy'])
```







RECURRENT NEURAL NETWORK

model = models.Sequential()
model.add(layers.SimpleRNN(128,
activation='relu', input_shape=(timesteps,
features)))

Add more recurrent layers or use LSTM/GRU layers

model.add(layers.Dense(output_size, activation='softmax'))







LONG SHORT-TERM MEMORY

model = models.Sequential()
model.add(layers.LSTM(128, activation='relu',
input_shape=(timesteps, features)))

Add more LSTM layers if needed

model.add(layers.Dense(output_size, activation='softmax'))

model.compile(optimizer='adam',
loss='sparse_categorical_crossentropy',
metrics=['accuracy'])





GATED RECURRENT UNIT

model = models.Sequential()
model.add(layers.GRU(128, activation='relu',
input_shape=(timesteps, features)))

Add more GRU layers if needed

model.add(layers.Dense(output_size, activation='softmax'))

model.compile(optimizer='adam',
loss='sparse_categorical_crossentropy',
metrics=['accuracy'])







106 TRANSFER LEARNING(E.G., VGG16)

from tensorflow.keras.applications import VGG16

```
# Load pre-trained VGG16 model without the top layer
base model = VGG16(weights='imagenet', include top=False,
input shape=(img height, img width, channels))
# Freeze convolutional layers
for layer in base_model.layers:
  layer.trainable = False
model = models.Sequential()
model.add(base model)
# Add custom classification layers
model.add(layers.Flatten())
model.add(layers.Dense(256, activation='relu'))
model.add(layers.Dropout(0.5))
model.add(layers.Dense(output_size, activation='softmax'))
model.compile(optimizer='adam',
       loss='sparse_categorical_crossentropy',
       metrics=['accuracy'])
```







BATCH NORMALIZATION

model.add(layers.BatchNormalization())

08

DATA AUGMENTATION

from tensorflow.keras.preprocessing.image import ImageDataGenerator

```
datagen = ImageDataGenerator(
  rotation_range=20,
  width_shift_range=0.2,
  height_shift_range=0.2,
  horizontal_flip=True,
  shear_range=0.2
)
```

datagen.fit(X_train) # X_train is your training data

model.fit(datagen.flow(X_train, y_train, batch_size=batch_size), epochs=epochs)





EARLY STOPPING

from tensorflow.keras.callbacks import EarlyStopping

early_stopping = EarlyStopping(monitor='val_loss', patience=3, restore_best_weights=True)

model.fit(X_train, y_train, epochs=epochs, validation_data= (X_val, y_val), callbacks=[early_stopping])

10

LEARNING RATE SCHEDULER

from tensorflow.keras.callbacks import LearningRateScheduler

```
def scheduler(epoch, Ir):
  if epoch % 10 == 0 and epoch != 0:
    return Ir * 0.9
  else:
    return Ir
```

Ir_scheduler = LearningRateScheduler(scheduler)

model.fit(X_train, y_train, epochs=epochs, validation_data= (X_val, y_val), callbacks=[lr_scheduler])





EARLY STOPPING

from sklearn.model_selection import GridSearchCV from tensorflow.keras.wrappers.scikit_learn import KerasClassifier

```
# Define your model creation function
def create_model(optimizer='adam', hidden_units=128, dropout_rate=0.2):
  model = models.Sequential()
  model.add(layers.Flatten(input shape=(input size,)))
  # Add hidden layers
  model.add(layers.Dense(hidden units, activation='relu'))
  model.add(layers.Dropout(dropout_rate))
  # Add output layer
  model.add(layers.Dense(output_size, activation='softmax'))
  model.compile(optimizer=optimizer,
          loss='sparse categorical crossentropy',
          metrics=['accuracy'])
  return model
# Create a KerasClassifier with your model creation function
model = KerasClassifier(build_fn=create_model, epochs=10, batch_size=32, verbose=0)
# Define the hyperparameters to search
param_grid = {
  'optimizer': ['adam', 'sgd', 'rmsprop'],
  'hidden_units': [64, 128, 256],
  'dropout_rate': [0.2, 0.5, 0.8]
# Use GridSearchCV for hyperparameter search
grid = GridSearchCV(estimator=model, param_grid=param_grid, cv=3)
grid_result = grid.fit(X_train, y_train)
# Print the best parameters and corresponding accuracy
print("Best Parameters: ", grid_result.best_params_)
print("Best Accuracy: ", grid_result.best_score_)
```



Never Miss a Post!Turn on the Notifications



Was it helpful?

Checkout our YouTube Channel for Machine Learning Projects and Other amazing Data Science Related Content





LIKE TO SUPPORT







Checkout Our Other Posts



07 Killer Data Science Project ideas

With Description



Actual Projects
That Data
Scientists Work

On In Companies



Data Science Concepts Explained

Overfitting & Underfitting



Data Science Interview

Questions & Answers

Save for later reference

