

DBSCAN

Groups items using the DBSCAN clustering algorithm.


Inputs

- Data: input dataset

Outputs

- Data: dataset with cluster index as a class attribute

The widget applies the **DBSCAN clustering** algorithm to the data and outputs a new dataset with cluster indices as a meta attribute. The widget also shows the sorted graph with distances to k-th nearest neighbors. With k values set to **Core point neighbors** as suggested in the [methods article](#). This gives the user the idea of an ideal selection for **Neighborhood distance** setting. As suggested by authors this parameter should be set to the first value in the first “valley” in the graph.



1. Set *minimal number of core neighbors* for a cluster and *maximal neighborhood distance.
2. Set the distance metric that is used in grouping the items.
3. If *Apply Automatically* is ticked, the widget will commit changes automatically. Alternatively, click *Apply*.
4. The graph shows the distance to the k -th nearest neighbor. k is set by the **Core point neighbor** option. With moving the black slider left and right you can select the right **Neighbourhood distance**.

Example

In the following example, we connected the File widget with selected Iris dataset to the DBSCAN widget. In the DBSCAN widget, we set **Core point neighbors** parameter to 5. And select the **Neighbourhood distance** to the value in the first “valley” in the graph. We show clusters in the Scatter Plot widget.

