

A Reproducible Cyber-Range Evaluation Protocol for Governed Multi-Agent Edge AI Security

Aridio Silva
@aridiosilva
Independent Researcher
<https://github.com/aridiosilva/SGAEIA>

September 2026

Abstract

Architectural security claims for agentic Edge AI require evaluation under identity compromise, prompt/tool injection, delegation abuse, dependency failure, network partition, evidence loss, and revocation. This protocol defines research questions, threat scenarios, metrics, experimental controls, evidence requirements, and reproducibility criteria for SGAEIA and comparable architectures. It intentionally reports no fabricated results.

Project: SGAEIA — Secure Governed Autonomous Edge Intelligence Architecture.

1 Purpose

Agentic AI security work identifies threats from tool use, memory, autonomy, and multi-agent interaction [16, 10, 9]. Edge systems add intermittent connectivity and heterogeneous trust domains [1, 12]. This protocol turns architectural claims into falsifiable experiments.

2 Research Questions

1. Can unauthorized agent actions be prevented under identity, capability, and delegation attacks?
2. Does the system remain fail-secure during edge/network/control-plane partitions?
3. Can a technology be replaced without violating invariants?
4. How quickly is authority revoked across distributed nodes?
5. What overhead is introduced by identity, PDP/PEP, telemetry, and evidence?
6. Can an independent party reproduce the results?

3 Topology

The range should contain cloud/regional control services, at least two edge sites, agent workloads, model endpoints, tool gateways, RAG/memory, event bus, telemetry/evidence, policy services, workload identity, and a simulated cyber-physical endpoint. Controlled partition and dependency failure must be possible.

4 Threat Scenarios

Scenario	Objective
Indirect prompt injection	attempt protected tool execution from untrusted content
Agent impersonation	test identity rejection
Delegation escalation	test subset/depth/expiry constraints
Memory/RAG poisoning	test provenance and retrieval authorization
PDP outage	verify critical fail-closed behavior
Evidence outage	verify buffering/failure policy
Network partition	verify offline authority cannot increase
Revocation	measure end-to-end authority removal
Adapter substitution	test invariant preservation
Unsafe actuation	verify approval and independent safety barrier

5 Metrics

Record authorization latency, task latency, throughput, blocked/allowed action counts, invariant violations, revocation propagation time, evidence completeness, recovery time, CPU/memory/network overhead, and p50/p95/p99 distributions. For revocation:

$$T_{revoke} = t_{last\ successful\ use} - t_{revocation\ request}.$$

6 Controls and Reproducibility

Pin versions and configuration, synchronize clocks, use synthetic credentials, isolate networks, archive policies/manifests, repeat experiments, predefine exclusions, and retain raw telemetry. Each run should archive topology, images/digests, policies, parameters, timestamps, attack scripts, evidence, raw results, and hashes.

7 Ethical and Safety Constraints

All offensive scenarios must run in isolated infrastructure under the researcher’s control. Cyber-physical testing should use simulators or non-hazardous devices. No attack traffic should target third parties. Logs should contain no personal or confidential data.

8 Threats to Validity

Internal validity can be affected by mocks, clock skew, caches, and nondeterminism; external validity by chosen technologies and topology; construct validity by metric quality; reproducibility by artifact availability and version pinning.

9 Conclusion

Publishing the protocol before results creates a falsifiable path from architectural claims to empirical evidence and reduces the risk of selecting metrics only after observing favorable outcomes.

Availability

Open reference implementation and specifications: <https://github.com/aridiosilva/SGAEIA>.

References

- [1] W. Shi et al., “Edge Computing: Vision and Challenges,” *IEEE Internet of Things Journal*, 3(5), 637–646, 2016. doi:10.1109/JIOT.2016.2579198.
- [2] Z. Zhou et al., “Edge Intelligence: Paving the Last Mile of Artificial Intelligence With Edge Computing,” *Proceedings of the IEEE*, 107(8), 1738–1762, 2019. doi:10.1109/JPROC.2019.2918951.
- [3] E. Li, Z. Zhou, X. Chen, “Edge Intelligence: On-Demand Deep Learning Model Co-Inference with Device-Edge Synergy,” *MECOMM*, 2018. doi:10.1145/3229556.3229562.
- [4] NIST, Zero Trust Architecture, SP 800-207, 2020. doi:10.6028/NIST.SP.800-207.
- [5] NIST, A Zero Trust Architecture Model for Access Control in Cloud-Native Applications in Multi-Cloud Environments, SP 800-207A, 2023. doi:10.6028/NIST.SP.800-207A.
- [6] NIST, Artificial Intelligence Risk Management Framework (AI RMF 1.0), AI 100-1, 2023. doi:10.6028/NIST.AI.100-1.
- [7] C. Autio et al., Artificial Intelligence Risk Management Framework: Generative Artificial Intelligence Profile, NIST AI 600-1, 2024. doi:10.6028/NIST.AI.600-1.
- [8] NIST, Secure Software Development Practices for Generative AI and Dual-Use Foundation Models, SP 800-218A, 2024.
- [9] MITRE, ATLAS: Adversarial Threat Landscape for Artificial-Intelligence Systems, <https://atlas.mitre.org/>, accessed Sep. 2026.
- [10] OWASP GenAI Security Project, Agentic Security Initiative and Agent Control Standard, <https://genai.owasp.org/>, accessed Sep. 2026.
- [11] SPIFFE Project, The SPIFFE Standard, <https://spiffe.io/docs/latest/spiffe-specs/>, accessed Sep. 2026.
- [12] ETSI, Multi-access Edge Computing (MEC), <https://www.etsi.org/technical-groups/mec/>, accessed Sep. 2026.
- [13] OpenAPI Initiative, OpenAPI Specification 3.2.0, 2025.
- [14] AsyncAPI Initiative, AsyncAPI Specification 3.1.0, 2026.
- [15] K.-T. Tran et al., “Multi-Agent Collaboration Mechanisms: A Survey of LLMs,” *arXiv:2501.06322*, 2025.
- [16] S. Datta et al., “Agentic AI Security: Threats, Defenses, Evaluation, and Open Challenges,” *arXiv:2510.23883*, 2025.