

# IMAI API

## Complete API Reference Documentation

Base URL: `https://imai.co/api`

Protocol: HTTPS

---

IMAI API provides access to audience demographic and psychographic attributes of Instagram, YouTube, TikTok, and Douyin users based on their active audience and social media presence. Supports user lookups by user ID or username.

**Authentication:** Send your API key in the `authkey` header with every request.

**Rate Limiting:** Max 10 requests/second per user. YouTube and TikTok Raw API: 100 req/sec. Instagram Raw API has endpoint-specific limits.

# Table of Contents

1. Pricing Table
2. Error Codes
3. Dictionaries
  - 3.1 Get Brand Logo
  - 3.2 List Interests and Brands
  - 3.3 List Languages
  - 3.4 Get Relevant Topic Tags
  - 3.5 List Topic Tags
  - 3.6 List Topic Tags (CSV)
  - 3.7 List Users (Autocomplete)
  - 3.8 Get Users Info by IDs
  - 3.9 List Geolocations
4. Audience Data
  - 4.1 New Report
  - 4.2 Audience Overlap
  - 4.3 Fetch Report File
5. Search
  - 5.1 Search for Influencers
  - 5.2 Unlock Influencers
6. Sponsored Posts
  - 6.1 Search Posts
  - 6.2 Top Brands / Hashtags / Mentions / Sponsors
7. Raw API - Instagram
  - 7.1 User Info / Feed / Reels / Stories / Highlights / IGTV
  - 7.2 Media Info / Comments / Replies
  - 7.3 Hashtag Feed & Info / Audio Feed / Search
8. Raw API - TikTok
  - 8.1 User Info / Feed / Media / Video
  - 8.2 Challenge Info & Feed / Music Info & Feed
  - 8.3 Comments / Replies / Search / Short Link
9. Raw API - YouTube
  - 9.1 Channel Info / Videos / Uploaded Videos
  - 9.2 Playlist / Video Info / Comments / Replies
10. Raw API - Douyin
  - 10.1 User Info / Feed / Media Info / Comments / Replies
11. Raw Export API
  - 11.1 Get Contact Details
  - 11.2 Export Notable Followers
  - 11.3 Match Emails
12. Finance
  - 12.1 Account Info

# 1. Pricing Table

| Category        | Endpoint                   | Cost                           |
|-----------------|----------------------------|--------------------------------|
| Audience Data   | /reports/new/              | 1 token (free if dry_run=true) |
| Audience Data   | /reports/overlap/          | 1 token per report returned    |
| Search          | /search/newv1/             | Tokens for unindexed results   |
| Sponsored Posts | /market_scan/posts/search/ | 0.02 tokens                    |
| Raw API (IG)    | /raw/ig/* endpoints        | 0.02 tokens, max 1 req/sec     |
| Raw API (TT)    | /raw/tt/* endpoints        | 0.02 tokens                    |
| Raw API (YT)    | /raw/yt/* endpoints        | 0.02 tokens                    |
| Raw API (DY)    | /raw/dy/* endpoints        | 0.02 tokens                    |
| Export          | /exports/contacts/         | 0.04 tokens                    |
| Export          | /exports/notable_users/    | 0.04-0.06 tokens per user      |
| Export          | /match_emails/             | 0.04 tokens per matched email  |

## 2. Error Codes

Error responses follow this format:

```
{ "success": false, "error": "Code", "error_message": "Message" }
```

| HTTP | Code                        | Description                              |
|------|-----------------------------|------------------------------------------|
| 400  | bad_request                 | Bad request                              |
| 400  | account_not_found           | Account does not exist on social media   |
| 400  | account_data_removed        | Info removed at account holder's request |
| 400  | account_removed             | Account removed from social media        |
| 400  | account_is_private          | User made account private                |
| 400  | empty_audience              | No specific audience for this account    |
| 400  | empty_audience_data         | No audience data at all                  |
| 400  | retry_later                 | Audience updating, retry in 5-10 min     |
| 400  | bad_filter                  | Bad filter value                         |
| 400  | entity_not_found            | Entity does not exist                    |
| 400  | entity_is_hidden            | Access restricted (geo/age)              |
| 400  | no_tokens_remaining         | Not enough tokens                        |
| 400  | no_quota_remaining          | Not enough quota                         |
| 400  | daily_tokens_limit_exceeded | Daily spending limit exceeded (UTC)      |
| 401  | not_authenticated           | No API Key provided                      |
| 403  | invalid_api_key             | Invalid API Key                          |
| 403  | permission_denied           | No permission for operation              |
| 403  | token_is_disabled           | Token disabled                           |
| 403  | tokens_expired              | Subscription expired                     |
| 403  | subscription_expired        | Active subscription expired              |
| 403  | subscription_required       | Subscription required                    |
| 404  | not_found                   | URL does not exist                       |
| 405  | method_not_allowed          | Wrong HTTP method used                   |
| 429  | rate_limit_exceeded         | Rate limit exceeded                      |
| 500  | internal_server_error       | Internal error, retry later              |

### 3. Dictionaries

Helper dictionaries for objects like brands, countries, cities, and languages. Requests to dictionaries are free. Recommended to cache as they update rarely.

#### GET /dict/brand-logos/{brand\_id} — Get Brand Logo

Returns the brand logo image file for a given brand ID.

| Name       | Type    | In   | Description |
|------------|---------|------|-------------|
| brand_id * | integer | path | Brand ID    |

#### GET /dict/interests/ — List Interests and Brands

Lists all interests and brands usable as filters in Search or returned in Audience Data reports. Instagram only.

| Name            | Type    | In    | Description   |
|-----------------|---------|-------|---------------|
| hide_deprecated | boolean | query | Default: true |

Response example:

```
{ "success": true, "data": { "interests": [{ "id": 1, "name": "Television & Film", "count": 13454, "deprecated": true}], "brands": [{ "id": 46, "name": "Aeropostale", "count": 111, "deprecated": false, "interest": [{ "id": 7}]}] } }
```

#### GET /dict/langs/ — List Languages

Lists all supported languages ordered by descending frequency.

| Name     | Type   | In    | Description                                      |
|----------|--------|-------|--------------------------------------------------|
| platform | string | query | instagram   tiktok   youtube. Default: instagram |

Response example:

```
{ "success": true, "data": [ { "code": "en", "name": "English", "count": 20972231 }, { "code": "es", "name": "Spanish", "count": 14818868 } ] }
```

#### GET /dict/relevant-tags/ — Get Relevant Topic Tags

Returns relevant topic tags for a query. Use # for hashtags and @ for usernames (URL-encoded).

| Name     | Type    | In    | Description                                      |
|----------|---------|-------|--------------------------------------------------|
| q *      | string  | query | Search query. e.g. %23cats for #cats             |
| limit    | integer | query | Max results. Default: 60                         |
| platform | string  | query | instagram   tiktok   youtube. Default: instagram |

Response example:

```
{ "success": true, "data": [ { "tag": "#cats", "distance": 0, "freq": 13.707, "tag_cnt": 897207 }, { "tag": "#catsofinstagram", "distance": 0.105, "freq": 13.801, "tag_cnt": 985930 } ] }
```

#### GET /dict/topic-tags/ — List Topic Tags

| Name | Type   | In    | Description                 |
|------|--------|-------|-----------------------------|
| q *  | string | query | Search query for topic tags |

|          |         |       |                                                  |
|----------|---------|-------|--------------------------------------------------|
| limit    | integer | query | Max results. Default: 25                         |
| platform | string  | query | instagram   tiktok   youtube. Default: instagram |

```
{ "success": true, "data": [{"tag": "string", "value": "string"}]}
```

## GET /dict/topic-tags/csv/ — List Topic Tags (CSV)

Returns CSV with all tags available in relevance search filter. Full response ~14MB for Instagram.

| Name     | Type    | In    | Description                                      |
|----------|---------|-------|--------------------------------------------------|
| skip     | integer | query | Default: 0                                       |
| limit    | integer | query | Return all if not provided                       |
| platform | string  | query | instagram   tiktok   youtube. Default: instagram |

## GET /dict/users/ — List Users (Autocomplete)

Autocomplete users available under audience lookalike, relevance filters, or social media accounts.

| Name     | Type    | In    | Description                                      |
|----------|---------|-------|--------------------------------------------------|
| q        | string  | query | Search query                                     |
| limit    | integer | query | Max results. Default: 10                         |
| type *   | string  | query | lookalike   topic-tags   search                  |
| platform | string  | query | instagram   tiktok   youtube. Default: instagram |

**Response example:**

```
{ "success": true, "data": [ { "user_id": "184692323", "username": "ladygaga", "fullname": "Lady Gaga", "followers": 36846974, "is_verified": true, "picture": "..."} ] }
```

## GET /dict/users/by\_ids — Get Users Info by IDs

| Name     | Type   | In    | Description                                      |
|----------|--------|-------|--------------------------------------------------|
| q *      | string | query | Comma-separated user IDs (max 20)                |
| type *   | string | query | lookalike   topic-tags   search                  |
| platform | string | query | instagram   tiktok   youtube. Default: instagram |

## GET /geos/ — List Geolocations

List geo locations. Set limit=50000 for the full list (~32k locations).

| Name         | Type    | In    | Description                                 |
|--------------|---------|-------|---------------------------------------------|
| q            | string  | query | Search query                                |
| limit        | integer | query | Limit results. Default: 10                  |
| country_code | string  | query | Limit to specific country                   |
| types        | string  | query | Comma-separated: city, subdivision, country |

**Response example:**

```
[ { "id": 51800, "type": ["city"], "name": "London", "title": "London, United Kingdom", "country": { "id": 62149 } } ]
```

## 4. Audience Data

### POST /reports/new/ — New Report

\$ 1 token per report (free if dry\_run=true)

Creates a new audience data report. Also accepts GET for testing. Use user\_id over username where possible. Reports stored for 60 days.

| Name                  | Type    | In    | Description                                                                                    |
|-----------------------|---------|-------|------------------------------------------------------------------------------------------------|
| data *                | object  | body  | Filter object with geo, language, gender, age_group, following_group, brand, interest, is_fake |
| url                   | string  | query | Instagram username, userId or profile link                                                     |
| ignore_removed        | boolean | query | Get old data for removed accounts. Default: false                                              |
| ignore_outdated       | boolean | query | Get report despite retry_later. Default: false                                                 |
| ignore_empty_audience | boolean | query | Ignore empty audience. Default: false                                                          |
| dry_run               | boolean | query | Check if report can be built without charging. Default: false                                  |
| platform              | string  | query | instagram   tiktok   youtube   douyin. Default: instagram                                      |

#### Request body example:

```
{ "filter": { "geo": [0], "language": ["string"], "gender": "MALE", "age_group": ["13-17"], "following_group": "-500", "brand": [0], "interest": [0], "is_fake": true } }
```

**Response includes:** report\_info (report\_id, created, profile\_updated), user\_profile (full profile data with stats, posts, reels, contacts, geo, similar users, brand affinity, top hashtags/mentions), audience\_likers, audience\_followers, audience\_commenters (each with demographics, geo, languages, interests, brands, credibility, notable users, lookalikes), and extra histograms.

**Key response fields in user\_profile:** type, user\_id, username, fullname, followers, posts\_count, engagements, engagement\_rate, avg\_likes, avg\_comments, avg\_views, avg\_reels\_plays, stat\_history, geo, contacts, top\_hashtags, top\_mentions, brand\_affinity, interests, similar\_users, top\_posts, commercial\_posts, recent\_posts, top\_reels, recent\_reels.

**Key audience data fields:** audience\_credibility, credibility\_class, audience\_types, audience\_genders, audience\_ages, audience\_genders\_per\_age, audience\_ethnicities, audience\_languages, audience\_brand\_affinity, audience\_interests, audience\_geo (countries/states/cities), audience\_lookalikes, notable\_users, audience\_reachability.

Response header X-Tokens-Cost contains the number of spent tokens.

### POST /reports/overlap/ — Audience Overlap

\$ 1 token per report returned

Check audience (followers) overlap for several users. Instagram and YouTube only. No limit on total accounts, but processing is limited to 1 minute. Works well on ~100 random bloggers. On timeout, retry in 10-15 minutes.

| Name     | Type   | In    | Description                             |
|----------|--------|-------|-----------------------------------------|
| platform | string | query | instagram   youtube. Default: instagram |
| urls     | string | query | Comma-separated usernames or user IDs   |
| fmt      | string | query | csv   json. Default: json               |

#### Response example:

```
{ "status": true, "report_info": {"total_followers": 69043993, "total_unique_followers": 40570297},  
  "data": [ {"user_id": "25749975", "username": "mercedesbenz", "followers": 26447483,  
    "unique_percentage": 0.342912, "overlapping_percentage": 0.657088} ], "cost": 1 }
```

## GET /reports/{report\_id}/ — Fetch Report File

Fetch a previously generated report in JSON or PDF format. Reports kept for 30 days.

| Name        | Type   | In    | Description                        |
|-------------|--------|-------|------------------------------------|
| report_id * | string | path  | Report ID from new report response |
| fmt *       | string | query | pdf   json                         |

Response is the same full report structure as the new report endpoint.

## 5. Search

### POST /search/newv1/ — Search for Influencers

\$ Tokens charged for unindexed results

Search for influencers matching filters. Tip: inspect search requests in IMAI web interface browser dev tools - same format. Video guide: [loom.com/share/a3c2f2b7257b4e999d1762391fbb93f0](https://loom.com/share/a3c2f2b7257b4e999d1762391fbb93f0)

| Name     | Type   | In    | Description                                      |
|----------|--------|-------|--------------------------------------------------|
| data *   | object | body  | Search filter, sort, paging, audience_source     |
| platform | string | query | instagram   tiktok   youtube. Default: instagram |

**Available search filters:** audience\_age, audience\_age\_range, audience\_brand, audience\_brand\_category, audience\_gender, audience\_geo, audience\_lang, audience\_race, audience\_relevance, brand, brand\_category, engagements, views, posts\_count, reels\_plays, shares, saves, followers, gender, age, geo, lang, followers\_growth, total\_views\_growth, total\_likes\_growth, relevance, text, text\_advanced, keywords, text\_tags, engagement\_rate, is\_hidden, is\_verified, account\_type, has\_ads, ads\_brands, with\_contact, audience\_credibility, audience\_credibility\_class, filter\_ids, last\_posted, has\_audience\_data, username, actions, post\_type, semantic.

**Sort:** field (e.g. engagements), direction (asc/desc), id.

**Paging:** limit (max 100), skip.

**audience\_source:** any.

**Request example:**

```
{ "filter": { "followers": { "left_number": 10000, "right_number": 100000}, "audience_gender": {"code": "FEMALE", "weight": 0.5}, "audience_geo": [{ "id": 51800, "weight": 0.05}], "engagement_rate": { "value": 2, "operator": "gte" } }, "sort": { "field": "engagements", "direction": "desc"}, "paging": { "limit": 100, "skip": 0}, "audience_source": "any" }
```

**Response:** accounts array (each with account info + match data including audience demographics), total count, shown\_accounts, cost.

### POST /search/unhide/ — Unlock Influencers

Show information for influencers hidden in search results.

| Name     | Type   | In    | Description                                      |
|----------|--------|-------|--------------------------------------------------|
| data *   | object | body  | { "search_result_ids": ["string"] }              |
| platform | string | query | instagram   tiktok   youtube. Default: instagram |

Response includes full account and audience match data, plus cost and tokens used.

## 6. Sponsored Posts

Scanning social media for sponsored posts detected via commercial hashtags or official paid partnership tags.

### **POST** /market\_scan/posts/search/ — Search Posts

\$ 0.02 tokens per succeeded request

Search sponsored posts with filters for date range, followers range, likes range, and more.

---

### **POST** /market\_scan/posts/top\_brands/ — Top Brands

Get top brands from sponsored posts.

---

### **POST** /market\_scan/posts/top\_hashtags/ — Top Hashtags

Get top hashtags from sponsored posts.

---

### **POST** /market\_scan/posts/top\_mentions/ — Top Mentions

Get top mentions from sponsored posts.

---

### **POST** /market\_scan/posts/top\_sponsors/ — Top Sponsors

Get top sponsors from sponsored posts.

## 7. Raw API - Instagram

\$ 0.02 tokens per request. Max 1 req/sec for most endpoints.

### GET /raw/ig/user/info/ — User Info

Returns user info by ID or username.

| Name  | Type   | In    | Description                       |
|-------|--------|-------|-----------------------------------|
| url * | string | query | Username, userId, or profile link |

```
{ "status": "ok", "user": { "pk": 0, "username": "string", "full_name": "string", "is_business": true, "is_private": true, "is_verified": true, "media_count": 0, "follower_count": 0, "following_count": 0, "biography": "string", "external_url": "string", "category": "string", "has_clips": "string" } }
```

### GET /raw/ig/user/feed/ — User Feed

Returns user feed posts.

| Name  | Type   | In    | Description                                  |
|-------|--------|-------|----------------------------------------------|
| url * | string | query | Username, userId, or profile link            |
| after | string | query | end_cursor from last response for pagination |

### GET /raw/ig/user/feed\_more/ — User Feed More Data

Additional feed data.

| Name  | Type   | In    | Description                       |
|-------|--------|-------|-----------------------------------|
| url * | string | query | Username, userId, or profile link |
| after | string | query | end_cursor for pagination         |

### GET /raw/ig/user/reels/ — User Reels

Returns user reels (up to 21/page). Paginate with end\_cursor.

| Name  | Type   | In    | Description                       |
|-------|--------|-------|-----------------------------------|
| url * | string | query | Username, userId, or profile link |
| after | string | query | end_cursor for pagination         |

```
{ "items": [{"media": {"pk": 0, "code": "string", "comment_count": 0, "like_count": 0, "play_count": 0, "video_duration": 0, "caption": {"text": "string"}}}], "more_available": "string", "end_cursor": "string", "status": "ok" }
```

### GET /raw/ig/user/reels\_more/ — User Reels More Data

Additional reels data (reshare\_count, repost\_count). Up to 12/page.

| Name  | Type   | In    | Description                       |
|-------|--------|-------|-----------------------------------|
| url * | string | query | Username, userId, or profile link |
| after | string | query | end_cursor for pagination         |

## GET /raw/ig/user/stories/ — User Stories

Returns user stories.

| Name  | Type   | In    | Description                       |
|-------|--------|-------|-----------------------------------|
| url * | string | query | Username, userId, or profile link |

## GET /raw/ig/user/highlights/ — User Highlights

Returns user highlights.

| Name  | Type   | In    | Description                       |
|-------|--------|-------|-----------------------------------|
| url * | string | query | Username, userId, or profile link |

## GET /raw/ig/user/igtv/ — User IGTV

Returns user IGTV videos.

| Name  | Type   | In    | Description                       |
|-------|--------|-------|-----------------------------------|
| url * | string | query | Username, userId, or profile link |

## GET /raw/ig/user/reposted\_feed/ — Reposts Feed

Returns user's reposted content.

| Name  | Type   | In    | Description                       |
|-------|--------|-------|-----------------------------------|
| url * | string | query | Username, userId, or profile link |

## GET /raw/ig/media/info/ — Media Info

Returns media/post information.

| Name  | Type   | In    | Description     |
|-------|--------|-------|-----------------|
| url * | string | query | Media URL or ID |

## GET /raw/ig/media/info\_more/ — Media Info More Data

Additional media data.

| Name  | Type   | In    | Description     |
|-------|--------|-------|-----------------|
| url * | string | query | Media URL or ID |

## GET /raw/ig/media/comments/ — Media Comments

Returns comments on a post.

| Name  | Type   | In    | Description           |
|-------|--------|-------|-----------------------|
| url * | string | query | Media URL or ID       |
| after | string | query | Cursor for pagination |

## GET /raw/ig/media/comments/replies/ — Comment Replies

Returns replies to a comment.

| Name  | Type   | In    | Description           |
|-------|--------|-------|-----------------------|
| url * | string | query | Media URL or ID       |
| after | string | query | Cursor for pagination |

## GET /raw/ig/hashtag/feed/ — Hashtag Feed

Returns posts for a hashtag.

| Name  | Type   | In    | Description           |
|-------|--------|-------|-----------------------|
| url * | string | query | Hashtag               |
| after | string | query | Cursor for pagination |

## GET /raw/ig/hashtag/info/ — Hashtag Info

Returns hashtag information.

| Name  | Type   | In    | Description |
|-------|--------|-------|-------------|
| url * | string | query | Hashtag     |

## GET /raw/ig/audio/feed/ — Audio Feed

Returns posts using an audio clip.

| Name  | Type   | In    | Description     |
|-------|--------|-------|-----------------|
| url * | string | query | Audio ID or URL |

## GET /raw/ig/highlight/info/ — Highlight Info

Returns highlight reel information.

| Name  | Type   | In    | Description  |
|-------|--------|-------|--------------|
| url * | string | query | Highlight ID |

## GET /raw/ig/search/users/ — Search Users

Search Instagram users.

| Name  | Type   | In    | Description  |
|-------|--------|-------|--------------|
| url * | string | query | Search query |

## GET /raw/ig/search/reels/ — Search Reels

Search Instagram reels.

| Name  | Type   | In    | Description  |
|-------|--------|-------|--------------|
| url * | string | query | Search query |

**GET** /raw/ig/usertags/feed/ — User Tags Feed

Returns posts the user is tagged in.

| Name  | Type   | In    | Description                       |
|-------|--------|-------|-----------------------------------|
| url * | string | query | Username, userId, or profile link |

## 8. Raw API - TikTok

\$ 0.02 tokens per request. 100 req/sec limit.

### GET /raw/tt/user/info/ — User Info

Returns TikTok user info.

| Name  | Type   | In    | Description         |
|-------|--------|-------|---------------------|
| url * | string | query | Username or user ID |

### GET /raw/tt/user/feed/ — User Feed

Returns user's feed videos.

| Name  | Type   | In    | Description           |
|-------|--------|-------|-----------------------|
| url * | string | query | Username or user ID   |
| after | string | query | Cursor for pagination |

### GET /raw/tt/user/media/ — Media Info

Returns media information.

| Name  | Type   | In    | Description     |
|-------|--------|-------|-----------------|
| url * | string | query | Media URL or ID |

### GET /raw/tt/user/media/video/ — Media Video Content

Returns video content/download URL.

| Name  | Type   | In    | Description     |
|-------|--------|-------|-----------------|
| url * | string | query | Media URL or ID |

### GET /raw/tt/challenge/info/ — Challenge Info

Returns challenge/hashtag info.

| Name  | Type   | In    | Description          |
|-------|--------|-------|----------------------|
| url * | string | query | Challenge name or ID |

### GET /raw/tt/challenge/feed/ — Challenge Feed

Returns videos in a challenge.

| Name  | Type   | In    | Description          |
|-------|--------|-------|----------------------|
| url * | string | query | Challenge name or ID |
| after | string | query | Cursor               |

### GET /raw/tt/music/info/ — Music Info

Returns music/sound info.

| Name  | Type   | In    | Description |
|-------|--------|-------|-------------|
| url * | string | query | Music ID    |

## GET /raw/tt/music/feed/ — Music Feed

Returns videos using a sound.

| Name  | Type   | In    | Description |
|-------|--------|-------|-------------|
| url * | string | query | Music ID    |
| after | string | query | Cursor      |

## GET /raw/tt/comments/ — Comments

Returns comments on a video.

| Name  | Type   | In    | Description     |
|-------|--------|-------|-----------------|
| url * | string | query | Video URL or ID |
| after | string | query | Cursor          |

## GET /raw/tt/reply/comments/ — Comment Replies

Returns replies to a comment.

| Name  | Type   | In    | Description     |
|-------|--------|-------|-----------------|
| url * | string | query | Video URL or ID |
| after | string | query | Cursor          |

## GET /raw/tt/search/users/ — Search Users

Search TikTok users.

| Name  | Type   | In    | Description  |
|-------|--------|-------|--------------|
| url * | string | query | Search query |

## GET /raw/tt/resolve\_short\_link/ — Resolve Short Link

Resolves a TikTok short link to full URL.

| Name  | Type   | In    | Description    |
|-------|--------|-------|----------------|
| url * | string | query | Short link URL |

## 9. Raw API - YouTube

\$ 0.02 tokens per request. 100 req/sec limit.

### GET /raw/yt/channel/info/ — Channel Info

Returns YouTube channel information.

| Name  | Type   | In    | Description       |
|-------|--------|-------|-------------------|
| url * | string | query | Channel URL or ID |

### GET /raw/yt/channel/videos/ — Channel Videos Preview

Returns preview of channel videos.

| Name  | Type   | In    | Description       |
|-------|--------|-------|-------------------|
| url * | string | query | Channel URL or ID |

### GET /raw/yt/channel/videos/uploaded/ — Uploaded Videos

Returns uploaded videos list.

| Name  | Type   | In    | Description       |
|-------|--------|-------|-------------------|
| url * | string | query | Channel URL or ID |

### GET /raw/yt/playlist/ — Playlist Videos

Returns up to 100 videos from a playlist.

| Name  | Type   | In    | Description        |
|-------|--------|-------|--------------------|
| url * | string | query | YouTube playlistId |

```
{ "success": true, "videos_list": { "total": 0, "videos": [ {"video_id": "string", "thumbnail": "string", "title": "string", "time": "string"} ] } }
```

### GET /raw/yt/video/ — Video Info

Returns video information.

| Name  | Type   | In    | Description            |
|-------|--------|-------|------------------------|
| url * | string | query | YouTube video page URL |

```
{ "success": true, "video_info": { "video_id": "string", "channel_id": "string", "title": "string", "views": 0, "likes": 0, "comments": 0, "duration": "string", "description": "string", "keywords": ["string"], "subtitles": [{"language_code": "string", "name": "string"}], "comments_tabs": [{"type": "top", "cursor": "string"}] } }
```

### GET /raw/yt/video/comments/ — Video Comments

Returns video comments with pagination. Use cursor from video info for first page.

| Name  | Type   | In    | Description            |
|-------|--------|-------|------------------------|
| url * | string | query | YouTube video page URL |

|         |        |       |                           |
|---------|--------|-------|---------------------------|
| after * | string | query | cursor from last response |
|---------|--------|-------|---------------------------|

```
{ "success": true, "comments_list": { "comments": [ {"comment_id": "string", "author_name": "string", "likes": 0, "text": "string", "reply_count": 0, "replies_cursor": "string"} ], "cursor": "string" } }
```

**GET** </raw/yt/video/comments/replies/> — **Comment Replies**

Returns replies to a specific comment. Use replies\_cursor from comments.

| Name    | Type   | In    | Description               |
|---------|--------|-------|---------------------------|
| url *   | string | query | YouTube video page URL    |
| after * | string | query | cursor from last response |

## 10. Raw API - Douyin

\$ 0.02 tokens per request.

### GET /raw/dy/user/info/ — User Info

Returns Douyin user information.

| Name  | Type   | In    | Description           |
|-------|--------|-------|-----------------------|
| url * | string | query | User/media identifier |

### GET /raw/dy/user/feed/ — User Feed

Returns Douyin user feed.

| Name  | Type   | In    | Description           |
|-------|--------|-------|-----------------------|
| url * | string | query | User/media identifier |

### GET /raw/dy/media/info/ — Media Info

Returns Douyin media information.

| Name  | Type   | In    | Description           |
|-------|--------|-------|-----------------------|
| url * | string | query | User/media identifier |

### GET /raw/dy/comments/ — Comments

Returns comments on Douyin content.

| Name  | Type   | In    | Description           |
|-------|--------|-------|-----------------------|
| url * | string | query | User/media identifier |

### GET /raw/dy/reply/comments/ — Comment Replies

Returns replies to Douyin comments.

| Name  | Type   | In    | Description           |
|-------|--------|-------|-----------------------|
| url * | string | query | User/media identifier |

# 11. Raw Export API

## GET /exports/contacts/ — Get Contact Details

\$ 0.04 tokens per success response

| Name     | Type   | In    | Description                                      |
|----------|--------|-------|--------------------------------------------------|
| url *    | string | query | Username, userId, or profile link                |
| platform | string | query | instagram   tiktok   youtube. Default: instagram |

Response example:

```
{ "success": true, "user_profile": { "user_id": "10529896", "username": "niomismart", "fullname": "Niomi Smart", "contacts": [ {"type": "email", "value": "niomi.smart@gleamfutures.com"}, {"type": "youtube", "value": "niomismart"} ] } }
```

Error no\_contacts returned if no contacts found.

## GET /exports/notable\_users/ — Export Notable Followers

\$ 0.04 tokens/user (min\_followers=1000) or 0.06 tokens/user (min\_followers=5000)

Export notable followers of an influencer. Free with dry\_run=true or only\_exported\_short=true.

| Name                | Type    | In    | Description                                               |
|---------------------|---------|-------|-----------------------------------------------------------|
| url *               | string  | query | Username, userId, or profile link                         |
| platform            | string  | query | instagram   tiktok   youtube. Default: instagram          |
| fmt                 | string  | query | json (JSONPerLine)   csv                                  |
| dry_run *           | boolean | query | Estimate cost without exporting. Default: false           |
| has_email           | boolean | query | Calculate users with email (dry_run only). Default: false |
| audience            | string  | query | all   followers   likers   commenters. Default: all       |
| min_followers       | integer | query | Min followers threshold. Default: 1000                    |
| exclude_exported    | boolean | query | Exclude previously exported. Default: true                |
| save_to_exported    | boolean | query | Save to exported list. Default: true                      |
| only_exported_short | boolean | query | Get only previously exported who follow. Default: false   |

Dry run response:

```
{"count": 0, "has_email": 0, "cost": 0}
```

## POST /match\_emails/ — Match Emails

\$ 0.04 tokens per matched email

Find social media accounts (Instagram, YouTube, TikTok) matching provided emails.

| Name   | Type   | In   | Description            |
|--------|--------|------|------------------------|
| data * | object | body | {"emails": ["string"]} |

Response example:

```
{ "success": true, "matched_count": 0, "matched_emails": [ {"email": "string", "users": [ {"type": "instagram", "user_id": "string", "username": "string", "followers": 0} ] } ], "not_matched_emails":
```

```
["string"] }
```

## 12. Finance

### GET /account/info/ — Account Info

Get information about your remaining tokens and quota. Free request.

| Name | Type | In | Description |
|------|------|----|-------------|
|------|------|----|-------------|

#### Response:

```
{"success": true, "credits": 0}
```

---

End of IMAI API Documentation