

# plookup: speeding up SNARKs on non-friendly functions with lookup tables

Ariel Gabizon   Zachary J. Williamson

Aztec

SNARKs are easy prey in a world full of nasty binary functions

$$\mathbf{a}, \mathbf{b}, \mathbf{c} \in \mathbb{F}$$

Want to show  $\mathbf{c} = \mathbf{a} \oplus \mathbf{b}$  as 8-bit strings

# SNARKs are easy prey in a world full of nasty binary functions

$$\mathbf{a}, \mathbf{b}, \mathbf{c} \in \mathbb{F}$$

Want to show  $\mathbf{c} = \mathbf{a} \oplus \mathbf{b}$  as 8-bit strings


Standard way requires 25-32 constraints: Give bit decomposition of  $\mathbf{a}, \mathbf{b}, \mathbf{c}$ , check bitwise xor.

Want to show  $\mathbf{c} = \mathbf{a} \oplus \mathbf{b}$  as 8-bit strings.

Standard way requires 25-32 constraints: Give bit decomposition of  $\mathbf{a}$ ,  $\mathbf{b}$ ,  $\mathbf{c}$ , check bitwise xor.

*This is a **multiplicative** factor you pay on each small operation while computing SHA/BLAKE*

# Approach 1: Keep SNARKs in friendly neighborhoods



Blake

# Our Approach: lookup tables (see also:

Arya[Bootle, Cerulli, Groth, Jakobsen, Maller])

Precompute table  $\mathbf{T}$  of all triplets  $(\mathbf{a}, \mathbf{b}, \mathbf{c})$

s.t.  $\mathbf{c} = \mathbf{a} \oplus \mathbf{b}$ .

# Our Approach: lookup tables (see also:

Arya[Bootle, Cerulli, Groth, Jakobsen, Maller])

Precompute table  $\mathbf{T}$  of all triplets  $(\mathbf{a}, \mathbf{b}, \mathbf{c})$   
s.t.  $\mathbf{c} = \mathbf{a} \oplus \mathbf{b}$ .

Instead of representing  $\oplus$  logic, check that  
 $(\mathbf{a}, \mathbf{b}, \mathbf{c}) \in \mathbf{T}$

# Our Approach: lookup tables (see also:

Arya[Bootle, Cerulli, Groth, Jakobsen, Maller])

Precompute table  $\mathbf{T}$  of all triplets  $(\mathbf{a}, \mathbf{b}, \mathbf{c})$   
s.t.  $\mathbf{c} = \mathbf{a} \oplus \mathbf{b}$ .

Instead of representing  $\oplus$  logic, check that  
 $(\mathbf{a}, \mathbf{b}, \mathbf{c}) \in \mathbf{T}$

After enough lookups, has amortized cost of  $\sim 1$   
constraint per  $\oplus$ .



## The plookup protocol in a nutshell

*(a simpler protocol we came up with while preparing the slides)*

# Basic tool: The multiset check

**example:** Given  $\mathbf{a}, \mathbf{b} \in \mathbb{F}^3$ , want to check

$$\{\mathbf{b}_1, \mathbf{b}_2, \mathbf{b}_3\} \stackrel{?}{=} \{\mathbf{a}_1, \mathbf{a}_2, \mathbf{a}_3\}$$

# Basic tool: The multiset check

**example:** Given  $\mathbf{a}, \mathbf{b} \in \mathbb{F}^3$ , want to check

$$\{\mathbf{b}_1, \mathbf{b}_2, \mathbf{b}_3\} \stackrel{?}{=} \{\mathbf{a}_1, \mathbf{a}_2, \mathbf{a}_3\}$$

Choose random  $\gamma \in \mathbb{F}$ . Check

$$(\mathbf{a}_1 + \gamma)(\mathbf{a}_2 + \gamma)(\mathbf{a}_3 + \gamma) \stackrel{?}{=} (\mathbf{b}_1 + \gamma)(\mathbf{b}_2 + \gamma)(\mathbf{b}_3 + \gamma)$$

# Basic tool: The multiset check

**example:** Given  $\mathbf{a}, \mathbf{b} \in \mathbb{F}^3$ , want to check

$$\{\mathbf{b}_1, \mathbf{b}_2, \mathbf{b}_3\} \stackrel{?}{=} \{\mathbf{a}_1, \mathbf{a}_2, \mathbf{a}_3\}$$

Choose random  $\gamma \in \mathbb{F}$ . Check

$$(\mathbf{a}_1 + \gamma)(\mathbf{a}_2 + \gamma)(\mathbf{a}_3 + \gamma) \stackrel{?}{=} (\mathbf{b}_1 + \gamma)(\mathbf{b}_2 + \gamma)(\mathbf{b}_3 + \gamma)$$

If  $\mathbf{a}, \mathbf{b}$  different as sets then w.h.p products different.

## Basic tool: The multiset check

**example:** Given  $\mathbf{a}, \mathbf{b} \in \mathbb{F}^3$ , want to check

$$\{\mathbf{b}_1, \mathbf{b}_2, \mathbf{b}_3\} \stackrel{?}{=} \{\mathbf{a}_1, \mathbf{a}_2, \mathbf{a}_3\}$$

Choose random  $\gamma \in \mathbb{F}$ . Check

$$(\mathbf{a}_1 + \gamma)(\mathbf{a}_2 + \gamma)(\mathbf{a}_3 + \gamma) \stackrel{?}{=} (\mathbf{b}_1 + \gamma)(\mathbf{b}_2 + \gamma)(\mathbf{b}_3 + \gamma)$$

If  $\mathbf{a}, \mathbf{b}$  different as sets then w.h.p products different.

**PlonK**'s grand product implements this super efficiently

Witness  $\mathbf{f} = \{\mathbf{f}_i\}_{i \in [n]}$  Table  $\mathbf{t} = \{\mathbf{t}_i\}_{i \in [d]}$

Want to prove  $\mathbf{f} \subset \mathbf{t}$ . (using randomness we can reduce tuples to single elements).

Witness  $\mathbf{f} = \{3, 1, 1\}$  Table  $\mathbf{t} = \{1, 3, 4\}$

1. Prover commits to  $\mathbf{s} := \textit{sorted version of } \mathbf{f} \cup \mathbf{t}$ .  
 $\mathbf{s} := (1, 1, 1, 3, 3, 4)$

Witness  $\mathbf{f} = \{3, 1, 1\}$  Table  $\mathbf{t} = \{1, 3, 4\}$

1. Prover commits to  $\mathbf{s} := \textit{sorted version of } \mathbf{f} \cup \mathbf{t}$ .  
 $\mathbf{s} := (1, 1, 1, 3, 3, 4)$
2. Prover shows  $\mathbf{s} = \mathbf{f} \cup \mathbf{t}$ .



Witness  $\mathbf{f} = \{3, 1, 1\}$  Table  $\mathbf{t} = \{1, 3, 4\}$

1. Prover commits to  $\mathbf{s} := \text{sorted version of } \mathbf{f} \cup \mathbf{t}$ .  
 $\mathbf{s} := (1, 1, 1, 3, 3, 4)$
2. Prover shows  $\mathbf{s} = \mathbf{f} \cup \mathbf{t}$ .
3. Look at difference multiset of  $\mathbf{s}$   
 $\mathbf{s}' := \{0, 0, 2, 0, 1\}$ , and difference multiset of  $\mathbf{t}$   
 $\mathbf{t}' := \{2, 1\}$

Witness  $\mathbf{f} = \{3, 1, 1\}$  Table  $\mathbf{t} = \{1, 3, 4\}$

1. Prover commits to  $\mathbf{s} := \text{sorted version of } \mathbf{f} \cup \mathbf{t}$ .  
 $\mathbf{s} := (1, 1, 1, 3, 3, 4)$
2. Prover shows  $\mathbf{s} = \mathbf{f} \cup \mathbf{t}$ .
3. Look at difference multiset of  $\mathbf{s}$   
 $\mathbf{s}' := \{0, 0, 2, 0, 1\}$ , and difference multiset of  $\mathbf{t}$   
 $\mathbf{t}' := \{2, 1\}$
4. Prover shows  $\mathbf{s}' = \mathbf{t}' \cup \{0, 0, 0\}$ .