

Plookup in action

Ariel Gabizon Zachary J. Williamson



Turbo-PLONK programs (based on PLONK[GWC])

a_1	b_1	c_1	d_1
\vdots	\vdots	\vdots	\vdots
a_i	b_i	c_i	d_i
a_{i+1}	b_{i+1}	c_{i+1}	d_{i+1}
\vdots	\vdots	\vdots	\vdots

- ▶ Local low-degree constraints between rows (e.g. $a_{i+1} = b_i^2 + c_i$)
- ▶ Global equality constraints between any two cells (e.g. $a_{100} = d_2$).

Ultra-PLONK programs

- ▶ Local low-degree constraints between rows (e.g. $\mathbf{a}_{i+1} = \mathbf{b}_i^2 + \mathbf{c}_i$).
- ▶ Global equality constraints between any two cells (e.g. $\mathbf{a}_{100} = \mathbf{d}_2$).
- ▶ **Lookup constraints** - e.g. $(\mathbf{a}_5, \mathbf{b}_5, \mathbf{c}_5)$ is contained in the rows of a predefined table \mathbf{T} .

Lookup constraints in SNARKs

First used in Arya[Bootle, Cerulli, Groth, Jakobsen, Maller]

Lookup constraints in SNARKs

First used in Arya[Bootle, Cerulli, Groth, Jakobsen, Maller]

Plookup [GW20] gives improved efficiency:

$2(|\mathbf{T}| + |\mathbf{w}|)$ prover group exp

$|\mathbf{T}|$ - number of rows in table

$|\mathbf{w}|$ - length of witness

Example: bitwise XOR with “direct” table

For row values (**a**, **b**, **c**) want to show $\mathbf{c} = \mathbf{a} \oplus \mathbf{b}$ as 11-bit strings.

Example: bitwise XOR with “direct” table

For row values $(\mathbf{a}, \mathbf{b}, \mathbf{c})$ want to show $\mathbf{c} = \mathbf{a} \oplus \mathbf{b}$ as 11-bit strings.

Use table \mathbf{T} of all triplets $(\mathbf{a}, \mathbf{b}, \mathbf{c})$
s.t. $\mathbf{c} = \mathbf{a} \oplus \mathbf{b}$.

Example: bitwise XOR with “direct” table

For row values $(\mathbf{a}, \mathbf{b}, \mathbf{c})$ want to show $\mathbf{c} = \mathbf{a} \oplus \mathbf{b}$ as 11-bit strings.

Use table \mathbf{T} of all triplets $(\mathbf{a}, \mathbf{b}, \mathbf{c})$
s.t. $\mathbf{c} = \mathbf{a} \oplus \mathbf{b}$.

$$|\mathbf{T}| = 2^{22}$$

Another approach - Sparse representations

Table T_1 of pairs $(\mathbf{a}, \mathbf{a}_s)$ - \mathbf{a} is 10-bit string, \mathbf{a}_s is “ \mathbf{a} with zeroes in between bits” -

$$\mathbf{a} = \sum \mathbf{a}_i \cdot 2^i, \mathbf{a}_s = \sum \mathbf{a}_i \cdot 4^i \quad (1)$$

Another approach - Sparse representations

Table T_1 of pairs $(\mathbf{a}, \mathbf{a}_s)$ - \mathbf{a} is 10-bit string, \mathbf{a}_s is “ \mathbf{a} with zeroes in between bits” -

$$\mathbf{a} = \sum \mathbf{a}_i \cdot 2^i, \mathbf{a}_s = \sum \mathbf{a}_i \cdot 4^i \quad (1)$$

Field addition on sparse form now gives bitwise XOR :

$$\mathbf{a} = (11) \quad \mathbf{b} = (10)$$

Another approach - Sparse representations

Table T_1 of pairs $(\mathbf{a}, \mathbf{a}_s)$ - \mathbf{a} is 10-bit string, \mathbf{a}_s is “ \mathbf{a} with zeroes in between bits” -

$$\mathbf{a} = \sum \mathbf{a}_i \cdot 2^i, \mathbf{a}_s = \sum \mathbf{a}_i \cdot 4^i \quad (1)$$

Field addition on sparse form now gives bitwise XOR :

$$\mathbf{a} = (11) \quad \mathbf{b} = (10)$$

$$\mathbf{a}_s = (0101)$$

$$\mathbf{b}_s = (0100)$$

Another approach - Sparse representations

Table T_1 of pairs $(\mathbf{a}, \mathbf{a}_s)$ - \mathbf{a} is 10-bit string, \mathbf{a}_s is “ \mathbf{a} with zeroes in between bits” -

$$\mathbf{a} = \sum \mathbf{a}_i \cdot 2^i, \mathbf{a}_s = \sum \mathbf{a}_i \cdot 4^i \quad (1)$$

Field addition on sparse form now gives bitwise XOR :

$$\mathbf{a} = (11) \quad \mathbf{b} = (10)$$

$$\mathbf{a}_s = (0101)$$

$$\mathbf{b}_s = (0100)$$

$$\mathbf{a}_s + \mathbf{b}_s = (1001)$$

Another approach - Sparse representations

Table T_1 of pairs $(\mathbf{a}, \mathbf{a}_s)$ - \mathbf{a} is 10-bit string, \mathbf{a}_s is “ \mathbf{a} with zeroes in between bits” -

$$\mathbf{a} = \sum \mathbf{a}_i \cdot 2^i, \mathbf{a}_s = \sum \mathbf{a}_i \cdot 4^i \quad (1)$$

Field addition on sparse form now gives bitwise XOR :

$$\mathbf{a} = (11) \quad \mathbf{b} = (10)$$

$$\mathbf{a}_s = (0101)$$

$$\mathbf{b}_s = (0100)$$

$$\mathbf{a}_s + \mathbf{b}_s = (1001)$$

Odd bits are XORs

Another approach - Sparse representations

After adding in sparse form, can use another lookup to “decode” XOR result $\mathbf{T}_2 = \{\mathbf{c}_s, \mathbf{c}_{\text{XOR}}\}$ so

$$\mathbf{c}_s = \sum \mathbf{c}_i 4^i, \mathbf{c}_{\text{XOR}} = \sum \phi(\mathbf{c}_i) 4^i,$$

$$\phi(0) = 0, \phi(1) = 1, \phi(2) = 0, \phi(3) = 1$$

Another approach - Sparse representations

After adding in sparse form, can use another lookup to “decode” XOR result $\mathbf{T}_2 = \{\mathbf{c}_s, \mathbf{c}_{\text{XOR}}\}$ so

$$\mathbf{c}_s = \sum \mathbf{c}_i 4^i, \mathbf{c}_{\text{XOR}} = \sum \phi(\mathbf{c}_i) 4^i,$$

$$\phi(0) = 0, \phi(1) = 1, \phi(2) = 0, \phi(3) = 1$$

Can get AND at same time (see Arya paper)

SHA-256 with Sparse representations on Steroids

MAJ' is one of the two main “chunks” of a SHA round:

- ▶ **a, b, c** 32-bit values
- ▶ **>>>** is right rotation.

MAJ' is one of the two main “chunks” of a SHA round:

- ▶ **a, b, c** 32-bit values
- ▶ **>>>** is right rotation.

$$\mathbf{MAJ}'(\mathbf{a}, \mathbf{b}, \mathbf{c}) := (\mathbf{a} \ggg 2) \oplus (\mathbf{a} \ggg 13) \oplus (\mathbf{a} \ggg 22) \oplus \mathbf{MAJ}(\mathbf{a}, \mathbf{b}, \mathbf{c})$$

MAJ' is one of the two main “chunks” of a SHA round:

- ▶ **a, b, c** 32-bit values
- ▶ **>>>** is right rotation.

$$\mathbf{MAJ}'(\mathbf{a}, \mathbf{b}, \mathbf{c}) := (\mathbf{a} \ggg 2) \oplus (\mathbf{a} \ggg 13) \oplus (\mathbf{a} \ggg 22) \oplus \mathbf{MAJ}(\mathbf{a}, \mathbf{b}, \mathbf{c})$$

We map $\mathbf{a}, \mathbf{b}, \mathbf{c}$ into 16-sparse form:

$$\sum \mathbf{a}_i 2^i \rightarrow \sum \mathbf{a}_i 16^i$$

We map **a**, **b**, **c** into 16-sparse form:

$$\sum a_i 2^i \rightarrow \sum a_i 16^i$$

In sparse form we simply add in field:

$$4 * ((\mathbf{a} \ggg 2) + (\mathbf{a} \ggg 13) + (\mathbf{a} \ggg 22)) + (\mathbf{a} + \mathbf{b} + \mathbf{c})$$

We map $\mathbf{a}, \mathbf{b}, \mathbf{c}$ into 16-sparse form:

$$\sum \mathbf{a}_i 2^i \rightarrow \sum \mathbf{a}_i 16^i$$

In sparse form we simply add in field:

$$4 * ((\mathbf{a} \ggg 2) + (\mathbf{a} \ggg 13) + (\mathbf{a} \ggg 22)) + (\mathbf{a} + \mathbf{b} + \mathbf{c})$$

Addition result is “injective enough” to retrieve output of \mathbf{MAJ}' .

Getting the rotations

Split 32-bit \mathbf{a} to limbs ($\mathbf{a}_2, \mathbf{a}_1, \mathbf{a}_0$) of 10, 11, 11 bits respectively.

Getting the rotations

Split 32-bit \mathbf{a} to limbs ($\mathbf{a}_2, \mathbf{a}_1, \mathbf{a}_0$) of 10, 11, 11 bits respectively.

We have in total 9 “rotate contributions”: 3 right-rotates - 2, 13, 22 of the three limbs.

Getting the rotations

Split 32-bit \mathbf{a} to limbs ($\mathbf{a}_2, \mathbf{a}_1, \mathbf{a}_0$) of 10, 11, 11 bits respectively.

We have in total 9 “rotate contributions”: 3 right-rotates - 2, 13, 22 of the three limbs.

But only two “non-trivial” contributions:
($\mathbf{a}_1, 13$), ($\mathbf{a}_0, 2$)

Getting the rotations

Split 32-bit \mathbf{a} to limbs ($\mathbf{a}_2, \mathbf{a}_1, \mathbf{a}_0$) of 10, 11, 11 bits respectively.

We have in total 9 “rotate contributions”: 3 right-rotates - 2, 13, 22 of the three limbs.

But only two “non-trivial” contributions:

$(\mathbf{a}_1, 13), (\mathbf{a}_0, 2)$

both can be computed with a table of right rotate by 2.

Getting the rotations

Split 32-bit \mathbf{a} to limbs ($\mathbf{a}_2, \mathbf{a}_1, \mathbf{a}_0$) of 10, 11, 11 bits respectively.

We have in total 9 “rotate contributions”: 3 right-rotates - 2, 13, 22 of the three limbs.

But only two “non-trivial” contributions:

$(\mathbf{a}_1, 13), (\mathbf{a}_0, 2)$

both can be computed with a table of right rotate by 2.

In total for **MAJ'**- 3 tables of size $\leq 2^{11}$