

Ranged Polynomial Protocols

Ariel Gabizon



Outline

- ▶ A few slides of motivation and context
- ▶ Polynomial Protocols - defs, results + open question.

Succinct arguments in a nutshell

Public program \mathbf{T} , public output z .

Succinct arguments in a nutshell

Public program T , public output z .

Want to prove “I know input x for program T that generates output z .”

Succinct arguments in a nutshell

Public program T , public output z .

Want to prove “I know input x for program T that generates output z .”

Want proof size and verification time to be much smaller than run time of T .

(SNARK:=Succinct Non-Interactive Argument of Knowledge)

Succinct arguments in a nutshell

Public program T , public output z .

Want to prove “I know input x for program T that generates output z .”

Want proof size and verification time to be much smaller than run time of T .

(SNARK:=Succinct Non-Interactive Argument of Knowledge)

Arithmetization [LFKN,.....]: Reduce claim to claim of form “I know polynomials that satisfy some identity”

Succinct arguments in a nutshell

Public program T , public output z .

Want to prove “I know input x for program T that generates output z .”

Want proof size and verification time to be much smaller than run time of T .

(SNARK:=Succinct Non-Interactive Argument of Knowledge)

Arithmetization [LFKN,.....]: Reduce claim to claim of form “I know polynomials that satisfy some identity”

Succinct arguments in a nutshell

Advantage of claims about polynomials is that suffice to check at one random point

Succinct arguments in a nutshell

Advantage of claims about polynomials is that suffice to check at one random point

But need to solve "chicken and egg problem":
Prover must commit to polynomials before knowing the challenge point.

Polynomial commitment schemes [KZG, 10]

- ▶ Prover send short commitment $\text{cm}(\mathbf{f})$ to polynomial.

Polynomial commitment schemes [KZG, 10]

- ▶ Prover send short commitment $\text{cm}(\mathbf{f})$ to polynomial.
- ▶ Later Verifier can choose value $i \in \mathbb{F}$.

Polynomial commitment schemes [KZG, 10]

- ▶ Prover send short commitment $\text{cm}(\mathbf{f})$ to polynomial.
- ▶ Later Verifier can choose value $\mathbf{i} \in \mathbb{F}$.
- ▶ Prover sends back $\mathbf{z} = \mathbf{f}(\mathbf{i})$; together with proof $\text{open}(\mathbf{f}, \mathbf{i})$ that \mathbf{z} is correct.

Polynomial commitment schemes [KZG, 10]

- ▶ Prover send short commitment $\text{cm}(\mathbf{f})$ to polynomial.
- ▶ Later Verifier can choose value $\mathbf{i} \in \mathbb{F}$.
- ▶ Prover sends back $\mathbf{z} = \mathbf{f}(\mathbf{i})$; together with proof $\text{open}(\mathbf{f}, \mathbf{i})$ that \mathbf{z} is correct.

KZG give us PCS with commitments and openings are practically 32 bytes.

Notation: $[\mathbf{x}] = \mathbf{g}^{\mathbf{x}}$ where \mathbf{g} generator of elliptic curve group.

Setup: $[1], [\mathbf{x}], \dots, [\mathbf{x}^d]$, for random $\mathbf{x} \in \mathbb{F}$.

Setup: $[1], [\mathbf{x}], \dots, [\mathbf{x}^d]$, for random $\mathbf{x} \in \mathbb{F}$.

$$\text{cm}(\mathbf{f}) := [\mathbf{f}(\mathbf{x})]$$

Setup: $[1], [\mathbf{x}], \dots, [\mathbf{x}^d]$, for random $\mathbf{x} \in \mathbb{F}$.

$$\text{cm}(\mathbf{f}) := [\mathbf{f}(\mathbf{x})]$$

$$\text{open}(\mathbf{f}, \mathbf{i}) := [\mathbf{h}(\mathbf{x})], \text{ where } \mathbf{h}(\mathbf{X}) := \frac{\mathbf{f}(\mathbf{X}) - \mathbf{f}(\mathbf{i})}{\mathbf{X} - \mathbf{i}}$$

Setup: $[1], [\mathbf{x}], \dots, [\mathbf{x}^d]$, for random $\mathbf{x} \in \mathbb{F}$.

$$\text{cm}(\mathbf{f}) := [\mathbf{f}(\mathbf{x})]$$

$$\text{open}(\mathbf{f}, \mathbf{i}) := [\mathbf{h}(\mathbf{x})], \text{ where } \mathbf{h}(\mathbf{X}) := \frac{\mathbf{f}(\mathbf{X}) - \mathbf{f}(\mathbf{i})}{\mathbf{X} - \mathbf{i}}$$

$$\text{verify}(\text{cm}, \boldsymbol{\pi}, \mathbf{z}, \mathbf{i}) :$$

$$\mathbf{e}(\text{cm} - [\mathbf{z}], [1]) \stackrel{?}{=} \mathbf{e}(\boldsymbol{\pi}, [\mathbf{x} - \mathbf{i}])$$

Idealized Polynomials Protocols

Preprocessing/inputs: \mathcal{P} and \mathcal{V} agree in advance on $\mathbf{g}_1, \dots, \mathbf{g}_t \in \mathbb{F}_{<d}[\mathbf{X}]$.

Protocol:

1. \mathcal{P} 's msgs are to ideal party \mathbf{I} . Must be $\mathbf{f}_i \in \mathbb{F}_{<d}[\mathbf{X}]$.
2. At protocol end \mathcal{V} asks \mathbf{I} if some (constant number) of identities hold between $\{\mathbf{f}_1, \dots, \mathbf{f}_\ell, \mathbf{g}_1, \dots, \mathbf{g}_t\}$. Outputs **acc** iff they do.

$$\mathfrak{d}(\mathbf{P}) := \left(\sum_{i \in [t]} \deg(\mathbf{f}_i) + 1 \right)$$

.

¹similar statements in Marlin/Fractal/Supersonic

$$\mathfrak{d}(\mathbf{P}) := \left(\sum_{i \in [t]} \deg(f_i) + 1 \right)$$

Thm:¹ Can compile to “real” protocol in Algebraic Group Model, where prover complexity $\mathfrak{d}(\mathbf{P})$.

¹similar statements in Marlin/Fractal/Supersonic

$$\mathfrak{d}(\mathbf{P}) := \left(\sum_{i \in [t]} \deg(f_i) + 1 \right)$$

Thm:¹ Can compile to “real” protocol in Algebraic Group Model, where prover complexity $\mathfrak{d}(\mathbf{P})$.

proof sketch: Use [KZG] polynomial commitment scheme. \mathcal{P} commits to all polys. \mathcal{V} checks identity at random challenge point.

¹similar statements in Marlin/Fractal/Supersonic

Ranged polynomials protocols

Preprocessing/inputs: Predefined polynomials

$$g_1, \dots, g_t \in \mathbb{F}_{<d}[\mathbf{X}]$$

Range: $\mathbf{H} \subset \mathbb{F}$.

Ranged polynomials protocols

Preprocessing/inputs: Predefined polynomials

$$g_1, \dots, g_t \in \mathbb{F}_{<d}[\mathbf{X}]$$

Range: $\mathbf{H} \subset \mathbb{F}$.

Protocol:

1. \mathcal{P} 's msgs are to ideal party \mathbf{I} . Must be $f_i \in \mathbb{F}_{<d}[\mathbf{X}]$.
2. At end, \mathcal{V} asks \mathbf{I} if some identity holds between $\{f_1, \dots, f_\ell, g_1, \dots, g_t\}$ **on** \mathbf{H} .

H-ranged protocol using polynomial protocol:

\mathcal{V} wants to check identities $\mathbf{P}_1, \mathbf{P}_2$ on \mathbf{H} .

- ▶ After \mathcal{P} finished sending $\{\mathbf{f}_i\}$, \mathcal{V} sends random $\mathbf{a}_1, \mathbf{a}_2 \in \mathbb{F}$.

H-ranged protocol using polynomial protocol:

\mathcal{V} wants to check identities $\mathbf{P}_1, \mathbf{P}_2$ on \mathbf{H} .

- ▶ After \mathcal{P} finished sending $\{\mathbf{f}_i\}$, \mathcal{V} sends random $\mathbf{a}_1, \mathbf{a}_2 \in \mathbb{F}$.
- ▶ \mathcal{P} sends $\mathbf{T} \in \mathbb{F}_{<d}[\mathbf{X}]$.

H-ranged protocol using polynomial protocol:

\mathcal{V} wants to check identities $\mathbf{P}_1, \mathbf{P}_2$ on \mathbf{H} .

- ▶ After \mathcal{P} finished sending $\{\mathbf{f}_i\}$, \mathcal{V} sends random $\mathbf{a}_1, \mathbf{a}_2 \in \mathbb{F}$.
- ▶ \mathcal{P} sends $\mathbf{T} \in \mathbb{F}_{<d}[\mathbf{X}]$.
- ▶ \mathcal{V} checks identity $\mathbf{a}_1 \cdot \mathbf{P}_1 + \mathbf{a}_2 \cdot \mathbf{P}_2 \equiv \mathbf{T} \cdot \mathbf{Z}_{\mathbf{H}}$.

$$\mathbf{Z}_{\mathbf{H}}(\mathbf{X}) := \prod_{\mathbf{a} \in \mathbf{H}} (\mathbf{X} - \mathbf{a}).$$

($\mathbf{Z}_{\mathbf{H}}$ will be a preprocessed polynomial).

\mathbf{H} -ranged protocol using polynomial protocol:

Motivates - for \mathbf{H} -ranged protocol \mathbf{P} define

$$\mathfrak{d}(\mathbf{P}) := \left(\sum_{i \in [t]} \deg(\mathbf{f}_i) + 1 \right) + \mathbf{D} - |\mathbf{H}|.$$

$\mathbf{D} :=$ max degree of identity \mathbf{C} checked in exec with honest \mathcal{P} .

Multiset equality check

Given $\mathbf{a}, \mathbf{b} \in \mathbb{F}^3$, want to check

$$\{\mathbf{b}_1, \mathbf{b}_2, \mathbf{b}_3\} \stackrel{?}{=} \{\mathbf{a}_1, \mathbf{a}_2, \mathbf{a}_3\}$$

Multiset equality check

Given $\mathbf{a}, \mathbf{b} \in \mathbb{F}^3$, want to check

$$\{\mathbf{b}_1, \mathbf{b}_2, \mathbf{b}_3\} \stackrel{?}{=} \{\mathbf{a}_1, \mathbf{a}_2, \mathbf{a}_3\}$$

Choose random $\gamma \in \mathbb{F}$. Check

$$(\mathbf{a}_1 + \gamma)(\mathbf{a}_2 + \gamma)(\mathbf{a}_3 + \gamma) \stackrel{?}{=} (\mathbf{b}_1 + \gamma)(\mathbf{b}_2 + \gamma)(\mathbf{b}_3 + \gamma)$$

Multiset equality check

Given $\mathbf{a}, \mathbf{b} \in \mathbb{F}^3$, want to check

$$\{\mathbf{b}_1, \mathbf{b}_2, \mathbf{b}_3\} \stackrel{?}{=} \{\mathbf{a}_1, \mathbf{a}_2, \mathbf{a}_3\}$$

Choose random $\gamma \in \mathbb{F}$. Check

$$(\mathbf{a}_1 + \gamma)(\mathbf{a}_2 + \gamma)(\mathbf{a}_3 + \gamma) \stackrel{?}{=} (\mathbf{b}_1 + \gamma)(\mathbf{b}_2 + \gamma)(\mathbf{b}_3 + \gamma)$$

If \mathbf{a}, \mathbf{b} different as sets then w.h.p products different.

Multiset equality check

Given $\mathbf{a}, \mathbf{b} \in \mathbb{F}^3$, want to check

$$\{\mathbf{b}_1, \mathbf{b}_2, \mathbf{b}_3\} \stackrel{?}{=} \{\mathbf{a}_1, \mathbf{a}_2, \mathbf{a}_3\}$$

Choose random $\gamma \in \mathbb{F}$. Check

$$(\mathbf{a}_1 + \gamma)(\mathbf{a}_2 + \gamma)(\mathbf{a}_3 + \gamma) \stackrel{?}{=} (\mathbf{b}_1 + \gamma)(\mathbf{b}_2 + \gamma)(\mathbf{b}_3 + \gamma)$$

If \mathbf{a}, \mathbf{b} different as sets then w.h.p products different.

Multiset equality check - polynomial version

Given $\mathbf{f}, \mathbf{g} \in \mathbb{F}_{<d}[\mathbf{X}]$, want to check
 $\{\mathbf{f}(\mathbf{x})\}_{\mathbf{x} \in H} \stackrel{?}{=} \{\mathbf{g}(\mathbf{x})\}_{\mathbf{x} \in H}$ as multisets

Reduces to:

$$\mathbf{H} = \{\alpha, \alpha^2, \dots, \alpha^n\}.$$

\mathcal{P} has sent $\mathbf{f}', \mathbf{g}' \in \mathbb{F}_{\langle n \rangle}[\mathbf{X}]$.

Wants to prove:

$$\prod_{i \in [n]} \mathbf{f}(\alpha^i) = \prod_{i \in [n]} \mathbf{g}(\alpha^i)$$

$$\mathbf{f} := \mathbf{f}' + \gamma, \mathbf{g} := \mathbf{g}' + \gamma$$

Multiplicative subgroups:

$$\mathbf{H} = \{ \alpha, \alpha^2, \dots, \alpha^n = 1 \}.$$

L_i is i 'th lagrange poly of \mathbf{H} :

$$L_i(\alpha^i) = 1, L_i(\alpha^j) = 0, j \neq i$$

Checking products with \mathbf{H} -ranged protocols [GWC19]

1. \mathcal{P} computes \mathbf{Z} with
$$\mathbf{Z}(\alpha) = 1, \mathbf{Z}(\alpha^i) = \prod_{j < i} f(\alpha^j)/g(\alpha^j).$$
2. Sends \mathbf{Z} to \mathbf{I} .

Checking products with \mathbf{H} -ranged protocols [GWC19]

1. \mathcal{P} computes \mathbf{Z} with
$$\mathbf{Z}(\boldsymbol{\alpha}) = 1, \mathbf{Z}(\boldsymbol{\alpha}^i) = \prod_{j \neq i} \mathbf{f}(\boldsymbol{\alpha}^j) / \mathbf{g}(\boldsymbol{\alpha}^j).$$
2. Sends \mathbf{Z} to \mathbf{I} .
3. \mathcal{V} checks following identities on \mathbf{H} .
 - 3.1 $\mathbf{L}_1(\mathbf{X})(\mathbf{Z}(\mathbf{X}) - 1) = 0$
 - 3.2 $\mathbf{Z}(\mathbf{X})\mathbf{f}(\mathbf{X}) = \mathbf{Z}(\boldsymbol{\alpha} \cdot \mathbf{X})\mathbf{g}(\mathbf{X})$

Checking products with \mathbf{H} -ranged protocols [GWC19]

1. \mathcal{P} computes \mathbf{Z} with
$$\mathbf{Z}(\boldsymbol{\alpha}) = 1, \mathbf{Z}(\boldsymbol{\alpha}^i) = \prod_{j \neq i} \mathbf{f}(\boldsymbol{\alpha}^j) / \mathbf{g}(\boldsymbol{\alpha}^j).$$
2. Sends \mathbf{Z} to \mathbf{I} .
3. \mathcal{V} checks following identities on \mathbf{H} .
 - 3.1 $\mathbf{L}_1(\mathbf{X})(\mathbf{Z}(\mathbf{X}) - 1) = 0$
 - 3.2 $\mathbf{Z}(\mathbf{X})\mathbf{f}(\mathbf{X}) = \mathbf{Z}(\boldsymbol{\alpha} \cdot \mathbf{X})\mathbf{g}(\mathbf{X})$

We get $\mathfrak{d}(\mathbf{P}) = \mathfrak{n} + 2\mathfrak{n} - |\mathbf{H}| = 2\mathfrak{n}$.

Example 2: Range checks

Integer $M < n$. Given $f \in \mathbb{F}_{<n}[X]$, want to check $f(x) \in [1..M]$ for each $x \in H$.

Example 2: Range checks

Integer $M < n$. Given $f \in \mathbb{F}_{<n}[X]$, want to check $f(x) \in [1..M]$ for each $x \in H$.

(most?) common SNARK operation: SNARK recursion requires simulating one field using another

Example 2: Range checks

Simplifying assumption: $[1..M] \subset \{f(\mathbf{x})\}_{\mathbf{x} \in H}$

Example 2: Range checks

Simplifying assumption: $[1..M] \subset \{f(\mathbf{x})\}_{\mathbf{x} \in H}$

Protocol:

1. \mathcal{P} computes "sorted version of \mathbf{f} ": $\mathbf{s} \in \mathbb{F}_{<n}[\mathbf{X}]$
with $\{\mathbf{s}(\mathbf{x})\}_{\mathbf{x} \in H} = \{\mathbf{f}(\mathbf{x})\}_{\mathbf{x} \in H}$,
 $\mathbf{s}(\alpha^i) \leq \mathbf{s}(\alpha^{i+1})$.

Example 2: Range checks

Simplifying assumption: $[1..M] \subset \{f(\mathbf{x})\}_{\mathbf{x} \in H}$

Protocol:

1. \mathcal{P} computes "sorted version of \mathbf{f} ": $\mathbf{s} \in \mathbb{F}_{<n}[\mathbf{X}]$
with $\{\mathbf{s}(\mathbf{x})\}_{\mathbf{x} \in H} = \{\mathbf{f}(\mathbf{x})\}_{\mathbf{x} \in H}$,
 $\mathbf{s}(\alpha^i) \leq \mathbf{s}(\alpha^{i+1})$.
2. \mathcal{P} sends \mathbf{s} to \mathbf{I} .

Example 2: Range checks

Simplifying assumption: $[1..M] \subset \{f(x)\}_{x \in H}$

Protocol:

1. \mathcal{P} computes "sorted version of f ": $s \in \mathbb{F}_{<n}[X]$
with $\{s(x)\}_{x \in H} = \{f(x)\}_{x \in H}$,
 $s(\alpha^i) \leq s(\alpha^{i+1})$.
2. \mathcal{P} sends s to \mathbf{I} .
3. \mathcal{V} checks that
 - 3.1 Mutli-set equality between s and f .

Example 2: Range checks

Simplifying assumption: $[1..M] \subset \{f(x)\}_{x \in H}$

Protocol:

1. \mathcal{P} computes "sorted version of f ": $s \in \mathbb{F}_{<n}[X]$
with $\{s(x)\}_{x \in H} = \{f(x)\}_{x \in H}$,
 $s(\alpha^i) \leq s(\alpha^{i+1})$.
2. \mathcal{P} sends s to \mathbf{I} .
3. \mathcal{V} checks that
 - 3.1 Multi-set equality between s and f .
 - 3.2 $s(\alpha) = 1$
 - 3.3 $s(\alpha^n) = M$

Example 2: Range checks

Simplifying assumption: $[1..M] \subset \{f(x)\}_{x \in H}$

Protocol:

1. \mathcal{P} computes "sorted version of f ": $s \in \mathbb{F}_{<n}[X]$
with $\{s(x)\}_{x \in H} = \{f(x)\}_{x \in H}$,
 $s(\alpha^i) \leq s(\alpha^{i+1})$.
2. \mathcal{P} sends s to \mathcal{I} .
3. \mathcal{V} checks that
 - 3.1 Multi-set equality between s and f .
 - 3.2 $s(\alpha) = 1$
 - 3.3 $s(\alpha^n) = M$
 - 3.4 For each $x \in H \setminus \{1\}$,

Example 2: Range checks

Simplifying assumption: $[1..M] \subset \{f(x)\}_{x \in H}$

Protocol:

1. \mathcal{P} computes "sorted version of f ": $s \in \mathbb{F}_{<n}[X]$
with $\{s(x)\}_{x \in H} = \{f(x)\}_{x \in H}$,
 $s(\alpha^i) \leq s(\alpha^{i+1})$.
2. \mathcal{P} sends s to \mathbf{I} .
3. \mathcal{V} checks that
 - 3.1 Multi-set equality between s and f .
 - 3.2 $s(\alpha) = 1$
 - 3.3 $s(\alpha^n) = M$
 - 3.4 For each $x \in H \setminus \{1\}$,

$$(s(x \cdot \alpha) - s(x))^2 = s(x \cdot \alpha) - s(x)$$

We get $\mathfrak{d}(\mathbf{P}) = 3n$

To remove assumption use preprocessed "table
poly" \mathbf{t} with $\{\mathbf{t}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}} = [1..\mathbf{M}]$
(details on next slide)

Preprocessed poly: $\mathbf{t} \in \mathbb{F}_{<\mathcal{M}}[\mathbf{X}]$ with
 $\{\mathbf{t}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}} = [1..\mathcal{M}]$

Preprocessed poly: $\mathbf{t} \in \mathbb{F}_{<M}[\mathbf{X}]$ with
 $\{\mathbf{t}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}} = [1..M]$

Protocol:

1. \mathcal{P} computes "sorted version of $\mathbf{f} \cup \mathbf{t}$ ":
 $\mathbf{s} \in \mathbb{F}_{<n+M}[\mathbf{X}]$ with
 $\{\mathbf{s}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}} = \{\mathbf{f}(\mathbf{x}), \mathbf{t}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}},$
 $\mathbf{s}(\alpha^i) \leq \mathbf{s}(\alpha^{i+1}).$

Preprocessed poly: $\mathbf{t} \in \mathbb{F}_{<M}[\mathbf{X}]$ with
 $\{\mathbf{t}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}} = [1..M]$

Protocol:

1. \mathcal{P} computes "sorted version of $\mathbf{f} \cup \mathbf{t}$ ":
 $\mathbf{s} \in \mathbb{F}_{<n+M}[\mathbf{X}]$ with
 $\{\mathbf{s}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}} = \{\mathbf{f}(\mathbf{x}), \mathbf{t}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}},$
 $\mathbf{s}(\alpha^i) \leq \mathbf{s}(\alpha^{i+1}).$
2. \mathcal{P} sends \mathbf{s} to \mathbf{I} .

Preprocessed poly: $\mathbf{t} \in \mathbb{F}_{\langle M \rangle}[\mathbf{X}]$ with
 $\{\mathbf{t}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}} = [1..M]$

Protocol:

1. \mathcal{P} computes "sorted version of $\mathbf{f} \cup \mathbf{t}$ ":
 $\mathbf{s} \in \mathbb{F}_{\langle n+M \rangle}[\mathbf{X}]$ with
 $\{\mathbf{s}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}} = \{\mathbf{f}(\mathbf{x}), \mathbf{t}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}},$
 $\mathbf{s}(\alpha^i) \leq \mathbf{s}(\alpha^{i+1}).$
2. \mathcal{P} sends \mathbf{s} to \mathbf{I} .
3. \mathcal{V} checks that
 - 3.1 Multi-set equality between \mathbf{s} and $\mathbf{f} \cup \mathbf{t}$.

Preprocessed poly: $\mathbf{t} \in \mathbb{F}_{\langle M \rangle}[\mathbf{X}]$ with
 $\{\mathbf{t}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}} = [1..M]$

Protocol:

1. \mathcal{P} computes "sorted version of $\mathbf{f} \cup \mathbf{t}$ ":
 $\mathbf{s} \in \mathbb{F}_{\langle n+M \rangle}[\mathbf{X}]$ with
 $\{\mathbf{s}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}} = \{\mathbf{f}(\mathbf{x}), \mathbf{t}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}},$
 $\mathbf{s}(\alpha^i) \leq \mathbf{s}(\alpha^{i+1}).$
2. \mathcal{P} sends \mathbf{s} to \mathbf{I} .
3. \mathcal{V} checks that
 - 3.1 Multi-set equality between \mathbf{s} and $\mathbf{f} \cup \mathbf{t}$.
 - 3.2 $\mathbf{s}(\alpha) = 1$
 - 3.3 $\mathbf{s}(\alpha^n) = M$
 - 3.4 For each $\mathbf{x} \in \mathbf{H} \setminus \{1\},$

Preprocessed poly: $\mathbf{t} \in \mathbb{F}_{\langle \mathbf{M} \rangle}[\mathbf{X}]$ with
 $\{\mathbf{t}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}} = [1..M]$

Protocol:

1. \mathcal{P} computes "sorted version of $\mathbf{f} \cup \mathbf{t}$ ":

$\mathbf{s} \in \mathbb{F}_{\langle \mathbf{n} + \mathbf{M} \rangle}[\mathbf{X}]$ with

$$\{\mathbf{s}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}} = \{\mathbf{f}(\mathbf{x}), \mathbf{t}(\mathbf{x})\}_{\mathbf{x} \in \mathbf{H}},$$

$$\mathbf{s}(\alpha^i) \leq \mathbf{s}(\alpha^{i+1}).$$

2. \mathcal{P} sends \mathbf{s} to \mathbf{I} .

3. \mathcal{V} checks that

3.1 Multi-set equality between \mathbf{s} and $\mathbf{f} \cup \mathbf{t}$.

3.2 $\mathbf{s}(\alpha) = 1$

3.3 $\mathbf{s}(\alpha^n) = M$

3.4 For each $\mathbf{x} \in \mathbf{H} \setminus \{1\}$,

$$(\mathbf{s}(\mathbf{x} \cdot \alpha) - \mathbf{s}(\mathbf{x}))^2 = \mathbf{s}(\mathbf{x} \cdot \alpha) - \mathbf{s}(\mathbf{x})$$

We get

$$\mathfrak{d}(\mathbf{P}) = \deg(\mathbf{s}) + \deg(\mathbf{Z}) + \mathbf{D} - |\mathbf{H}| = 3n + 4M.$$

Given integer d decomposing each element to d elements in range $M^{1/d}$ can give us

$$d(P) = 4dn + 4M^{1/d}$$

(by sending an auxiliary polynomial of degree $< dn$ with the decomposition of each element and then running the $M^{1/d}$ size range proof on this polynomial).

Question: can we do better?