

sq:* Cached quotients for fast lookups

Liam Eagen

Dario Fiore

Ariel Gabizon

IMDEA

Zeta Function Technologies

December 21, 2022

Abstract

We present a protocol for checking the values of a committed polynomial $f(X) \in \mathbb{F}_{<N}[X]$ over a multiplicative subgroup $\mathbb{H} \subset \mathbb{F}$ of size n are contained in a table $\mathbf{t} \in \mathbb{F}^N$. After an $O(N \log N)$ preprocessing step, the prover algorithm runs in time $O(n \log n)$. Thus, we continue to improve upon the recent breakthrough sequence of results[ZBK⁺22, PK22, ?, ?] starting from Caulk [ZBK⁺22], which achieve sublinear complexity in the table size N . The two most recent works in this sequence [?, ?] achieved prover complexity $O(n \cdot \log^2 n)$.

Moreover, **sq** has the following attractive features

1. As in [ZBK⁺22, PK22, ?] our construction relies on homomorphic table commitments, which makes them amenable to vector lookups in the manner described in Section 4 of [GW20].
2. As opposed to [ZBK⁺22, PK22, ?, ?] the **sq** verifier doesn't involve pairings with prover defined \mathbb{G}_2 points, which makes recursive aggregation of proofs more convenient.
3. The construction can be altered to a version we call **sq*** so that we lose the mentioned aggregability, increase preprocessing time to $O(n \cdot N)$, and in return reduce prover complexity to a *linear* number of field and group operations!

1 Introduction

The *lookup problem* is fundamental to the efficiency of modern zk-SNARKs. Somewhat informally, it asks for a protocol to prove the values of a committed polynomial $\phi(X) \in \mathbb{F}_{<n}[X]$ are contained in a table T of size N of predefined legal values. When the table T corresponds to an operation without an efficient low-degree arithmetization in \mathbb{F} , such a protocol produces significant savings in proof construction time for programs containing the operation. Building on previous work of [BCG⁺18], **lookup** [GW20] was the first to explicitly describe a solution to this problem in the polynomial-IOP context.

*Pronounced “seek you”.

lookup described a protocol with prover complexity quasilinear in both n and N . This left the intriguing question of whether the dependence on N could be made *sublinear* after performing a preprocessing step for the table T . Caulk [ZBK⁺22] answered this question in the affirmative by leveraging bi-linear pairings, achieving a run time of $O(n^2 + n \log N)$. Caulk+ [PK22] improved this to $O(n^2)$ getting rid of the dependence on table size completely.

However, the quadratic dependence on n of these works makes them impractical for a circuit with many lookup gates. We resolve this issue by giving a protocol called **cq** that is quasi-linear in n and has no dependence on N after the preprocessing step.

1.1 Comparison of results

Table 1: Scheme comparison. n = witness size, N = Table size, “Aggregatable” = All prover defined pairing arguments in \mathbb{G}_1

Scheme	Preprocessing	Proof size	Prover Work	Verifier Work	Homomorphic?	Aggregatable?
Caulk [ZBK ⁺ 22]	$O(N \log N) \mathbb{F}, \mathbb{G}_1$	$14 \mathbb{G}_1, 1 \mathbb{G}_2, 4 \mathbb{F}$	$3n + m - \ell \mathbb{G}_1 \text{ exp},$ $n \mathbb{G}_2 \text{ exp}$	$2 \mathbb{G}_1, 1 \mathbb{G}_2$	✓	✗
Caulk+ [PK22]	$O(N \log N) \mathbb{F}, \mathbb{G}_1$	$7 \mathbb{G}_1, 1 \mathbb{G}_2, 2 \mathbb{F}$	$18n \mathbb{G}_1 \text{ exp}$	$4 \mathbb{G}_1, 2 \mathbb{F}$	✓	✗
flookup [?]	$O(N \log^2 N) \mathbb{F}, \mathbb{G}_1$	$6 \mathbb{G}_1, 1 \mathbb{G}_2, 4 \mathbb{F}$	$273n \mathbb{G}_1 \text{ exp}$	$20 \mathbb{G}_1, 16 \mathbb{F}$	✗	✗
baloo [?]	$O(N \log N) \mathbb{F}, \mathbb{G}_1$	$12 \mathbb{G}_1, 1 \mathbb{G}_2, 4 \mathbb{F}$	$8n \mathbb{G}_1 \text{ exp}$	$6 \mathbb{G}_1, 4 \mathbb{F}$	✓	✗
cq	$O(N \log N) \mathbb{F}, \mathbb{G}_1$	$3n + 3a \mathbb{G}_1, 1 \mathbb{G}_2$	$11n + 11a \mathbb{G}_1 \text{ exp},$ $\approx 54(n+a) \log(n+a) \mathbb{F} \text{ mul}$	$7 \mathbb{G}_1, 6 \mathbb{F}$	✓	✓
cq*	$O(N \cdot n) \mathbb{F}, \mathbb{G}_1$	$n + a \mathbb{G}_1, 1 \mathbb{G}_2$	$9n + 9a \mathbb{G}_1 \text{ exp},$ $\approx 54(n+a) \log(n+a) \mathbb{F} \text{ mul}$	$9 \mathbb{G}_1, 6 \mathbb{F}$	✓	✗

Table with relative proof size, prover ops, verifier ops proof-size caulk caulk+ flookup
baloo $12 \mathbb{G}_1, 1 \mathbb{G}_2, 4 \mathbb{F}$ this work $6 \mathbb{G}_1, 1 \mathbb{G}_2$

1.2 Technical Overview

The innovation of Caulk While [ZBK⁺22, PK22, ?, ?] use preprocessing and pairings to extract a subtable of witness size;

Our approach here we use preprocessing and pairings more directly to run an existing lookup protocol - mvlookup, in time independent from table size -logarithmic derivative method Let’s review this protocol: It relies on the following lemma from [?] that says that $f|_{\mathbb{H}} \in \mathfrak{t}$ if and only if for some $m \in \mathbb{F}^N$

$$\sum_{i \in [N]} \frac{m_i}{X + t_i} = \sum_{i \in [n]} \frac{1}{X + f_i}$$

Roughly, the protocol of [?] checks this identity on a random β , by sending polynomials A and B that agree on \mathbb{V} with the rational function values of the LHS and RHS respectively. Given commitments to A, B we can check the equality holds via various sumcheck techniques, e.g. that described in [BCR⁺19]. The RHS is not a problem because it is a

sum of size n . Interpolating A , and computing its commitment is actually not a problem either, because the number of non-zero values is at most n . So if we precompute the commitments to the Lagrange base of \mathbb{V} we're fine.

The main challenge, and innovation, is to convince the verifier \mathbf{V} that A is correctly formed.

This protocol is amenable, because polynomials involved have sparsity depending on witness - For large table problem is computing A that agrees with $m/(t + \beta)$ on \mathbb{V}

- Need way to compute A

2 Preliminaries

2.1 Notation:

\mathbb{H} - small space \mathbb{V} - big space Lagrange bases for big and small space

AGM - real and ideal pairing checks, agm - real and ideal pairing KZG

2.2 log derivative method

Lemma from mvlookup

Lemma 2.1. *Given $f \in \mathbb{F}^n$, and $t \in \mathbb{F}^N$, we have $f \subset t$ as sets if and only if for some $m \in \mathbb{F}^N$ the following identity of rational functions holds*

$$\sum_{i \in [n]} \frac{1}{X + f_i} = \sum_{i \in [N]} \frac{m_i}{X + t_i}.$$

3 Cached quotients

Notation: In this section and the next we use the following conventions. $\mathbb{V} \subset \mathbb{F}$ denotes a multiplicative subgroup of order N which is a power of two. We denote by \mathbf{g} a generator of \mathbb{V} . Hence, $\mathbb{V} = \{\mathbf{g}, \mathbf{g}^2, \dots, \mathbf{g}^N = 1\}$. Given $P \in \mathbb{F}[X]$ and integer $i \in [N]$, we denote $P_i := P(\mathbf{g}^i)$. For $i \in [N]$, we denote by $L_i \in \mathbb{F}_{<N}[X]$ the i 'th Lagrange polynomial of \mathbb{V} . Thus, $(L_i)_i = 1$ and $(L_i)_j = 0$ for $i \neq j \in [N]$.

For a polynomial $A(X) \in \mathbb{F}_{<N}[X]$, we say it is n -sparse if $A_i \neq 0$ for at most n values $i \in [N]$. The *sparse representation* of such A consists of the (at most) n pairs (i, A_i) such that $A_i \neq 0$. We denote $\text{supp}(A) := \{i \in [N] | A_i \neq 0\}$.

The main result of this section is a method to compute a commitment to a quotient polynomial - derived from a product with a preprocessed polynomial; in a number of operations depending only on the sparsity of the other polynomial in the product.

The result crucially relies on the following lemma derived from a result of Feist and Khovratovich[FK].

Lemma 3.1. Fix $T \in \mathbb{F}_{<N}[X]$, and a subgroup $\mathbb{V} \subset \mathbb{F}$ of size N . There is an algorithm that given the \mathbb{G}_1 elements $\{[x^i]_1\}_{i \in \{0, \dots, N\}}$ computes for $i \in [N]$, the elements $q_i := [Q_i(x)]_1$ where $Q_i(X) \in \mathbb{F}[X]$ is such that

$$L_i(X) \cdot T(X) = T_i \cdot L_i(X) + Z_{\mathbb{V}}(X) \cdot Q_i(X)$$

in $O(N \cdot \log N)$ \mathbb{G}_1 operations.

Proof. Recall the definition of the Lagrange polynomial

$$L_i(X) = \frac{Z_{\mathbb{V}}(X)}{Z'_{\mathbb{V}}(\mathbf{g}^i)(X - \mathbf{g}^i)}.$$

Substituting this definition, we can write the quotient $Q_i(X)$ as

$$Q_i(X) = \frac{T(X) - T_i}{Z'_{\mathbb{V}}(\mathbf{g}^i)(X - \mathbf{g}^i)} = Z'_{\mathbb{V}}(\omega^i)^{-1} K_i(X),$$

for $K_i(X) := \frac{T(X) - T_i}{X - \mathbf{g}^i}$. Note that the values $\{[K_i(X)]_1\}_{i \in [N]}$ are exactly the KZG opening proofs of $T(X)$ at the elements of \mathbb{V} . Thus, the algorithm of Feist and Khovratovich [FK, Tom] can be used to compute commitments to all the proofs $[K_i(X)]_1$ in $O(N \log N)$ \mathbb{G}_1 -operations. This works by writing the vector of $[K_i(X)]_1$ as a the product of a matrix with the vector of $[X^i]_1$. This matrix is a DFT matrix times a Toeplitz matrix, both of which have algorithms for evaluating matrix vector products in $O(N \log N)$ operations. Thus, all the KZG proofs can be computed in $O(N \log N)$ field operations and operations in \mathbb{G}_1 .

Finally, the algorithm just needs to scale each $[K_i(X)]_1$ by $Z'_{\mathbb{V}}(\omega^i)$ to compute $[Q_i(X)]_1$. Conveniently, these values admit a very simple description when $Z_{\mathbb{V}}(X) = X^N - 1$ is a group of roots of unity.

$$Z'_{\mathbb{V}}(X)^{-1} = (NX^{N-1})^{-1} \equiv X/N \bmod Z_{\mathbb{V}}(X)$$

In total, the prover computes the coefficients of $T(X)$ in $O(N \log N)$ field operations, computes the KZG proofs for $T(\omega^i) = t_i$ in $O(N \log N)$ group operations, and then scales these proofs by ω^i/n in $O(N)$ group operations. In total, this takes $O(N \log N)$ field and group operations in \mathbb{G}_1 . \square

We're now ready to state the main theorem of this section.

Theorem 3.2. Fix integer parameters $0 \leq n \leq N$ such that n, N are powers of two. Fix $T \in \mathbb{F}_{<N}[X]$, and a subgroup $\mathbb{V} \subset \mathbb{F}$ of size N . Let $\mathbf{srs} = \{[x^i]_1\}_{i \in [0, \dots, N]}$ for some $x \in \mathbb{F}$. There is an algorithm \mathcal{A} that after a preprocessing step of $O(N \log N)$ \mathbb{F} - and \mathbb{G}_1 -operations starting with \mathbf{srs} does the following.

Given input $A(X) \in \mathbb{F}_{<N}[X]$ that is n -sparse and given in sparse representation, \mathcal{A} computes in $O(n)$ \mathbb{F} -operations and n \mathbb{G}_1 -operations the element $\mathbf{cm} = [Q(x)]_1$ where $Q \in \mathbb{F}_{<N}[X]$ is such that

$$A(X) \cdot T(X) = Q(X) \cdot Z_{\mathbb{V}}(X) + R(X),$$

for $R(X) \in \mathbb{F}_{<N}[X]$.

Proof. The preprocessing step consists of computing the quotient commitments $[Q_i(X)]_1$ in $O(N \log N)$ operations, as described in Lemma 3.1. As stated in the lemma, for each $i \in [N]$ we have

$$L_i(X) \cdot T(X) = T_i \cdot L_i(X) + Z_{\mathbb{V}}(X) \cdot Q_i(X).$$

By assumption, the polynomial $A(X)$ can be written as a linear combination of at most n summands in the Lagrange basis of \mathbb{V} .

$$A(X) = \sum_{i \in \text{supp}(A)} A_i \cdot L_i(X)$$

Substituting this into the product with $T(X)$, and substituting each of the products $L_i(X)T(X)$ with the appropriate cached quotient $Q_i(X)$ we find

$$\begin{aligned} A(X)T(X) &= \sum_{i \in \text{supp}(A)} A_i \cdot L_i(X)T(X) = \sum_{i \in \text{supp}(A)} A_i \cdot T_i L_i(X) + A_i \cdot Z_{\mathbb{V}}(X) Q_i(X) \\ &= \sum_{i \in \text{supp}(A)} A_i \cdot T_i L_i(X) + Z_{\mathbb{V}}(X) \cdot \sum_{i \in \text{supp}(A)} A_i \cdot Q_i(X). \end{aligned}$$

Observing that the terms of the first sum are all of degree smaller than N , we get that

$$\begin{aligned} Q(X) &= \sum_{i \in \text{supp}(A)} A_i \cdot Q_i(X) \\ R(X) &= \sum_{i \in \text{supp}(A)} A_i T_i \cdot L_i(X) \end{aligned}$$

Hence, commitments to both the quotient $Q(X)$ and remainder $R(X)$ can be computed in at most n group operations as

$$\begin{aligned} [Q(X)]_1 &= \sum_{i \in \text{supp}(A)} A_i \cdot [Q_i(X)]_1 \\ [R(X)]_1 &= \sum_{i \in \text{supp}(A)} A_i T_i \cdot [L_i(X)]_1 \end{aligned}$$

□

4 Main protocol

Definition 4.1. \mathcal{R} is all pairs (cm, f) such that cm is a commitment to f and $f|_{\mathbb{H}} \subset T$.
..bla problem is relation is defined only after srs is chosen

4.1 Definitions

Ad-hoc dfn of ks protocol for table lookup

Relations dependent on srs. Tuple $\text{gen}, \text{lslnTable}_{\mathbb{H}}$

- $\text{gen}(\mathbf{t}, N) \rightarrow \text{srs}$
- $\text{lslnTable}_{\mathbb{H}}$ a protocol between \mathbf{P} and \mathbf{V} where \mathbf{P} has input $f \in \mathbb{F}_{<n}[X]$, \mathbf{V} has $[f(x)]_1$. Both have \mathbf{t} and srs . such that
 - Completeness: If $f|_{\mathbb{H}} \subset \mathbf{t}$ then \mathbf{V} outputs acc with probability one.
 - Knowledge soundness in the algebraic group model: For any $\mathbf{t} \in \mathbb{F}^n$, the probability of any algebraic \mathcal{A} to win the following game is $\text{negl}(\lambda)$
 1. Let $\text{srs} = \text{gen}(\mathbf{t}, N)$.
 2. \mathcal{A} sends a message cm and values f_1, \dots, f_n such that $\text{cm} = \sum_{i \in [n]} f_i \cdot [L_i(x)]_1$.
 3. \mathcal{A} and \mathbf{V} engage in the protocol $\text{lslnTable}_{\mathbb{H}}(\mathbf{t}, \text{cm})$ with \mathcal{A} taking the role of \mathbf{P} .
 4. \mathcal{A} wins if
 - * \mathbf{V} outputs acc
 - * $f|_{\mathbb{H}} \not\subset \mathbf{t}$.

Main protocol: Preprocessed inputs: $[Z_{\mathbb{V}}(x)]_2, [T(x)]_2$ Input (cm, f) .

Round 1: Committing to the multiplicites vector

1. \mathbf{P} computes poly $m \in \mathbb{F}_{<N}[X]$ such that $m_i = \text{number of times } \mathbf{t}_i \text{ appears in } f|_{\mathbb{H}}$
2. \mathbf{P} sends $\mathbf{m} := [m(x)]_1$.

Round 2: Interpolating the rational identity at a random β ; checking the identity for A using pairings

1. \mathbf{V} chooses and sends random $\beta \in \mathbb{F}$.
2. \mathbf{P} computes $A \in \mathbb{F}_{<N}[X]$ such that for $i \in [N]$, $A_i = m_i / (\mathbf{t}_i + \beta)$.
3. \mathbf{P} sends $\mathbf{a} := [A(x)]_1$.
4. \mathbf{P} computes $\mathbf{q}_a := [Q_A(x)]_2$ where $Q_A \in \mathbb{F}_{<N}[X]$ is such that

$$A(X)(T(X) + \beta) - m(X) = Q_A(X) \cdot Z_{\mathbb{V}}(X)$$
5. \mathbf{P} computes $B \in \mathbb{F}_{<n}[X]$ such that for $i \in [n]$, $B_i = 1/(f_i + \beta)$.

6. **P** sends $\mathbf{q}_b := [B(x)]_1$.

7. **P** computes $Q_B(X)$ such that

$$B(X)(f(x) + \beta) - 1 = Q_B(X) \cdot Z_{\mathbb{H}}(X)$$

8. **P** computes and sends the value $a_0 := A(0)$.

9. **V** sets $b_0 := (N \cdot a_0)/n$.

10. **P** computes and sends $\mathbf{p} = [P(x)]_1$ where

$$P(X) := A(X) \cdot X^{d-N}$$

11. **V** checks that A encodes the correct values:

$$e(\mathbf{a}, [T(x)]_2 + [\beta]_2) = e(\mathbf{q}_a, [Z_{\mathbb{V}}(x)]_2) \cdot e(\mathbf{m}, [1]_2)$$

12. **V** checks that A has the appropriate degree:

$$e(\mathbf{a}, [x^{d-N}]_2) = e(\mathbf{p}, [1]_2).$$

Round 3: Checking the identities for B at random $\gamma \in \mathbb{F}$

1. **V** sends random $\gamma, \eta, \zeta \in \mathbb{F}$.

2. **P** sends $b_\gamma := B(\gamma), Q_{b,\gamma} := Q_B(\gamma), f_\gamma := f(\gamma)$.

3. As part of checking the correctness of \mathbf{q}_b , **V** computes $Z_{\mathbb{H}}(\gamma) = \gamma^n - 1$ and computes

$$Q_{b,\gamma} := \frac{b_\gamma \cdot (f_\gamma + \beta) - 1}{Z_{\mathbb{H}}(\gamma)}$$

4. As part of checking P is correct, **V** computes

$$P_\gamma := b_\gamma \cdot \gamma^{d-n}$$

5. To perform a batched KZG check for the correctness of the values $a_\gamma, b_\gamma, f_\gamma, P_\gamma$

(a) **V** sends random $\eta \in \mathbb{F}$. **P** and **V** separately compute

$$v := b_\gamma + \eta \cdot f_\gamma + \eta^2 \cdot Q_{b,\gamma} + \eta^3 \cdot P_\gamma$$

(b) **P** computes $\pi_\gamma := [h(x)]_1$ for

$$h(X) := \frac{B(X) + \eta \cdot f(X) + \eta^2 \cdot Q_B(X) + \eta^3 \cdot P(X) - v}{X - \gamma}$$

(c) **V** computes

$$\mathbf{c} := \mathbf{b} + \eta \cdot \mathbf{f} + \eta^2 \cdot \mathbf{q}_b + \eta^3 \cdot \mathbf{p}$$

and checks that

$$e(\mathbf{c} - [v]_1 + \gamma \cdot \pi_\gamma, [1]_2) = e(\pi_\gamma, [x]_2)$$

6. To perform a batched KZG check for the correctness of the values a_0, b_0

(a) **P** and **V** separately compute

$$u := a_0 + \zeta \cdot b_0.$$

(b) **P** computes and sends $\pi_0 := [h_0(x)]_1$ for

$$h_0(X) := \frac{A(X) + \zeta \cdot B(X)}{X}$$

(c) **V** computes

$$\mathbf{c}_0 := \mathbf{a} + \zeta \mathbf{b}$$

and checks that

$$e(\mathbf{c}_0 - [u]_1, [1]_2) = e(\pi_0, [x]_2)$$

Stats: verifier pairings:4 - pair \mathbf{a} with random combination of T and $[x^{d-N}]_2$, pair \mathbf{q}_a with Z_V .

Lemma 4.2. *The element q_A in Step 4 can be computed in $n \log n$ \mathbb{G}_2 -operations and $O(n \log n)$ \mathbb{F} -operations*

Lemma 4.3. *The elements π_0, π_γ can be computed in $2 \cdot n \log n$ \mathbb{G}_1 -operations and $O(n \log n)$ \mathbb{F} -operations*

Knowledge soundness proof: Look at the following events

References

- [BCG⁺18] J. Bootle, A. Cerulli, J. Groth, S. K. Jakobsen, and M. Maller. Arya: Nearly linear-time zero-knowledge proofs for correct program execution. In Thomas Peyrin and Steven D. Galbraith, editors, *Advances in Cryptology - ASIACRYPT 2018 - 24th International Conference on the Theory and Application of Cryptology and Information Security, Brisbane, QLD, Australia, December 2-6, 2018, Proceedings, Part I*, volume 11272 of *Lecture Notes in Computer Science*, pages 595–626. Springer, 2018.
- [BCR⁺19] E. Ben-Sasson, A. Chiesa, M. Riabzev, N. Spooner, M. Virza, and N. P. Ward. Aurora: Transparent succinct arguments for R1CS. In *Advances in Cryptology - EUROCRYPT 2019 - 38th Annual International Conference on the Theory and Applications of Cryptographic Techniques, Darmstadt, Germany, May 19-23, 2019, Proceedings, Part I*, pages 103–128, 2019.

- [FK] D. Feist and D. Khovratovich. Fast amortized kate proofs.
- [GW20] A. Gabizon and Z. J. Williamson. plookup: A simplified polynomial protocol for lookup tables. *IACR Cryptol. ePrint Arch.*, page 315, 2020.
- [PK22] J. Posen and A. A. Kattis. Caulk+: Table-independent lookup arguments. 2022.
- [Tom] A. Tomescu. Feist-khovratovich technique for computing kzg proofs fast.
- [ZBK⁺22] A. Zapico, V. Buterin, D. Khovratovich, M. Maller, A. Nitulescu, and M. Simkin. Caulk: Lookup arguments in sublinear time. *IACR Cryptol. ePrint Arch.*, page 621, 2022.