

DOC_INTEL: Data Dictionary

Complete schema reference for all DOC_INTEL tables, columns, and relationships.

Database: DOC_INTEL

Quick Lookup: Common Columns by Name

These column names appear across multiple tables. Use the table below to verify which table(s) contain the column you need.

Column	Tables
FILE_PATH	ingestion_registry, parsed_documents, classified_documents, document_attributes, document_catalog, document_pages, extraction_overrides, pipeline_events, document_bookmarks, search_feedback
PROCESSING_VERSION	ingestion_registry, parsed_documents, classified_documents, document_attributes, document_catalog, extraction_overrides
SOURCE_FOLDER	ingestion_registry, classified_documents, document_catalog, document_pages, pipeline_events
IR_FILE_ID	ingestion_registry, document_catalog, document_pages, pipeline_events
INSURED_NAME	document_attributes, document_catalog, document_bookmarks
LINE_OF_BUSINESS	

Column	Tables
	document_attributes, document_catalog
INGESTION_STATUS	ingestion_registry, document_catalog
CREATED_AT	document_bookmarks, entitlement_roles, lines_of_business, user_entitlements, user_role_assignments, ingestion_stages, parsed_documents, document_pages
USER_NAME	user_entitlements, user_role_assignments, document_bookmarks, saved_searches, search_feedback, user_preferences, agent_audit_log, pipeline_events
DOCUMENT_TYPE	document_catalog, extraction_schemas, document_bookmarks

Columns That Do NOT Exist (Common Mistakes)

Attempted Column	Fix
document_catalog.FILE_NAME	Does not exist. Derive from FILE_PATH : SPLIT_PART(file_path, '/', -1)
extraction_overrides.CREATED_AT	Use SUBMITTED_AT instead
classified_documents.LINE_OF_BUSINESS	Only on document_attributes and document_catalog
classified_documents.INSURED_NAME	Only on document_attributes and document_catalog
user_entitlements.ROLE_NAME	Only on entitlement_roles .JOIN via user_role_assignments.role_id

Schema: DATA (Pipeline Tables)

ingestion_registry

Master registry of every file ever seen by the pipeline. Single source of truth for deduplication and processing state.

Column	Type	Nullable	Description
registry_id	VARCHAR	NOT NULL (PK)	UUID — unique row identifier
file_path	VARCHAR	NOT NULL	Relative path within the stage (e.g., documents/my-file.pdf)
stage_name	VARCHAR	NOT NULL	Fully-qualified stage name
file_format	VARCHAR	NOT NULL	Uppercase file extension: TIFF, PDF, DOCX, JPEG, PNG, HTML, TXT
file_size_bytes	BIGINT	YES	File size in bytes from stage DIRECTORY()
file_hash	VARCHAR	YES	SHA2(256) of file bytes for change detection (set on parse)
ir_file_id	VARCHAR	YES	ImageRight FileID (from metadata sidecar)
source_folder	VARCHAR	YES	Source folder / organizational grouping: Claims, Underwriting,

Column	Type	Nullable	Description
			Reinsurance, etc.
ir_document_type	VARCHAR	YES	Native ImageRight document type classification
ir_policy_number	VARCHAR	YES	Policy # from IR UserKey1
ir_claim_number	VARCHAR	YES	Claim # from IR UserKey2
ir_assigned_to	VARCHAR	YES	IR workflow assignee (email)
ir_date_created	TIMESTAMP_NTZ	YES	When document was created in ImageRight
ir_metadata	VARIANT	YES	Full JSON sidecar from metadata stage
ingestion_status	VARCHAR	YES	State machine: PENDING / PROCESSING / COMPLETE / FAILED / ABANDONED / SKIPPED
processing_version	INT	YES	Version number; increments when file changes or is force-reprocessed
force_reprocess	BOOLEAN	YES	Admin flag: TRUE triggers new version regardless of content
first_seen_at	TIMESTAMP_NTZ	YES	When file was first detected on stage

Column	Type	Nullable	Description
last_seen_at	TIMESTAMP_NTZ	YES	Last time file was seen during a stage scan
processing_started_at	TIMESTAMP_NTZ	YES	When PROCESSING state was entered
processing_completed_at	TIMESTAMP_NTZ	YES	When COMPLETE state was entered
processing_attempts	INT	YES	Count of parse attempts (resets on force-reprocess)
last_error	VARCHAR	YES	Error message from most recent failure
error_stage	VARCHAR	YES	Which pipeline stage failed: PARSE / CLASSIFY / EXTRACT
content_hash	VARCHAR	YES	SHA2 of extracted text — used for change detection after parse
previous_content_hash	VARCHAR	YES	Prior content_hash for diff tracking
created_by	VARCHAR	YES	User who triggered registration
updated_at	TIMESTAMP_NTZ	YES	Timestamp of last row modification

Indexes: Clustered by (source_folder, ingestion_status)

Constraints: PK (registry_id), UNIQUE (file_path, processing_version)

parsed_documents

AI_PARSE_DOCUMENT output — raw text and structure per document version.

Column	Type	Description
parse_id	VARCHAR	UUID PK
file_path	VARCHAR	FK to ingestion_registry
processing_version	INT	FK to ingestion_registry
file_format	VARCHAR	Format from registry
parse_mode	VARCHAR	OCR or LAYOUT
parse_result	VARIANT	Full AI_PARSE_DOCUMENT JSON response
page_count	INT	Total pages in document
raw_content	VARCHAR	Concatenated full text across all pages
parse_status	VARCHAR	PENDING / COMPLETE / FAILED
parse_error	VARCHAR	Error message if failed
parse_started_at	TIMESTAMP_NTZ	Parse start time
parse_completed_at	TIMESTAMP_NTZ	Parse completion time
parse_duration_ms	BIGINT	Elapsed parse time

document_pages

One row per page — optimized for granular Cortex Search retrieval.

Column	Type	Description
page_id	VARCHAR	UUID PK

Column	Type	Description
file_path	VARCHAR	FK to parsed_documents
processing_version	INT	FK to parsed_documents
page_index	INT	0-based page number
page_content	VARCHAR	Text content of this page
total_pages	INT	Total pages in the document
ir_file_id	VARCHAR	Denormalized from registry
source_folder	VARCHAR	Denormalized from registry (for clustering)
ir_policy_number	VARCHAR	Denormalized from registry
ir_claim_number	VARCHAR	Denormalized from registry

`classified_documents`

AI_CLASSIFY output with confidence scoring.

Column	Type	Description
classification_id	VARCHAR	UUID PK
file_path	VARCHAR	FK
processing_version	INT	FK
source_folder	VARCHAR	Denormalized for clustering
ai_classification	VARIANT	Full AI_CLASSIFY JSON response (labels array)
primary_document_type	VARCHAR	Highest-confidence label (first in array)
all_document_types	ARRAY	All returned labels

Column	Type	Description
confidence_score	FLOAT	Estimated confidence (0.95=1 label, 0.50=4+ labels)
ir_document_type	VARCHAR	Native ImageRight type (for comparison)
classification_match	BOOLEAN	TRUE if AI classification matches IR native type
needs_review	BOOLEAN	TRUE if confidence < threshold (default 0.70)
classified_at	TIMESTAMP_NTZ	Classification timestamp

document_attributes

AI_EXTRACT output — specialty insurance key attributes.

Column	Type	Description
attribute_id	VARCHAR	UUID PK
file_path	VARCHAR	FK
processing_version	INT	FK
extracted_attributes	VARIANT	Full AI_EXTRACT JSON response
document_date	DATE	Document creation/issuance date
insured_name	VARCHAR	Named insured or policyholder
policy_number	VARCHAR	Policy or binder number (COALESCE with ir_policy_number)
claim_number	VARCHAR	Claim or loss number
carrier_name	VARCHAR	Insurance company or Lloyd's syndicate
broker_name	VARCHAR	Wholesale broker, MGA, or retail agency

Column	Type	Description
line_of_business	VARCHAR	D&O, E&O, Cyber, EPL, Environmental, etc.
coverage_form	VARCHAR	Claims-Made / Occurrence / Claims-Made-and-Reported
retroactive_date	DATE	Prior acts date for claims-made coverage
effective_date	DATE	Policy inception date
expiration_date	DATE	Policy expiration date
loss_date	DATE	Date of loss or wrongful act
per_occurrence_limit	VARCHAR	Per-claim limit as text (e.g., "\$5,000,000")
aggregate_limit	VARCHAR	Aggregate limit as text
retention_or_deductible	VARCHAR	SIR or deductible as text
monetary_amounts	VARIANT	All financial values as structured JSON
exclusions_noted	VARCHAR	Key exclusions mentioned
action_required	VARCHAR	Next steps, deadlines, notice requirements
doc_status	VARCHAR	bound / quoted / open / closed / denied / settled / in-litigation
doc_summary	VARCHAR	2-3 sentence AI-generated summary
extraction_confidence	FLOAT	Overall extraction quality estimate
low_confidence_fields	ARRAY	Fields where extraction may be unreliable
extracted_at	TIMESTAMP_NTZ	Extraction timestamp

`document_catalog` (Dynamic Table)

Unified view of the latest COMPLETE version of each document, with overrides applied.

Inherits all columns from `document_attributes` + `classified_documents` + `ingestion_registry` + `parsed_documents`. See individual tables above.

Additional columns: | Column | Type | Description | |---|---|---|
`upload_timestamp` | `TIMESTAMP_NTZ` | Alias of `first_seen_at` | | `full_text` | `VARCHAR` | Full extracted text (from `parsed_documents.raw_content`) |

Refresh: `TARGET_LAG` = 1 hour

Row Access Policy: `doc_intel_folder_policy` on `source_folder` column

Schema: TELEMETRY

`pipeline_events`

Central event log — all pipeline and user activity.

Column	Type	Description
<code>event_id</code>	<code>VARCHAR</code>	UUID PK
<code>event_time</code>	<code>TIMESTAMP_NTZ</code>	Event timestamp
<code>event_type</code>	<code>VARCHAR</code>	See event type catalog below
<code>stage_name</code>	<code>VARCHAR</code>	INGEST / PARSE / CLASSIFY / EXTRACT / CATALOG / SEARCH / ANALYST / AGENT / FEEDBACK / OVERRIDE / ADMIN / ALERT
<code>file_path</code>	<code>VARCHAR</code>	Related file (if applicable)
<code>ir_file_id</code>	<code>VARCHAR</code>	ImageRight File ID
<code>source_folder</code>	<code>VARCHAR</code>	Source folder (organizational grouping)

Column	Type	Description
user_name	VARCHAR	Snowflake user who triggered event
warehouse_name	VARCHAR	Warehouse used
status	VARCHAR	SUCCESS / FAILED / SKIPPED / RETRY / QUEUED / TRIGGERED
duration_ms	BIGINT	Elapsed time in milliseconds
error_message	VARCHAR	Error detail if status=FAILED
error_code	VARCHAR	Error code if available
credits_used	FLOAT	Snowflake credits consumed
rows_processed	BIGINT	Rows affected
metadata	VARIANT	Event-specific structured data

agent_audit_log

Full audit trail of all CoWork/agent interactions.

Column	Type	Description
query_id	VARCHAR	UUID PK
query_time	TIMESTAMP_NTZ	Query timestamp
user_name	VARCHAR	Snowflake user
user_role	VARCHAR	Active role at query time
question	VARCHAR	User's question text
tool_used	VARCHAR	SEARCH / ANALYST / BOTH
search_query	VARCHAR	Query sent to Cortex Search
analyst_question	VARCHAR	Question sent to Cortex Analyst
generated_sql	VARCHAR	SQL generated by Cortex Analyst

Column	Type	Description
result_count	INT	Number of results returned
response_text	VARCHAR	Agent response (truncated at 1000 chars)
latency_ms	BIGINT	Total response latency
feedback_score	INT	1=positive, -1=negative, NULL=none
feedback_at	TIMESTAMP_NTZ	When feedback was submitted
session_id	VARCHAR	Chat session UUID

Schema: ADMIN

`system_config`

Key-value configuration store.

Key	Default	Type	Description
max_processing_attempts	3	INTEGER	Retry limit before ABANDONED
search_result_limit	10	INTEGER	Default search result count
classify_confidence_threshold	0.70	FLOAT	Minimum confidence before flagging
pipeline_target_lag_minutes	60	INTEGER	Target document latency in minutes
cost_alert_multiplier	2.0	FLOAT	Alert when daily cost exceeds N× average
queue_backlog_threshold	500	INTEGER	Alert when pending count exceeds this

Key	Default	Type	Description
error_rate_threshold_pct	5	FLOAT	Alert when error rate exceeds this %
enable_pii_masking	true	BOOLEAN	Enable PII masking policies
enable_feedback_collection	true	BOOLEAN	Enable thumbs up/down collection
max_saved_searches_per_user	50	INTEGER	Per-user saved search limit

extraction_overrides

User-submitted attribute corrections.

Column	Description
override_id	UUID PK
file_path	Document the correction applies to
processing_version	Document version
field_name	Attribute being corrected (e.g., <code>insured_name</code>)
original_value	AI-extracted value before correction
corrected_value	Corrected value
override_reason	User's explanation
submitted_by	User who submitted correction
submitted_at	Submission timestamp
approved_by	Admin who approved/rejected
approved_at	Approval timestamp
override_status	PENDING / APPROVED / REJECTED

classification_labels

Document type labels used by AI_CLASSIFY. Managed via Admin → Classification Labels.

Column	Type	Description
label	VARCHAR	PK — document type name (e.g., “Certificate of Insurance”)
category	VARCHAR	Grouping category (e.g., “Compliance”, “Claims”, “Policy”)
sort_order	INT	Display order within category
is_active	BOOLEAN	Whether the label is available for new classifications
created_at	TIMESTAMP_NTZ	When the label was created

lines_of_business

Configurable lines of business. Drives the AI_CLASSIFY LOB detection and filter dropdowns throughout the app.

Column	Type	Description
lob_code	VARCHAR(50)	PK — short code used in match_rules and entitlements (e.g., “DO”, “Cyber”)
lob_name	VARCHAR(200)	Display name used as AI_CLASSIFY label (e.g., “Directors & Officers”)
description	VARCHAR(500)	Human-readable description of the LOB
is_active	BOOLEAN	Whether the LOB is available for new classifications (default TRUE)

Column	Type	Description
sort_order	INT	Display order in dropdowns and tables
created_at	TIMESTAMP_NTZ	When the LOB was created

Seeded values: Cyber, DO, EO, EPL, Environmental, GL, Property, Excess, Marine, WC

extraction_schemas

Extraction attribute definitions used by AI_EXTRACT. Supports tiered schemas (COMMON, CATEGORY, LOB_SPECIFIC).

Column	Type	Description
schema_id	INT	Auto-increment PK
attribute_name	VARCHAR	Field name to extract
attribute_description	VARCHAR	Description passed to AI_EXTRACT prompt
attribute_type	VARCHAR	Expected type: text, date, number, array
schema_tier	VARCHAR	COMMON / CATEGORY / LOB_SPECIFIC
document_type	VARCHAR	Display grouping label
match_rule	VARIANT	JSON filter: <code>{"category": "Claims"}</code> or <code>{"category": "Claims", "lob": "DO"}</code>
sort_order	INT	Order within tier
is_active	BOOLEAN	Whether attribute is extracted

saved_searches

Per-user saved search queries.

Column	Description
search_id	UUID PK

Column	Description
user_name	Snowflake user
search_name	User-given name
query_text	Search query string
filter_state	VARIANT — filter selections (folder, type, LOB, etc.)
result_count	Last known result count
last_run_at	When search was last executed
is_shared	Whether search is shared with team

`search_feedback`

User feedback on search results and agent responses.

Column	Description
feedback_id	UUID PK
user_name	User who submitted feedback
feedback_type	SEARCH_RESULT or AGENT_RESPONSE
query_text	Search query or agent question
file_path	Document (for search result feedback)
agent_query_id	FK to agent_audit_log (for agent feedback)
feedback_score	1=positive, -1=negative
feedback_comment	Optional text comment

Schema: APP (Views)

All views in `DOC_INTEL.APP` expose data from DATA and TELEMETRY schemas with row-level security applied. Users must use APP schema views — direct table access is restricted.

View	Source	Security
v_document_catalog	document_catalog	

View	Source	Security
		Row access policy on source_folder
v_pipeline_health	TELEMETRY.v_pipeline_health	Admin only
v_ingestion_registry	ingestion_registry	Admin only
v_cost_by_folder	TELEMETRY.v_cost_by_folder	Admin only
v_search_analytics	TELEMETRY.v_search_analytics	Admin only
v_quality_metrics	TELEMETRY.v_quality_metrics	Admin only
v_error_summary	TELEMETRY.v_error_summary	Admin only
v_agent_audit_log	agent_audit_log	Anonymized (no response text)

Schema: SERVICES (Cortex AI Services)

document_analytics_sv

Purpose: Semantic view over document_catalog for Cortex Analyst natural language to SQL. Powers the “Ask an Analytics Question” NL box on the Analytics page via the /api/analyst route.

Source: DOC_INTEL.DATA.document_catalog

Access: Granted to DOC_INTEL_USER and DOC_INTEL_ADMIN

Column	Type	Semantic Role	Description
file_path	STRING	DIMENSION	Full path to the source document file on stage
ir_file_id	STRING	DIMENSION	ImageRight File ID — unique identifier in source system
source_folder	STRING	DIMENSION	Source folder: Claims, Underwriting, Reinsurance, Compliance,

Column	Type	Semantic Role	Description
			Correspondence, Accounting, Policies
ir_assigned_to	STRING	DIMENSION	Person assigned in ImageRight workflow
ir_policy_number	STRING	DIMENSION	Policy number from ImageRight UserKey1
ir_claim_number	STRING	DIMENSION	Claim/loss number from ImageRight UserKey2
document_type	STRING	DIMENSION	AI-classified document type (Submission, FNOL, Coverage Opinion, etc.)
file_format	STRING	DIMENSION	Source format: TIFF, PDF, DOCX, JPEG, PNG, HTML, TXT
classification_confidence	FLOAT	MEASURE	AI classification confidence 0–1 (below 0.70 = review recommended)
needs_review	BOOLEAN	DIMENSION	True if confidence below configured threshold
insured_name	STRING	DIMENSION	Named insured or policyholder organization
carrier_name	STRING	DIMENSION	Insurance company or Lloyd's syndicate
broker_name	STRING	DIMENSION	Wholesale broker, MGA, or retail agency

Column	Type	Semantic Role	Description
line_of_business	STRING	DIMENSION	Specialty LOB: D&O, E&O, Cyber, EPL, Environmental, Fiduciary, Professional Liability, Excess/ Umbrella, Marine, Aviation, Surety
coverage_form	STRING	DIMENSION	Coverage trigger: Claims-Made, Occurrence, Claims-Made-and-Reported
document_date	DATE	DIMENSION	Document creation or effective date
retroactive_date	DATE	DIMENSION	Prior acts date for claims-made coverage
effective_date	DATE	DIMENSION	Policy or endorsement effective/inception date
expiration_date	DATE	DIMENSION	Policy or endorsement expiration date
loss_date	DATE	DIMENSION	Date of loss, wrongful act, or incident
per_occurrence_limit	STRING	DIMENSION	Per-claim limit as text (e.g. "\$5,000,000")
aggregate_limit	STRING	DIMENSION	Policy aggregate limit as text (e.g. "\$10,000,000")
retention_or_deductible	STRING	DIMENSION	SIR or deductible as text (e.g. "\$250,000 SIR")

Column	Type	Semantic Role	Description
<code>doc_status</code>	STRING	DIMENSION	Status: bound, quoted, declined, open, closed, reserved, denied, settled, in-litigation
<code>exclusions_noted</code>	STRING	DIMENSION	Key exclusions: prior knowledge, pollution, war, bodily injury, cyber, etc.
<code>action_required</code>	STRING	DIMENSION	Required follow-up actions or deadlines
<code>upload_timestamp</code>	TIMESTAMP	DIMENSION	When the document was first seen in the ingestion stage
<code>page_count</code>	INTEGER	MEASURE	Total pages in the document

Example analytics questions (handled by Cortex Analyst): - “How many D&O claims are open by month this year?” - “What is the breakdown of documents by line of business?” - “Which source folders have the most low-confidence classifications?” - “Show me total claim count by insured sorted by open claims” - “What is the average page count by document type?”