

```
"""
```

```
download_models.py
```

Run this ONCE, with internet access, before starting the API:

```
python download_models.py
```

MediaPipe's Tasks API (the version used by tryon_engine.py) loads its pose-landmarker model from a local .task file rather than bundling it inside the pip package. This script fetches the official model file from Google's public model store and saves it under ./models/.

No customer or saree data is ever sent anywhere by this script or by the API itself – this only downloads a generic, publicly published ML model file (not trained on your data, doesn't touch your data).

```
"""
```

```
import os
import urllib.request
```

```
MODEL_DIR =
os.path.join(os.path.dirname(os.path.abspath
```

```
h(__file__)), "models")
POSE_MODEL_URL = (

"https://storage.googleapis.com/mediapipe-
models/pose_landmarker/"

"pose_landmarker_full/float16/latest/pose_l
andmarker_full.task"
)
POSE_MODEL_PATH = os.path.join(MODEL_DIR,
"pose_landmarker_full.task")

def main():
    os.makedirs(MODEL_DIR, exist_ok=True)

    if os.path.exists(POSE_MODEL_PATH):
        print(f"Already present:
{POSE_MODEL_PATH}")
        return

    print(f"Downloading pose landmarker
model from:\n {POSE_MODEL_URL}")

    urllib.request.urlretrieve(POSE_MODEL_URL,
POSE_MODEL_PATH)
    size_mb =
os.path.getsize(POSE_MODEL_PATH) / (1024 *
1024)
    print(f"Saved to {POSE_MODEL_PATH}
({size_mb:.1f} MB)")
```

```
if __name__ == "__main__":  
    main()
```