

class7: machine learning 1

Ari_Fon (PID: A15390446)

2/8/2022


#clustering methods

Find groups (a.k.a) clusters in my data

##k-means clustering

Make up some data to test with.

```
#make up some data with 2 clear groups  
tmp <- c(rnorm(30, mean= 3), rnorm(30, mean= -3))  
  
x <- cbind(tmp, rev(tmp))  
  
plot(x)
```



The `kmeans()` function does k-means clustering

```

k <- kmeans(x, centers=4, nstart=20)
k

## K-means clustering with 4 clusters of sizes 17, 17, 13, 13
##
## Cluster means:
##      tmp
## 1  2.609879 -3.307485
## 2 -3.307485  2.609879
## 3 -2.396884  3.783276
## 4  3.783276 -2.396884
##
## Clustering vector:
## [1] 4 4 4 4 1 1 1 4 1 1 1 1 1 1 1 4 1 1 1 1 1 4 4 1 4 4 4 1 4 4 3 3 2 3 3 3 2 3
## [39] 3 2 2 2 2 2 3 2 2 2 2 2 2 2 3 2 2 2 3 3 3 3
##
## Within cluster sum of squares by cluster:
## [1] 11.43859 11.43859 16.70071 16.70071
## (between_SS / total_SS =  95.2 %)
##
## Available components:
##
## [1] "cluster"      "centers"      "totss"        "withinss"     "tot.withinss"
## [6] "betweenss"    "size"         "iter"         "ifault"

```

We can use the dollar syntax to get at the results (components of the returned list).

Q1. How many points are in each cluster?

```
k$size
```

```
## [1] 17 17 13 13
```

What component of your result object details -Cluster size -Cluster assignment/membership
-Cluster center?

```
k$size
```

```
## [1] 17 17 13 13
```

```
k$cluster
```

```
## [1] 4 4 4 4 1 1 1 4 1 1 1 1 1 1 1 4 1 1 1 1 1 4 4 1 4 4 4 1 4 4 3 3 2 3 3 3 2 3
## [39] 3 2 2 2 2 2 3 2 2 2 2 2 2 2 3 2 2 2 3 3 3 3

```


```
k$centers
```

```
##      tmp
## 1  2.609879 -3.307485
## 2 -3.307485  2.609879
## 3 -2.396884  3.783276
## 4  3.783276 -2.396884

```

Plot x colored by the kmeans cluster assignment and add cluster centers as blue points

```
plot(x, col= k$cluster)
points(k$centers, col="blue", pch=15, cex=2)
```



Hierarchical Clustering


The `hclust()` function needs a distance matrix as input not our original data. For this we use the `dist()` function

```
hc <- hclust(dist(x))
hc
```

```
##
## Call:
## hclust(d = dist(x))
##
## Cluster method   : complete
## Distance         : euclidean
## Number of objects: 60
```

```
plot(hc)
abline(h=10, col="red")
```

Cluster Dendrogram



To get our cluster membership vector we need to cut our tree and for this we use the `cutree()`

```
cutree(hc, h=10)
```

[illegible]

You can cut by a given height $h=$ or into a given number of k groups with $k=$

```
cutree(hc, k=2)
```

```
## [1] 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 2 2 2 2 2 2 2 2  
## [39] 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
```

#Principal Component Analysis

PCA of UK food data

Let's read our data about the weird stuff folks from the UK eat and drink

```
url <- "https://tinyurl.com/UK-foods"
x <- read.csv(url, row.names=1)
```

Look at the first bit of the file:

```
head(x)
```

```
##           England Wales Scotland N.Ireland
## Cheese           105   103     103       66
## Carcass_meat     245   227     242      267
## Other_meat       685   803     750     586
## Fish             147   160     122       93
## Fats_and_oils    193   235     184     209
## Sugars           156   175     147     139
```


How many columns in this dataset:

```
ncol(x)
```


```
## [1] 4
```

We can make some plots to try to understand this data a bit more. For example barplots:

```
barplot(as.matrix(x))
```



```
barplot(as.matrix(x), beside=TRUE)
```



#PCA to the rescue

The main base R function for PCA is called `prcomp()`. `prcomp()` expects the observations to be rows and the variables to be columns therefore we need to first transpose our data.frame matrix with the `t()` transpose function.

```
pca <- prcomp(t(x))
summary(pca)
```

Importance of components:


##	PC1	PC2	PC3	PC4
## Standard deviation	324.1502	212.7478	73.87622	5.552e-14
## Proportion of Variance	0.6744	0.2905	0.03503	0.000e+00
## Cumulative Proportion	0.6744	0.9650	1.00000	1.000e+00

What is in this returned pca object?

```
attributes(pca)
```


```
## $names
## [1] "sdev"      "rotation" "center"    "scale"     "x"
##
## $class
## [1] "prcomp"
```

```
plot(pca$x[,1:2], col=c("orange", "red", "blue", "green"), pch=15)
text(pca$x[,1], pca$x[,2], labels=colnames(x))
```



We can look at how the variables contribute to our new PCs by examining the `pca$rotation` component of our results

```
barplot(pca$rotation[,1], las=2)
```



#PCA of RNA-Seq Data example...

Read data first:

```
url2 <- "https://tinyurl.com/expression-CSV"
rna.data <- read.csv(url2, row.names=1)
head(rna.data)
```

```
##      wt1 wt2 wt3 wt4 wt5 ko1 ko2 ko3 ko4 ko5
## gene1 439 458 408 429 420 90 88 86 90 93
## gene2 219 200 204 210 187 427 423 434 433 426
## gene3 1006 989 1030 1017 973 252 237 238 226 210
## gene4 783 792 829 856 760 849 856 835 885 894
## gene5 181 249 204 244 225 277 305 272 270 279
## gene6 460 502 491 491 493 612 594 577 618 638
```

How many genes(how many rows?)

```
nrow(rna.data)
```

```
## [1] 100
```

How many experiments (columns)?


```
ncol(rna.data)
```

```
## [1] 10
```

Let's do PCA of this dataset. First take the transpose as that is what the `prcomp()` function wants...


```
pca <- prcomp( t(rna.data), scale= TRUE)
summary(pca)
```

```
## Importance of components:
```

```
##              PC1      PC2      PC3      PC4      PC5      PC6      PC7
## Standard deviation  9.6237  1.5198  1.05787  1.05203  0.88062  0.82545  0.80111
## Proportion of Variance 0.9262  0.0231  0.01119  0.01107  0.00775  0.00681  0.00642
## Cumulative Proportion 0.9262  0.9493  0.96045  0.97152  0.97928  0.98609  0.99251
##              PC8      PC9      PC10
## Standard deviation  0.62065  0.60342  3.327e-15
## Proportion of Variance 0.00385  0.00364  0.000e+00
## Cumulative Proportion 0.99636  1.00000  1.000e+00
```

We can make our score plot (a.k.a PCA plot) from the `pca$x` .

```
plot(pca$x[,1], pca$x[,2])
```



Make a little color vector to color up our plot by `wt` and `ko`

```
colvec <- c(rep("red",5), rep("blue",5))  
plot(pca$x[,1], pca$x[,2], col= colvec, pch=15)
```

