

Quiz - 2021

1. Information extraction:

- ☐ Necessarily requires training data.
- ☐ Is used to identify characteristic entities in a document.
- ☐ Is always bootstrapped by using ontologies.
- ☒ ~~Can be used to populate ontologies.~~

2. What is **TRUE** regarding Fagin's algorithm?

- ☐ Posting files need to be indexed by TF-IDF weights
- ☐ It performs a complete scan over the posting files
- ☐ It never reads more than $(kn)^{1/2}$ entries from a posting list
- ☒ ~~It provably returns the k documents with the largest aggregate scores~~

3. Which of the following statements on Latent Semantic Indexing (LSI) and Word Embeddings (WE) is false?

- ☐ The dimensions of LSI can be interpreted as concepts, whereas those of WE cannot
- ☐ LSI does not depend on the order of words in the document, whereas WE does
- ☐ LSI is deterministic (given the dimension), whereas WE is not
- ☒ ~~LSI does take into account the frequency of words in the documents, whereas WE with negative sampling does not~~

4. When constructing a word embedding, what is **TRUE** regarding negative samples?

- ☒ ~~They are oversampled if less frequent~~
- ☐ Their frequency is decreased down to its logarithm
- ☐ They are words that do not appear as context words
- ☐ They are selected among words that are not stop-words

5. A page that points to all other pages but is not pointed by any other page would have:

- ☐ Nonzero authority
- ☐ Zero hub
- ☒ ~~Nonzero PageRank~~
- ☐ None of the above

6. When computing PageRank iteratively, the computation ends when:

- ☐ The difference among the eigenvalues of two subsequent iterations falls below a predefined threshold

- ☒ ~~The norm of the difference of rank vectors of two subsequent iterations falls below a predefined threshold~~
- ☐ The probability of visiting an unseen node falls below a predefined threshold
- ☐ All nodes of the graph have been visited at least once

7. In Ranked Retrieval, the result at position k is non-relevant and at $k+1$ is relevant. Which of the following is always true?

Hint: $P@k$ and $R@k$ are the precision and recall of the result set consisting of the k top-ranked documents.

- ☐ $P@k-1 > P@k+1$
- ☐ $R@k-1 = R@k+1$
- ☒ ~~$R@k-1 < R@k+1$~~
- ☐ $P@k-1 = P@k+1$

8. Which of the following is **TRUE** regarding community detection?

- ☒ ~~The high betweenness of an edge indicates that the communities are well connected by that edge~~
- ☐ The Girvan-Newman algorithm attempts to maximize the overall betweenness measure of a community graph
- ☐ The high modularity of a community indicates a large difference between the number of edges of the community and the number of edges of a null model
- ☐ The Louvain algorithm attempts to minimize the overall modularity measure of a community graph

9. What is **WRONG** regarding the Transformer model?

- ☒ ~~Its computation cannot be parallelized compared to LSTMs and other sequential models.~~
- ☐ It uses a self-attention mechanism to compute representations of the input and output.
- ☐ Its complexity is quadratic to the input size.
- ☐ It captures the semantic context of the input.

10. In User-Based Collaborative Filtering, which of the following is **TRUE**?

- ☐ Pearson Correlation Coefficient and Cosine Similarity have the same value range and return the same similarity ranking for the users.
- ☒ ~~Pearson Correlation Coefficient and Cosine Similarity have different value ranges and can return different similarity rankings for the users~~
- ☐ Pearson Correlation Coefficient and Cosine Similarity have different value ranges, but return the same similarity ranking for the users
- ☐ Pearson Correlation Coefficient and Cosine Similarity have the same value range but can return different similarity rankings for the users

11. Which of the following is **TRUE** for Recommender Systems (RS)?

- ☐ The complexity of the Content-based RS depends on the number of users
- ☐ Item-based RS need not only the ratings but also the item features
- ☐ Matrix Factorization is typically robust to the cold-start problem.
- ☒ ~~Matrix Factorization can predict a score for any user-item combination in the dataset.~~

12. Considering the transaction below, which one is **WRONG**?

Transaction ID	Items Bought
1	Tea
2	Tea, Yoghurt
3	Tea, Yoghurt, Kebap
4	Kebap
5	Tea, Kebap

- ☐ {Yoghurt} \rightarrow {Kebab} has 50% confidence
- ☐ {Yoghurt, Kebap} has 20% support
- ☐ {Tea} has the highest support
- ☒ ~~{Yoghurt} has the lowest support among all itemsets~~

13. Suppose that in a given FP Tree, an item in a leaf node N exists in every path. Which of the following is **TRUE**?

- ☐ N co-occurs with its prefixes in every transaction
- ☐ For every node P that is a parent of N in the FP tree, confidence $(P \rightarrow N) = 1$
- ☒ ~~{N}'s minimum possible support is equal to the number of paths~~
- ☐ The item N exists in every candidate set

14. Which of the following properties is part of the RDF Schema Language?

- ☐ Description
- ☐ Type
- ☐ Predicate
- ☒ ~~Domain~~

15. Which of the following is wrong regarding Ontologies?

- ☐ We can create more than one ontology that conceptualizes the same real-world entities
- ☐ Ontologies help in the integration of data expressed in different models
- ☒ ~~Ontologies dictate how semi-structured data are serialized~~
- ☐ Ontologies support domain-specific vocabularies