Prompts used:

im building a chess game in java and i need the piece classes. can you write an abstract Sprite parent class plus all six subclasses king queen rook bishop knight pawn each as its own file. Sprite should have an abstract method canMoveTo(int toRow, int toCol, Sprite[][] board) that each subclass implements with its own movement rules plus a getSymbol() that returns a single char like K or P and a concrete getImageFileName() in the parent that builds names like wK.png or bP.png from the color and symbol so i dont have to repeat that in every subclass. add a pathClear(int toRow, int toCol, Sprite[][] board) helper in the parent that checks the squares strictly between the from and to squares so captures still work. important board setup its a Sprite[][] indexed [row][col] white is at the bottom and moves toward row 0 black is at the top and moves toward row 7 please dont flip this. for the pawn specifically direction is -1 for white and +1 for black two square first move is only allowed from the starting row and only when both squares are empty and pawns capture diagonally one square forward only. canMoveTo must be pure no mutation. dont put check detection pin detection or turn logic in the Sprite hierarchy.

The program is currently very slow, how could I make it faster? Use only explore agents, and then make a plan for editor agents.

write a java swing JPanel that draws an 8x8 chessboard with alternating light and dark squares using Graphics2D
given a Sprite[][] board where each piece has a getImageFileName() like wK.png load each png from an /assets folder and draw it centered on its square. cache the images in a HashMap so they dont reload every repaint
add a simple piece animation when a piece moves interpolate its pixel position over about 200 ms using a Swing Timer and repaint each tick. only update the board after the animation finishes
highlight the selected square yellow and all legal target squares green by calling canMoveTo on every square

Reflection

I corrected Ai's asset filename parsing, because sometimes it would daydream filenames and I had to fix string concatonation. I also had to adjust a lot of coordinates as not everything was fully centered.

Computer science knowledge helped me tell the Ai more technical things that were specific enough for it to not need to imagine that much. AI is bad at imagining, and if I do that part for it, it can focus on creating, and make a better program.