

Day 3: Lisp I

Sunday, February 14, 2021 4:01 PM

- Why learn Lisp?
 - Breadth of CS education (very different types of language)
 - Used for this class
 - Lingua Franca of AI
 - So you know what's missing in other languages.
- History of Lisp
 - John McCarthy implemented a list processing language based on Lambda Calculus (universal equivalent to Turing machines)
 - Lots of variant diversion, then merged back into Common Lisp (de facto implementation: Steel Bank Common Lisp)
 - Scheme is a very simplified version of lisp for teaching. Has many fewer features than Lisp
- Lisp high-level
 - Usually interpreted, but also compilable
 - Conducive to bottom-up design
 - Symbols are first-class objects, as are functions
 - Heavy use of lists, built on pointers
 - Lots of parens, no operator precedence
- In Lisp, programs and data are both just lists, so programs can easily manipulate themselves.
 - He thinks that AI will eventually be built with self-modifying code, which is easy in lisp.
- In Lisp:
 - Memory is not a vector, it's a bag of "Cons Cells" or "pairs", which are pairs of pointers.
 - Symbols are unique, stored in a "symbol table" (hashmap) that points to functions/variables
 - Garbage collected
 - A million built in types
- Symbols
 - First-class objects
 - Unique by value, not identity ("john" !== "john", but JOHN === JOHN)
 - All caps/case insensitive
 - Symbols are self-evaluating: typing a symbol inherently accesses its value
- Selection of things he mentions about lisp that aren't obvious:
 - Math predicates (zerop = is it 0, plusp = is it positive, etc.)
 - Bitwise: logand, logior, logxor, etc.
- Normally, evaluator evaluates arguments then passes to functions. For a few special forms, it doesn't evaluate them before passing them to the compiler.
 - Special forms: quote, defvar, setf, if, defun, etc.
- DEFVAR: defines a global variable
 - Convention is to put asterixes before/after to indicate a global variable
 - Doesn't reassign if the variable already exists
 - Defparameter always reassigns
 - Defconstant is a constant
- DEFUN: (DEFUN add (a, b) (+ a b))
- CONS: takes exactly two things (any two things) and puts them into a data structure

together

- (CONS a b) or (a . b)
- CONS Cells are implemented as two pointers to any datatype (a value or another cell).
- Access a with CAR and b with CDR (ex. (CDR (a . b)))
- Lists in Lisp are either NIL or (something . NIL) (ie. Right branching trees that ends in nil). This definition can be applied recursively.
 - EX: (A . (B . NIL)) prints (A B)
 - (1 2 3) is internally (1 . (2 . (3 . NIL)))
- S-Expressions
 - Everything is an S-expression
 - S-expressions are atoms or lists
 - Atoms: a symbol, all uppercase
 - Lists: a cell with a CAR and CDR, which branches right to NIL
- Lists can be constructed manually or with a call to `list`
- Cells are powerful
 - Caaar = Car car car, etc.
- PROG1: run a series of expressions and return the value of the last one (PROG1 returns the value of the first one, PROG2 the second)
- COND: basically if/else if/else if/else



Day 3

LISP 101

Why do you have to learn it?

- Breadth of CS education
- I use LISP to demonstrate AI programs
- Lingua Franca of AI
- So you know what's missing in other languages
 - But other languages now have garbage collection, first-class objects, funargs, etc.
 - WELL, YOU CAN DO YOUR HOMEWORK IN PYTHON IF YOU REALLY HAVE TO....

History of Lisp

- John McCarthy implemented list processing language based on Church's lambda calculus
 - lambda calculus is universal (equiv to Turing machine in power)
- Lisp 1.5 (invention of the upgrade)
- MacLisp (MIT lab version)
- Interlisp (Xerox/BBN)
- Franz Liszt (Berkeley version)
- Lisp Machine Incorporated (Special graphic workstations; Xerox Interlisp-D)

The difference between Scheme and Lisp

- Scheme is a Pedagogical Language with minimal elements
 - used for MIT's old intro to computer science, and our CS 121b
- Lisp is a production language with every abstraction known to mankind built-in

Lisp Top View

- Interpreter rather than compiler
 - BUT INCLUDES A COMPILER!
- Interactive
- Bottom-up design
- First class symbols and functions
- Flexible List structures
- Lots of Parentheses

The cool part

- In most languages, your SOURCE code is an editable text file, and after compiling away all the symbolic human-readable parts, the object is a binary file.
- In lisp, the programs are lists made of symbols, so you can write programs which manipulate other programs.

Basic Ideas

- Memory is not a vector, but a bag of "Cons Cells" or "pairs"
- Symbols are unique and internalized in a "symbol table" pointing to functions and variable data structures.
- When symbol values are changed, a "garbage collector" finds disconnected cells and makes them ready for reuse.

Symbols are not "Strings"

- "john" and "john" might be character-by-character equal, but do not reside in same memory location.
- JOHN in lisp is hashed and has a unique place in a "symbol table" indicating its value and/or associated function.
- We will focus mainly on symbols and numbers in lists, but there is more!

Symbols are used as variables

- (setf JOHN 27)
- JOHN -> 27
- (setf JOHN 'ARCHITECT)
- JOHN -> ARCHITECT
- (SETF LST '(1 2 3 4 5))
- LST -> (1 2 3 4 5)

Built-in Type Specifiers

- array, atom, bignum, bit, bit-vector, character, common, compiled-function, complex, cons, double-float, fixnum, float, function, **hash-table**, integer, keyword, list, long-float, nil, null, number, package, pathname, random-state, ratio, rational, readtable, sequence, short-float, simple-array, simple-bit-vector, simple-string, simple-vector, single-float, standard-char, stream, string, string-char, symbol, t, vector

—Plus, you can define your own datatypes easily with defstruct!

Read-Eval-Print Loop (REPL)

- loop
 - read in an expression from the console;
 - evaluate the expression;
 - print the result of evaluation to the console;
- end loop.

Hierarchical Evaluation

- i. Strings/Numbers: Themselves
- ii. Symbols: Value of variable or function
 - T and NIL shouldn't be redefined!
- iii. Lists: **First entry is a function name**, to be applied to evaluated arguments
 - (function arg arg)
 - (+ 3 (* 5 4))
 - (* (+ a b)(+ c d))

RECURSIVE Evaluation

- in list evaluation, first element function is applied to EVALUATED arguments:
- $(* (+ a b) (+ c d))$
- $*$ is applied to its arguments
 - $(+ a b)$ and $(+ c d)$
 - to evaluate $(+ a b)$, $+$ is applied to value of a and value of b
 - to evaluate $(+ c d)$, $+$ is applied to value of c and value of d
- then $*$ is applied

Numbers eval to themselves

- Lisp number are just symbols which evaluate to themselves
- Lisp introduced "bignums" for doing number theory etc.
- 298745379862873098743982984786432
- Other radixes
 - $\#2r1001 == 9$
 - $\#16r1a = 26$
- Rationals (both num and denom kept)
- Complex Numbers

Math Functions

- predicates: zero? plus? minus? odd? even?
- Comparisons: = /< > <= >=
- arithmetic: + - * / mod rem floor
- Bitwise: Logand logior logxor etc
- Trig: sin cos tan etc.

List Calculation is PREFIX

- PREFIX notation for calculation
- (1 * 3 + 2 * 4) NOT!
- (+ (* 1 3) (* 2 4)) YUP!
- The evaluator reads the expression sees that + is not a special form
 - evals the arguments (recursively if necessary)
 - First is (* 1 3)
 - Now eval the arguments for *
 - second is (* 2 4)
 - Finally (+ 3 8) -> 11

Regular vs. Special Forms

- for 95% of functions, evaluator first evaluates arguments then passes values to functions
- 5% of functions are "special forms" where the arguments are not evaluated first.

The first Special Form: QUOTE

- how can we type in a symbol?
 - `john` -> 5 we get its value.
- `(QUOTE john)` -> `john` the symbol
- quote has a special "character macro"
 - `'(1 2 3)` expands to `(QUOTE (1 2 3))`
 - which returns the list `(1 2 3)`
- What happens if you type `(1 2 3)`?

Special Forms

- (quote john) also 'john
- (defvar john 25)
- (setf john 9)
- (if T (print 'hello)(FIB 1000))
 - you don't want to eval both branches.
- If and other conditionals have to be special forms because only one of its branches gets evaluated.
- DEFUN is a special form

DEFVAR, DEFPARAMETER, DEFCONST

- ▶ (DEFVAR *NAME* (VALUE EXPRESSION))
- ▶ DEFVAR DECLARES A "SPECIAL" (GLOBAL) VARIABLE
 - ▶ USUALLY *NAME* TO SET IT APART
 - ▶ DOES NOT EVAL ASSIGN IF *NAME* ALREADY HAS VALUE
 - ▶ This means if you change value and reload file it doesn't reset
- ▶ DEFPARAMETER always evaluates the assignment
- ▶ DEFCONSTANT tells compiler the variable won't change

IF is a Special Form

- T and NIL are used for True and False
- IF is a special form so both branches aren't evaluated:
- (if T (print 'hello)(FIB 1000))
 - you don't want to eval both branches.
- If and other conditionals have to be special forms because only one of its branches gets evaluated.

Defining a new function

- (DEFUN name (args) body)
 - arguments include &optional &key &aux &rest
- DEFUN is a special form which binds the f-value of a symbol
- (DEFUN square (x)(* x x))
- Lisp is EXTENSIBLE, now square is no different from built-in functions

CONS

- Definition of basic "compound" data structure:
- (setf something (cons a b))
- (car something) -> value of a
- (cdr something) -> value of b
 - CAR and CDR are historic names
 - contents of address register
 - contents of data register

(Anything . Anything)

- A cell is a tree composed of 2 things.
- A list is either NIL or (thing . NIL)
 - a right-branching tree ending in NIL prints flat:
(A . (B . NIL)) prints (A B)
 - (1 2 3) is really (1 . (2 . (3 . NIL))), OK?
- Lists of lists:
- ((john . male)(mary . female)) is
- ((john . male) . ((mary . female) . NIL))
- More below...

How is CONS implemented?

- Need to know?
- Basic unit is called a "CONS CELL"
- CELL contains Two pointers to addresses of any other datatype
- Addresses point to other CELLS or to distinctive places in memory holding numbers or symbols.

S-EXPRESSIONS

- ▶ In Lisp, everything is an S-expression
- ▶ An S-expression is an atom or a list
- ▶ You can think of these as using two different kinds of storage locations—one kind for atoms, another kind for the parts of a list
 - ▶ This is an oversimplification, but it will do for now

ATOMS

- ▶ An atom is a simple thing, and we draw it in a simple way:



- ▶ Sometimes we don't bother with the boxes:

HELLO ABC NIL

LISTS

- ▶ A list has two parts: a CAR and a CDR
- ▶ We draw this as a box, called a **cons cell**, with two compartments, called the **car field** and the **cdr field**




- ▶ In each of these compartments we put an arrow pointing to its respective value:



EXAMPLE I




EXAMPLE II




EXAMPLE III

((A) B)



EXAMPLE IV

((A B) (C D))



DOTTED PAIRS

- ▶ In a simple list, every right-pointing arrow points to a cons cell or to NIL
- ▶ If a right-pointing arrow points to an atom, we have a **dotted pair**

(A . B)




LISP LISTS ARE IMPLEMENTED WITH DOTTED PAIRS

(A) =  = (A . NIL)

- ▶ Therefore, (A) = (A . NIL)
- ▶ All structures in Lisp can be created from atoms and dotted pairs

EXAMPLE V

$((A . B) . (C . D))$



Basic for building lists

- $(\text{cons } 1 \ 2) \rightarrow (1 . 2)$
- $(\text{cons } 1 \ \text{nil}) \rightarrow (1)$
- $(\text{cons } 1 \ (\text{cons } 2 \ \text{nil})) \rightarrow (1 \ 2)$
- $(\text{cons } (\text{cons } 1 \ 2) \ (\text{cons } 3 \ \text{nil})) \rightarrow$
- $((1 \ 2) \ 3)$
- $(\text{list } 1 \ 2 \ 3) \rightarrow$
- $(\text{cons } 1 \ (\text{cons } 2 \ (\text{cons } 3 \ \text{nil}))) \rightarrow$
- $(1 \ 2 \ 3)$

Cons is powerful gizmo!

- Can construct arbitrarily complex data forms
- CAR and CDR can be used to access them
 - CAAR CADAR CDDDR down 4 levels
 - This is not great form anymore
 - Use First, Second, Third, fourth for
 - Car Cadr Caddr Caddr
 - Beware of "Last"

Lists

- A list is a right-branching tree terminating in NIL.
- the LIST function is a super-CONS:
 - (list 1) -> (cons 1 nil) -> (1)
 - (list 1 2 3 4) --> (1 2 3 4)
 - (list 'john (list 'loves 'mary)) ->
 - (john (loves Mary))
 - (list 1 2 3 'a 'b 'c "foobar")

What can be done with lists?

- (length list)
- (reverse list)
- (append list1 list2)
- (NTH i list)
- (SUBST new old tree)
- (member item list)
- (sort list #'<)

FUNCTIONS ON LISTS

- ▶ CAR, CDR, FIRST, REST, SECOND, THIRD, NTH, NTHCDR, LAST, BUTLAST
- ▶ UNION, INTERSECTION, SET-DIFFERENCE, SUBSETP, MEMBER
- ▶ LENGTH, REVERSE

Flow Control in Lisp

- (IF (Predicate) (then expression))
- (IF (predicate) (then expr)(else expr))
- (AND (exp1)(exp2)(exp3)...) Stops at first NIL
- (OR (exp1)(exp2)(exp3)...) Returns first NON-NIL
- (Null exp) Test for NIL

More control

- (PROGN (exp1)(exp2)(exp3)...) a sequence construct returns val of exp3
- (COND ((pred1)(exp1) (exp2)...) ((pred2)(exp2)...) (T NIL))
- PROG1 and PROG2 return the first and second result from a sequence