## DMD HW4 - SQL Queries

## Nikolay Troshkov

## September 2015

I configured a PostgreSQL database with some test data. In order to avoid quotes in my queries, I changed tables and columns names from CamelCase to underscore\_syntax. That's why they differ from the ones used in assignment PDF. I hope this is not an issue.

```
1
```

```
SELECT movie_name
FROM movies
WHERE NOT EXISTS (
    SELECT *
   FROM movie_supplier
      LEFT JOIN suppliers
        ON movie_supplier.supplier_id = suppliers.supplier_Id
   WHERE supplier_name IN ('PIXAR', 'LOINSGATE')
   AND movie_supplier.movie_id = movies.movie_id
);
2
SELECT movie_name
FROM movies, inventory
WHERE movies.movie_id = inventory.movie_id
AND tape_id IN (
  SELECT tape_id
 FROM rentals
 WHERE duration = (
    SELECT MAX (duration)
   FROM rentals
);
```

```
SELECT supplier_name
FROM suppliers
WHERE suppliers.supplier_id NOT IN (
  SELECT ms. supplier_id
  FROM movie_supplier AS ms, inventory AS i
  WHERE NOT EXISTS (
      SELECT *
      \label{eq:from_inventory} \textbf{FROM} \ \text{inventory} \ , \ \ \text{movie\_supplier}
      WHERE movie_supplier.movie_id = inventory.movie_id
      AND movie_supplier.supplier_id = ms.supplier_id
      AND inventory.movie_id = i.movie_id
);
4
SELECT
  suppliers.supplier_name,
  COUNT(inventory.movie_id)
FROM suppliers
  LEFT OUTER JOIN (
      inventory
      LEFT JOIN movie_supplier
        ON inventory.movie_id = movie_supplier.movie_id
    ON suppliers.supplier_id = movie_supplier.supplier_id
GROUP BY suppliers.supplier_name;
5
SELECT DISTINCT movie_name
FROM movies, orders
WHERE movies.movie_id = orders.movie_id
AND (
      SELECT SUM(copies)
      FROM orders
      WHERE movie_id = movies.movie_id
      GROUP BY movie_id
    ) > 4;
```

```
SELECT *
FROM customers, rentals
WHERE customers.cust_id = rentals.customer_id
      AND (
        rentals.tape_id IN (
          SELECT inventory.tape_id
          FROM inventory, movie_supplier
          WHERE inventory.movie_id = movie_supplier.movie_id
                AND movie_supplier.supplier_id IN (
            SELECT supplier_id
            FROM suppliers
            WHERE supplier_name = 'VWS_Video'
          )
        OR rentals.tape_id IN (
          SELECT inventory.tape_id
          FROM inventory, movies
          WHERE inventory.movie_id = movies.movie_id
                AND movies.movie_name = 'Fatal_Attraction_1987'
        )
      );
7
SELECT
  movies.movie_name,
  COUNT(movies.movie_name)
FROM movies
  LEFT JOIN inventory
    ON movies.movie_id = inventory.movie_id
GROUP BY movies.movie_name
HAVING COUNT(movies.movie_name) > 1;
8
SELECT
  first_name,
  last_name
FROM customers
  LEFT JOIN rentals
    ON customers.cust_id = rentals.customer_id
WHERE rentals.duration > INTERVAL '5 days';
```

```
9
```

```
SELECT supplier_name
FROM suppliers
  LEFT JOIN movie_supplier
    ON suppliers.supplier_id = movie_supplier.supplier_id
WHERE movie_supplier.movie_id = (
  SELECT movie_id
  FROM movies
  WHERE movie_name = 'Almost_Angels_1962'
AND movie_supplier.price = (
  SELECT MIN(price)
  FROM movie_supplier
  WHERE movie_id = (
    \textbf{SELECT} \ movie\_id
    FROM movies
    WHERE movie_name = 'Almost_Angels_1962'
  )
);
10
SELECT movie_name
FROM movies
WHERE movie_id NOT IN (
  SELECT movie_id
  FROM inventory
);
```