Entity–Relationship Model

Database Design

Database Abstraction Layers

1. Conceptual Model
2. Logical Model
3. Physical Database Design

Database design



Book of Duty

- **Describe information requirements (Entities)**
  - Objects used (e.g., student, professor, lecture)
  - Domains of attributes of objects
  - Identifiers, references / relationships
- Describe processes (relations)
  - E.g., examination, degree, register course
- Describe processing requirements (constraints)
  - Cardinalities: how many students?
  - Distributions: skew of lecture attendance
  - Workload: how often a process is carried out
  - Priorities and service level agreements

Entity/Relationship (ER) Models

- Entity
- Relationship
- Attribute
- Key
- Role

Entity/Relationship (ER) Models

- Entity
- Relationship
- Attribute
- Key
- Role



Entity/Relationship (ER) Models

- Entity
- Relationship
- Attribute
- Key
- Role



University


requires
prerequisite
follow-up
StuID
Name
Semester
Student
attends
Lecture
LecID
CP
Title
Grade
tests
gives
ResID
Name
Area
Researcher
works-with
Professor
Level
Room
ProfID
Name

Natural Language Version

- Students have a StuID, Name and Semester. The StuID identifies a student uniquely.
- Lectures have a LecID, CP and Title. The LecID identifies a lecture uniquely.
- Professors have a ProfID, Name, Level and Room. The ProfID identifies a professor uniquely.
- Researchers have a ResD, Name and (research) Area. The AssiID identifies an assistent uniquely.
- Students attend lectures.
- Lectures can be prerequisites for other lectures.
- Professors give lectures.
- Researchers work with professors.
- Students are tested by professors about lectures. Students receive grades as part of these tests.
- Is this the only possible interpretation?

Why ER?

- Advantages
  - ER diagrams are easy to create
  - ER diagrams are easy to edit
  - ER diagrams are easy to read (from the layman)
  - ER diagrams express all information requirements
- Other aspects
  - Minimality
  - Tools (e.g., Visio)
  - Graphical representation
- General
  - Try to be concise, complete, comprehensible, and correct
  - *Controversy whether ER/UML is useful in practice?*
  - No controversy that everybody needs to learn ER/UML

Functionalities

$$R \subseteq E_1 \times E_2$$



Functionalities of n-ary relationships



$$R : E_1 \text{ x } \ldots \text{ x } E_{k\text{-}1} \text{ x } E_{k+1} \text{ x } \ldots \text{ x } E_n \rightarrow E_k$$

Example: *seminar*



supervise : Professor ✗ Student → Topic

supervise : Topic ✗ Student → Professor

Constraints

The following is not possible:

1. Students may only do at most one seminar with a prof.
2. Students may only work on a topic at most once.

The following is possible:

Profs may recycle topics and assign the same topic to several students.

Example



Dashed lines represent illegal references

Functionalities



Two Binary vs. One Ternary Relat.

- A thief steals a painting as part of a theft.

  Model as two binary relationships

  Model as one ternary relationship

  What is better?

ER: Rules of thumb

- Attribute vs. Entity
  - Entity if the concept has more than one relationship
  - Attribute if the concept has only one 1:1 relationship
- Partitioning of ER Models
  - Most realistic models are larger than a page
  - Partition by domains (library, research, finances, ...)
- Good vs. Bad models
  - Do not model redundancy or tricks to improve performance
  - Less entities is better (the fewer, the better!)
  - Remember the C4 rule. (concise, correct, complete, compr.)

(min, max)-Notation



$$R \subseteq E_1 \text{ x } \ldots \text{ x } E_i \text{ x } \ldots \text{ x } E_n$$

For all $e_i \in E_i$:

- At least min_i records $(\ldots, e_i, \ldots)$ exist in R AND
- At most max_i records $(\ldots, e_i, \ldots)$ exist in R

Geometric Modelling





Geometric Modelling







Weak Entities



The existince of room depends on the existence of the associated building.

Why must such relationships be N:1 (or 1:1)?

RoomNr is only unique within a building.

Key of a room: BldNr **and** RoomNr

Exams depend on the student



Can the existence of an entity depend on several other entities? (E.g., exam on student and prof?)

Corner Case 1

- A human cannot exist without a heart.
- A heart cannot exist without a human.
- Anne lives on Bob‘s heart. Bob lives on Anne‘s heart. Possible?
- Heart transplantation – possible?

ER describes possible worlds and their rules

ER does not describe legal transitions!

Corner Case 2

- A human can only survive with ***at least one*** kidney.
- A relationship can only survive with ***all*** its entities.
- **Not expressible with ER!** (Why not?)



Why is this a bad model?



Why is this example so itchy?

- Is the following "instance" legal?



% engages in relationship with Lecture via requires

Answer: Yes!

When "requires" dies, "%" dies, too

When "lecture" dies, "%" dies, too

but, not cleanly modelled – transitivity of weakness

N.B. weakness of "Relationship" cannot be modelled!!!

Why is this example so itchy?

- Is the following "instance" legal?



Answer: Yes!
when "R" dies, "A" dies, too
when "E" dies, "A" dies, too
no way to model that it is an "**either or**" relationship
yet another weakness of ER (lack of negation)

Solution

- Model attributes as two weak entities

  attributes of relationships

  attributes of entities

- (Give up on relationships as weak entities)
- Not perfect because redundant

  but the pricest way to model ER as ER