JDBC - CREATE DATABASE EXAMPLE

http://www.tutorialspoint.com/jdbc/jdbc-create-database.htm

Copyright © tutorialspoint.com

This tutorial provides an example on how to create a Database using JDBC application. Before executing the following example, make sure you have the following in place —

- You should have admin privilege to create a database in the given schema. To execute the following example, you need to replace the *username* and *password* with your actual user name and password.
- Your MySQL or whatever database you are using, is up and running.

Required Steps

The following steps are required to create a new Database using JDBC application –

- **Import the packages:** Requires that you include the packages containing the JDBC classes needed for database programming. Most often, using *import java.sql.** will suffice.
- **Register the JDBC driver:** Requires that you initialize a driver so you can open a communications channel with the database.
- **Open a connection:** Requires using the *DriverManager.getConnection* method to create a Connection object, which represents a physical connection with the database server.

To create a new database, you need not give any database name while preparing database URL as mentioned in the below example.

- **Execute a query:** Requires using an object of type Statement for building and submitting an SQL statement to the database.
- **Clean up the environment**. Requires explicitly closing all database resources versus relying on the JVM's garbage collection.

Sample Code

Copy and past the following example in JDBCExample.java, compile and run as follows –

```
//STEP 1. Import required packages
import java.sql.*;
public class JDBCExample {
   // JDBC driver name and database URL
   static final String JDBC_DRIVER = "com.mysql.jdbc.Driver";
   static final String DB_URL = "jdbc:mysql://localhost/";
   // Database credentials
   static final String USER = "username";
   static final String PASS = "password";
   public static void main(String[] args) {
   Connection conn = null;
   Statement stmt = null;
   try{
      //STEP 2: Register JDBC driver
      Class.forName("com.mysql.jdbc.Driver");
      //STEP 3: Open a connection
      System.out.println("Connecting to database...");
      conn = DriverManager.getConnection(DB_URL, USER, PASS);
      //STEP 4: Execute a query
      System.out.println("Creating database...");
      stmt = conn.createStatement();
```

```
String sql = "CREATE DATABASE STUDENTS";
      stmt.executeUpdate(sql);
      System.out.println("Database created successfully...");
   }catch(SQLException se){
      //Handle errors for JDBC
      se.printStackTrace();
   }catch(Exception e){
      //Handle errors for Class.forName
      e.printStackTrace();
   }finally{
      //finally block used to close resources
      try{
         if(stmt!=null)
            stmt.close();
      }catch(SQLException se2){
      }// nothing we can do
      try{
         if(conn!=null)
            conn.close();
      }catch(SQLException se){
         se.printStackTrace();
      }//end finally try
   }//end try
   System.out.println("Goodbye!");
}//end main
}//end JDBCExample
```

Now, let us compile the above example as follows -

```
C:\>javac JDBCExample.java
C:\>
```

When you run **JDBCExample**, it produces the following result –

```
C:\>java JDBCExample
Connecting to database...
Creating database...
Database created successfully...
Goodbye!
C:\>
Loading [MathJax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js
```