Workshop

Building Containerlab with cEOS-lab

How to build a lab environment with Containerlab and cEOS-lab

Petr Ankudinov, 2023



CONTAINERlab

Credits and References

Credits to Roman Dodin and other cLab contributors for making the world a better place!

This repository is based on many awesome open source repositories and some free/commercial Github features:


- Containerlab
- VS Code
- DevContainers
- Marp
- Excalidraw VS Code Plugin
- Github Actions
- Github Pages
- Github Codespaces
- Carbon
- And many more...

All photos are taken from Pexels and Unsplash. Excellent free stock photos resources. It's not possible to reference every author individually, but their work is highly appreciated.

Agenda

- Setup Docker on the host
- Install Containerlab and import cEOS-lab image
- Clone this repository and deploy the lab
- Inspect and destroy the lab
- Deploy the lab with a custom startup config
- Make a packet capture
- cLab in a Container
- Possible caveats

This workshop is a step-by-step guide explaining how to build a lab environment with Containerlab and Arista cEOS-lab. It is focusing on essential and cEOS-lab specific features. Please check Containerlab documentation for details.



Prerequisites

- This workshop requires:
 - Ubuntu LTS 22.04 or later
 - 8 GB RAM and 4 vCPUs
- Only x86 architecture is supported. It is technically possible to run Container lab on ARM, but there are no network images available for ARM as of Aug 2023.
- You can use Github Codespaces or VSCode devcontainer for this workshop. The detailed procedure is described in the appendix.
- The appendix also provides instructions for creating a KVM VM with Ubuntu Cloud Image.
- There is also Vagrant file available in this repository. Use it at your own risk.

Setup Docker on the Host

Check if Docker is already installed. In this case you can skip the steps below.

- 1. Install Docker on the host. The detailed instructions are available here. You can used one-liner script for that.
- 2. Add your user to the docker group.
- 3. Logout and login again to apply the changes.
- 4. Check the Docker version and run hello-world container to test functionality.

```
# install Docker
sudo curl -fsSL https://get.docker.com | sh
# add user to the docker group
sudo usermod -aG docker ${USER}
# test docker
docker --version
docker run hello-world
```

cEOS/cLab Workshop 2023 5

Setup Git (Optional)

- Git must be pre-installed. Otherwise you are in a wrong place. Escape! 👾 🥖
- Setup your name and email address:

```
git config --global user.name "<first-and-2nd-name>"
git config --global user.email "<your-email>"
```

• Check the current configuration:

```
git config --list
```

Clone this Repository

```
$ cd ${HOME}
$ git clone https://github.com/arista-netdevops-community/building-containerlab-with-ceos.git
Cloning into 'building-containerlab-with-ceos'...
remote: Enumerating objects: 198, done.
remote: Counting objects: 100% (198/198), done.
remote: Compressing objects: 100% (120/120), done.
remote: Total 198 (delta 109), reused 152 (delta 66), pack-reused 0
Receiving objects: 100% (198/198), 1.31 MiB | 6.59 MiB/s, done.
Resolving deltas: 100% (109/109), done.
$ ls | grep ceos
building-containerlab-with-ceos
$ cd building-containerlab-with-ceos
```

Download cEOS-lab Image

- 1. Login to Arista Software Download portal. You need to have an account to download the image.
- 2. Select EOS > Active Releases > 4.30 > EOS-4.30.2F > cEOS-lab.
- 3. Download cEOS-lab-4.30.2F.tar.xz image.
- 4. Upload the image to your lab VM. For example, you can use SFTP to transfer the image:

```
sftp ${REMOTE_USER}@${UBUNTU_VM_IP}:/home/${REMOTE_USER}/${IMAGE_DIR} <<< $'put cEOS-lab-4.30.2F.tar*' # for example: # sftp user@10.10.10.11:/home/user/images <<< $'put cEOS-lab-4.30.2F.tar*'
```

NOTE: if you are using Vagrant, add the image to .gitignored directory. It will be automatically copied to the VM.

If Github Codespace is used and token is set, the image will be pulled from arista.com automatically.



□ Active Releases



□ **EOS-4.30.2F**

■ ■ vEOS-lab

□ Docs

cEOS-lab-4.30.2F.tar.xz

cEOS-lab-4.30.2F.tar.xz.json

cEOS-lab-4.30.2F.tar.xz.md5sum

cEOS-lab-4.30.2F.tar.xz.sha512sum

cEOS64-lab-4.30.2F.tar.xz

cEOS64-lab-4.30.2F.tar.xz.json

cEOS64-lab-4.30.2F.tar.xz.md5sum

cEOS64-lab-4.30.2F.tar.xz.sha512sum

Import cEOS-lab Image

1. Go to the directory with the uploaded image and import the image:

```
docker import cEOS-lab-4.30.2F.tar.xz ceos-lab:4.30.2F
```

NOTE: you can also import the image with the tag latest to allow quick "upgrade" of those lab where specific version is not required: docker tag ceos-lab:4.30.2F ceos-lab:latest

2. Confirm that the image was imported successfully:

```
$ docker image ls
REPOSITORY
             TAG
                       IMAGE ID
                                     CREATED
                                                     SIZE
ceos-lab
             4.30.2F
                       21b540a4a343
                                     45 minutes ago 1.95GB
                                     45 minutes ago
ceos-lab
             latest
                       21b540a4a343
                                                     1.95GB
hello-world
             latest
                       b038788ddb22
                                     3 months ago
                                                     9.14kB
```

Install Containerlab

• It's just a one-liner:

```
bash -c "$(curl -sL https://get.containerlab.dev)"
```

• Refer to the Containerlab quick start documentation for the details.


Deploy The Lab

Inspect default_cfg.clab.yml and deploy the lab:

```
sudo containerlab deploy --debug --topo default_cfg.clab.yml
```

 This command will deploy Containerlab with the default EOS configuration provided by Containerlab. The --debug flag is optional, but provides additional information while Containerlab is starting.

NOTE: If there is a single <code>.clab.yml</code> file in the current directory, it is possible to use sudo containerlab deploy command without specifying the topology file. As we have multiple files in the directory, we must specify the topology explicitly.



Inspect the Lab

Once the lab is ready, you'll see a table with the list of deployed containers, their host names and management IPs:

You can call the table again any time with sudo clab inspect -t default_cfg.clab.yml.

Containerlab creates corresponding entries in the /etc/hosts file as well:

```
$ cat /etc/hosts | grep -i clab-
###### CLAB-ceos-lab-START ######
192.168.123.22 clab-ceos-lab-leaf2
192.168.123.11 clab-ceos-lab-spine1
192.168.123.12 clab-ceos-lab-spine2
192.168.123.100 clab-ceos-lab-a_host
192.168.123.21 clab-ceos-lab-leaf1
###### CLAB-ceos-lab-END ######
```

You can also list containers using docker command:

```
$ docker container ls
                                                       CREATED
CONTAINER ID IMAGE
                               COMMAND
                                                                      STATUS
                                                                                     PORTS
                                                                                              NAMES
22464060dcf8 ceos-lab:latest "bash -c '/mnt/flash..."
                                                       5 minutes ago
                                                                      Up 5 minutes
                                                                                              clab-ceos-lab-spine1
                                                                                              clab-ceos-lab-spine2
3f53d1de7add ceos-lab:latest "bash -c '/mnt/flash..."
                                                       5 minutes ago Up 5 minutes
                                                       5 minutes ago Up 5 minutes
                                                                                              clab-ceos-lab-leaf1
a7f7c80aa90f
             ceos-lab:latest "bash -c '/mnt/flash..."
421665f3e67f
             ceos-lab:latest "bash -c '/mnt/flash..."
                                                       5 minutes ago Up 5 minutes
                                                                                              clab-ceos-lab-a host
142ab91f0ceb ceos-lab:latest "bash -c '/mnt/flash..." 5 minutes ago Up 5 minutes
                                                                                              clab-ceos-lab-leaf2
```

Access cEOS-lab CLI

There are few options to access cEOS-lab CLI:

• SSH to the container. For ex.:

```
# the default login is `admin` and password is `admin`
ssh admin@clab-ceos-lab-leaf1
```

• Connect to the "console" using Docker command. For ex.: docker exec -it clab-ceos-lab-leaf1 Cli

NOTE: docker exec -it clab-ceos-lab-leaf1 bash allows to connect directly to the switch shell.

Execute few command to confirm that cEOS-lab is functioning:

- show version
- show lldp neighbors
- show running-config