LE14.1

Bookmark this page

LE14.1.1 Average Memory Access Time

1.0/1.0 point (ungraded)

A particular cache design responds in 1 cycle on a cache hit, but takes an *additional* 20 clock cycles if there's a cache miss. If we want an average memory access time of 2 cycles or better, what is the minimal acceptable cache hit ratio?

minimum acceptable cache hit ratio:

0.95 ✔

Submit

LE14.1.2 Multi-level cache AMAT

1.0/1.0 point (ungraded)

A hierarchical memory system consists of a two-level SRAM cache and a large DRAM main memory. The system first checks the L1 cache. If the access to L1 is a cache miss, the system then checks the L2 cache. If the access to L2 is a cache miss, an access is made to main memory.

For L1: the cache hit time is 1 ns, the hit ratio is 95%

For L2: the cache hit time is 4 ns, the hit ratio is 98%

For main memory: the access time is 40ns

What is the average memory access time in ns?

1.24 ✔

Submit

Discussion

Topic: 14. Caches and the Memory Hierarchy / LE14.1

Hide Discussion

Add a Post

Show all posts — by recent activity

- formula for AMAT — 5
  Hi, The formula for AMAT in the slides is **AMAT = HitTime + MissRatio × MissPenalty**. But in question 1 the formula used seems to...
- LE14.1.1 Average Memory Access Time ,Need More explanation ,kindly help — 3

‹ Previous Next ›

Calculator