



[Course](#)

[Progress](#)

[Dates](#)

[Discussion](#)

[🏠 Course](#) / [17. Virtualizing the Processor](#) / [Lecture Videos \(38:19\)](#)



[< Previous](#)



[Next >](#)

LE17.2 SVC Handlers

[🔖 Bookmark this page](#)

LE17.2.1: Wait SVC Handler

0.0/1.0 point (ungraded)

The WAIT() supervisor call expects the address of a user’s memory location in R0. The WAIT handler examines the value of that memory location and if it’s positive, decrements the value in the memory location by 1 and resumes execution of the user’s program at the instruction following the WAIT() SVC. If the memory location is not positive, the handler should arrange to re-execute the WAIT() SVC next time the user’s program runs and then yield the remainder of the current time slice.

Your goal is to fill in the required code for Wait_h(), the kernel-mode handler for the WAIT SVC. You can use the kernel procedure GetUserLocn(addr) to get the values of a location in the user’s memory and SetUserLocation(addr,v) to set the value of a memory location. The kernel subroutine Scheduler() is also available for your use. Select the correct choice of instructions to include in the **if** and **else** clauses of the Wait_h() stub shown below. Make sure to include all the required instructions. Assume that the selected instructions are executed in the order they appear.

```
Wait_h() {
    int locn = UserMState.Regis[0]; // user location to test
    int value = GetUserLocation(locn); // current value
    if (value > 0) {
        // if clause code

    } else {
        // else clause code

    }
}
```

if clause code (select all that apply):

☐ UserMState.Regis[XP] = UserMState.Regis[XP] - 4;

☐ SetUserLocation(locn,value)

☐ SetUserLocation(locn,value-1)

☐ GetUserLocation(locn)

☐ Scheduler();

else clause code (select all that apply):

☐ UserMState.Regis[XP] = UserMState.Regis[XP] - 4;

☐ SetUserLocation(locn,value)

☐ SetUserLocation(locn,value-1)

☐ GetUserLocation(locn)

☐ Scheduler();

Submit

LE17.2.2: YieldN SVC Handler

0.0/1.0 point (ungraded)

The Yield() SVC can be used in user-mode programs on a time-sharing system to give up the remainder of their current time slice. The kernel implementation of the Yield simply calls the kernel Scheduler() routine to choose another process to execute. When the yielding process is next scheduled, user-mode execution resumes with the instruction following the Yield() SVC.

Complete the code for the handler for a new SVC, YieldN(), which expects a numeric value, N, in the user’s R0 and behaves as if the user program had contained N consecutive Yield() SVCs. When execution resumes following the completion of YieldN(), R0 should contain 0. Select the correct choice of instructions to include in the **if** and **else** clauses of the YieldN_h() stub shown below. Make sure to include all the required instructions. Assume that the selected instructions are executed in the order they appear.

```
YieldN_h() {
    if (UserMState.Reg[0] > 0) {
        // if clause code

    } else {
        // else clause code

    }
}
```

if clause code (select all that apply):

- ☐ UserMState.Reg[0] = UserMState.Reg[0] - 1;
- ☐ UserMState.Reg[0] = UserMState.Reg[0] - N;
- ☐ UserMState.Reg[0] = 0;
- ☐ UserMState.Reg[XP] = UserMState.Reg[XP] - 4;
- ☐ UserMState.Reg[LP] = UserMState.Reg[LP] - 4;
- ☐ YieldN();
- ☐ Scheduler();

else clause code (select all that apply):

- ☐ UserMState.Reg[0] = UserMState.Reg[0] - 1;
- ☐ UserMState.Reg[0] = UserMState.Reg[0] - N;
- ☐ UserMState.Reg[0] = 0;
- ☐ UserMState.Reg[XP] = UserMState.Reg[XP] - 4;
- ☐ UserMState.Reg[LP] = UserMState.Reg[LP] - 4;
- ☐ YieldN();
- ☐ Scheduler();

Submit

 Calculator

Discussion

Hide Discussion

Topic: 17. Virtualizing the Processor / LE17.2 SVC Handlers

Add a Post

Show all posts ▾by recent activity ▾

?

How does wait SVC work?

What's the purpose of >...The WAIT handler examines the value of that memory location and if it's positive, decrements the value in t...

3

✓

[Spoiler] LE17.2.2: YieldN SVC Handler, Zeroing?

Community TA

3

< Previous

Next Up: Worked Examples >
8 min + 1 activity

© All Rights Reserved



edX

- About
- Affiliates
- edX for Business
- Open edX
- Careers
- News

Legal

- Terms of Service & Honor Code
- Privacy Policy
- Accessibility Policy
- Trademark Policy
- Sitemap

Connect

- Blog
- Contact Us
- Help Center
- Media Kit
- Donate



Calculator



© 2021 edX Inc. All rights reserved.
深圳市恒宇博科技有限公司 [粤ICP备17044299号-2](#)