

<u>Help</u>

selfpoised 🗸

<u>Course Progress</u> <u>Dates Course Notes Discussion</u>

★ Course / 1. Basics of Information / Lecture Videos (38:24)

()

< Previous 15 of 20 > Next >

LE1.6

☐ Bookmark this page

LE1.6.1: Huffman Encoding

1/1 point (ungraded)

A Huffman code assigns a 3-bit codeword for message A and a 4-bit codeword for message B. It is known that A and B have different probabilities, and hence carry different amounts of information. Which message carries more information?

More info in:

A

B

Can't tell

Submit

LE1.6.2: Huffman's Algorithm

5/5 points (ungraded)

After spending the afternoon in the dentist's chair, Ben Bitdiddle has invented a new language called AEIOU made up entirely of vowels (the only sounds he could make with someone's hand in his mouth). The AEIOU alphabet consists of the five letters "A", "E", "I", "O", and "U" which occur in messages with the following probabilities:

Letterp(Letter)A0.11E0.25I0.20O0.35U0.09

Use Huffman's algorithm to construct a variable-length code that minimizes the expected number of bits used to encode each letter of a message one-at-a-time.

Please enter the *length* of the variable-length code for each letter.

Length of encoding for A (in bits): 2

Length of encoding for E (in bits): 2

Length of encoding for I (in bits): 2

Length of encoding for O (in bits): 2

Length of encoding for U (in bits): 3


Discussion

Topic: 1. Basics of Information / LE1.6

Hide Discussion

Add a Post

☑ <u>LE1.6.1 Which is the relation between probability and amount of information?</u>



© All Rights Reserved



edX

<u>About</u>

Affiliates

edX for Business

Open edX

Careers

News

Legal

Terms of Service & Honor Code

Privacy Policy

Accessibility Policy

Trademark Policy

<u>Sitemap</u>

Connect

Blog

Contact Us

Help Center

<u>Media Kit</u>

Donate













© 2021 edX Inc. All rights reserved.

深圳市恒宇博科技有限公司 粤ICP备17044299号-2