
Programming Assignment #1 of WI 21 CSE 251B

Fangzhou Ai

Department of Electrical and Computer Engineering
University of California, San Diego
La Jolla, CA 92093
faai@eng.ucsd.edu

Yue Qiao

Department of Electrical and Computer Engineering
University of California, San Diego
La Jolla, CA 92093
yuq021@eng.ucsd.edu

Abstract

This paper is a report for the programming assignment 1 for Lecture CSE 251B.

1 Load and preprocess the data

Load data Data loading could be done by easily calling the given function `load_data()`;

Preprocess data After loading the data, we get a dictionary contains 4 different kinds of cars, the keys are the cars' names and values are a list contains a series of images, we also get a dictionary `cnt` which include how many images we have within each car's category. To turn the data into a more convenient form for training, we did the following things: 1. turn the list into a Numpy array for more fancy matrix operations and 2. we write our own label encoding program to turn each category into a vector (eg. 'Minivan' would be `[0, 1, 0, 0]`).

2 Cross validation procedure

Split the data Notice that ideally we want to split the data in a way that each type of car would evenly distributed within training set, validation set and test set, by looking at our database, we found that each category has almost the same number of pictures (Convertible: 149 # of images, Minivan: 148 # of images, Pickup: 150 # of images, Sedan: 150 # of images), therefore we choose to split each set into k parts then combine them together to form the new data set, in which case we can guarantee that each part would evenly contains all types of cars.

Cross validation To make sure each part would be test set once and validation set once, we maintained an index array `[0, 1, ..., k - 1]`, the first element indicate the index of test set, the second element indicate the index of validation set, the rest elements indicate the training set, after each training procedure, we let each element pump 1 then mod k , so the first time the test set would be the part 0, validation set is part 1, training set is 2 to $k - 1$, the second time the test set would be the part 1, validation set is part 2, training set is `[3, 4, ..., k - 1, 0]`, at the last training procedure the test set would be the part $k - 1$, validation set is part 0, training set is 1 to $k - 2$. Hence each set has been set to test set and validation set once.

Table 1: Mean and std of different set.

Set	Mean	STD
Training	4.65502e-20	0.999999
Validation	-0.00031	0.860112
test	-0.00054	0.833020

3 Principal components analysis

Implement PCA The verified mean and std on each set is shown in table Table 1.

4 Logistic regression

4.1 (a)

The logistic regression code is shown in list Listing 1. We only need one output because we only have 2 categories, if we assume the output is the probability of the first category, then the probability for the second one is naturally $1 - p$.

Listing 1: Logistic regression implementation

```

import numpy as np
def simple_logistic_model(w, input):
    ''' logistic model without hidden layer
    Args:
        input, which dimension is  $M * (1 + d)$ , means  $M$  pics
        each pixel number is  $d$ , appended by 1
        w, parameters, dimension of  $d + 1 * 1$ 
    Returns:
        x, dimension of  $M * 1$ 
    '''
    x = np.dot(input, w)
    x = 1 / (1 + np.exp(-x))
    return x

```

4.2 (b)

The loss of the validation set is shown in Fig 1. And the accuracy on test set is around 63.33%, here we have 40 PCA components. Looking at the PCA components (the first 4 are shown in Fig 2), we found that since the objects are not aligned, it's very hard for PCA to get accurate car's shape, thus not able to achieve high accuracy.

4.3 (c)

5 Softmax regression

6 Individual contributions to the project




Figure 1: Cross entropy loss on validation set




Figure 2: First 4 PCA components.