HaanJi: Tenant-Vocabulary Repair, Speculative Tool Execution and Verifiable Consent Receipts for a Hinglish Voice Receptionist

Aritra Hazra, Prabhav Upadhayay, Anuj Uniyal — B.Tech IT (AI), Medi-Caps University · Draft for review, October 2026 · Code and data: github.com/aritra-25hazra/haanji

Abstract — Voice agents for small Indian businesses fail on three specific points: the catalogue words a booking turns on are exactly the words a general recogniser mangles; latency is felt at the turn, not on average; and "the AI booked it" is no record of consent. We present HaanJi, an open-source engine with one mechanism for each. *Bhasha Bridge* indexes a tenant's catalogue by an Indic-aware phonetic key and repairs recogniser output only when the recogniser was unsure *and* the key matches exactly. *Speculative Turn Execution* runs read-only tools from partial transcripts and claims a result only for byte-identical arguments. The *Pramaan Ledger* seals every write into an Ed25519-signed, hash-chained receipt that binds the action to the caller's confirmed words and refuses writes without one. On an ablation over 21 scripted calls in five vertical packs and two languages (five seeds), the bridge reduces catalogue entity error from 32.4% to 0.71% at 30% synthetic noise with no harmful correction, and lifts task success from 78.4% to 92.7%; against Soundex, Metaphone, Double Metaphone, NYSIIS and edit distance alone, with everything else fixed, the key is best on synthetic noise (every pairwise McNemar $p < 0.001$) and within a point of the classics on real recogniser output. Speculation lowers read-turn latency from 286 to 161 ms (p50) at a 46.2% hit rate without changing a transcript. The ledger detects 80/80 single-field mutations, deletion and re-hashed forgery, and accepts zero unconfirmed writes in every configuration. A pilot on synthetic Indian-English speech through Whisper exposed an open confidence gate and harmful corrections, fixed by three stated guards; real recordings and a user study are the next step.

I. Introduction

A neighbourhood clinic answers a fraction of its calls; the callers who get through speak Hinglish and name services, doctors and localities a general-purpose recogniser has never seen. The ingredients for an automated receptionist — streaming recognition, a language model, synthesis — are commodities. What is not is a system a business can *trust to take a booking*: one that hears its own vocabulary, answers without a pause, and can show afterwards what was agreed.

We make three contributions, each small, measured and tested, and one methodological one. (1) **Bhasha Bridge**: a per-tenant phonetic index with a key written for Indian-English phonology and a two-condition correction rule that cannot damage a transcript the recogniser got right. (2) **Speculative Turn Execution**: prediction and early execution of read-only tools from partial transcripts, with purity, argument identity, freshness and invalidation enforced by tests. (3) **Pramaan Ledger**: signed, hash-chained receipts that bind a write to the caller's confirmation and refuse writes without one, verifiable by anyone with the public key. (4) A reproducible harness — four-way ablation, a corruption model independent of the correction layer, classic-key baselines, significance tests — that regenerates every number from a clean checkout with no network.

II. Related Work

Contextual biasing steers end-to-end recognisers towards phrases supplied at request time [Pundak 2018; Zhao 2019] but acts only before the fact and only if the recogniser honours the list; we bias *and* repair. Soundex, Metaphone and Double Metaphone [Russell 1918; Philips 1990, 2000] encode English phonology; Hinglish merges distinctions English keeps (v/w, s/sh, dental/retroflex) and keeps some English merges apart, so we state a small Indic rule set and test it rule by rule. Indian-accented and code-mixed speech is documented as hard for general models [Bali 2014; Javed 2023, 2024; Radford 2023]. Speculating on the likely branch and discarding the work if wrong is the oldest latency trick in architecture [Hennessy & Patterson 2017] and, recently, in decoding [Leviathan 2023; Chen 2023]; we apply it at the dialogue turn with the same correctness argument. Hash chains, Merkle trees and transparency logs [Haber & Stornetta 1991; Merkle 1987; Laurie 2013] with Ed25519 [Bernstein 2012] are standard; what we seal — the confirmation question, the reply, their timing and confidence — and the refusal of unconfirmed writes are not. Explicit confirmation before consequential actions is a long-standing design in spoken dialogue [Bohus & Rudnicky 2005; Skantze 2005].

III. System

One pass through the turn controller is the whole hot path: partial transcripts feed the speculation engine; the final transcript is corrected by Bhasha Bridge, checked by the guardrails, then handed to the dialogue adapter (a

deterministic policy by default; a hosted model behind the same boundary, which cannot write); tool calls claim speculative results or execute; writes are sealed by the ledger; the reply is synthesised, cancellable on barge-in. A *vertical pack* is one YAML file — catalogue, staff, hours, persona, refusals, lexicon seeds, knowledge, scenarios; six packs in three languages (Hinglish, Benglish, Marathinglish) share one engine. The system is deployed (engine, console, WhatsApp webhook, a Twilio media-stream bridge) and the demo runs with mock providers.

A. Bhasha Bridge

The key applies an ordered rule list before encoding: long vowels shorten; v/w, s/sh/z, ch/chh, t/d/th/dh, k/kh/q/c, g/gh, b/bh/p, n/m, l/r merge; h and y drop; a word-initial vowel is bucketed (a dropped initial /h/); vowels after the first position are removed. A span is replaced only when recogniser confidence is below 0.85 *and* its key equals a lexicon key exactly with surface edit distance ≤ 2 (≤ 3 for phrases). Grammar words, the words of the booking dialogue itself, tokens of fewer than four letters and lexicon forms of fewer than four letters are never evidence; the last three guards came from the real-recogniser pilot (§V-D).

B. Speculative Turn Execution

A deterministic predictor with a small logistic scorer proposes a read-only tool from each partial; the engine runs it at once. Only registry-declared read-only tools are speculated; a result is claimed only for byte-identical arguments (predictor and policy share one extractor); results expire after 4 s and are claimed once; any write invalidates everything; at most 2 in flight, 3 per turn. A test asserts the transcript is identical with speculation on and off.

C. Pramaan Ledger

Payload hash = SHA-256 over canonical JSON of the action, its arguments, the confirmation proof (question, reply, timings, confidence), the excerpt, the pack version and the timestamp; chain hash = SHA-256(previous chain hash ‖ payload hash); Ed25519 signature over the chain hash; a signed Merkle root per day published outside the server. `append` raises on a missing proof inside the transaction. Personal fields are encrypted per customer so that erasure (crypto-shredding) leaves the chain valid. Property-based tests cover every mutation, interior deletion and reordering, and state what the chain alone cannot see (truncation), which the anchor catches.

IV. Method

Entity error rate (EER) is the fraction of catalogue entities in what the caller said that the transcript gets wrong; *task success* is reaching the scenario's expected outcome; latency is engine-side in nominal milliseconds under a time-scaled simulation; every correction is classified beneficial, neutral or *harmful*. Noise comes from (i) hand-authored corruptions in the packs' 21 scenarios and (ii) a corruption model written independently of the lexicon that substitutes Indian-English confusions on content words, including words in no lexicon. Experiments: the four-way ablation (full / no speculation / no bridge / neither) on authored scenarios; a transcript-level experiment over 2,097 corrupted sentences per noise level built from every catalogue entity in eight frames; an end-to-end sweep under the same noise; six keyers swapped under identical rules with McNemar's test on paired per-sentence outcomes; a per-rule ablation; eleven ledger attacks; a concurrency ladder; and a pilot through a real recogniser. Five seeds × three repetitions; intervals are 95% t-intervals over seeds.

V. Results

A. Correction

At 30% noise over 2,097 sentences and 2,862 entities, EER falls from 32.4% to 0.71% (97.8% relative) at 98.9% precision; harmful corrections are zero in every seed at every rate (McNemar off vs on: b = 809, c = 0, p < 0.001). End to end, task success rises from 78.4% to 92.7% at 30% noise and from 62.2% to 84.4% at 45%; the Benglish pack gains as much as the Hinglish ones.

Table I. Entity error after correction at 30% noise by keyer (synthetic), and on the 300-utterance real-recogniser pilot.

keyer	synthetic	pilot	harmful (pilot)
edit distance only	1.68%	32.4%	6
exact spelling	32.01%	33.3%	0
Soundex	3.98%	30.6%	0
Metaphone	8.04%	31.5%	0
NYSIIS	3.46%	32.4%	0
Double Metaphone	6.99%	31.1%	0
Bhasha (ours)	0.80%	30.1%	0

Every classic key is worse than ours on synthetic noise (pairwise McNemar p < 0.001). On the pilot the keys are within a point of one another: where the recogniser paraphrases and merges tokens rather than substituting sounds, the key matters less than the safety rule. A per-rule ablation shows three rules carry the synthetic result (k/kh/q/c, v/w, initial h) and eleven are not exercised by the corruption model — a statement about the harness's coverage as much as the key.

B. Speculation

Read-turn p50 falls from 286 to 161 ms (43.8%) and p90 from 374 to 270 ms, at a 46.2% hit rate; no outcome and

no transcript changes. Write turns are never speculated: the booking turn's p90 is 228 ms without speculation and 233 ms with it. With the bridge off the hit rate falls to 21.7%: the predictor derives arguments from the same mangled entities the policy does.

C. Ledger

80/80 single-field mutations across eight fields, a deleted receipt and a re-hashed forgery are detected; zero unconfirmed writes are accepted in any configuration, seed or attack. Property-based tests generate random receipts and mutations with the same result, and record that truncation is caught by the published daily root rather than by the chain.

D. A real recogniser

Synthetic Indian-English speech (three OS voices) through faster-whisper, decoded as English with no hints: WER 89%, EER 33.8% → 30.1% after the guards. Whisper's word probabilities fell below the 0.85 gate for 80% of words, so the bridge's first condition was effectively off and it made 8 harmful corrections (six were *slot* → *Salt*, a fragment of the locality Salt Lake, one sound key away) until three guards were stated; their gain was evaluated on the data that motivated them and is therefore optimistic. The recogniser's dominant errors — paraphrase, translation, merged tokens — are outside what token-level matching can repair; biasing is the lever for those. A corruption model learned from Whisper's output on public rural Hindi telephone speech (Gram Vaani, 110 utterances, WER 80%, 26% of words dropped) and replayed over the benchmark corpus gives the honest range: the bridge removes 28–32% of entity errors under data-shaped noise at over 95% precision and no harmful corrections, against 97% under our own model, which substitutes and never drops.

E. Concurrency and cost

One process answered 5 to 50 concurrent scripted callers with turn p50 under 7 ms, p95 under 187 ms and no errors at 2548 calls per minute; the expected-outcome rate fell from 97% to 70% because sixty callers filled one calendar and the fixed script did not take the offered alternative, which is the calendar working.

VI. Threats to Validity

EER ignores date and number errors (task success does not). The corruption model was written by us; mitigated by corrupting words outside every lexicon, by counting harmful corrections, and now by a model learned from a real recogniser's output. Latencies are engine-side under simulated time; scripted callers do not adapt; five packs and 21 scenarios are a small authored sample; five seeds give honest but wide intervals, and overlapping intervals are read as "not separated".

VII. Conclusion

A voice receptionist for Indian small businesses fails for three specific reasons, and each has a small, inspectable, measured mechanism here. The bridge removes most catalogue entity errors under heavy synthetic noise without harm and beats the classic keys; on a real recogniser's output it needed two more stated rules to stay safe and then helped far less, which sends the next work to recordings rather than to more synthetic noise. Speculation takes a large fraction off read-turn latency with identical transcripts. The ledger makes an unconfirmed booking impossible rather than unlikely, with or without a hosted model in the loop, and survives the right to be forgotten. Everything regenerates from a clean checkout.

References

Bali, K. et al. (2014). "I am borrowing ya mixing?" EMNLP CodeSwitch. · Bernstein, D. J. et al. (2012). High-speed high-security signatures. J. Crypt. Eng. · Bohus, D., Rudnicky, A. (2005). Sorry, I didn't catch that! SIGdial. · Chen, C. et al. (2023). Accelerating LLM decoding with speculative sampling. arXiv:2302.01318. · Haber, S., Stornetta, W. S. (1991). How to time-stamp a digital document. J. Cryptology. · Hennessy, J., Patterson, D. (2017). Computer Architecture, 6e. · Javed, T. et al. (2023). Svarah. Interspeech. · Javed, T. et al. (2024). IndicVoices. ACL Findings. · Laurie, B. et al. (2013). Certificate Transparency. RFC 6962. · Leviathan, Y. et al. (2023). Fast inference via speculative decoding. ICML. · Merkle, R. (1987). A digital signature based on a conventional encryption function. CRYPTO. · Philips, L. (1990, 2000). Metaphone; Double Metaphone. · Pundak, G. et al. (2018). Deep context. SLT. · Radford, A. et al. (2023). Robust speech recognition via large-scale weak supervision. ICML. · Russell, R. C. (1918). US Patent 1,261,167. · Skantze, G. (2005). Exploring human error recovery strategies. Speech Comm. · Zhao, D. et al. (2019). Shallow-fusion end-to-end contextual biasing. Interspeech.