

Row-level security

INTERMEDIATE DAX IN POWER BI



Carl Rosseel
Curriculum Manager

What is row-level security?

Row-level security (RLS) in Power BI can be used to restrict data access for given users:

- Way to restrict data access for the logged in user
- You can define roles and rules with Power BI desktop
- A dashboard could look completely different depending on the person accessing it

What is row-level security?

Row-Level Security (RLS) uses filters to restrict data at the row level

Name	Total Sales	Region
Jenny	48,431	East
Jane	76,528	West
Dwayne	24,167	West
Thomas	52,125	East

Region = East

What is row-level security?

Row-Level Security (RLS) uses filters to restrict data at the row level

Name	Total Sales	Region
Jenny	48,431	East
Jane	76,528	West
Dwayne	24,167	West
Thomas	52,125	East

Region = East


Name	Total Sales	Region
Jenny	48,431	East
Thomas	52,125	East

Use cases of row-level security in Power BI

- Row-level security has multiple use cases:
 - User access requirements based on role (such as sales)
 - Restricting access requirements for a specific user or group of users
 - User wants specific/filtered data presented (such as a customer)


Use cases of row-level security in Power BI

- Row-Level Security has multiple use cases:
 - User access requirements based on role (such as sales)
 - Restricting access requirements for a specific user
 - User wants specific/filtered data presented (such as a customer)
- Switzerland Sales dashboard




Use cases of row-level security in Power BI

- Row-Level Security has multiple use cases:
 - User access requirements based on role (such as sales)
 - **Restricting access requirements for a specific user or group of users**
 - User wants specific/filtered data presented (such as a customer)
- Non sales dashboard



Use cases of row-level security in Power BI

- Row-Level Security has multiple use cases:
 - User access requirements based on role (such as sales)
 - Restricting access requirements for a specific user or group of users
 - **User wants specific/filtered data presented (such as a customer)**
- General Manager



DAX and row-level security

Row-level security utilizes DAX to:

- Provide filtered values at a row level
- Filter on fact or dimension tables
- *Example:* `[Is Salesperson] = True`

Dynamic row-level security

Ensures users only see the information appropriate for their roles

DAX has two main functions to enable this:

- `USERPRINCIPALNAME()`
 - Returns the user principal name (UPN), which is equal to the email address
 - Gives the same result in Power BI Desktop and Power BI Service
 - Preferred method
- `USERNAME()`
 - Alternative method to enable RLS with its own use cases
 - Outside the scope of this course

You can use these functions to create **personalized dashboards!**

Let's secure it!

INTERMEDIATE DAX IN POWER BI

Managed roles in Power BI

INTERMEDIATE DAX IN POWER BI



Carl Rosseel
Curriculum Manager

Let's practice!

INTERMEDIATE DAX IN POWER BI