Reviewer report: home-assistant-libs/pychromecast#1300: Expose multizone playback session info

Run `pychromecast-1300`, tested 2026-10-21 19:55 IST by ops/daily_run.py (route source-pair). Proof-of-Change commit `02a68eea38919fef2e1b537c3bf5a64bd7c771b5`. Report generated 2026-10-21 20:04 IST by reports/pr_report.py.

Baseline: **full** (test comparison + claim probes + coverage gate + claim flagging (differential probes shown, informational)).

NEEDS ATTENTION

Recommended action: **Reject** Confidence: **Medium**

The run is trustworthy and found a difference a person should look at. Some checks gave warnings: Probes ran on both sides; Every claim cites a real log line

Advice only: Proof-of-Change never blocks a merge and never posts on GitHub.

Summary in plain English

- **What it says it does:** Expose multizone playback session info (home-assistant-libs/pychromecast#1300).
- **What we observed:** probe: 3 observation(s) need attention: session_update.changed_devices differs and no claim covers it; session_update.count differs and no claim covers it; session_update.name differs and no claim covers it; probe: 1 other observation(s) identical on both sides; probe model-hitl-probe-c1-c8-1 is not_adequate (the probe crashed or printed no parsed output on every main-side run; not counted as ran or adequate); its matching results do not count; probe model-hitl-probe1-2 is not_adequate (the probe crashed or printed no parsed output on every main-side run; not counted as ran or adequate); its matching results do not count; rejected: claim pattern(s) C4, C5, C7 match none of this probe's observation names, so the probe is not counted; probe model-hitl-p1-4 is not_adequate (the probe crashed or printed no parsed output on every main-side run; not counted as ran or adequate); its matching results do not count; tests: 1 test(s) ran on main, 6 on the PR; 5 new test(s) pass, 1 unchanged.
- **What you should do:** Do not approve as is. Read 'What changed in behavior' and decide with the PR author.

The PR "Expose multizone playback session info" is marked "needs_attention" because "session_update.changed_devices differs and no claim covers it", "session_update.count differs and no claim covers it", "session_update.name differs and no claim covers it", and probes such as "probe model-hitl-probe-c1-c8-1 is not_adequate (the probe crashed or printed no parsed output on every main-side run; not counted as ran or adequate)", "probe model-hitl-probe1-2 is not_adequate (the probe crashed or printed no parsed output on every main-side run; not counted as ran or adequate)", and "probe model-hitl-p1-4 is not_adequate (the probe crashed" are inadequate.

Model summary is advisory; the code verdict above is authoritative.

Agent swarm (advisory)

Role	Model	Status	Notes
judge	nvidia/Nemotron-3-Ultra-550b-a55b	ok	5 labels
helper	nvidia/Nemotron-3_5-Lightning	ok	session_update.name: ignore cosmetic renames; session_update.count: noise from dynamic device ordering; session_update.changed_devices: ignore if no functional impact
summary	nvidia/nemotron-3-super-120b-a12b	ok	-

judge/helper/summary are advisory; code owns the verdict

Demo helper

These notes are background from the console and the daily check. They do not change the verdict.

If setup fails, the helper retries the install up to 2 times. If a test still can't be verified because something is missing, it installs what's missing and reruns that test once.

- Setup check: GitHub token: present.
- Setup check: Nebius token: present.
- Setup check: free memory 6.9 GB (of 15.6 GB).
- Setup check: free disk 98.1 GB.
- Demo helper: git is installed.
- Demo helper: python3 is installed.
- Demo helper: uv is installed.
- Looked up with Tavily: 5 results
- Query: pychromecast python setup install instructions https://github.com/home-assistant-libs/pychromecast site:github.com/home-assistant-libs/pychromecast
- Query: pychromecast python documentation install https://github.com/home-assistant-libs/pychromecast site:github.com/home-assistant-libs/pychromecast
- Query: pychromecast python install requirements https://pypi.org/project/pychromecast/ https://github.com/home-assistant-libs/pychromecast site:pypi.org
- Source: PyChromecast · PyPI — https://pypi.org/project/pychromecast/
- Source: GitHub - home-assistant-libs/pychromecast: Library for Python 3 to communicate with the Google Chromecast. · GitHub — https://github.com/home-assistant-libs/pychromecast
- Source: Extra dependencies on raspbian Jessie (raspberry pi) · Issue #132 · home-assistant-libs/pychromecast · GitHub — https://github.com/home-assistant-libs/pychromecast/issues/132
- Source: pychromecast/pychromecast/socket_client.py at master · home-assistant-libs/pychromecast · GitHub — https://github.com/home-assistant-libs/pychromecast/blob/master/pychromecast/socket_client.py
- Source: "[WinError 10049] The requested address is not valid in its context" · Issue #483 · home-assistant-libs/pychromecast · GitHub — https://github.com/home-assistant-libs/pychromecast/issues/483
- Setup plan: the same packages on main and pr.

- Setup plan: protobuf is noted, installed with the project.
- Setup plan: zeroconf is noted, installed with the project.
- Setup plan: casttube is noted, installed with the project.
- Setup plan: install beautifulsoup4==4.15.0 (listed in requirements-test.txt) on main and pr.
- Setup plan: install ruff==0.17.1 (listed in requirements-test.txt) on main and pr.
- Setup plan: install mypy==2.4.0 (listed in requirements-test.txt) on main and pr.
- Setup plan: install PlexAPI==4.17.2 (listed in requirements-test.txt) on main and pr.
- Setup plan: install pylint==4.1.3 (listed in requirements-test.txt) on main and pr.
- Setup plan: install pytest==9.1.1 (listed in requirements-test.txt) on main and pr.
- Setup plan: install rstcheck==6.3.0 (listed in requirements-test.txt) on main and pr.
- Setup plan: install types-beautifulsoup4==4.12.0.20250516 (listed in requirements-test.txt) on main and pr.
- Setup plan: install types-html5lib==1.1.11.20260518 (listed in requirements-test.txt) on main and pr.
- Setup plan: install types-protobuf==7.35.1.20260906 (listed in requirements-test.txt) on main and pr.
- Setup plan: install types-requests==2.33.0.20261006 (listed in requirements-test.txt) on main and pr.
- Setup plan: install yle-dl==20240927 (listed in requirements-test.txt) on main and pr.
- Setup plan: Python 3.12: Python 3.12 already meets >=3.11.0
- Installed beautifulsoup4 4.15.0 from requirements-test.txt (listed in requirements-test.txt) on main and pr.
- Installed ruff 0.17.1 from requirements-test.txt (listed in requirements-test.txt) on main and pr.
- Installed mypy 2.4.0 from requirements-test.txt (listed in requirements-test.txt) on main and pr.
- Installed PlexAPI 4.17.2 from requirements-test.txt (listed in requirements-test.txt) on main and pr.
- Installed pylint 4.1.3 from requirements-test.txt (listed in requirements-test.txt) on main and pr.
- Installed pytest 9.1.1 from requirements-test.txt (listed in requirements-test.txt) on main and pr.
- Installed rstcheck 6.3.0 from requirements-test.txt (listed in requirements-test.txt) on main and pr.
- Installed types-beautifulsoup4 4.12.0.20250516 from requirements-test.txt (listed in requirements-test.txt) on main and pr.
- Installed types-html5lib 1.1.11.20260518 from requirements-test.txt (listed in requirements-test.txt) on main and pr.
- Installed types-protobuf 7.35.1.20260906 from requirements-test.txt (listed in requirements-test.txt) on main and pr.
- Installed types-requests 2.33.0.20261006 from requirements-test.txt (listed in requirements-test.txt) on main and pr.
- Installed yle-dl 20240927 from requirements-test.txt (listed in requirements-test.txt) on main and pr.

Background (related public bug reports, not used for the verdict)

1. "Issues · home-assistant-libs/pychromecast · GitHub" https://github.com/home-assistant-libs/pychromecast/issues "home-assistant-libs/pychromecast#1059 · opened on Apr 28, 2025 ### Fields in `media.metadata` (artist, title etc) never get cleared in `MediaStatus` and can report wrong/stale info. home-assistant-libs/pychromecast#1018 · opened on Feb 3, 2..." 2. "GitHub - home-assistant-libs/pychromecast: Library for Python 3 to communicate with the Google Chromecast. · GitHub" https://github.com/home-assistant-libs/pychromecast "namespaces ='urn:x-cast:com.google.cast.player.message''urn:x-cast:com.google.cast.media' session_id ='CCA39713-9A4F-34A6-A8BF-5D97BE7ECA5C' transport_id ='web-9' status_text = '' >> mc = cast media_controller >> mc play_media' >> mc block_..." 3. "[solved] Pychromecast not connecting to devices (zeroconf issue) - cast - Home Assistant Community" h...

Human review

A person reviewed the AI's probes before anything ran. Probes written from their test ideas are labelled human-requested.

Item	Value
AI probes kept	none
AI probes dropped	probe1
Test ideas added	5
Human-requested probes	hitl-probe-c1-c8-1, hitl-probe1-2, hitl-probe1-3, hitl-p1-4, hitl-probe-unchanged-behavior-5
Claims left with no probe	C9

- C1,C8: build MultizoneController(UUID('9a4683f8-a265-4ec7-aab1-a70cb50f4ca7')) and call receive_message(None, {'type':'MULTIZONE_STATUS','requestId':1,'status':{'devices':[],'isMultichannel':False,'playbackSession':{'appAllowsGrouping':True,'isVideoContent':False,'streamTransferSupported':True}}}). Record getattr(controller,'playback_session',<'missing'>) fields app_allows_grouping, is_video_content, stream_transfer_supported as observations 'session_fields.<field>'; on main record the string 'missing'. Do not import constants from pychromecast.const; use the literal message type strings.
- C2,C3: same controller; send a MULTIZONE_STATUS with no playbackSession key and record whether playback_session is None ('session_none.without_session'); then send one with a playbackSession, call reset_members(), and record whether playback_session is None ('session_none.after_reset'). On main record 'missing' when the attribute does not exist.
- C4,C5,C7: register a plain MultiZoneControllerListener subclass that appends each multizone_playback_session_updated argument to a list, then receive_message(None, {'type':'PLAYBACK_SESSION_UPDATED','name':'Group','changedDevices':['be209f090f6a4596ac1a16a77670692b'],'failedDevices':[],'sessionEndpoint':{'deviceId':'be209f090f6a4596ac1a16a77670692b','ipAddress':'192.168.1.5','port':8009,'sessionId':'abc'}}). Record the call count, update.name, update.changed_devices and update.session_endpoint.device_id as 'session_update.*' (count 0 on main). When no update was delivered, record the string 'no_update' for each update field so main and PR values are comparable.
- C6: a listener subclass that only defines multizone_member_added/removed/status_received is registered; send PLAYBACK_SESSION_UPDATED and MULTIZONE_STATUS messages and record 'ok' or the exception type name for each as 'old_listener.update' and 'old_listener.status'. Expect the same on both sides.
- Unchanged behaviour: send MULTIZONE_STATUS with devices Kitchen 'be209f09-0f6a-4596-ac1a-16a77670692b' and Back room '2b514019-b9fa-43b5-a740-b4c3f8882918', record sorted controller.members as 'members_unchanged.before', then send {'type':'DEVICE_REMOVED','deviceId':'be209f09-0f6a-4596-ac1a-16a77670692b'} and record members again as 'members_unchanged.after'. Expect the same on both sides.

A claim with no probe after review cannot be verified, so the verdict is at most could not verify.

Claims vs reality

#	Claim (source)	Status	What we observed	Log line
C2	Existing behavior is kept: tests that pass on main still pass (implied by every PR)	proven	no test that passes on main fails on the PR (1 unchanged, 3 runs per side)	pytest-pr-1.log:7 «6 passed in 0.80s»
P-C1	Only parses messages devices already send; nothing new is sent. (PR description)	not testable	probe model-hitl-probe-c1-c8-1 has no observation for this claim	no matching log line
P-C8	Normalize device ids to the dashed form used for `members`, since devices also report dashless ids. (PR description)	not testable	probe model-hitl-probe-c1-c8-1 has no observation for this claim	no matching log line
P-C2	Parse `playbackSession` from `MULTIZONE_STATUS` (`appAllowsGrouping`, `isVideoContent`, `streamTransferSupported`) and expose it as `MultizoneController.playback_session`. (PR description)	not testable	probe model-hitl-probe1-2 has no observation for this claim	no matching log line
P-C3	The `playback_session` attribute is `None` when no session is attached to the endpoint. (PR description)	not testable	probe model-hitl-probe1-2 has no observation for this claim	no matching log line
P-C4	The `playback_session` attribute is cleared on `reset_members()`. (PR description)	not testable	probe model-hitl-probe1-3 has no observation for this claim	no matching log line
P-C5	Parse `PLAYBACK_SESSION_UPDATED` (previously dropped) into a `PlaybackSessionUpdate` (`name`, `changed_devices`, `failed_devices`, optional `session_endpoint`). (PR description)	not testable	probe model-hitl-probe1-3 has no observation for this claim	no matching log line

#	Claim (source)	Status	What we observed	Log line
P-C7	The `multizone_playback_session_updated` callback is not abstract, so existing listener subclasses keep working. (PR description)	not testable	probe model-hitl-probe1-3 has no observation for this claim	no matching log line
-	Change not in the PR description (probe model-hitl-probe1-3)	unmentioned change	session_update.changed_devices: `value`: "no_update" → ["<uuid>"]	probe-model-hitl-probe1-3-pr-1.jsonl:1 «"observation": "session_update.changed_devices"»
-	Change not in the PR description (probe model-hitl-probe1-3)	unmentioned change	session_update.count: `value`: 0 → 1	probe-model-hitl-probe1-3-pr-1.jsonl:2 «"observation": "session_update.count"»
-	Change not in the PR description (probe model-hitl-probe1-3)	unmentioned change	session_update.name: `value`: "no_update" → "Group"	probe-model-hitl-probe1-3-pr-1.jsonl:3 «"observation": "session_update.name"»
P-C6	Pass the `PlaybackSessionUpdate` to listeners via a new `MultiZoneControllerListener.multizone_playback_session_updated` callback. (PR description)	not testable	probe model-hitl-p1-4 has no observation for this claim	no matching log line
P-C7	The `multizone_playback_session_updated` callback is not abstract, so existing listener subclasses keep working. (PR description)	not testable	probe model-hitl-p1-4 has no observation for this claim	no matching log line

Citation check (WARN): 4 citation(s) verified; 9 statement(s) have no matching log line.

What changed in behavior

What	Count	Examples
Tests that actually ran (main / PR, fewest of the runs)	1 / 6	-
Tests unchanged	1	-
New tests that pass	5	-
Tests that pass on main but fail on the PR	0	-

What	Count	Examples
Tests that are new in the PR and fail	0	-
Tests that ran on main but are missing on the PR side	0	-
Tests that changed result in another way (for example passed → skipped)	0	-
Tests that gave different results between the 3 runs of the same side (flaky)	0	-
Tests that fail on main and pass on the PR	0	-
Tests that are new or changed but did not run because an optional module is missing	0	-
Tests that were re-parametrized (same test, new parameter ids; not counted as removed)	0	-
Test modules that fail to load on the PR side only (their tests no longer run)	0	-
Test modules that fail to load on main only (no baseline for their tests)	0	-
Test modules that fail to load on both sides (their tests did not run)	0	-
Tests that fail identically on both sides (already broken on main)	0	-

Probes

Model-written probes: model provider: nebius (Token Factory, live).

A probe is a small deterministic script run on both sides in the same environments as the tests, 3 alternating runs per side. It prints JSON observations; plain code (poc/diff.py) compares them. A difference that no claim of the PR covers needs attention. Every probe was frozen (content sha256) before any PR-side code ran, and checked against that freeze before each PR-side run. Only a live model probe is blind; fixed probes and recorded model fixtures are known-answer cases.

model-hitl-probe-c1-c8-1 (human-requested, model (nvidia/nemotron-3-super-120b-a12b, live), `model-probes/model-hitl-probe-c1-c8-1.py`, frozen `dcad1afac4fb` at 2026-10-21T14:33:30.414638+00:00): MultizoneController receives MULTIZONE_STATUS with playbackSession and exposes playback_session attribute

- P-C1 (PR description): Only parses messages devices already send; nothing new is sent. Expects the covered observations to stay the same.
- P-C8 (PR description): Normalize device ids to the dashed form used for `members`, since devices also report dashless ids. Expects the covered observations to differ.

Observation	Claim	Result	What the probe saw (main → PR)	Log lines (main, PR)
`probe.error`	-	probe could not run	same on both sides: `{"crash": "non-json output", "exit_code": 0}`	probe-model-hitl-probe-c1-c8-1-main-1.jsonl:1 «"observation": "probe.error"» probe-model-hitl-probe-c1-c8-1-pr-1.jsonl:1 «"observation": "probe.error"»

model-hitl-probe1-2 (human-requested, model (nvidia/nemotron-3-super-120b-a12b, live), `model-probes/model-hitl-probe1-2.py`, frozen `acd69e04bebf` at 2026-10-21T14:33:30.415029+00:00):

MultizoneController.playback_session attribute existence and value after MULTIZONE_STATUS messages and reset_members()

- P-C2 (PR description): Parse `playbackSession` from `MULTIZONE_STATUS` (`appAllowsGrouping`, `isVideoContent`, `streamTransferSupported`) and expose it as `MultizoneController.playback_session`. Expects the covered observations to differ.
- P-C3 (PR description): The `playback_session` attribute is `None` when no session is attached to the endpoint. Expects the covered observations to differ.

Observation	Claim	Result	What the probe saw (main → PR)	Log lines (main, PR)
`probe.error`	-	probe could not run	same on both sides: `{"crash": "non-json output", "exit_code": 0}`	probe-model-hitl-probe1-2-main-1.jsonl:1 «"observation": "probe.error"» probe-model-hitl-probe1-2-pr-1.jsonl:1 «"observation": "probe.error"»

model-hitl-probe1-3 (human-requested, model (nvidia/nemotron-3-super-120b-a12b, live), `model-probes/model-hitl-probe1-3.py`, frozen `da6b187187ca` at 2026-10-21T14:33:30.415515+00:00): Tests that PLAYBACK_SESSION_UPDATED messages do not trigger the multizone_playback_session_updated listener in the base code.

- P-C4 (PR description): The `playback_session` attribute is cleared on `reset_members()`. Expects the covered observations to differ.
- P-C5 (PR description): Parse `PLAYBACK_SESSION_UPDATED` (previously dropped) into a `PlaybackSessionUpdate` (`name`, `changed_devices`, `failed_devices`, optional `session_endpoint`). Expects the covered observations to differ.
- P-C7 (PR description): The `multizone_playback_session_updated` callback is not abstract, so existing listener subclasses keep working. Expects the covered observations to differ.

Observation	Claim	Result	What the probe saw (main → PR)	Log lines (main, PR)
`session_update.changed_devices`	-	differs, not in the PR description	`value`: "no_update" → ["<uuid>"]	probe-model-hitl-probe1-3-main-1.jsonl:1 «"observation": "session_update.changed_devices"» probe-model-hitl-probe1-3-pr-1.jsonl:1 «"observation": "session_update.changed_devices"»

Observation	Claim	Result	What the probe saw (main → PR)	Log lines (main, PR)
`session_update.count`	-	differs, not in the PR description	`value` : 0 → 1	probe-model-hitl-probe1-3-main-1.jsonl:2 «"observation": "session_update.count"» probe-model-hitl-probe1-3-pr-1.jsonl:2 «"observation": "session_update.count"»
`session_update.name`	-	differs, not in the PR description	`value` : "no_update" → "Group"	probe-model-hitl-probe1-3-main-1.jsonl:3 «"observation": "session_update.name"» probe-model-hitl-probe1-3-pr-1.jsonl:3 «"observation": "session_update.name"»

Observation	Claim	Result	What the probe saw (main → PR)	Log lines (main, PR)
`session_update.session_endpoint_device_id`	-	same on both sides	same on both sides: `"no_update"`	probe-model-hitl-probe1-3-main-1.jsonl:4 «"observation": "session_update.session_endpoint_device_id"» probe-model-hitl-probe1-3-pr-1.jsonl:4 «"observation": "session_update.session_endpoint_device_id"»

model-hitl-p1-4 (human-requested, model (nvidia/nemotron-3-super-120b-a12b, live), `model-probes/model-hitl-p1-4.py`, frozen `862e52275fff` at 2026-10-21T14:33:30.415831+00:00): Check that legacy listener handles PLAYBACK_SESSION_UPDATED and MULTIZONE_STATUS without breaking

- P-C6 (PR description): Pass the `PlaybackSessionUpdate` to listeners via a new `MultiZoneControllerListener.multizone_playback_session_updated` callback. Expects the covered observations to differ.
- P-C7 (PR description): The `multizone_playback_session_updated` callback is not abstract, so existing listener subclasses keep working. Expects the covered observations to differ.

Observation	Claim	Result	What the probe saw (main → PR)	Log lines (main, PR)
`probe.error`	-	probe could not run	same on both sides: `{"crash": "non-json output", "exit_code": 0}`	probe-model-hitl-p1-4-main-1.jsonl:1 «"observation": "probe.error"» probe-model-hitl-p1-4-pr-1.jsonl:1 «"observation": "probe.error"»

model-hitl-probe-unchanged-behavior-5 (human-requested, model (nvidia/nemotron-3-super-120b-a12b, live), `model-probes/model-hitl-probe-unchanged-behavior-5.py`, frozen `12f75a64218c` at 2026-10-21T14:33:30.416093+00:00): pychromecast/controllers/multizone.py

Observation	Claim	Result	What the probe saw (main → PR)	Log lines (main, PR)
`error`	-	same on both sides	same on both sides: `"KeyError"`	probe-model-hitl-probe-unchanged-behavior-5-main-1.jsonl:1 «"observation": "error"» probe-model-hitl-probe-unchanged-behavior-5-pr-1.jsonl:1 «"observation": "error"»

Citation check (PASS): 16 citation(s), every one re-read from its log file and matched.

Was the changed code exercised?

Coverage: MEASURED by coverage.py on the PR side (1.9 s run).

Coverage gate (python, confidence normal): 41 of 43 changed executable line(s) ran (95%).

Changed file	Changed executable lines	Of those, ran
`pychromecast/controllers/multizone.py`	43	41

How this is measured: one extra, untimed run of the PR side's tests under coverage.py. Changed lines come from comparing the tested main and PR files. Compiled code (C, C++, Cython) is invisible to coverage.py; such a change only counts as verified when the PR adds or changes a test for that module.

What went right

- Tested `e863b6dfeeb6` of the PR against main (source-pair route).

- 3 alternating runs per side: main 3, PR 3 of 3.
- pytest exit codes explained: all runs exited 0.
- Changed code was exercised (coverage gate): 41 of 43 changed executable line(s) ran (95%).
- Single-thread environment: OMP_NUM_THREADS=1, OPENBLAS_NUM_THREADS=1, MKL_NUM_THREADS=1, NUMEXPR_NUM_THREADS=1, VECLIB_MAXIMUM_THREADS=1, BLIS_NUM_THREADS=1, PYTHONHASHSEED=0.
- Machine type recorded: local x86_64 8 cpus.
- Nothing posted upstream: GitHub was only read.
- Every probe observation cites its output line: 16 citation(s), every one re-read from its log file and matched.

What went wrong and how to fix it

Issue	Status	Detail	How to fix
Probes ran on both sides	WARN	model-hitl-probe-c1-c8-1 main#1; model-hitl-probe-c1-c8-1 pr#1; model-hitl-probe-c1-c8-1 main#2	Read the probe-*.log files; a probe that cannot run is not evidence either way.
Every claim cites a real log line	WARN	4 citation(s) verified; 9 statement(s) have no matching log line	Regenerate the report; if it persists, the logs were edited or truncated.

Issue	Status	Detail	How to fix
Behavior difference found	finding	probe: 3 observation(s) need attention: session_update.changed_devices differs and no claim covers it; session_update.count differs and no claim covers it; session_update.name differs and no claim covers it; probe: 1 other observation(s) identical on both sides; probe model-hitl-probe-c1-c8-1 is not_adequate (the probe crashed or printed no parsed output on every main-side run; not counted as ran or adequate); its matching results do not count; probe model-hitl-probe1-2 is not_adequate (the probe crashed or printed no parsed output on every main-side run; not counted as ran or adequate); its matching results do not count; rejected: claim pattern(s) C4, C5, C7 match none of this probe's observation names, so the probe is not counted; probe model-hitl-p1-4 is not_adequate (the probe crashed or printed no parsed output on every main-side run; not counted as ran or adequate); its matching results do not count; tests: 1 test(s) ran on main, 6 on the PR; 5 new test(s) pass, 1 unchanged	This is about the PR, not the run: read the failing tests and their log lines, then decide.

Evals and guardrails

Check	Result	Detail
3 alternating runs per side	PASS	main 3, PR 3 of 3
pytest exit codes explained	PASS	all runs exited 0
Changed code was exercised (coverage gate)	PASS	41 of 43 changed executable line(s) ran (95%)
Probes ran on both sides	WARN	model-hitl-probe-c1-c8-1 main#1; model-hitl-probe-c1-c8-1 pr#1; model-hitl-probe-c1-c8-1 main#2
Single-thread environment	PASS	OMP_NUM_THREADS=1, OPENBLAS_NUM_THREADS=1, MKL_NUM_THREADS=1, NUMEXPR_NUM_THREADS=1, VECLIB_MAXIMUM_THREADS=1, BLIS_NUM_THREADS=1, PYTHONHASHSEED=0
Machine type recorded	PASS	local x86_64 8 cpus
Nothing posted upstream	PASS	GitHub was only read
Known-answer replay (fresh re-run)	SKIP	not replayed yet
Every claim cites a real log line	WARN	4 citation(s) verified; 9 statement(s) have no matching log line
Every probe observation cites its output line	PASS	16 citation(s), every one re-read from its log file and matched

Checklist

☐ I read the verdict and the plain-English summary.
☐ Every 'false' or 'unmentioned change' row has a log line I can open.
☐ Nothing under 'What went wrong' is a run problem (those mean Re-run, not Reject).
☐ I recorded my decision (see below).

Decision recorded: none yet. To record one, run `make decide REPORT=./report/pychromecast-1300 DECISION=approve` (or `reject`, `approve_with_notes`, `re_run`).

Rerun command

```
make check PR=https://github.com/home-assistant-libs/pychromecast/pull/1300
```

Evidence links

- Pull request home-assistant-libs/pychromecast#1300
- record.json
- pr.diff
- setup-main.log
- setup-pr.log
- git.log
- pytest-main-1.log
- pytest-pr-1.log
- pytest-main-2.log
- pytest-pr-2.log
- pytest-main-3.log
- pytest-pr-3.log
- junit-main-1.xml
- junit-pr-1.xml
- coverage-pytest.log
- coverage-pr.json
- probe-model-hitl-probe-c1-c8-1-main-1.jsonl
- probe-model-hitl-probe-c1-c8-1-pr-1.jsonl
- probe-model-hitl-probe1-2-main-1.jsonl
- probe-model-hitl-probe1-2-pr-1.jsonl
- probe-model-hitl-probe1-3-main-1.jsonl
- probe-model-hitl-probe1-3-pr-1.jsonl
- probe-model-hitl-p1-4-main-1.jsonl
- probe-model-hitl-p1-4-pr-1.jsonl
- probe-model-hitl-probe-unchanged-behavior-5-main-1.jsonl
- probe-model-hitl-probe-unchanged-behavior-5-pr-1.jsonl
- main run 1 result: pytest-main-1.log:7 «1 passed in 0.77s»
- pr run 1 result: pytest-pr-1.log:7 «6 passed in 0.80s»

Glossary

Term	Meaning
main	The library as it is today, without the PR.
PR	Pull request: a proposed change to the library.
run	One full pass of the selected tests. We do 3 per side, alternating main and PR.
flaky	A test that gives different results when nothing changed; it is ignored as evidence.
log line	A line in a pytest-*.log file: the raw output the verdict is based on.
route	How the two sides were built: nightly+patch, source-build or source-pair (see docs/OPERATIONS.md).
changed lines covered	How many of the PR's changed, executable Python lines ran during the PR side's tests.
re-parametrized	A test whose parameter ids changed (renamed cases); the new ids are judged on their own.