REPORT

Reviewer report: pyinvoke/invoke#1101: Let explicit

hide=None override configured output hiding

Run invoke-1101, tested 2026-11-09 13:01 IST by ops/daily_run.py (route source-pair).
Proof-of-Change commit

ef12096677e9cf59e8673436d74ec65d53771d7c. Report generated 2026-11-09 15:06 IST by

reports/pr_report.py.

Baseline: full (test comparison + claim probes + coverage gate + claim flagging (differential probes shown,

informational)).

NEEDS ATTENTION

Recommended action: Reject Confidence: Medium

The run is trustworthy and found a difference a person should look at. Limitation:

tests/runners.py::Runner_::hide::explicit_None_overrides_config[True],

tests/runners.py::Runner_::hide::explicit_None_overrides_config[out],

tests/runners.py::Runner_::hide::explicit_None_overrides_config[err],

tests/runners.py::Runner_::warn::honors_config,
tests/runners.py::Runner_::warn::kwarg_beats_config,

tests/runners.py::Runner_::warn::does_not_apply_to_watcher_errors,

tests/runners.py::Runner_::warn::does_not_apply_to_timeout_errors,

tests/runners.py::Runner_::hide::honors_config (+109 more) did not run on the base. They are not a new pass,

and this result does not cover them. Some checks gave warnings: Changed test file failed to collect

Advice only: Proof-of-Change never blocks a merge and never posts on GitHub.

Summary in plain English

• What it says it does: Let explicit hide=None override configured output hiding (pyinvoke/invoke#1101).

• What we observed: 3 new test(s) fail on the PR; 387 test(s) ran on main, 390 on the PR; 0 new test(s) pass, 278

unchanged (5 of them skipped on both sides); 114 test failure(s) pre-existing and identical on both sides; probe

model-p1 is uninformative (uninformative: every observation is probe-broken (the same exception or skip value

on both sides)); its matching results do not count; Limitation:

tests/runners.py::Runner_::hide::explicit_None_overrides_config[True],

tests/runners.py::Runner_::hide::explicit_None_overrides_config[out],

tests/runners.py::Runner_::hide::explicit_None_overrides_config[err],

tests/runners.py::Runner_::warn::honors_config,
tests/runners.py::Runner_::warn::kwarg_beats_config,

tests/runners.py::Runner_::warn::does_not_apply_to_watcher_errors,

tests/runners.py::Runner_::warn::does_not_apply_to_timeout_errors,

tests/runners.py::Runner_::hide::honors_config (+109 more) did not run on the base. They are not a new pass,

and this result does not cover them..

• What you should do: Do not approve as is. Read 'What changed in behavior' and decide with the PR author.

Demo helper

These notes are background from the console and the daily check. They do not change the verdict.

If setup fails, the helper retries the install up to 2 times. If a test still can't be verified because something is

missing or fails to import, it looks up the cause, installs the fix on both sides and reruns that step, up to 3 tries.

• Setup check: GitHub token: present.

• Setup check: Nebius token: present.

• Setup check: free memory 10.6 GB (of 15.6 GB).

• Setup check: free disk 92.0 GB.

• Demo helper: git is installed.

• Demo helper: python3 is installed.

• Demo helper: uv is installed.

• Looked up with Tavily: [redacted] results

• Query: invoke python setup install instructions https://github.com/pyinvoke/invoke

site:github.com/pyinvoke/invoke

• Query: invoke python documentation install https://github.com/pyinvoke/invoke site:github.com/pyinvoke/invoke

• Query: invoke python install requirements https://pypi.org/project/invoke/ https://github.com/pyinvoke/invoke

site:pypi.org

• Source: invoke-common-tasks · PyPI — https://pypi.org/project/invoke-common-tasks/

• Source: invoke · PyPI — https://pypi.org/project/invoke/

• Source: invoke/invoke/program.py at main · pyinvoke/invoke · GitHub —

https://github.com/pyinvoke/invoke/blob/master/invoke/program.py

• Source: invoke/invoke/runners.py at main · pyinvoke/invoke · GitHub —

https://github.com/pyinvoke/invoke/blob/master/invoke/runners.py

• Source: ImportError: cannot import name yaml2 · Issue #319 · pyinvoke/invoke · GitHub —

https://github.com/pyinvoke/invoke/issues/319

• Source: Invoke 0.13 breaks on Windows (unavailable default shell) · Issue #371 · pyinvoke/invoke · GitHub —

https://github.com/pyinvoke/invoke/issues/371

• Source: Dealing with virtual environments · Issue #838 · pyinvoke/invoke · GitHub —

https://github.com/pyinvoke/invoke/issues/838

• Setup plan: the same packages on main and pr.

• Setup plan: Python 3.12: Python 3.12 already meets >=3.9

• Installed icecream 2.2.0 from project (named by the error and listed in the project) on main and pr.

• Before rerun: could_not_verify: tests produced no results on both sides (collection failed; see pytest logs);

probe model-p1 is uninformative (uninformative: every observation is probe-broken (the same exception or skip

value on both sides)); its matching results do not count

• After rerun: needs_attention: 3 new test(s) fail on the PR; 387 test(s) ran on main, 390 on the PR; 0 new test(s)

pass, 278 unchanged (5 of them skipped on both sides); 114 test failure(s) pre-existing and identical on both

sides; probe model-p1 is uninformative (uninformative: every observation is probe-broken (the same exception or

skip value on both sides)); its matching results do not count; Limitation:

tests/runners.py::Runner_::hide::explicit_None_overrides_config[True],

tests/runners.py::Runner_::hide::explicit_None_overrides_config[out],

tests/runners.py::Runner_::hide::explicit_None_overrides_config[err],

tests/runners.py::Runner_::warn::honors_config,
tests/runners.py::Runner_::warn::kwarg_beats_config,

tests/runners.py::Runner_::warn::does_not_apply_to_watcher_errors,

tests/runners.py::Runner_::warn::does_not_apply_to_timeout_errors,

tests/runners.py::Runner_::hide::honors_config (+109 more) did not run on the base. They are not a new pass,

and this result does not cover them.

Limitation: tests/runners.py::Runner_::hide::explicit_None_overrides_config[True],

tests/runners.py::Runner_::hide::explicit_None_overrides_config[out],

tests/runners.py::Runner_::hide::explicit_None_overrides_config[err],

tests/runners.py::Runner_::warn::honors_config,
tests/runners.py::Runner_::warn::kwarg_beats_config,

tests/runners.py::Runner_::warn::does_not_apply_to_watcher_errors,

tests/runners.py::Runner_::warn::does_not_apply_to_timeout_errors,

tests/runners.py::Runner_::hide::honors_config (+109 more) did not run on the base. They are not a new pass,

and this result does not cover them.

Claims vs reality

| # | Claim (source) | Status | What we observed | Log line

| C2 | Existing behavior is kept: tests that pass on main still pass (implied by every PR) | false | 3 test(s) fail on the

PR, e.g. tests.runners.Runner_.hide::explicit_None_overrides_config[True] | pytest-pr-1.log:13534 «FAILED

tests/runners.py::Runner_::hide::explicit_None_overrides_config[True]»

| P-C1 | Explicit hide=None should override configured output hiding. (PR description) | not testable | probe

model-p1, c1.hide_value: same on both sides: "AttributeError" | probe-model-p1-pr-1.jsonl:1 «"observation":

"c1.hide_value"»

| P-C2 | Explicit hide=None currently falls back to configured output hiding, despite being documented to print

both streams. (PR description) | not testable | probe model-p1, c2.fallback_indicator: same on both sides:

"AttributeError" | probe-model-p1-pr-1.jsonl:2 «"observation": "c2.fallback_indicator"»

| P-C3 | Preserve None as an explicit value for hide, while retaining the existing fallback for other options. (PR

description) | not testable | probe model-p1, c3.hide_default: same on both sides: "AttributeError" |

probe-model-p1-pr-1.jsonl:3 «"observation": "c3.hide_default"»

| P-C4 | All three regression cases fail before the fix; a real subprocess now displays its output. (PR description) |

not testable | probe model-p1, c4.output_displayed: same on both sides: "AttributeError" |

probe-model-p1-pr-1.jsonl:5 «"observation": "c4.output_displayed"»

| - | Change not in the PR description (this run) | unmentioned change | 3 test(s) are new in the PR and fail, e.g.

tests.runners.Runner_.hide::explicit_None_overrides_config[True] | pytest-pr-1.log:13534 «FAILED

tests/runners.py::Runner_::hide::explicit_None_overrides_config[True]»

Citation check (PASS): 6 citation(s), every one re-read from its log file and matched.

What changed in behavior

| What | Count | Examples

| Tests that actually ran (main / PR, fewest of the runs) | 387 / 390 | | Tests unchanged | 392 | | New tests that pass | 0 | | Tests that pass on main but fail on the PR | 0 | | Tests that are new in the PR and fail | 3 | tests.runners.Runner_.hide::explicit_None_overrides_config[True],

tests.runners.Runner_.hide::explicit_None_overrides_config[err],

tests.runners.Runner_.hide::explicit_None_overrides_config[out]

| Tests that ran on main but are missing on the PR side | 0 | | Tests that changed result in another way (for example passed -> skipped) | 0 | | Tests that gave different results between the 3 runs of

the same side (flaky) | 0 | | Tests that fail on main and pass on the PR | 0 | | Tests that are new or changed but did not run because an optional module is missing | 0 | | Tests that were re-parametrized (same test, new parameter ids; not counted as removed) | 0 | | Test modules that fail to load on the PR side only (their tests no longer run) | 0 | | Test modules that fail to load on main only (no baseline for their tests) | 0 | | Test modules that fail to load on both sides (their tests did not run) | 0 | | Tests that fail identically on both sides (already broken on main) | 114 |

tests.runners.Local_.env::uses_execve_for_pty_True,

tests.runners.Local_.get_pid::is_top_level_pid_when_using_pty,

tests.runners.Local_.pty.fallback::can_be_overridden_by_config,

tests.runners.Local_.pty.fallback::can_be_overridden_by_kwarg,

tests.runners.Local_.pty.fallback::overridden_fallback_affects_result_pty_value

tests.runners.Runner_.hide::explicit_None_overrides_config[True] fails with: invoke.exceptions.ThreadException:

tests.runners.Runner_.hide::explicit_None_overrides_config[err] fails with: invoke.exceptions.ThreadException:

tests.runners.Runner_.hide::explicit_None_overrides_config[out] fails with: invoke.exceptions.ThreadException:

Probes

Model-written probes: model provider: nebius (Token Factory, live).

A probe is a small deterministic script run on both sides in the same environments as the tests, 3 alternating runs

per side. It prints JSON observations; plain code (poc/diff.py) compares them. A difference that no claim of the

PR covers needs attention. Every probe was frozen (content sha256) before any PR-side code ran, and checked

against that freeze before each PR-side run. Only a live model probe is blind; fixed probes and recorded model

fixtures are known-answer cases.

model-p1 (model (nvidia/nemotron-3-super-120b-a12b, live), model-probes/model-p1.py, frozen fa8efca9adcb at

2026-11-09T07:34:32.310323+00:00): Probe for claims C1, C2, C3, C4

• P-C1 (PR description): Explicit hide=None should override configured output hiding. Expects the covered

observations to differ.

• P-C2 (PR description): Explicit hide=None currently falls back to configured output hiding, despite being

documented to print both streams. Expects the covered observations to stay the same.

• P-C3 (PR description): Preserve None as an explicit value for hide, while retaining the existing fallback for other

options. Expects the covered observations to differ.

• P-C4 (PR description): All three regression cases fail before the fix; a real subprocess now displays its output.

Expects the covered observations to differ.

| Observation | Claim | Result | What the probe saw (main -> PR) | Log lines (main, PR)

| c1.hide_value | P-C1 | probe could not run | same on both sides: "AttributeError" |

probe-model-p1-main-1.jsonl:1 «"observation": "c1.hide_value"»
probe-model-p1-pr-1.jsonl:1 «"observation":

"c1.hide_value"»

| c2.fallback_indicator | P-C2 | probe could not run | same on both sides: "AttributeError" |

probe-model-p1-main-1.jsonl:2 «"observation": "c2.fallback_indicator"»
probe-model-p1-pr-1.jsonl:2

«"observation": "c2.fallback_indicator"»

| c3.hide_default | P-C3 | probe could not run | same on both sides: "AttributeError" |

probe-model-p1-main-1.jsonl:3 «"observation": "c3.hide_default"»
probe-model-p1-pr-1.jsonl:3

«"observation": "c3.hide_default"»

| c3.hide_none | P-C3 | probe could not run | same on both sides: "AttributeError" |

probe-model-p1-main-1.jsonl:4 «"observation": "c3.hide_none"»
probe-model-p1-pr-1.jsonl:4 «"observation":

"c3.hide_none"»

| c4.output_displayed | P-C4 | probe could not run | same on both sides: "AttributeError" |

probe-model-p1-main-1.jsonl:5 «"observation": "c4.output_displayed"»
probe-model-p1-pr-1.jsonl:5

«"observation": "c4.output_displayed"»

Citation check (PASS): 10 citation(s), every one re-read from its log file and matched.

Was the changed code exercised?

Coverage: MEASURED by coverage.py on the PR side (5.9 s run).

Coverage gate (python, confidence normal): 4 of 4 changed executable line(s) ran (100%).

| Changed file | Changed executable lines | Of those, ran

| invoke/runners.py | 4 | 4

How this is measured: one extra, untimed run of the PR side's tests under coverage.py. Changed lines come

from comparing the tested main and PR files. Compiled code (C, C++, Cython) is invisible to coverage.py; such a

change only counts as verified when the PR adds or changes a test for that module.

What went right

• Tested d67a16bfb0fb of the PR against main (source-pair route).

• 3 alternating runs per side: main 3, PR 3 of 3.

• pytest exit codes explained: pytest exit 1; 114 failure(s)/error(s) pre-existing and identical on both sides.

• Changed code was exercised (coverage gate): 4 of 4 changed executable line(s) ran (100%).

• Probes ran on both sides: 1 probe(s), 3 alternating runs per side, every run printed its observations.

• Single-thread environment: OMP_NUM_THREADS=1, OPENBLAS_NUM_THREADS=1,

MKL_NUM_THREADS=1, NUMEXPR_NUM_THREADS=1, VECLIB_MAXIMUM_THREADS=1,

BLIS_NUM_THREADS=1, PYTHONHASHSEED=0.

• Machine type recorded: local x86_64 8 cpus.

• Nothing posted upstream: GitHub was only read.

• Known-answer replay (fresh re-run): replayed 2026-10-10 06:30:21 IST, harness 1.0.

• Every claim cites a real log line: 6 citation(s), every one re-read from its log file and matched.

• Every probe observation cites its output line: 10 citation(s), every one re-read from its log file and matched.

What went wrong and how to fix it

| Issue | Status | Detail | How to fix

| Changed test file failed to collect | WARN | pytest could not collect tests/runners.py. That changed test file is not

a pass. | Keep this beside the already-on-base note when that note is present. The result does not cover a file

that failed to collect.

| Behavior difference found | finding | 3 new test(s) fail on the PR; 387 test(s) ran on main, 390 on the PR; 0 new

test(s) pass, 278 unchanged (5 of them skipped on both sides); 114 test failure(s) pre-existing and identical on

both sides; probe model-p1 is uninformative (uninformative: every observation is probe-broken (the same

exception or skip value on both sides)); its matching results do not count; Limitation:

tests/runners.py::Runner_::hide::explicit_None_overrides_config[True],

tests/runners.py::Runner_::hide::explicit_None_overrides_config[out],

tests/runners.py::Runner_::hide::explicit_None_overrides_config[err],

tests/runners.py::Runner_::warn::honors_config,
tests/runners.py::Runner_::warn::kwarg_beats_config,

tests/runners.py::Runner_::warn::does_not_apply_to_watcher_errors,

tests/runners.py::Runner_::warn::does_not_apply_to_timeout_errors,

tests/runners.py::Runner_::hide::honors_config (+109 more) did not run on the base. They are not a new pass,

and this result does not cover them. | This is about the PR, not the run: read the failing tests and their log lines,

then decide.

Evals and guardrails

| Check | Result | Detail

| 3 alternating runs per side | PASS | main 3, PR 3 of 3

| pytest exit codes explained | PASS | pytest exit 1; 114 failure(s)/error(s) pre-existing and identical on both sides

| Changed code was exercised (coverage gate) | PASS | 4 of 4 changed executable line(s) ran (100%)

| Probes ran on both sides | PASS | 1 probe(s), 3 alternating runs per side, every run printed its observations

| Single-thread environment | PASS | OMP_NUM_THREADS=1, OPENBLAS_NUM_THREADS=1,

MKL_NUM_THREADS=1, NUMEXPR_NUM_THREADS=1, VECLIB_MAXIMUM_THREADS=1,

BLIS_NUM_THREADS=1, PYTHONHASHSEED=0

| Machine type recorded | PASS | local x86_64 8 cpus

| Nothing posted upstream | PASS | GitHub was only read

| Changed test file failed to collect | WARN | pytest could not collect tests/runners.py. That changed test file is not

a pass.

| Known-answer replay (fresh re-run) | PASS | replayed 2026-10-10 06:30:21 IST, harness 1.0

| Every claim cites a real log line | PASS | 6 citation(s), every one re-read from its log file and matched

| Every probe observation cites its output line | PASS | 10 citation(s), every one re-read from its log file and

matched

Checklist

• I read the verdict and the plain-English summary.

• Every 'false' or 'unmentioned change' row has a log line I can open.

• Nothing under 'What went wrong' is a run problem (those mean Re-run, not Reject).

• I recorded my decision (see below).

Decision recorded: none yet. To record one, run make decide

REPORT=poc-main/reports/daily/2026-11-09/invoke-1101 DECISION=approve (or reject,

approve_with_notes, re_run).

Rerun command

make check PR=https://github.com/pyinvoke/invoke/pull/1101

Evidence links

• Pull request pyinvoke/invoke#1101

• record.json

• pr.diff

• setup-main.log

• setup-pr.log

• git.log

• pytest-main-1.log

• pytest-pr-1.log

• pytest-main-2.log

• pytest-pr-2.log

• pytest-main-3.log

• pytest-pr-3.log

• junit-main-1.xml

• junit-pr-1.xml

• coverage-pytest.log

• coverage-pr.json

• probe-model-p1-main-1.jsonl

• probe-model-p1-pr-1.jsonl

• main run 1 result: pytest-main-1.log:13328 «114 failed, 273 passed, 5 skipped, 5 warnings in 2.18s»

• pr run 1 result: pytest-pr-1.log:13629 «117 failed, 273 passed, 5 skipped, 5 warnings in 2.19s»

Glossary

| Term | Meaning

| main | The library as it is today, without the PR.

| PR | Pull request: a proposed change to the library.

| run | One full pass of the selected tests. We do 3 per side, alternating main and PR.

| flaky | A test that gives different results when nothing changed; it is ignored as evidence.

| log line | A line in a pytest-*.log file: the raw output the verdict is based on.

| route | How the two sides were built: nightly+patch, source-build or source-pair (see docs/OPERATIONS.md).

| changed lines covered | How many of the PR's changed, executable Python lines ran during the PR side's tests.

| re-parametrized | A test whose parameter ids changed (renamed cases); the new ids are judged on their own.

rebuilt from cleaned text

Written 2026-11-09 15:06 IST