REPORT

Reviewer report: urllib3/urllib3#5361: Drop support for

EOL Python 3.10

Run urllib3-5361, tested 2026-11-08 18:12 IST by ops/daily_run.py (route source-pair).
Proof-of-Change commit

ef12096677e9cf59e8673436d74ec65d53771d7c. Report generated 2026-11-09 12:04 IST by

reports/pr_report.py.

Baseline: full (test comparison + claim probes + coverage gate + claim flagging (differential probes shown,

informational)).

COULD NOT VERIFY

Recommended action: Re-run Confidence: Low

The run did not produce a usable comparison, so there is no conclusion about the PR. The run did not finish

cleanly, so it says nothing about the PR.

Advice only: Proof-of-Change never blocks a merge and never posts on GitHub.

Summary in plain English

• What it says it does: Drop support for EOL Python 3.10 (urllib3/urllib3#5361).

• What we observed: not verified: no AI-written probe ran any changed line, so the change itself was not

exercised by a probe; 340 test(s) ran on main, 340 on the PR; 0 new test(s) pass, 290 unchanged; 50 test

failure(s) pre-existing and identical on both sides; probe model-probe1 is uninformative (uninformative: every

observation is probe-broken (the same exception or skip value on both sides)); its matching results do not count.

• What you should do: Do not decide yet. Fix the problem under 'How to fix' and run the check again.

Demo helper

These notes are background from the console and the daily check. They do not change the verdict.

If setup fails, the helper retries the install up to 2 times. If a test still can't be verified because something is

missing or fails to import, it looks up the cause, installs the fix on both sides and reruns that step, up to 3 tries.

• Setup check: GitHub token: present.

• Setup check: Nebius token: present.

• Setup check: free memory 3.1 GB (of 15.6 GB).

• Setup check: free disk 93.1 GB.

• Demo helper: git is installed.

• Demo helper: python3 is installed.

• Demo helper: uv is installed.

• Looked up with Tavily: [redacted] results

• Query: urllib3 python setup install instructions https://github.com/urllib3/urllib3 site:github.com/urllib3/urllib3

• Query: urllib3 python documentation install https://github.com/urllib3/urllib3 site:github.com/urllib3/urllib3

• Query: urllib3 python install requirements https://pypi.org/project/urllib3/ https://github.com/urllib3/urllib3

site:pypi.org

• Source: urllib3 · PyPI — https://pypi.org/project/urllib3/

• Source: urllib3 installation requires setuptools >= 36.2.5 · Issue #1753 · urllib3/urllib3 · GitHub —

https://github.com/urllib3/urllib3/issues/1753

• Source: urllib3/docs/user-guide.rst at main · urllib3/urllib3 · GitHub —

https://github.com/urllib3/urllib3/blob/main/docs/user-guide.rst

• Source: ImportError during install of urllib3[secure] on Jython · Issue #1133 · urllib3/urllib3 · GitHub —

https://github.com/urllib3/urllib3/issues/1133

• Source: GitHub - urllib3/urllib3: urllib3 is a user-friendly HTTP client library for Python · GitHub —

https://github.com/urllib3/urllib3

• Source: Installing urllib3 · Issue #829 · urllib3/urllib3 · GitHub — https://github.com/urllib3/urllib3/issues/829

• Source: urllib3>=2.0 does not work with system Python on macOS —

https://github.com/urllib3/urllib3/issues/3020?timeline_page=1

• Setup plan: the PR changes install docs (.github/workflows/ci.yml, docs/contributing.rst, noxfile.py,

pyproject.toml); setup was read from main's copy and applied the same on both sides.

• Setup plan: the same packages on main and pr.

• Setup plan: install trustme>=1.2.1 (listed in the test extra) on main and pr.

• Setup plan: Python 3.12: Python 3.12 already meets >=3.10, >=3.11

• Installed trustme 1.2.1 from pyproject (listed in the test extra) on main and pr.

Setup: pytest plugin asyncio was turned off. Pytest stopped at startup the same way on both sides, and the

traceback pointed into that third-party plugin (AttributeError: module 'pytest' has no attribute

'pyodide_options_stack'). The tests were run again with the plugin turned off. This does not change how the

verdict is chosen. Detection fired. Pytest stopped at startup the same way on both sides. Plugin chosen: asyncio.

The installed pytest plugin list was read. Retry flags: -p no:asyncio. Outcome: worked.

Claims vs reality

| # | Claim (source) | Status | What we observed | Log line

| C2 | Existing behavior is kept: tests that pass on main still pass (implied by every PR) | proven | no test that

passes on main fails on the PR (340 unchanged, 3 runs per side) | pytest-pr-1.log:5516 «20 failed, 290 passed,

18 warnings, 48 errors in 62.36s (0:01:02)»

| P-C1 | The PR drops support for Python 3.10, meaning the library will no longer be compatible with that version.

(PR description) | not testable | probe model-probe1, c1.nox_python_versions: same on both sides:

"FileNotFoundError" | probe-model-probe1-pr-1.jsonl:1 «"observation": "c1.nox_python_versions"»

Citation check (PASS): 2 citation(s), every one re-read from its log file and matched.

What changed in behavior

| What | Count | Examples

| Tests that actually ran (main / PR, fewest of the runs) | 340 / 340 | | Tests unchanged | 340 | | New tests that pass | 0 | | Tests that pass on main but fail on the PR | 0 | | Tests that are new in the PR and fail | 0 | | Tests that ran on main but are missing on the PR side | 0 | | Tests that changed result in another way (for example passed -> skipped) | 0 | | Tests that gave different results between the 3 runs of the same side (flaky) | 0 | -

| Tests that fail on main and pass on the PR | 0 | | Tests that are new or changed but did not run because an optional module is missing | 0 | | Tests that were re-parametrized (same test, new parameter ids; not counted as removed) | 0 | | Test modules that fail to load on the PR side only (their tests no longer run) | 0 | | Test modules that fail to load on main only (no baseline for their tests) | 0 | | Test modules that fail to load on both sides (their tests did not run) | 0 | | Tests that fail identically on both sides (already broken on main) | 50 |

test.contrib.emscripten.test_emscripten::test_404[node-True],

test.contrib.emscripten.test_emscripten::test_bad_method[node-True], test.contrib.emscripten.test_emscripten::t

est_cache_content_ignored_during_and_after_partial_read[node-True],

test.contrib.emscripten.test_emscripten::test_disabled_redirects[node-True],

test.contrib.emscripten.test_emscripten::test_has_jspi[node-True]

Probes

Model-written probes: model provider: nebius (Token Factory, live).

A probe is a small deterministic script run on both sides in the same environments as the tests, 3 alternating runs

per side. It prints JSON observations; plain code (poc/diff.py) compares them. A difference that no claim of the

PR covers needs attention. Every probe was frozen (content sha256) before any PR-side code ran, and checked

against that freeze before each PR-side run. Only a live model probe is blind; fixed probes and recorded model

fixtures are known-answer cases.

model-probe1 (model (nvidia/nemotron-3-super-120b-a12b, live), model-probes/model-probe1.py, frozen

85a167585509 at 2026-11-08T12:44:04.968923+00:00): model-written probe of the changed files (no description

given)

• P-C1 (PR description): The PR drops support for Python 3.10, meaning the library will no longer be compatible

with that version. Expects the covered observations to differ.

| Observation | Claim | Result | What the probe saw (main -> PR) | Log lines (main, PR)

| c1.nox_python_versions | P-C1 | probe could not run | same on both sides: "FileNotFoundError" |

probe-model-probe1-main-1.jsonl:1 «"observation":

"c1.nox_python_versions"»
probe-model-probe1-pr-1.jsonl:1 «"observation": "c1.nox_python_versions"»

diff-api (diff (auto-derived from base-side code, model-free); informational under baseline full,

diff-probes/diff-api.py, frozen c4f0753f99e9 at 2026-11-08T12:44:05.124544+00:00): Public functions touched by

the PR, called with type-appropriate inputs on both sides.

| Observation | Claim | Result | What the probe saw (main -> PR) | Log lines (main, PR)

| dummyserver.app.redirect_after.import | - | probe could not run | same on both sides: {"raises":

"ModuleNotFoundError"} | probe-diff-api-main-1.jsonl:1 «"observation":

"dummyserver.app.redirect_after.import"»
probe-diff-api-pr-1.jsonl:1 «"observation":

"dummyserver.app.redirect_after.import"»

| noxfile.test.import | - | probe could not run | same on both sides: {"raises": "ModuleNotFoundError"} |

probe-diff-api-main-1.jsonl:2 «"observation": "noxfile.test.import"»
probe-diff-api-pr-1.jsonl:2 «"observation":

"noxfile.test.import"»

| urllib3.fields.guess_content_type.input0 | - | probe could not run | same on both sides: {"raises": "TypeError"} |

probe-diff-api-main-1.jsonl:3 «"observation":

"urllib3.fields.guess_content_type.input0"»
probe-diff-api-pr-1.jsonl:3 «"observation":

"urllib3.fields.guess_content_type.input0"»

| urllib3.fields.guess_content_type.input1 | - | same on both sides | same on both sides:

"application/octet-stream" | probe-diff-api-main-1.jsonl:4 «"observation":

"urllib3.fields.guess_content_type.input1"»
probe-diff-api-pr-1.jsonl:4 «"observation":

"urllib3.fields.guess_content_type.input1"»

| urllib3.fields.guess_content_type.input10 | - | same on both sides | same on both sides:

"application/octet-stream" | probe-diff-api-main-1.jsonl:5 «"observation":

"urllib3.fields.guess_content_type.input10"»
probe-diff-api-pr-1.jsonl:5 «"observation":

"urllib3.fields.guess_content_type.input10"»

| urllib3.fields.guess_content_type.input11 | - | same on both sides | same on both sides:

"application/octet-stream" | probe-diff-api-main-1.jsonl:6 «"observation":

"urllib3.fields.guess_content_type.input11"»
probe-diff-api-pr-1.jsonl:6 «"observation":

"urllib3.fields.guess_content_type.input11"»

| urllib3.fields.guess_content_type.input2 | - | probe could not run | same on both sides: {"raises": "TypeError"} |

probe-diff-api-main-1.jsonl:7 «"observation":

"urllib3.fields.guess_content_type.input2"»
probe-diff-api-pr-1.jsonl:7 «"observation":

"urllib3.fields.guess_content_type.input2"»

| urllib3.fields.guess_content_type.input3 | - | probe could not run | same on both sides: {"raises": "TypeError"} |

probe-diff-api-main-1.jsonl:8 «"observation":

"urllib3.fields.guess_content_type.input3"»
probe-diff-api-pr-1.jsonl:8 «"observation":

"urllib3.fields.guess_content_type.input3"»

| urllib3.fields.guess_content_type.input4 | - | same on both sides | same on both sides:

"application/octet-stream" | probe-diff-api-main-1.jsonl:9 «"observation":

"urllib3.fields.guess_content_type.input4"»
probe-diff-api-pr-1.jsonl:9 «"observation":

"urllib3.fields.guess_content_type.input4"»

| urllib3.fields.guess_content_type.input5 | - | probe could not run | same on both sides: {"raises": "TypeError"} |

probe-diff-api-main-1.jsonl:10 «"observation":

"urllib3.fields.guess_content_type.input5"»
probe-diff-api-pr-1.jsonl:10 «"observation":

"urllib3.fields.guess_content_type.input5"»

| urllib3.fields.guess_content_type.input6 | - | same on both sides | same on both sides:

"application/octet-stream" | probe-diff-api-main-1.jsonl:11 «"observation":

"urllib3.fields.guess_content_type.input6"»
probe-diff-api-pr-1.jsonl:11 «"observation":

"urllib3.fields.guess_content_type.input6"»

| urllib3.fields.guess_content_type.input7 | - | probe could not run | same on both sides: {"raises": "TypeError"} |

probe-diff-api-main-1.jsonl:12 «"observation":

"urllib3.fields.guess_content_type.input7"»
probe-diff-api-pr-1.jsonl:12 «"observation":

"urllib3.fields.guess_content_type.input7"»

| urllib3.fields.guess_content_type.input8 | - | same on both sides | same on both sides:

"application/octet-stream" | probe-diff-api-main-1.jsonl:13 «"observation":

"urllib3.fields.guess_content_type.input8"»
probe-diff-api-pr-1.jsonl:13 «"observation":

"urllib3.fields.guess_content_type.input8"»

| urllib3.fields.guess_content_type.input9 | - | same on both sides | same on both sides:

"application/octet-stream" | probe-diff-api-main-1.jsonl:14 «"observation":

"urllib3.fields.guess_content_type.input9"»
probe-diff-api-pr-1.jsonl:14 «"observation":

"urllib3.fields.guess_content_type.input9"»

| urllib3.filepost.choose_boundary.input0 | - | flaky between runs | value: "1824f5fcdd4a097a1414104498a08174"

-> "2bbf870598820eb606f623683003547d" | probe-diff-api-main-1.jsonl:15 «"observation":

"urllib3.filepost.choose_boundary.input0"»
probe-diff-api-pr-1.jsonl:15 «"observation":

"urllib3.filepost.choose_boundary.input0"»

Citation check (PASS): 32 citation(s), every one re-read from its log file and matched.

Was the changed code exercised?

Coverage: MEASURED by coverage.py on the PR side (76.4 s run).

Coverage gate (python, confidence normal): 14 of 19 changed executable line(s) ran (74%).

| Changed file | Changed executable lines | Of those, ran

| dummyserver/app.py | 1 | 0

| dummyserver/socketserver.py | 0 | 0

| noxfile.py | 0 | 0

| src/urllib3/_base_connection.py | 1 | 1

| src/urllib3/_collections.py | 0 | 0

| src/urllib3/_request_methods.py | 1 | 1

| src/urllib3/connection.py | 1 | 0

| src/urllib3/connectionpool.py | 2 | 1

| src/urllib3/contrib/socks.py | 1 | 0

| src/urllib3/fields.py | 2 | 2

| src/urllib3/filepost.py | 2 | 2

| src/urllib3/poolmanager.py | 0 | 0

| src/urllib3/response.py | 2 | 1

| src/urllib3/util/connection.py | 1 | 1

| src/urllib3/util/request.py | 1 | 1

| src/urllib3/util/retry.py | 0 | 0

| src/urllib3/util/ssltransport.py | 1 | 1

| src/urllib3/util/timeout.py | 1 | 1

| src/urllib3/util/url.py | 2 | 2

How this is measured: one extra, untimed run of the PR side's tests under coverage.py. Changed lines come

from comparing the tested main and PR files. Compiled code (C, C++, Cython) is invisible to coverage.py; such a

change only counts as verified when the PR adds or changes a test for that module.

What went right

• Tested ac14eb4bb693 of the PR against main (source-pair route).

• 3 alternating runs per side: main 3, PR 3 of 3.

• pytest exit codes explained: pytest exit 1; 50 failure(s)/error(s) pre-existing and identical on both sides.

• Changed code was exercised (coverage gate): 14 of 19 changed executable line(s) ran (74%).

• Probes ran on both sides: 2 probe(s), 3 alternating runs per side, every run printed its observations.

• Single-thread environment: OMP_NUM_THREADS=1, OPENBLAS_NUM_THREADS=1,

MKL_NUM_THREADS=1, NUMEXPR_NUM_THREADS=1, VECLIB_MAXIMUM_THREADS=1,

BLIS_NUM_THREADS=1, PYTHONHASHSEED=0.

• Machine type recorded: local x86_64 8 cpus.

• Nothing posted upstream: GitHub was only read.

• Known-answer replay (fresh re-run): replayed 2026-10-10 06:30:21 IST, harness 1.0.

• Every claim cites a real log line: 2 citation(s), every one re-read from its log file and matched.

• Every probe observation cites its output line: 32 citation(s), every one re-read from its log file and matched.

What went wrong and how to fix it

| Issue | Status | Detail | How to fix

| Run did not finish | COULD NOT VERIFY | not verified: no AI-written probe ran any changed line, so the change

itself was not exercised by a probe; 340 test(s) ran on main, 340 on the PR; 0 new test(s) pass, 290 unchanged;

50 test failure(s) pre-existing and identical on both sides; probe model-probe1 is uninformative (uninformative:

every observation is probe-broken (the same exception or skip value on both sides)); its matching results do not

count | Read the setup/build log under Evidence links; build failures usually need a compiler or a newer nightly.

| Install docs unchanged by the PR | WARN | the PR changes .github/workflows/ci.yml, docs/contributing.rst,

noxfile.py, pyproject.toml | Setup was read from main's install docs and applied the same on both sides; the PR's

own install steps differ, so read the result with that in mind.

Evals and guardrails

| Check | Result | Detail

| 3 alternating runs per side | PASS | main 3, PR 3 of 3

| pytest exit codes explained | PASS | pytest exit 1; 50 failure(s)/error(s) pre-existing and identical on both sides

| Changed code was exercised (coverage gate) | PASS | 14 of 19 changed executable line(s) ran (74%)

| Probes ran on both sides | PASS | 2 probe(s), 3 alternating runs per side, every run printed its observations

| Install docs unchanged by the PR | WARN | the PR changes .github/workflows/ci.yml, docs/contributing.rst,

noxfile.py, pyproject.toml

| Single-thread environment | PASS | OMP_NUM_THREADS=1, OPENBLAS_NUM_THREADS=1,

MKL_NUM_THREADS=1, NUMEXPR_NUM_THREADS=1, VECLIB_MAXIMUM_THREADS=1,

BLIS_NUM_THREADS=1, PYTHONHASHSEED=0

| Machine type recorded | PASS | local x86_64 8 cpus

| Nothing posted upstream | PASS | GitHub was only read

| Known-answer replay (fresh re-run) | PASS | replayed 2026-10-10 06:30:21 IST, harness 1.0

| Every claim cites a real log line | PASS | 2 citation(s), every one re-read from its log file and matched

| Every probe observation cites its output line | PASS | 32 citation(s), every one re-read from its log file and

matched

Checklist

• I read the verdict and the plain-English summary.

• Every 'false' or 'unmentioned change' row has a log line I can open.

• Nothing under 'What went wrong' is a run problem (those mean Re-run, not Reject).

• I recorded my decision (see below).

Decision recorded: none yet. To record one, run make decide

REPORT=poc-main/reports/daily/2026-11-08/urllib3-5361 DECISION=approve (or reject,

approve_with_notes, re_run).

Rerun command

make check PR=https://github.com/urllib3/urllib3/pull/5361

Evidence links

• Pull request urllib3/urllib3#5361

• record.json

• pr.diff

• setup-main.log

• setup-pr.log

• git.log

• pytest-main-1.log

• pytest-pr-1.log

• pytest-main-2.log

• pytest-pr-2.log

• pytest-main-3.log

• pytest-pr-3.log

• junit-main-1.xml

• junit-pr-1.xml

• coverage-pytest.log

• coverage-pr.json

• probe-model-probe1-main-1.jsonl

• probe-model-probe1-pr-1.jsonl

• probe-diff-api-main-1.jsonl

• probe-diff-api-pr-1.jsonl

• main run 1 result: pytest-main-1.log:5516 «20 failed, 290 passed, 18 warnings, 48 errors in 54.30s»

• pr run 1 result: pytest-pr-1.log:5516 «20 failed, 290 passed, 18 warnings, 48 errors in 62.36s (0:01:02)»

Glossary

| Term | Meaning

| main | The library as it is today, without the PR.

| PR | Pull request: a proposed change to the library.

| run | One full pass of the selected tests. We do 3 per side, alternating main and PR.

| flaky | A test that gives different results when nothing changed; it is ignored as evidence.

| log line | A line in a pytest-*.log file: the raw output the verdict is based on.

| route | How the two sides were built: nightly+patch, source-build or source-pair (see docs/OPERATIONS.md).

| changed lines covered | How many of the PR's changed, executable Python lines ran during the PR side's tests.

| re-parametrized | A test whose parameter ids changed (renamed cases); the new ids are judged on their own.

rebuilt from cleaned text

Written 2026-11-09 12:04 IST