REPORT

Reviewer report: pyinvoke/invoke#1097: Use

command-line names in missing-argument errors

Run invoke-1097, tested 2026-11-06 17:25 IST by ops/daily_run.py (route source-pair). Proof-of-Change commit

ef12096677e9cf59e8673436d74ec65d53771d7c. Report generated 2026-11-06 17:30 IST by

reports/pr_report.py.

Baseline: full (test comparison + claim probes + coverage gate + claim flagging (differential probes shown,

informational)).

COULD NOT VERIFY

Recommended action: Re-run Confidence: Low

The run did not produce a usable comparison, so there is no conclusion about the PR. The run did not finish

cleanly, so it says nothing about the PR.

Advice only: Proof-of-Change never blocks a merge and never posts on GitHub.

Summary in plain English

• What it says it does: Use command-line names in missing-argument errors (pyinvoke/invoke#1097).

• What we observed: could not verify: claim(s) C1, C2 expect a difference but no observation matches (2 test(s)

fail on main and pass on the PR; 137 test(s) ran on main, 137 on the PR; 0 new test(s) pass, 136 unchanged (1

of them skipped on both sides); probe model-probe1-rewrite is not_adequate (the probe crashed or printed no

parsed output on every main-side run; not counted as ran or adequate); its matching results do not count).

• What you should do: Do not decide yet. Fix the problem under 'How to fix' and run the check again.

Demo helper

These notes are background from the console and the daily check. They do not change the verdict.

If setup fails, the helper retries the install up to 2 times. If a test still can't be verified because something is

missing or fails to import, it looks up the cause, installs the fix on both sides and reruns that step, up to 3 tries.

• Setup check: GitHub token: present.

• Setup check: Nebius token: present.

• Setup check: free memory 9.9 GB (of 15.6 GB).

• Setup check: free disk 93.5 GB.

• Demo helper: git is installed.

• Demo helper: python3 is installed.

• Demo helper: uv is installed.

• Looked up with Tavily: [redacted] results

• Query: invoke python setup install instructions https://github.com/pyinvoke/invoke

site:github.com/pyinvoke/invoke

• Query: invoke python documentation install https://github.com/pyinvoke/invoke site:github.com/pyinvoke/invoke

• Query: invoke python install requirements https://pypi.org/project/invoke/ https://github.com/pyinvoke/invoke

site:pypi.org

• Source: invoke-common-tasks · PyPI — https://pypi.org/project/invoke-common-tasks/

• Source: invoke · PyPI — https://pypi.org/project/invoke/

• Source: invoke/invoke/runners.py at main · pyinvoke/invoke · GitHub —

https://github.com/pyinvoke/invoke/blob/master/invoke/runners.py

• Source: ImportError: cannot import name yaml2 · Issue #319 · pyinvoke/invoke · GitHub —

https://github.com/pyinvoke/invoke/issues/319

• Source: Dealing with virtual environments · Issue #838 · pyinvoke/invoke · GitHub —

https://github.com/pyinvoke/invoke/issues/838

• Source: Running a task from inside a Python script · Issue #112 · pyinvoke/invoke · GitHub —

https://github.com/pyinvoke/invoke/issues/112

• Source: Issue with Python 3.11, or type annotations: the inspect module changed · Issue #833 ·

pyinvoke/invoke · GitHub — https://github.com/pyinvoke/invoke/issues/833

• Setup plan: the same packages on main and pr.

• Setup plan: install invocations>=3.3 (listed in dev-requirements.txt) on main and pr.

• Setup plan: install coverage>=6.2,<7 (listed in dev-requirements.txt) on main and pr.

• Setup plan: install releases>=2 (listed in dev-requirements.txt) on main and pr.

• Setup plan: install alabaster==0.7.12 (listed in dev-requirements.txt) on main and pr.

• Setup plan: install pytest-relaxed>=2 (listed in dev-requirements.txt) on main and pr.

• Setup plan: install pytest-cov>=4 (listed in dev-requirements.txt) on main and pr.

• Setup plan: install flake8>=4,<5 (listed in dev-requirements.txt) on main and pr.

• Setup plan: install black>=22.8,<22.9 (listed in dev-requirements.txt) on main and pr.

• Setup plan: install setuptools>56 (listed in dev-requirements.txt) on main and pr.

• Setup plan: install icecream>=2.1 (listed in dev-requirements.txt) on main and pr.

• Setup plan: install mypy==0.971 (listed in dev-requirements.txt) on main and pr.

• Setup plan: install types-PyYAML==6.0.12.4 (listed in dev-requirements.txt) on main and pr.

• Setup plan: Python 3.12: Python 3.12 already meets >=3.6, >=3.9

• Setup plan: Python rule: one Python version is used on both sides: the lowest version that meets the

requirements of both main and the pull request; if none meets both, the check stops as a setup problem and

records both.

• Repository crawl: 11 page(s) crawled, 8 read in full, 1 setup step(s) used first in the sandbox (0 Tavily call(s),

0.0 credit(s)).

Claims vs reality

| # | Claim (source) | Status | What we observed | Log line

| C2 | Existing behavior is kept: tests that pass on main still pass (implied by every PR) | proven | no test that

passes on main fails on the PR (136 unchanged, 3 runs per side) | pytest-pr-1.log:273 «137 passed, 1 skipped, 5

warnings in 0.84s»

| P-C1 | When a required param_1 argument is exposed as param-1 on the command line, omitting it reports the

Python attribute name instead of the CLI name. (PR description) | not testable | probe model-probe1-rewrite has

no observation for this claim | no matching log line

| P-C2 | Using the argument's first public name in that error causes the missing-argument error to show the CLI

name instead of the Python attribute name. (PR description) | not testable | probe model-probe1-rewrite has no

observation for this claim | no matching log line

| P-C3 | Validation: two new cases fail before the fix, with the control passing. (PR description) | not testable |

probe model-probe1-rewrite has no observation for this claim | no matching log line

Citation check (WARN): 1 citation(s) verified; 3 statement(s) have no matching log line.

What changed in behavior

| What | Count | Examples

| Tests that actually ran (main / PR, fewest of the runs) | 137 / 137 | | Tests unchanged | 136 | | New tests that pass | 0 | | Tests that pass on main but fail on the PR | 0 | | Tests that are new in the PR and fail | 0 | | Tests that ran on main but are missing on the PR side | 0 | | Tests that changed result in another way (for example passed -> skipped) | 0 | | Tests that gave different results between the 3 runs of the same side (flaky) | 0 | | Tests that fail on main and pass on the PR | 2 | tests.parser_parser.Parser_.parse_argv.positional_arguments::

omitted_positionals_report_cli_names[param-1-param_1], tests.parser_parser.Parser_.parse_argv.positional_ar

guments::omitted_positionals_report_cli_names[public-name-internal_name]

| Tests that are new or changed but did not run because an optional module is missing | 0 | | Tests that were re-parametrized (same test, new parameter ids; not counted as removed) | 0 | | Test modules that fail to load on the PR side only (their tests no longer run) | 0 | | Test modules that fail to load on main only (no baseline for their tests) | 0 | | Test modules that fail to load on both sides (their tests did not run) | 0 | | Tests that fail identically on both sides (already broken on main) | 0 | -

Probes

Model-written probes: model provider: nebius (Token Factory, live).

Probe test settings: read from main's checkout (pytest.ini), the same on both sides. Variables: none.

A probe is a small deterministic script run on both sides in the same environments as the tests, 3 alternating runs

per side. It prints JSON observations; plain code (poc/diff.py) compares them. A difference that no claim of the

PR covers needs attention. Every probe was frozen (content sha256) before any PR-side code ran, and checked

against that freeze before each PR-side run. Only a live model probe is blind; fixed probes and recorded model

fixtures are known-answer cases.

model-probe1-rewrite (model (nvidia/nemotron-3-super-120b-a12b, live), model-probes/model-probe1-rewrite.py,

frozen 3a3b82a8adb9 at 2026-11-06T12:00:12.494462+00:00): Test missing-argument error for dashed name,

internal attribute, and control cases.

• P-C1 (PR description): When a required param_1 argument is exposed as param-1 on the command line,

omitting it reports the Python attribute name instead of the CLI name. Expects the covered observations to differ.

• P-C2 (PR description): Using the argument's first public name in that error causes the missing-argument error

to show the CLI name instead of the Python attribute name. Expects the covered observations to differ.

• P-C3 (PR description): Validation: two new cases fail before the fix, with the control passing. Expects the

covered observations to stay the same.

| Observation | Claim | Result | What the probe saw (main -> PR) | Log lines (main, PR)

| probe.error | - | probe could not run | same on both sides: {"crash": "non-json output", "exit_code": 1} |

probe-model-probe1-rewrite-main-1.jsonl:1 «"observation":

"probe.error"»
probe-model-probe1-rewrite-pr-1.jsonl:1 «"observation": "probe.error"»

Citation check (PASS): 2 citation(s), every one re-read from its log file and matched.

Was the changed code exercised?

Coverage: MEASURED by coverage.py on the PR side (11.7 s run).

Coverage gate (python, confidence normal): 1 of 1 changed executable line(s) ran (100%).

| Changed file | Changed executable lines | Of those, ran

| invoke/parser/parser.py | 1 | 1

How this is measured: one extra, untimed run of the PR side's tests under coverage.py. Changed lines come

from comparing the tested main and PR files. Compiled code (C, C++, Cython) is invisible to coverage.py; such a

change only counts as verified when the PR adds or changes a test for that module.

What went right

• Tested f887e02c1959 of the PR against main (source-pair route).

• 3 alternating runs per side: main 3, PR 3 of 3.

• pytest exit codes explained: all runs exited 0.

• Changed code was exercised (coverage gate): 1 of 1 changed executable line(s) ran (100%).

• Single-thread environment: OMP_NUM_THREADS=1, OPENBLAS_NUM_THREADS=1,

MKL_NUM_THREADS=1, NUMEXPR_NUM_THREADS=1, VECLIB_MAXIMUM_THREADS=1,

BLIS_NUM_THREADS=1, PYTHONHASHSEED=0.

• Machine type recorded: local x86_64 8 cpus.

• Nothing posted upstream: GitHub was only read.

• Every probe observation cites its output line: 2 citation(s), every one re-read from its log file and matched.

What went wrong and how to fix it

| Issue | Status | Detail | How to fix

| Run did not finish | COULD NOT VERIFY | could not verify: claim(s) C1, C2 expect a difference but no

observation matches (2 test(s) fail on main and pass on the PR; 137 test(s) ran on main, 137 on the PR; 0 new

test(s) pass, 136 unchanged (1 of them skipped on both sides); probe model-probe1-rewrite is not_adequate (the

probe crashed or printed no parsed output on every main-side run; not counted as ran or adequate); its matching

results do not count) | Read the setup/build log under Evidence links; build failures usually need a compiler or a

newer nightly.

| Probes ran on both sides | WARN | model-probe1-rewrite main#1; model-probe1-rewrite pr#1;

model-probe1-rewrite main#2 | Read the probe-*.log files; a probe that cannot run is not evidence either way.

| Every claim cites a real log line | WARN | 1 citation(s) verified; 3 statement(s) have no matching log line |

Regenerate the report; if it persists, the logs were edited or truncated.

Evals and guardrails

| Check | Result | Detail

| 3 alternating runs per side | PASS | main 3, PR 3 of 3

| pytest exit codes explained | PASS | all runs exited 0

| Changed code was exercised (coverage gate) | PASS | 1 of 1 changed executable line(s) ran (100%)

| Probes ran on both sides | WARN | model-probe1-rewrite main#1; model-probe1-rewrite pr#1;

model-probe1-rewrite main#2

| Single-thread environment | PASS | OMP_NUM_THREADS=1, OPENBLAS_NUM_THREADS=1,

MKL_NUM_THREADS=1, NUMEXPR_NUM_THREADS=1, VECLIB_MAXIMUM_THREADS=1,

BLIS_NUM_THREADS=1, PYTHONHASHSEED=0

| Machine type recorded | PASS | local x86_64 8 cpus

| Nothing posted upstream | PASS | GitHub was only read

| Known-answer replay (fresh re-run) | SKIP | not replayed yet

| Every claim cites a real log line | WARN | 1 citation(s) verified; 3 statement(s) have no matching log line

| Every probe observation cites its output line | PASS | 2 citation(s), every one re-read from its log file and

matched

Checklist

• I read the verdict and the plain-English summary.

• Every 'false' or 'unmentioned change' row has a log line I can open.

• Nothing under 'What went wrong' is a run problem (those mean Re-run, not Reject).

• I recorded my decision (see below).

Decision recorded: none yet. To record one, run make decide

REPORT=poc-217-invoke-live/reports/daily/2026-11-06-220223-invoke-ef120966/invoke-1097

DECISION=approve (or reject, approve_with_notes, re_run).

How long each step took

| Step | Seconds

| sandbox prep (checkout) | 14.5

| Tavily setup lookup | 11.5
| demo_helper | 0.0
| Python setup | 0.0
| dependency install | 0.0
| model: claims/probe writing | 9.6
| probes | 137.5
| main side install | 78.8
| tests (both sides) | 74.2
| verdict | 0.2

| record | 0.0
| tests (main side) | 14.7
| tests (PR side) | 14.2
| model call 1 (claims) | 9.5
| model call 2 (probes) | 83.1
| model call 3 (probes) | 9.5

Rerun command
make check PR=https://github.com/pyinvoke/invoke/pull/1097

Evidence links
• Pull request pyinvoke/invoke#1097
• record.json
• pr.diff
• git.log
• pytest-main-1.log
• pytest-pr-1.log
• pytest-main-2.log
• pytest-pr-2.log
• pytest-main-3.log
• pytest-pr-3.log
• junit-main-1.xml
• junit-pr-1.xml
• coverage-pytest.log
• coverage-pr.json
• probe-model-probe1-rewrite-main-1.jsonl
• probe-model-probe1-rewrite-pr-1.jsonl

• main run 1 result: pytest-main-1.log:270 «134 passed, 1 skipped, 5 warnings in 0.88s»

• pr run 1 result: pytest-pr-1.log:273 «137 passed, 1 skipped, 5 warnings in 0.84s»

Glossary

| Term | Meaning

| main | The library as it is today, without the PR.

| PR | Pull request: a proposed change to the library.

| run | One full pass of the selected tests. We do 3 per side, alternating main and PR.

| flaky | A test that gives different results when nothing changed; it is ignored as evidence.

| log line | A line in a pytest-*.log file: the raw output the verdict is based on.

| route | How the two sides were built: nightly+patch, source-build or source-pair (see docs/OPERATIONS.md).

| changed lines covered | How many of the PR's changed, executable Python lines ran during the PR side's tests.

| re-parametrized | A test whose parameter ids changed (renamed cases); the new ids are judged on their own.

rebuilt from cleaned text

Written 2026-11-06 17:30 IST