REPORT

Reviewer report: Textualize/rich#4110: Fix hyperlinks

being split into multiple links when text is highlighted

Run rich-4110, tested 2026-11-10 12:52 IST by ops/daily_run.py (route source-pair).
Proof-of-Change commit

ef12096677e9cf59e8673436d74ec65d53771d7c. Report generated 2026-11-10 17:38 IST by

reports/pr_report.py.

Baseline: full (test comparison + claim probes + coverage gate + claim flagging (differential probes shown,

informational)).

COULD NOT VERIFY

Recommended action: Re-run Confidence: Low

The run did not produce a usable comparison, so there is no conclusion about the PR. The run did not finish

cleanly, so it says nothing about the PR.

Advice only: Proof-of-Change never blocks a merge and never posts on GitHub.

Summary in plain English

• What it says it does: Fix hyperlinks being split into multiple links when text is highlighted (Textualize/rich#4110).

• What we observed: install failed (2); see setup-main.log.

• What you should do: Do not decide yet. Fix the problem under 'How to fix' and run the check again.

Demo helper

These notes are background from the console and the daily check. They do not change the verdict.

If setup fails, the helper retries the install up to 2 times. If a test still can't be verified because something is

missing or fails to import, it looks up the cause, installs the fix on both sides and reruns that step, up to 3 tries.

• Setup check: GitHub token: present.

• Setup check: Nebius token: present.

• Setup check: free memory 11.5 GB (of 15.6 GB).

• Setup check: free disk 92.1 GB.

• Demo helper: git is installed.

• Demo helper: python3 is installed.

• Demo helper: uv is installed.

• Looked up with Tavily: [redacted] results

• Query: rich python setup install instructions https://github.com/Textualize/rich site:github.com/Textualize/rich

• Query: rich python documentation install https://github.com/Textualize/rich site:github.com/Textualize/rich

• Query: rich python install requirements https://pypi.org/project/rich/ https://github.com/Textualize/rich

site:pypi.org

• Source: rich — https://pypi.org/project/rich/

• Source: rich-pyfiglet — https://pypi.org/project/rich-pyfiglet/

• Source: GitHub - Textualize/rich: Rich is a Python library for rich text and beautiful formatting in the terminal. ·

GitHub — https://github.com/textualize/rich

• Source: [BUG] rich fails to install using pip in editable mode · Issue #346 · Textualize/rich · GitHub —

https://github.com/Textualize/rich/issues/346

• Source: GitHub - Textualize/rich-cli: Rich-cli is a command line toolbox for fancy output in the terminal · GitHub

— https://github.com/textualize/rich-cli

• Source: rich/.readthedocs.yml at main · Textualize/rich · GitHub —

https://github.com/Textualize/rich/blob/main/.readthedocs.yml

• Setup plan: the same packages on main and pr.

• Setup plan: markdown-it-py is noted, installed with the project.

• Setup plan: pygments is noted, installed with the project.

• Setup plan: install alabaster==1.0.0 (listed in requirements.txt) on main and pr.

• Setup plan: install Sphinx==8.2.3 (listed in requirements.txt) on main and pr.

• Setup plan: install sphinx-rtd-theme==3.0.2 (listed in requirements.txt) on main and pr.

• Setup plan: install sphinx-copybutton==0.5.2 (listed in requirements.txt) on main and pr.

• Setup plan: install pytest (listed in tox.ini deps) on main and pr.

• Setup plan: install pytest-cov (listed in tox.ini deps) on main and pr.

• Setup plan: install attrs (listed in tox.ini deps) on main and pr.

• Setup plan: install typing-extensions (listed in tox.ini deps) on main and pr.

• Setup plan: install uv (listed in tox.ini deps) on main and pr.

• Setup plan: Python 3.15: switched the local sandbox to .local/bin/python3.15

• Setup plan: refused rich-cli: its PyPI page does not link to this GitHub repository

• rerun, setup problem: main install failed after 3 tries.

• Demo helper: setup failure already labelled; the probe was not rerun.

Claims vs reality

No tests ran, so no claim could be checked.

What changed in behavior

Not measured: install failed (2); see setup-main.log.

Probes

Model-written probes: model provider: nebius (Token Factory, live).

No probes ran: this record predates probes.

Was the changed code exercised?

Coverage: NOT MEASURED (coverage has not been run for this check).

Coverage gate (python, confidence lower): coverage of the changed Python lines was NOT MEASURED

(coverage has not been run for this check).

How this is measured: one extra, untimed run of the PR side's tests under coverage.py. Changed lines come

from comparing the tested main and PR files. Compiled code (C, C++, Cython) is invisible to coverage.py; such a

change only counts as verified when the PR adds or changes a test for that module.

What went right

• Tested 266bde4c8baa of the PR against main (source-pair route).

• Single-thread environment: OMP_NUM_THREADS=1, OPENBLAS_NUM_THREADS=1,

MKL_NUM_THREADS=1, NUMEXPR_NUM_THREADS=1, VECLIB_MAXIMUM_THREADS=1,

BLIS_NUM_THREADS=1, PYTHONHASHSEED=0.

• Machine type recorded: local x86_64 8 cpus.

• Nothing posted upstream: GitHub was only read.

• Known-answer replay (fresh re-run): replayed 2026-10-10 06:30:21 IST, harness 1.0.

What went wrong and how to fix it

| Issue | Status | Detail | How to fix

| Run did not finish | COULD NOT VERIFY | install failed (2); see setup-main.log | Read the setup/build log under

Evidence links; build failures usually need a compiler or a newer nightly.

| Changed code was exercised (coverage gate) | WARN | coverage of the changed Python lines was NOT

MEASURED (coverage has not been run for this check) | The coverage run did not produce data (see

coverage.why); run the check again.

Evals and guardrails

| Check | Result | Detail

| Changed code was exercised (coverage gate) | WARN | coverage of the changed Python lines was NOT

MEASURED (coverage has not been run for this check)

| Single-thread environment | PASS | OMP_NUM_THREADS=1, OPENBLAS_NUM_THREADS=1,

MKL_NUM_THREADS=1, NUMEXPR_NUM_THREADS=1, VECLIB_MAXIMUM_THREADS=1,

BLIS_NUM_THREADS=1, PYTHONHASHSEED=0

| Machine type recorded | PASS | local x86_64 8 cpus

| Nothing posted upstream | PASS | GitHub was only read

| Known-answer replay (fresh re-run) | PASS | replayed 2026-10-10 06:30:21 IST, harness 1.0

| Every claim cites a real log line | SKIP | no log lines to cite (no tests ran)

Checklist

• I read the verdict and the plain-English summary.

• Every 'false' or 'unmentioned change' row has a log line I can open.

• Nothing under 'What went wrong' is a run problem (those mean Re-run, not Reject).

• I recorded my decision (see below).

Decision recorded: none yet. To record one, run make decide

REPORT=poc-main/reports/daily/2026-11-10/rich-4110 DECISION=approve (or reject,

approve_with_notes, re_run).

Rerun command

make check PR=https://github.com/Textualize/rich/pull/4110

Evidence links

• Pull request Textualize/rich#4110

• record.json

• pr.diff

• setup-main.log

• git.log

Glossary

| Term | Meaning

| main | The library as it is today, without the PR.

| PR | Pull request: a proposed change to the library.

| run | One full pass of the selected tests. We do 3 per side, alternating main and PR.

| flaky | A test that gives different results when nothing changed; it is ignored as evidence.

| log line | A line in a pytest-*.log file: the raw output the verdict is based on.

| route | How the two sides were built: nightly+patch, source-build or source-pair (see docs/OPERATIONS.md).

| changed lines covered | How many of the PR's changed, executable Python lines ran during the PR side's tests.

| re-parametrized | A test whose parameter ids changed (renamed cases); the new ids are judged on their own.

rebuilt from cleaned text

Written 2026-11-10 17:38 IST