REPORT

Reviewer report: lincolnloop/python-qrcode#430: Honor

--ascii when writing to a file (#428)

Run python_qrcode-430, tested 2026-11-08 11:32 IST by ops/daily_run.py (route source-pair). Proof-of-Change

commit ef12096677e9cf59e8673436d74ec65d53771d7c. Report generated 2026-11-09 12:01 IST by

reports/pr_report.py.

Baseline: full (test comparison + claim probes + coverage gate + claim flagging (differential probes shown,

informational)).

NEEDS ATTENTION

Recommended action: Reject Confidence: Medium

The run is trustworthy and found a difference a person should look at. Some checks gave warnings: Optional

modules installed; Probes ran on both sides; Every claim cites a real log line

Advice only: Proof-of-Change never blocks a merge and never posts on GitHub.

Summary in plain English

• What it says it does: Honor --ascii when writing to a file (#428) (lincolnloop/python-qrcode#430).

• What we observed: probe: 1 observation(s) need attention: probe.error differs and no claim covers it; probe

model-probe1 is not_adequate (the probe crashed or printed no parsed output on every main-side run; not

counted as ran or adequate); its matching results do not count; probe model-probe2 is not_adequate (the probe

crashed or printed no parsed output on every main-side run; not counted as ran or adequate); its matching

results do not count; tests: 9 test(s) ran on main, 10 on the PR; 1 new test(s) pass, 14 unchanged (5 of them

skipped on both sides).

• What you should do: Do not approve as is. Read 'What changed in behavior' and decide with the PR author.

Demo helper

These notes are background from the console and the daily check. They do not change the verdict.

If setup fails, the helper retries the install up to 2 times. If a test still can't be verified because something is

missing or fails to import, it looks up the cause, installs the fix on both sides and reruns that step, up to 3 tries.

• Setup check: GitHub token: present.

• Setup check: Nebius token: present.

• Setup check: free memory 5.6 GB (of 15.6 GB).

• Setup check: free disk 93.2 GB.

• Demo helper: git is installed.

• Demo helper: python3 is installed.

• Demo helper: uv is installed.

• Looked up with Tavily: [redacted] results

• Query: python-qrcode python setup install instructions
https://github.com/lincolnloop/python-qrcode

site:github.com/lincolnloop/python-qrcode

• Query: python-qrcode python documentation install https://github.com/lincolnloop/python-qrcode

site:github.com/lincolnloop/python-qrcode

• Query: python-qrcode python install requirements https://pypi.org/project/python-qrcode/

https://github.com/lincolnloop/python-qrcode site:pypi.org

• Source: ImportError: No module named qrcode · Issue #103 —

https://github.com/lincolnloop/python-qrcode/issues/103

• Source: Need to pip install colorama on Windows #131 —

https://github.com/lincolnloop/python-qrcode/issues/131

• Source: import Image error · Issue #129 · lincolnloop/python-qrcode —

https://github.com/lincolnloop/python-qrcode/issues/129

• Source: GitHub - lincolnloop/python-qrcode: Python QR Code image generator · GitHub —

https://github.com/lincolnloop/python-qrcode

• Source: python-qrcode/CHANGES.rst at main - GitHub —

https://github.com/lincolnloop/python-qrcode/blob/main/CHANGES.rst

• Setup plan: the same packages on main and pr.

• Setup plan: colorama is noted, installed with the project.

• Setup plan: deprecation is noted, installed with the project.

• Setup plan: install qrcode (PyPI page links to this GitHub repository) on main and pr.

• Setup plan: Python 3.12: Python 3.12 already meets >=3.10

• Installed qrcode 8.2 from tavily (PyPI page links to this GitHub repository) on main and pr.

Claims vs reality

| # | Claim (source) | Status | What we observed | Log line

| C2 | Existing behavior is kept: tests that pass on main still pass (implied by every PR) | proven | no test that

passes on main fails on the PR (14 unchanged, 3 runs per side) | pytest-pr-1.log:7 «10 passed, 5 skipped in

0.53s»

| P-C1 | When --ascii and --output are used together without a custom image factory, the program writes ASCII

art to the output file instead of a PNG image. (PR description) | proven | probe model-probe1,

probe1.ascii_output_contains_block: value: "<absent>" -> true | probe-model-probe1-pr-1.jsonl:1 «"observation":

"probe1.ascii_output_contains_block"»

| P-C2 | Using --ascii with --output no longer requires the Pillow library because it skips calling make_image().

(PR description) | proven | probe model-probe1, probe1.ascii_output_is_png: value: "<absent>" -> false |

probe-model-probe1-pr-1.jsonl:2 «"observation": "probe1.ascii_output_is_png"»

| P-C3 | The test qr "text" --ascii --output=file.txt expects the output file to contain ASCII art (including the ■

character) and not the PNG magic bytes. (PR description) | not testable | probe model-probe1 has no

observation for this claim | no matching log line

| - | Change not in the PR description (probe model-probe1) | unmentioned change | probe.error: value: {"crash":

"non-json output", "exit_co... -> "<absent>" | no matching log line

| P-C4 | Running qr "text" --output=file.png without --ascii continues to produce a PNG file, showing no

regression. (PR description) | not testable | probe model-probe2 has no observation for this claim | no matching

log line

Citation check (WARN): 3 citation(s) verified; 3 statement(s) have no matching log line.

What changed in behavior

| What | Count | Examples

| Tests that actually ran (main / PR, fewest of the runs) | 9 / 10 | | Tests unchanged | 14 | -

| New tests that pass | 1 | | Tests that pass on main but fail on the PR | 0 | | Tests that are new in the PR and fail | 0 | | Tests that ran on main but are missing on the PR side | 0 | | Tests that changed result in another way (for example passed -> skipped) | 0 | | Tests that gave different results between the 3 runs of the same side (flaky) | 0 | | Tests that fail on main and pass on the PR | 0 | | Tests that are new or changed but did not run because an optional module is missing | 0 | | Tests that were re-parametrized (same test, new parameter ids; not counted as removed) | 0 | | Test modules that fail to load on the PR side only (their tests no longer run) | 0 | | Test modules that fail to load on main only (no baseline for their tests) | 0 | | Test modules that fail to load on both sides (their tests did not run) | 0 | | Tests that fail identically on both sides (already broken on main) | 0 | -

Probes

Model-written probes: model provider: nebius (Token Factory, live).

A probe is a small deterministic script run on both sides in the same environments as the tests, 3 alternating runs

per side. It prints JSON observations; plain code (poc/diff.py) compares them. A difference that no claim of the

PR covers needs attention. Every probe was frozen (content sha256) before any PR-side code ran, and checked

against that freeze before each PR-side run. Only a live model probe is blind; fixed probes and recorded model

fixtures are known-answer cases.

model-probe1 (model (nvidia/nemotron-3-super-120b-a12b, live), model-probes/model-probe1.py, frozen

a4612c476c70 at 2026-11-08T06:05:28.418344+00:00): Test --ascii --output behavior

• P-C1 (PR description): When --ascii and --output are used together without a custom image factory, the

program writes ASCII art to the output file instead of a PNG image. Expects the covered observations to differ.

• P-C2 (PR description): Using --ascii with --output no longer requires the Pillow library because it skips calling

make_image(). Expects the covered observations to differ.

• P-C3 (PR description): The test qr "text" --ascii --output=file.txt expects the output file to contain ASCII art

(including the ■ character) and not the PNG magic bytes. Expects the covered observations to differ.

| Observation | Claim | Result | What the probe saw (main -> PR) | Log lines (main, PR)

| probe.error | - | differs, not in the PR description | value: {"crash": "non-json output", "exit_co... -> "<absent>" |

probe-model-probe1-main-1.jsonl:1 «"observation": "probe.error"»
no matching log line

| probe1.ascii_output_contains_block | P-C1 | as claimed | value: "<absent>" -> true | no matching log

line
probe-model-probe1-pr-1.jsonl:1 «"observation": "probe1.ascii_output_contains_block"»

| probe1.ascii_output_is_png | P-C2 | as claimed | value: "<absent>" -> false | no matching log

line
probe-model-probe1-pr-1.jsonl:2 «"observation": "probe1.ascii_output_is_png"»

model-probe2 (model (nvidia/nemotron-3-super-120b-a12b, live), model-probes/model-probe2.py, frozen

edb116eacffb at 2026-11-08T06:05:28.418492+00:00): Test --output without --ascii behavior

• P-C4 (PR description): Running qr "text" --output=file.png without --ascii continues to produce a PNG file,

showing no regression. Expects the covered observations to stay the same.

| Observation | Claim | Result | What the probe saw (main -> PR) | Log lines (main, PR)

| probe.error | - | probe could not run | same on both sides: {"crash": "non-json output", "exit_code": 1} |

probe-model-probe2-main-1.jsonl:1 «"observation": "probe.error"»
probe-model-probe2-pr-1.jsonl:1

«"observation": "probe.error"»

diff-api (diff (auto-derived from base-side code, model-free); informational under baseline full,

diff-probes/diff-api.py, frozen ccc949c5db34 at 2026-11-08T06:05:28.419691+00:00): Public functions touched

by the PR, called with type-appropriate inputs on both sides.

| Observation | Claim | Result | What the probe saw (main -> PR) | Log lines (main, PR)

| qrcode.console_scripts.main.input0 | - | probe could not run | same on both sides: {"raises":

"ModuleNotFoundError"} | probe-diff-api-main-1.jsonl:1 «"observation":

"qrcode.console_scripts.main.input0"»
probe-diff-api-pr-1.jsonl:1 «"observation":

"qrcode.console_scripts.main.input0"»

Citation check (PASS): 7 citation(s), every one re-read from its log file and matched.

Was the changed code exercised?

Coverage: MEASURED by coverage.py on the PR side (1.5 s run).

Coverage gate (python, confidence normal): 3 of 6 changed executable line(s) ran (50%).

| Changed file | Changed executable lines | Of those, ran

| qrcode/console_scripts.py | 6 | 3

How this is measured: one extra, untimed run of the PR side's tests under coverage.py. Changed lines come

from comparing the tested main and PR files. Compiled code (C, C++, Cython) is invisible to coverage.py; such a

change only counts as verified when the PR adds or changes a test for that module.

Missing optional modules

• 5 unchanged test(s) skipped on both sides because PIL is not installed (coverage gap, verdict unaffected).

What went right

• Tested 2416274db1ac of the PR against main (source-pair route).

• 3 alternating runs per side: main 3, PR 3 of 3.

• pytest exit codes explained: all runs exited 0.

• Changed code was exercised (coverage gate): 3 of 6 changed executable line(s) ran (50%).

• Single-thread environment: OMP_NUM_THREADS=1, OPENBLAS_NUM_THREADS=1,

MKL_NUM_THREADS=1, NUMEXPR_NUM_THREADS=1, VECLIB_MAXIMUM_THREADS=1,

BLIS_NUM_THREADS=1, PYTHONHASHSEED=0.

• Machine type recorded: local x86_64 8 cpus.

• Nothing posted upstream: GitHub was only read.

• Known-answer replay (fresh re-run): replayed 2026-10-10 06:30:21 IST, harness 1.0.

• Every probe observation cites its output line: 7 citation(s), every one re-read from its log file and matched.

What went wrong and how to fix it

| Issue | Status | Detail | How to fix

| Optional modules installed | WARN | unchanged tests skipped on both sides: PIL (5) | Add the module(s) to

optional_test_deps for this library in ops/daily_run.py and run again.

| Probes ran on both sides | WARN | model-probe1 main#1; model-probe1 main#2; model-probe1 main#3 | Read

the probe-*.log files; a probe that cannot run is not evidence either way.

| Every claim cites a real log line | WARN | 3 citation(s) verified; 3 statement(s) have no matching log line |

Regenerate the report; if it persists, the logs were edited or truncated.

| Behavior difference found | finding | probe: 1 observation(s) need attention: probe.error differs and no claim

covers it; probe model-probe1 is not_adequate (the probe crashed or printed no parsed output on every

main-side run; not counted as ran or adequate); its matching results do not count; probe model-probe2 is

not_adequate (the probe crashed or printed no parsed output on every main-side run; not counted as ran or

adequate); its matching results do not count; tests: 9 test(s) ran on main, 10 on the PR; 1 new test(s) pass, 14

unchanged (5 of them skipped on both sides) | This is about the PR, not the run: read the failing tests and their

log lines, then decide.

Evals and guardrails

| Check | Result | Detail

| 3 alternating runs per side | PASS | main 3, PR 3 of 3

| pytest exit codes explained | PASS | all runs exited 0

| Changed code was exercised (coverage gate) | PASS | 3 of 6 changed executable line(s) ran (50%)

| Optional modules installed | WARN | unchanged tests skipped on both sides: PIL (5)

| Probes ran on both sides | WARN | model-probe1 main#1; model-probe1 main#2; model-probe1 main#3

| Single-thread environment | PASS | OMP_NUM_THREADS=1, OPENBLAS_NUM_THREADS=1,

MKL_NUM_THREADS=1, NUMEXPR_NUM_THREADS=1, VECLIB_MAXIMUM_THREADS=1,

BLIS_NUM_THREADS=1, PYTHONHASHSEED=0

| Machine type recorded | PASS | local x86_64 8 cpus

| Nothing posted upstream | PASS | GitHub was only read

| Known-answer replay (fresh re-run) | PASS | replayed 2026-10-10 06:30:21 IST, harness 1.0

| Every claim cites a real log line | WARN | 3 citation(s) verified; 3 statement(s) have no matching log line

| Every probe observation cites its output line | PASS | 7 citation(s), every one re-read from its log file and

matched

Checklist

• I read the verdict and the plain-English summary.

• Every 'false' or 'unmentioned change' row has a log line I can open.

• Nothing under 'What went wrong' is a run problem (those mean Re-run, not Reject).

• I recorded my decision (see below).

Decision recorded: none yet. To record one, run make decide

REPORT=poc-main/reports/daily/2026-11-08/python_qrcode-430 DECISION=approve (or reject,

approve_with_notes, re_run).

Rerun command

make check PR=https://github.com/lincolnloop/python-qrcode/pull/430

Evidence links

• Pull request lincolnloop/python-qrcode#430

• record.json

• pr.diff

• setup-main.log

• setup-pr.log

• git.log

• pytest-main-1.log

• pytest-pr-1.log

• pytest-main-2.log

• pytest-pr-2.log

• pytest-main-3.log

• pytest-pr-3.log

• junit-main-1.xml

• junit-pr-1.xml

• coverage-pytest.log

• coverage-pr.json

• probe-model-probe1-main-1.jsonl

• probe-model-probe1-pr-1.jsonl

• probe-model-probe2-main-1.jsonl

• probe-model-probe2-pr-1.jsonl

• probe-diff-api-main-1.jsonl

• probe-diff-api-pr-1.jsonl

• main run 1 result: pytest-main-1.log:7 «9 passed, 5 skipped in 0.54s»

• pr run 1 result: pytest-pr-1.log:7 «10 passed, 5 skipped in 0.53s»

Glossary

| Term | Meaning

| main | The library as it is today, without the PR.

| PR | Pull request: a proposed change to the library.

| run | One full pass of the selected tests. We do 3 per side, alternating main and PR.

| flaky | A test that gives different results when nothing changed; it is ignored as evidence.

| log line | A line in a pytest-*.log file: the raw output the verdict is based on.

| route | How the two sides were built: nightly+patch, source-build or source-pair (see docs/OPERATIONS.md).

| changed lines covered | How many of the PR's changed, executable Python lines ran during the PR side's tests.

| re-parametrized | A test whose parameter ids changed (renamed cases); the new ids are judged on their own.

rebuilt from cleaned text

Written 2026-11-09 12:01 IST