REPORT

Reviewer report: urllib3/urllib3#5371: Allow None as

filename in multipart file tuple type annotations

Run urllib3-5371, tested 2026-11-13 11:39 IST by ops/daily_run.py (route source-pair).
Proof-of-Change commit

ef12096677e9cf59e8673436d74ec65d53771d7c. Report generated 2026-11-13 12:33 IST by

reports/pr_report.py.

Baseline: full (test comparison + claim probes + coverage gate + claim flagging (differential probes shown,

informational)).

VERIFIED

Recommended action: Approve with notes Confidence: Medium

The PR's tests behave the same or better than on main, in all 3 runs per side. Some checks gave warnings:

Probes ran on both sides; Every claim cites a real log line

Advice only: Proof-of-Change never blocks a merge and never posts on GitHub.

Summary in plain English

• What it says it does: Allow None as filename in multipart file tuple type annotations (urllib3/urllib3#5371).

• What we observed: 29 test(s) ran on main, 34 on the PR; 5 new test(s) pass, 29 unchanged; probe: claim(s) C1

proven; probe model-p2 is not_adequate (the probe crashed or printed no parsed output on every main-side run;

not counted as ran or adequate); its matching results do not count.

• What you should do: You can approve; read the notes under 'What went wrong' first.

Demo helper

These notes are background from the console and the daily check. They do not change the verdict.

If setup fails, the helper retries the install up to 2 times. If a test still can't be verified because something is

missing or fails to import, it looks up the cause, installs the fix on both sides and reruns that step, up to 3 tries.

• Setup check: GitHub token: present.

• Setup check: Nebius token: present.

• Setup check: free memory 6.5 GB (of 15.6 GB).

• Setup check: free disk 91.7 GB.

• Demo helper: git is installed.

• Demo helper: python3 is installed.

• Demo helper: uv is installed.

• Looked up with Tavily: [redacted] results

• Query: urllib3 python setup install instructions https://github.com/urllib3/urllib3 site:github.com/urllib3/urllib3

• Query: urllib3 python documentation install https://github.com/urllib3/urllib3 site:github.com/urllib3/urllib3

• Query: urllib3 python install requirements https://pypi.org/project/urllib3/ https://github.com/urllib3/urllib3

site:pypi.org

• Source: urllib3 · PyPI — https://pypi.org/project/urllib3/

• Source: GitHub - urllib3/urllib3: urllib3 is a user-friendly HTTP client library for Python · GitHub —

https://github.com/urllib3/urllib3

• Source: urllib3 installation requires setuptools >= 36.2.5 · Issue #1753 · urllib3/urllib3 · GitHub —

https://github.com/urllib3/urllib3/issues/1753

• Source: urllib3/CHANGES.rst at main · urllib3/urllib3 · GitHub —

https://github.com/urllib3/urllib3/blob/main/CHANGES.rst

• Source: Installing urllib3 · Issue #829 · urllib3/urllib3 · GitHub — https://github.com/urllib3/urllib3/issues/829

• Setup plan: the same packages on main and pr.

• Setup plan: install trustme>=1.2.1 (listed in the test extra) on main and pr.

• Setup plan: Python 3.12: Python 3.12 already meets >=3.10

• Installed trustme 1.2.1 from pyproject (listed in the test extra) on main and pr.

Setup: pytest plugin asyncio was turned off. Pytest stopped at startup the same way on both sides, and the

traceback pointed into that third-party plugin (AttributeError: module 'pytest' has no attribute

'pyodide_options_stack'). The tests were run again with the plugin turned off. This does not change how the

verdict is chosen. Detection fired. Pytest stopped at startup the same way on both sides. Plugin chosen: asyncio.

The installed pytest plugin list was read. Retry flags: -p no:asyncio. Outcome: worked.

Claims vs reality

| # | Claim (source) | Status | What we observed | Log line

| C2 | Existing behavior is kept: tests that pass on main still pass (implied by every PR) | proven | no test that

passes on main fails on the PR (29 unchanged, 3 runs per side) | pytest-pr-1.log:87 «34 passed in 2.68s»

| P-C1 | RequestField.from_tuples and encode_multipart_formdata support omitting the filename by passing

(None, data, ...) in multipart form data, emitting Content-Disposition: form-data; name="..." without a filename

parameter. (PR description) | proven | probe model-p1, c1.requestfield_fromtuples_none_filename: same on

both sides: "Content-Disposition: form-data; name=\"field\"\r\nContent-Type: application/octet-stre... |

probe-model-p1-pr-1.jsonl:1 «"observation": "c1.requestfield_fromtuples_none_filename"»

| P-C1 | RequestField.from_tuples and encode_multipart_formdata support omitting the filename by passing

(None, data, ...) in multipart form data, emitting Content-Disposition: form-data; name="..." without a filename

parameter. (PR description) | not testable | probe model-p2 has no observation for this claim | no matching log

line

Citation check (WARN): 2 citation(s) verified; 1 statement(s) have no matching log line.

What changed in behavior

| What | Count | Examples

| Tests that actually ran (main / PR, fewest of the runs) | 29 / 34 | | Tests unchanged | 29 | | New tests that pass | 5 | | Tests that pass on main but fail on the PR | 0 | | Tests that are new in the PR and fail | 0 | | Tests that ran on main but are missing on the PR side | 0 | | Tests that changed result in another way (for example passed -> skipped) | 0 | | Tests that gave different results between the 3 runs of the same side (flaky) | 0 | | Tests that fail on main and pass on the PR | 0 | -

| Tests that are new or changed but did not run because an optional module is missing | 0 | | Tests that were re-parametrized (same test, new parameter ids; not counted as removed) | 0 | | Test modules that fail to load on the PR side only (their tests no longer run) | 0 | | Test modules that fail to load on main only (no baseline for their tests) | 0 | | Test modules that fail to load on both sides (their tests did not run) | 0 | | Tests that fail identically on both sides (already broken on main) | 0 | -

Probes

Model-written probes: model provider: nebius (Token Factory, live).

A probe is a small deterministic script run on both sides in the same environments as the tests, 3 alternating runs

per side. It prints JSON observations; plain code (poc/diff.py) compares them. A difference that no claim of the

PR covers needs attention. Every probe was frozen (content sha256) before any PR-side code ran, and checked

against that freeze before each PR-side run. Only a live model probe is blind; fixed probes and recorded model

fixtures are known-answer cases.

model-p1 (model (nvidia/nemotron-3-super-120b-a12b, live), model-probes/model-p1.py, frozen 8bb79a51a043

at 2026-11-13T06:10:46.115571+00:00): Test RequestField.from_tuples with None filename

• P-C1 (PR description): RequestField.from_tuples and encode_multipart_formdata support omitting the filename

by passing (None, data, ...) in multipart form data, emitting Content-Disposition: form-data; name="..." without a

filename parameter. Expects the covered observations to stay the same.

| Observation | Claim | Result | What the probe saw (main -> PR) | Log lines (main, PR)

| c1.requestfield_fromtuples_none_filename | P-C1 | as claimed | same on both sides: "Content-Disposition:

form-data; name=\"field\"\r\nContent-Type: application/octet-stre... | probe-model-p1-main-1.jsonl:1

«"observation": "c1.requestfield_fromtuples_none_filename"»
probe-model-p1-pr-1.jsonl:1 «"observation":

"c1.requestfield_fromtuples_none_filename"»

| c1.requestfield_fromtuples_none_filename_3tuple | P-C1 | as claimed | same on both sides:

"Content-Disposition: form-data; name=\"field\"\r\nContent-Type: text/plain\r\n\r\n" |

probe-model-p1-main-1.jsonl:2 «"observation":

"c1.requestfield_fromtuples_none_filename_3tuple"»
probe-model-p1-pr-1.jsonl:2 «"observation":

"c1.requestfield_fromtuples_none_filename_3tuple"»

| c1.requestfield_fromtuples_str_filename | P-C1 | as claimed | same on both sides: "Content-Disposition:

form-data; name=\"field\"; filename=\"file.txt\"\r\nContent-Type:... | probe-model-p1-main-1.jsonl:3 «"observation":

"c1.requestfield_fromtuples_str_filename"»
probe-model-p1-pr-1.jsonl:3 «"observation":

"c1.requestfield_fromtuples_str_filename"»

| c1.requestfield_fromtuples_str_filename_3tuple | P-C1 | as claimed | same on both sides: "Content-Disposition:

form-data; name=\"field\"; filename=\"file.txt\"\r\nContent-Type:... | probe-model-p1-main-1.jsonl:4 «"observation":

"c1.requestfield_fromtuples_str_filename_3tuple"»
probe-model-p1-pr-1.jsonl:4 «"observation":

"c1.requestfield_fromtuples_str_filename_3tuple"»

model-p2 (model (nvidia/nemotron-3-super-120b-a12b, live), model-probes/model-p2.py, frozen a032e2f779a9

at 2026-11-13T06:10:46.115747+00:00): Test encode_multipart_formdata with None filename (if available)

• P-C1 (PR description): RequestField.from_tuples and encode_multipart_formdata support omitting the filename

by passing (None, data, ...) in multipart form data, emitting Content-Disposition: form-data; name="..." without a

filename parameter. Expects the covered observations to stay the same.

| Observation | Claim | Result | What the probe saw (main -> PR) | Log lines (main, PR)

| probe.error | - | probe could not run | same on both sides: {"crash": "non-json output", "exit_code": 1} |

probe-model-p2-main-1.jsonl:1 «"observation": "probe.error"»
probe-model-p2-pr-1.jsonl:1 «"observation":

"probe.error"»

Citation check (PASS): 10 citation(s), every one re-read from its log file and matched.

Was the changed code exercised?

Coverage: MEASURED by coverage.py on the PR side (6.4 s run).

Coverage gate (python, confidence normal): 1 of 1 changed executable line(s) ran (100%).

| Changed file | Changed executable lines | Of those, ran

| src/urllib3/fields.py | 1 | 1

How this is measured: one extra, untimed run of the PR side's tests under coverage.py. Changed lines come

from comparing the tested main and PR files. Compiled code (C, C++, Cython) is invisible to coverage.py; such a

change only counts as verified when the PR adds or changes a test for that module.

What went right

• Tested fbdcad00a2e4 of the PR against main (source-pair route).

• 3 alternating runs per side: main 3, PR 3 of 3.

• pytest exit codes explained: all runs exited 0.

• Changed code was exercised (coverage gate): 1 of 1 changed executable line(s) ran (100%).

• Single-thread environment: OMP_NUM_THREADS=1, OPENBLAS_NUM_THREADS=1,

MKL_NUM_THREADS=1, NUMEXPR_NUM_THREADS=1, VECLIB_MAXIMUM_THREADS=1,

BLIS_NUM_THREADS=1, PYTHONHASHSEED=0.

• Machine type recorded: local x86_64 8 cpus.

• Nothing posted upstream: GitHub was only read.

• Known-answer replay (fresh re-run): replayed 2026-10-10 06:30:21 IST, harness 1.0.

• Every probe observation cites its output line: 10 citation(s), every one re-read from its log file and matched.

What went wrong and how to fix it

| Issue | Status | Detail | How to fix

| Probes ran on both sides | WARN | model-p2 main#1; model-p2 pr#1; model-p2 main#2 | Read the probe-*.log

files; a probe that cannot run is not evidence either way.

| Every claim cites a real log line | WARN | 2 citation(s) verified; 1 statement(s) have no matching log line |

Regenerate the report; if it persists, the logs were edited or truncated.

Evals and guardrails

| Check | Result | Detail

| 3 alternating runs per side | PASS | main 3, PR 3 of 3

| pytest exit codes explained | PASS | all runs exited 0

| Changed code was exercised (coverage gate) | PASS | 1 of 1 changed executable line(s) ran (100%)

| Probes ran on both sides | WARN | model-p2 main#1; model-p2 pr#1; model-p2 main#2

| Single-thread environment | PASS | OMP_NUM_THREADS=1, OPENBLAS_NUM_THREADS=1,

MKL_NUM_THREADS=1, NUMEXPR_NUM_THREADS=1, VECLIB_MAXIMUM_THREADS=1,

BLIS_NUM_THREADS=1, PYTHONHASHSEED=0

| Machine type recorded | PASS | local x86_64 8 cpus

| Nothing posted upstream | PASS | GitHub was only read

| Known-answer replay (fresh re-run) | PASS | replayed 2026-10-10 06:30:21 IST, harness 1.0

| Every claim cites a real log line | WARN | 2 citation(s) verified; 1 statement(s) have no matching log line

| Every probe observation cites its output line | PASS | 10 citation(s), every one re-read from its log file and

matched

Checklist

• I read the verdict and the plain-English summary.

• Every 'false' or 'unmentioned change' row has a log line I can open.

• Nothing under 'What went wrong' is a run problem (those mean Re-run, not Reject).

• I recorded my decision (see below).

Decision recorded: none yet. To record one, run make decide

REPORT=poc-main/reports/daily/2026-11-13/urllib3-5371 DECISION=approve (or reject,

approve_with_notes, re_run).

Rerun command

make check PR=https://github.com/urllib3/urllib3/pull/5371

Evidence links

• Pull request urllib3/urllib3#5371

• record.json

• pr.diff

• setup-main.log

• setup-pr.log

• git.log

• pytest-main-1.log

• pytest-pr-1.log

• pytest-main-2.log

• pytest-pr-2.log

• pytest-main-3.log

• pytest-pr-3.log

• junit-main-1.xml

• junit-pr-1.xml

• coverage-pytest.log

• coverage-pr.json

• probe-model-p1-main-1.jsonl

• probe-model-p1-pr-1.jsonl

• probe-model-p2-main-1.jsonl

• probe-model-p2-pr-1.jsonl

• main run 1 result: pytest-main-1.log:87 «29 passed in 2.58s»

• pr run 1 result: pytest-pr-1.log:87 «34 passed in 2.68s»

Glossary

| Term | Meaning

| main | The library as it is today, without the PR.

| PR | Pull request: a proposed change to the library.

| run | One full pass of the selected tests. We do 3 per side, alternating main and PR.

| flaky | A test that gives different results when nothing changed; it is ignored as evidence.

| log line | A line in a pytest-*.log file: the raw output the verdict is based on.

| route | How the two sides were built: nightly+patch, source-build or source-pair (see docs/OPERATIONS.md).

| changed lines covered | How many of the PR's changed, executable Python lines ran during the PR side's tests.

| re-parametrized | A test whose parameter ids changed (renamed cases); the new ids are judged on their own.

rebuilt from cleaned text

Written 2026-11-13 12:33 IST