

Binary Classification

Alan Ritter

(many slides from Greg Durrett and Vivek Srikumar)

This Lecture

- ▶ Linear classification fundamentals
- ▶ Naive Bayes, maximum likelihood in generative models
- ▶ Three discriminative models: logistic regression, perceptron, SVM
 - ▶ Different motivations but very similar update rules / inference!

Classification

Classification

Classification


- ▶ Datapoint x with label $y \in \{0, 1\}$

Classification

- ▶ Datapoint x with label $y \in \{0, 1\}$
- ▶ Embed datapoint in a feature space $f(x) \in \mathbb{R}^n$
but in this lecture $f(x)$ and x are interchangeable


Classification

- ▶ Datapoint x with label $y \in \{0, 1\}$
- ▶ Embed datapoint in a feature space $f(x) \in \mathbb{R}^n$
but in this lecture $f(x)$ and x are interchangeable




Classification

- ▶ Datapoint x with label $y \in \{0, 1\}$
- ▶ Embed datapoint in a feature space $f(x) \in \mathbb{R}^n$
but in this lecture $f(x)$ and x are interchangeable
- ▶ Linear decision rule: $w^\top f(x) + b > 0$




Classification

- ▶ Datapoint x with label $y \in \{0, 1\}$
- ▶ Embed datapoint in a feature space $f(x) \in \mathbb{R}^n$
but in this lecture $f(x)$ and x are interchangeable
- ▶ Linear decision rule: $w^\top f(x) + b > 0$




Classification

- ▶ Datapoint x with label $y \in \{0, 1\}$
- ▶ Embed datapoint in a feature space $f(x) \in \mathbb{R}^n$
but in this lecture $f(x)$ and x are interchangeable
- ▶ Linear decision rule: $w^\top f(x) + b > 0$
 $w^\top f(x) > 0$




Classification


- ▶ Datapoint x with label $y \in \{0, 1\}$
- ▶ Embed datapoint in a feature space $f(x) \in \mathbb{R}^n$
but in this lecture $f(x)$ and x are interchangeable
- ▶ Linear decision rule: $w^\top f(x) + b > 0$
 $w^\top f(x) > 0$
- ▶ Can delete bias if we augment feature space:
 $f(x) = [0.5, 1.6, 0.3]$
↓
[0.5, 1.6, 0.3, 1]




Linear functions are powerful!



Linear functions are powerful!





Linear functions are powerful!





$$f(x) = [x_1, x_2, x_1^2, x_2^2, x_1 x_2]$$



Linear functions are powerful!





Linear functions are powerful!



Linear functions are powerful!



Linear functions are powerful!



- ▶ “Kernel trick” does this for “free,” but is too expensive to use in NLP applications, training is $O(n^2)$ instead of $O(n \cdot (\text{num feats}))$

Classification: Sentiment Analysis

Classification: Sentiment Analysis

this movie was great! would watch again

Classification: Sentiment Analysis

this movie was great! would watch again

Positive

Classification: Sentiment Analysis

this movie was great! would watch again

Positive

Classification: Sentiment Analysis

this movie was great! would watch again

Positive

that film was awful, I'll never watch again

Classification: Sentiment Analysis

this movie was great! would watch again

Positive

that film was awful, I'll never watch again

Negative

Classification: Sentiment Analysis

this movie was great! would watch again

Positive

that film was awful, I'll never watch again

Negative

Classification: Sentiment Analysis

this movie was great! would watch again

Positive

that film was awful, I'll never watch again

Negative

Classification: Sentiment Analysis

this movie was great! would watch again

Positive

that film was awful, I'll never watch again

Negative

- ▶ Surface cues can basically tell you what's going on here: presence or absence of certain words (*great, awful*)

Classification: Sentiment Analysis

this movie was great! would watch again

Positive

that film was awful, I'll never watch again

Negative

- ▶ Surface cues can basically tell you what's going on here: presence or absence of certain words (*great, awful*)
- ▶ Steps to classification:

Classification: Sentiment Analysis

this movie was great! would watch again

Positive

that film was awful, I'll never watch again

Negative

- ▶ Surface cues can basically tell you what's going on here: presence or absence of certain words (*great, awful*)
- ▶ Steps to classification:
 - ▶ Turn examples like this into feature vectors

Classification: Sentiment Analysis

this movie was great! would watch again

Positive

that film was awful, I'll never watch again

Negative

- ▶ Surface cues can basically tell you what's going on here: presence or absence of certain words (*great, awful*)
- ▶ Steps to classification:
 - ▶ Turn examples like this into feature vectors
 - ▶ Pick a model / learning algorithm

Classification: Sentiment Analysis

this movie was great! would watch again

Positive

that film was awful, I'll never watch again

Negative

- ▶ Surface cues can basically tell you what's going on here: presence or absence of certain words (*great, awful*)
- ▶ Steps to classification:
 - ▶ Turn examples like this into feature vectors
 - ▶ Pick a model / learning algorithm
 - ▶ Train weights on data to get our classifier

Feature Representation

this movie was great! would watch again

Positive

- ▶ Convert this example to a vector using *bag-of-words features*

Feature Representation

this movie was great! would watch again

Positive

- ▶ Convert this example to a vector using *bag-of-words features*

[contains *the*] [contains *a*] [contains *was*] [contains *movie*] [contains *film*] ...

Feature Representation

this movie was great! would watch again

Positive

- ▶ Convert this example to a vector using *bag-of-words features*

[contains *the*] [contains *a*] [contains *was*] [contains *movie*] [contains *film*] ...
position 0 position 1 position 2 position 3 position 4

Feature Representation

this movie was great! would watch again

Positive

- ▶ Convert this example to a vector using *bag-of-words features*

[contains *the*] [contains *a*] [contains *was*] [contains *movie*] [contains *film*] ...
position 0 position 1 position 2 position 3 position 4

$$f(x) = [$$

Feature Representation

this movie was great! would watch again

Positive

- ▶ Convert this example to a vector using *bag-of-words features*

[contains *the*] [contains *a*] [contains *was*] [contains *movie*] [contains *film*] ...
position 0 position 1 position 2 position 3 position 4

$$f(x) = [0$$

Feature Representation

this movie was great! would watch again

Positive

- ▶ Convert this example to a vector using *bag-of-words features*

[contains *the*] [contains *a*] [contains *was*] [contains *movie*] [contains *film*] ...

position 0

position 1

position 2

position 3

position 4

$$f(x) = [0 \quad 0 \quad 1 \quad 1 \quad 0 \quad \dots]$$

Feature Representation

this movie was great! would watch again

Positive

- ▶ Convert this example to a vector using *bag-of-words features*

[contains *the*] [contains *a*] [contains *was*] [contains *movie*] [contains *film*] ...

position 0

position 1

position 2

position 3

position 4

$$f(x) = [0$$

0

1

Feature Representation

this movie was great! would watch again

Positive

- ▶ Convert this example to a vector using *bag-of-words features*

[contains *the*] [contains *a*] [contains *was*] [contains *movie*] [contains *film*] ...

position 0

position 1

position 2

position 3

position 4

$$f(x) = [0$$

0

1

1

Feature Representation

this movie was great! would watch again

Positive

- ▶ Convert this example to a vector using *bag-of-words features*

[contains *the*] [contains *a*] [contains *was*] [contains *movie*] [contains *film*] ...

position 0

position 1

position 2

position 3

position 4

$$f(x) = [0$$

0

1

1

0

Feature Representation

this movie was great! would watch again

Positive

- ▶ Convert this example to a vector using *bag-of-words features*

[contains *the*] [contains *a*] [contains *was*] [contains *movie*] [contains *film*] ...

position 0

position 1

position 2

position 3

position 4

$$f(x) = [0$$

0

1

1

0

...

Feature Representation

this movie was great! would watch again Positive

- ▶ Convert this example to a vector using *bag-of-words features*

[contains <i>the</i>]	[contains <i>a</i>]	[contains <i>was</i>]	[contains <i>movie</i>]	[contains <i>film</i>]	...
position 0	position 1	position 2	position 3	position 4	
$f(x) = [0$	0	1	1	0	...

- ▶ Very large vector space (size of vocabulary), sparse features

Feature Representation

this movie was great! would watch again Positive

- ▶ Convert this example to a vector using *bag-of-words features*

[contains <i>the</i>]	[contains <i>a</i>]	[contains <i>was</i>]	[contains <i>movie</i>]	[contains <i>film</i>]	...
position 0	position 1	position 2	position 3	position 4	
$f(x) = [0$	0	1	1	0	...

- ▶ Very large vector space (size of vocabulary), sparse features
- ▶ Requires *indexing* the features (mapping them to axes)

Feature Representation

this movie was great! would watch again Positive

- ▶ Convert this example to a vector using *bag-of-words features*

[contains <i>the</i>]	[contains <i>a</i>]	[contains <i>was</i>]	[contains <i>movie</i>]	[contains <i>film</i>]	...
position 0	position 1	position 2	position 3	position 4	
$f(x) = [0$	0	1	1	0	...

- ▶ Very large vector space (size of vocabulary), sparse features
- ▶ Requires *indexing* the features (mapping them to axes)
- ▶ More sophisticated feature mappings possible (tf-idf), as well as lots of other features: character n-grams, parts of speech, lemmas, ...

Naive Bayes

Naive Bayes

- ▶ Data point $x = (x_1, \dots, x_n)$, label $y \in \{0, 1\}$

Naive Bayes

- ▶ Data point $x = (x_1, \dots, x_n)$, label $y \in \{0, 1\}$
- ▶ Formulate a probabilistic model that places a distribution $P(x, y)$

Naive Bayes

- ▶ Data point $x = (x_1, \dots, x_n)$, label $y \in \{0, 1\}$
- ▶ Formulate a probabilistic model that places a distribution $P(x, y)$
- ▶ Compute $P(y|x)$, predict $\text{argmax}_y P(y|x)$ to classify

Naive Bayes

- ▶ Data point $x = (x_1, \dots, x_n)$, label $y \in \{0, 1\}$
- ▶ Formulate a probabilistic model that places a distribution $P(x, y)$
- ▶ Compute $P(y|x)$, predict $\text{argmax}_y P(y|x)$ to classify

$$P(y|x) = \frac{P(y)P(x|y)}{P(x)}$$

Bayes' Rule

Naive Bayes

- ▶ Data point $x = (x_1, \dots, x_n)$, label $y \in \{0, 1\}$
- ▶ Formulate a probabilistic model that places a distribution $P(x, y)$
- ▶ Compute $P(y|x)$, predict $\text{argmax}_y P(y|x)$ to classify

$$P(y|x) = \frac{P(y)P(x|y)}{P(x)}$$

Bayes' Rule

constant: irrelevant
for finding the max

Naive Bayes

- ▶ Data point $x = (x_1, \dots, x_n)$, label $y \in \{0, 1\}$
- ▶ Formulate a probabilistic model that places a distribution $P(x, y)$
- ▶ Compute $P(y|x)$, predict $\text{argmax}_y P(y|x)$ to classify

$$P(y|x) = \frac{P(y)P(x|y)}{P(x)}$$

Bayes' Rule

$\alpha P(y)P(x|y)$

constant: irrelevant
for finding the max

Naive Bayes

- ▶ Data point $x = (x_1, \dots, x_n)$, label $y \in \{0, 1\}$
- ▶ Formulate a probabilistic model that places a distribution $P(x, y)$
- ▶ Compute $P(y|x)$, predict $\text{argmax}_y P(y|x)$ to classify

$$P(y|x) = \frac{P(y)P(x|y)}{P(x)}$$

Bayes' Rule

\leftarrow constant: irrelevant
for finding the max

$$\propto P(y)P(x|y)$$

$$= P(y) \prod_{i=1}^n P(x_i|y)$$

Naive Bayes

- ▶ Data point $x = (x_1, \dots, x_n)$, label $y \in \{0, 1\}$
- ▶ Formulate a probabilistic model that places a distribution $P(x, y)$
- ▶ Compute $P(y|x)$, predict $\text{argmax}_y P(y|x)$ to classify

$$\begin{aligned} P(y|x) &= \frac{P(y)P(x|y)}{P(x)} && \text{Bayes' Rule} \\ &\propto P(y)P(x|y) && \text{constant: irrelevant} \\ &= P(y) \prod_{i=1}^n P(x_i|y) && \text{for finding the max} \end{aligned}$$


“Naive” assumption:

The diagram consists of two arrows. One arrow points from the term $P(x)$ in the first equation to the text "constant: irrelevant for finding the max". Another arrow points from the term n in the third equation to the text "‘Naive’ assumption:".

Naive Bayes

- ▶ Data point $x = (x_1, \dots, x_n)$, label $y \in \{0, 1\}$
- ▶ Formulate a probabilistic model that places a distribution $P(x, y)$
- ▶ Compute $P(y|x)$, predict $\text{argmax}_y P(y|x)$ to classify

$$\begin{aligned} P(y|x) &= \frac{P(y)P(x|y)}{P(x)} && \text{Bayes' Rule} \\ &\propto P(y)P(x|y) && \text{constant: irrelevant} \\ &= P(y) \prod_{i=1}^n P(x_i|y) && \text{for finding the max} \\ &&& \text{“Naive” assumption:} \end{aligned}$$



Naive Bayes


- ▶ Data point $x = (x_1, \dots, x_n)$, label $y \in \{0, 1\}$
- ▶ Formulate a probabilistic model that places a distribution $P(x, y)$
- ▶ Compute $P(y|x)$, predict $\text{argmax}_y P(y|x)$ to classify

$$\begin{aligned} P(y|x) &= \frac{P(y)P(x|y)}{P(x)} \\ &\propto P(y)P(x|y) \\ &= P(y) \prod_{i=1}^n P(x_i|y) \end{aligned}$$

Bayes' Rule

constant: irrelevant
for finding the max

“Naive” assumption:



$$\text{argmax}_y P(y|x) = \text{argmax}_y \log P(y|x) = \text{argmax}_y \left[\log P(y) + \sum_{i=1}^n \log P(x_i|y) \right]$$

Naive Bayes

- ▶ Data point $x = (x_1, \dots, x_n)$, label $y \in \{0, 1\}$
- ▶ Formulate a probabilistic model that places a distribution $P(x, y)$
- ▶ Compute $P(y|x)$, predict $\text{argmax}_y P(y|x)$ to classify

$$P(y|x) = \frac{P(y)P(x|y)}{P(x)}$$


$$\propto P(y)P(x|y)$$

$$= P(y) \prod_{i=1}^n P(x_i|y)$$

Bayes' Rule

constant: irrelevant
for finding the max

“Naive” assumption:



linear model!

$$\text{argmax}_y P(y|x) = \text{argmax}_y \log P(y|x) = \text{argmax}_y \left[\log P(y) + \sum_{i=1}^n \log P(x_i|y) \right]$$

Naive Bayes Example

$$it\ was\ great \longrightarrow P(y|x) \propto []$$

$$P(y|x) \propto P(y) \prod_{i=1}^n P(x_i|y)$$

$$\operatorname{argmax}_y \log P(y|x) = \operatorname{argmax}_y \left[\log P(y) + \sum_{i=1}^n \log P(x_i|y) \right]$$

Maximum Likelihood Estimation

Maximum Likelihood Estimation

- ▶ Data points (x_j, y_j) provided (j indexes over examples)

Maximum Likelihood Estimation

- ▶ Data points (x_j, y_j) provided (j indexes over examples)
- ▶ Find values of $P(y)$, $P(x_i|y)$ that maximize data likelihood (generative):

Maximum Likelihood Estimation

- ▶ Data points (x_j, y_j) provided (j indexes over examples)
- ▶ Find values of $P(y)$, $P(x_i|y)$ that maximize data likelihood (generative):

$$\prod_{j=1}^m P(y_j, x_j) = \prod_{j=1}^m P(y_j) \left[\prod_{i=1}^n P(x_{ji}|y_j) \right]$$

Maximum Likelihood Estimation

- ▶ Data points (x_j, y_j) provided (j indexes over examples)
- ▶ Find values of $P(y)$, $P(x_i|y)$ that maximize data likelihood (generative):

$$\prod_{j=1}^m P(y_j, x_j) = \prod_{j=1}^m P(y_j) \left[\prod_{i=1}^n P(x_{ji}|y_j) \right]$$


data points (j) features (i)

Maximum Likelihood Estimation

- ▶ Data points (x_j, y_j) provided (j indexes over examples)
- ▶ Find values of $P(y)$, $P(x_i|y)$ that maximize data likelihood (generative):

$$\prod_{j=1}^m P(y_j, x_j) = \prod_{j=1}^m P(y_j) \left[\prod_{i=1}^n P(x_{ji}|y_j) \right]$$

data points (j) features (i) i th feature of j th example

Maximum Likelihood Estimation

Maximum Likelihood Estimation

- ▶ Imagine a coin flip which is heads with probability p

Maximum Likelihood Estimation

- ▶ Imagine a coin flip which is heads with probability p
- ▶ Observe (H, H, H, T) and maximize likelihood:

Maximum Likelihood Estimation

- ▶ Imagine a coin flip which is heads with probability p
- ▶ Observe (H, H, H, T) and maximize likelihood: $\prod_{j=1}^m P(y_j) = p^3(1 - p)$

Maximum Likelihood Estimation


- ▶ Imagine a coin flip which is heads with probability p
- ▶ Observe (H, H, H, T) and maximize likelihood: $\prod_{j=1}^m P(y_j) = p^3(1 - p)$
- ▶ Easier: maximize *log* likelihood

$$\sum_{j=1}^m \log P(y_j) = 3 \log p + \log(1 - p)$$

Maximum Likelihood Estimation

- ▶ Imagine a coin flip which is heads with probability p
- ▶ Observe (H, H, H, T) and maximize likelihood: $\prod_{j=1}^m P(y_j) = p^3(1 - p)$
- ▶ Easier: maximize *log* likelihood


$$\sum_{j=1}^m \log P(y_j) = 3 \log p + \log(1 - p)$$



Maximum Likelihood Estimation

- ▶ Imagine a coin flip which is heads with probability p
- ▶ Observe (H, H, H, T) and maximize likelihood: $\prod_{j=1}^m P(y_j) = p^3(1 - p)$
- ▶ Easier: maximize *log* likelihood

$$\sum_{j=1}^m \log P(y_j) = 3 \log p + \log(1 - p)$$




Maximum Likelihood Estimation

- ▶ Imagine a coin flip which is heads with probability p
- ▶ Observe (H, H, H, T) and maximize likelihood: $\prod_{j=1}^m P(y_j) = p^3(1 - p)$

- ▶ Easier: maximize *log* likelihood

$$\sum_{j=1}^m \log P(y_j) = 3 \log p + \log(1 - p)$$

- ▶ Maximum likelihood parameters for binomial/multinomial = read counts off of the data + normalize



Maximum Likelihood Estimation

- ▶ Data points (x_j, y_j) provided (j indexes over examples)
- ▶ Find values of $P(y)$, $P(x_i|y)$ that maximize data likelihood (generative):

$$\prod_{j=1}^m P(y_j, x_j) = \prod_{j=1}^m P(y_j) \left[\prod_{i=1}^n P(x_{ji}|y_j) \right]$$

data points (j) features (i) i th feature of j th example

- ▶ Equivalent to maximizing logarithm of data likelihood:

$$\sum_{j=1}^m \log P(y_j, x_j) = \sum_{j=1}^m \left[\log P(y_j) + \sum_{i=1}^n \log P(x_{ji}|y_j) \right]$$

Maximum Likelihood for Naive Bayes

this movie was great! would watch again

+

I liked it well enough for an action flick

+

I expected a great film and left happy

+

brilliant directing and stunning visuals

+

that film was awful, I'll never watch again

—

I didn't really like that movie

—

dry and a bit distasteful, it misses the mark

—

great potential but ended up being a flop

—

Maximum Likelihood for Naive Bayes

this movie was great! would watch again

+

I liked it well enough for an action flick

+

I expected a great film and left happy

+

brilliant directing and stunning visuals

+

that film was awful, I'll never watch again

—

I didn't really like that movie

—

dry and a bit distasteful, it misses the mark

—

great potential but ended up being a flop

—

$$P(+) = \frac{1}{2}$$

$$P(-) = \frac{1}{2}$$

Maximum Likelihood for Naive Bayes

this movie was great! would watch again

+

I liked it well enough for an action flick

+

I expected a great film and left happy

+

brilliant directing and stunning visuals

+

that film was awful, I'll never watch again

—

I didn't really like that movie

—

dry and a bit distasteful, it misses the mark

—

great potential but ended up being a flop

—

$$P(+) = \frac{1}{2}$$

$$P(-) = \frac{1}{2}$$

$$P(\text{great}|+) = \frac{1}{2}$$

Maximum Likelihood for Naive Bayes

this movie was great! would watch again

+

I liked it well enough for an action flick

+

I expected a great film and left happy

+

brilliant directing and stunning visuals

+

that film was awful, I'll never watch again

—

I didn't really like that movie

—

dry and a bit distasteful, it misses the mark

—

great potential but ended up being a flop

—

$$P(+) = \frac{1}{2}$$

$$P(-) = \frac{1}{2}$$

$$P(\text{great}|+) = \frac{1}{2}$$

$$P(\text{great}|-) =$$

Maximum Likelihood for Naive Bayes

this movie was great! would watch again

+

I liked it well enough for an action flick

+

I expected a great film and left happy

+

brilliant directing and stunning visuals

+

that film was awful, I'll never watch again

—

I didn't really like that movie

—

dry and a bit distasteful, it misses the mark

—

great potential but ended up being a flop

—

$$P(+) = \frac{1}{2}$$

$$P(-) = \frac{1}{2}$$

$$P(\text{great}|+) = \frac{1}{2}$$

$$P(\text{great}|-) = \frac{1}{4}$$

Maximum Likelihood for Naive Bayes

this movie was **great!** would watch again

+

I liked it well enough for an action flick

+

I expected a **great** film and left happy

+

brilliant directing and stunning visuals

+

that film was awful, I'll never watch again

—

I didn't really like that movie

—

dry and a bit distasteful, it misses the mark

—

great potential but ended up being a flop

—

it was great

$$P(+) = \frac{1}{2}$$

$$P(-) = \frac{1}{2}$$

$$P(\text{great}|+) = \frac{1}{2}$$

$$P(\text{great}|-) = \frac{1}{4}$$

Maximum Likelihood for Naive Bayes

this movie was great! would watch again

+

I liked it well enough for an action flick

+

I expected a great film and left happy

+

brilliant directing and stunning visuals

+

that film was awful, I'll never watch again

-

I didn't really like that movie

-

dry and a bit distasteful, it misses the mark

-

great potential but ended up being a flop

-

$$P(+) = \frac{1}{2}$$

$$P(-) = \frac{1}{2}$$

$$P(\text{great}|+) = \frac{1}{2}$$

$$P(\text{great}|-) = \frac{1}{4}$$

$$\text{it was great} \longrightarrow P(y|x) \propto \begin{bmatrix} P(+)\text{P(great|+)} \\ P(-)\text{P(great|-)} \end{bmatrix}$$

Maximum Likelihood for Naive Bayes

this movie was great! would watch again

+

I liked it well enough for an action flick

+

I expected a great film and left happy

+

brilliant directing and stunning visuals

+

that film was awful, I'll never watch again

-

I didn't really like that movie

-

dry and a bit distasteful, it misses the mark

-

great potential but ended up being a flop

-

$$P(+) = \frac{1}{2}$$

$$P(-) = \frac{1}{2}$$

$$P(\text{great}|+) = \frac{1}{2}$$


$$P(\text{great}|-) = \frac{1}{4}$$

$$\text{it was great} \longrightarrow P(y|x) \propto \begin{bmatrix} P(+)\text{P(great|+)} \\ P(-)\text{P(great|-)} \end{bmatrix} = \begin{bmatrix} 1/4 \\ 1/8 \end{bmatrix} = \begin{bmatrix} 2/3 \\ 1/3 \end{bmatrix}$$

Naive Bayes: Summary

► Model


$$P(x, y) = P(y) \prod_{i=1}^n P(x_i | y)$$



Naive Bayes: Summary

► Model

$$P(x, y) = P(y) \prod_{i=1}^n P(x_i|y)$$




► Inference

$$\operatorname{argmax}_y \log P(y|x) = \operatorname{argmax}_y \left[\log P(y) + \sum_{i=1}^n \log P(x_i|y) \right]$$

Naive Bayes: Summary

► Model

$$P(x, y) = P(y) \prod_{i=1}^n P(x_i|y)$$



► Inference


$$\operatorname{argmax}_y \log P(y|x) = \operatorname{argmax}_y \left[\log P(y) + \sum_{i=1}^n \log P(x_i|y) \right]$$

► Alternatively: $\log P(y=+|x) - \log P(y=-|x) > 0$

Naive Bayes: Summary

► Model

$$P(x, y) = P(y) \prod_{i=1}^n P(x_i|y)$$



► Inference

$$\operatorname{argmax}_y \log P(y|x) = \operatorname{argmax}_y \left[\log P(y) + \sum_{i=1}^n \log P(x_i|y) \right]$$


► Alternatively: $\log P(y=+|x) - \log P(y=-|x) > 0$

$$\Leftrightarrow \log \frac{P(y=+)}{P(y=-)} + \sum_{i=1}^n \log \frac{P(x_i|y=+)}{P(x_i|y=-)} > 0$$

Naive Bayes: Summary

► Model

$$P(x, y) = P(y) \prod_{i=1}^n P(x_i|y)$$



► Inference

$$\operatorname{argmax}_y \log P(y|x) = \operatorname{argmax}_y \left[\log P(y) + \sum_{i=1}^n \log P(x_i|y) \right]$$

► Alternatively: $\log P(y=+|x) - \log P(y=-|x) > 0$

$$\Leftrightarrow \log \frac{P(y=+)}{P(y=-)} + \sum_{i=1}^n \log \frac{P(x_i|y=+)}{P(x_i|y=-)} > 0$$

► Learning: maximize $P(x, y)$ by reading counts off the data

Problems with Naive Bayes

the film was beautiful, stunning cinematography and gorgeous sets, but boring —

$$P(x_{\text{beautiful}}|+) = 0.1 \quad P(x_{\text{beautiful}}|-) = 0.01$$

$$P(x_{\text{stunning}}|+) = 0.1 \quad P(x_{\text{stunning}}|-) = 0.01$$

$$P(x_{\text{gorgeous}}|+) = 0.1 \quad P(x_{\text{gorgeous}}|-) = 0.01$$

$$P(x_{\text{boring}}|+) = 0.01 \quad P(x_{\text{boring}}|-) = 0.1$$

Problems with Naive Bayes

the film was beautiful, stunning cinematography and gorgeous sets, but boring —

$$P(x_{\text{beautiful}}|+) = 0.1 \quad P(x_{\text{beautiful}}|-) = 0.01$$

$$P(x_{\text{stunning}}|+) = 0.1 \quad P(x_{\text{stunning}}|-) = 0.01$$

$$P(x_{\text{gorgeous}}|+) = 0.1 \quad P(x_{\text{gorgeous}}|-) = 0.01$$

$$P(x_{\text{boring}}|+) = 0.01 \quad P(x_{\text{boring}}|-) = 0.1$$

- ▶ Correlated features compound: *beautiful* and *gorgeous* are not independent!

Problems with Naive Bayes

the film was beautiful, stunning cinematography and gorgeous sets, but boring —

$$P(x_{\text{beautiful}}|+) = 0.1 \quad P(x_{\text{beautiful}}|-) = 0.01$$

$$P(x_{\text{stunning}}|+) = 0.1 \quad P(x_{\text{stunning}}|-) = 0.01$$

$$P(x_{\text{gorgeous}}|+) = 0.1 \quad P(x_{\text{gorgeous}}|-) = 0.01$$

$$P(x_{\text{boring}}|+) = 0.01 \quad P(x_{\text{boring}}|-) = 0.1$$

- ▶ Correlated features compound: *beautiful* and *gorgeous* are not independent!
- ▶ Naive Bayes is naive, but another problem is that it's *generative*: spends capacity modeling $P(x,y)$, when what we care about is $P(y|x)$

Problems with Naive Bayes

the film was beautiful, stunning cinematography and gorgeous sets, but boring —

$$P(x_{\text{beautiful}}|+) = 0.1 \quad P(x_{\text{beautiful}}|-) = 0.01$$

$$P(x_{\text{stunning}}|+) = 0.1 \quad P(x_{\text{stunning}}|-) = 0.01$$

$$P(x_{\text{gorgeous}}|+) = 0.1 \quad P(x_{\text{gorgeous}}|-) = 0.01$$

$$P(x_{\text{boring}}|+) = 0.01 \quad P(x_{\text{boring}}|-) = 0.1$$

- ▶ Correlated features compound: *beautiful* and *gorgeous* are not independent!
- ▶ Naive Bayes is naive, but another problem is that it's *generative*: spends capacity modeling $P(x,y)$, when what we care about is $P(y|x)$
- ▶ Discriminative models model $P(y|x)$ directly (SVMs, most neural networks, ...)

Homework 1 Demo

(Numpy)

Logistic Regression


Logistic Regression

Logistic Regression

$$P(y = +|x) = \text{logistic}(w^\top x)$$

Logistic Regression


$$P(y = +|x) = \text{logistic}(w^\top x)$$



Logistic Regression

$$P(y = +|x) = \text{logistic}(w^\top x)$$


$$P(y = +|x) = \frac{\exp(\sum_{i=1}^n w_i x_i)}{1 + \exp(\sum_{i=1}^n w_i x_i)}$$



Logistic Regression

$$P(y = +|x) = \text{logistic}(w^\top x)$$

$$P(y = +|x) = \frac{\exp(\sum_{i=1}^n w_i x_i)}{1 + \exp(\sum_{i=1}^n w_i x_i)}$$




- ▶ To learn weights: maximize discriminative log likelihood of data $P(y|x)$

Logistic Regression

$$P(y = +|x) = \text{logistic}(w^\top x)$$

$$P(y = +|x) = \frac{\exp(\sum_{i=1}^n w_i x_i)}{1 + \exp(\sum_{i=1}^n w_i x_i)}$$




- ▶ To learn weights: maximize discriminative log likelihood of data $P(y|x)$

$$\mathcal{L}(x_j, y_j = +) = \log P(y_j = +|x_j)$$

Logistic Regression

$$P(y = +|x) = \text{logistic}(w^\top x)$$

$$P(y = +|x) = \frac{\exp(\sum_{i=1}^n w_i x_i)}{1 + \exp(\sum_{i=1}^n w_i x_i)}$$



- ▶ To learn weights: maximize discriminative log likelihood of data $P(y|x)$


$$\mathcal{L}(x_j, y_j = +) = \log P(y_j = +|x_j)$$

$$= \sum_{i=1}^n w_i x_{ji} - \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

Logistic Regression

$$P(y = +|x) = \text{logistic}(w^\top x)$$

$$P(y = +|x) = \frac{\exp(\sum_{i=1}^n w_i x_i)}{1 + \exp(\sum_{i=1}^n w_i x_i)}$$



- To learn weights: maximize discriminative log likelihood of data $P(y|x)$

$$\begin{aligned}\mathcal{L}(x_j, y_j = +) &= \log P(y_j = +|x_j) \\ &= \sum_{i=1}^n w_i x_{ji} - \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)\end{aligned}$$

sum over features →

Logistic Regression

Logistic Regression

$$\mathcal{L}(x_j, y_j = +) = \log P(y_j = + | x_j) = \sum_{i=1}^n w_i x_{ji} - \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

Logistic Regression

$$\mathcal{L}(x_j, y_j = +) = \log P(y_j = + | x_j) = \sum_{i=1}^n w_i x_{ji} - \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

$$\frac{\partial \mathcal{L}(x_j, y_j)}{\partial w_i} =$$

Logistic Regression

$$\mathcal{L}(x_j, y_j = +) = \log P(y_j = + | x_j) = \sum_{i=1}^n w_i x_{ji} - \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

$$\frac{\partial \mathcal{L}(x_j, y_j)}{\partial w_i} = x_{ji} - \frac{\partial}{\partial w_i} \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

Logistic Regression

$$\mathcal{L}(x_j, y_j = +) = \log P(y_j = + | x_j) = \boxed{\sum_{i=1}^n w_i x_{ji}} - \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

$$\frac{\partial \mathcal{L}(x_j, y_j)}{\partial w_i} = \boxed{x_{ji}} - \frac{\partial}{\partial w_i} \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

Logistic Regression

$$\mathcal{L}(x_j, y_j = +) = \log P(y_j = + | x_j) = \sum_{i=1}^n w_i x_{ji} - \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

$$\frac{\partial \mathcal{L}(x_j, y_j)}{\partial w_i} = x_{ji} - \frac{\partial}{\partial w_i} \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

$$= x_{ji} - \frac{1}{1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right)} \frac{\partial}{\partial w_i} \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

deriv
of log

Logistic Regression

$$\mathcal{L}(x_j, y_j = +) = \log P(y_j = + | x_j) = \sum_{i=1}^n w_i x_{ji} - \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

$$\frac{\partial \mathcal{L}(x_j, y_j)}{\partial w_i} = x_{ji} - \frac{\partial}{\partial w_i} \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

$$= x_{ji} - \frac{1}{1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right)} \frac{\partial}{\partial w_i} \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

$$= x_{ji} - \frac{1}{1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right)} x_{ji} \exp \left(\sum_{i=1}^n w_i x_{ji} \right)$$

deriv
of log

deriv
of exp

Logistic Regression

$$\mathcal{L}(x_j, y_j = +) = \log P(y_j = + | x_j) = \boxed{\sum_{i=1}^n w_i x_{ji}} - \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

$$\frac{\partial \mathcal{L}(x_j, y_j)}{\partial w_i} = \boxed{x_{ji}} - \frac{\partial}{\partial w_i} \log \left(\boxed{1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right)} \right)$$

$$= x_{ji} - \frac{1}{\boxed{1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right)}} \frac{\partial}{\partial w_i} \left(\boxed{1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right)} \right)$$

$$= x_{ji} - \frac{1}{1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right)} x_{ji} \exp \left(\sum_{i=1}^n w_i x_{ji} \right)$$

deriv
of log

deriv
of exp

Logistic Regression

$$\mathcal{L}(x_j, y_j = +) = \log P(y_j = + | x_j) = \sum_{i=1}^n w_i x_{ji} - \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

$$\frac{\partial \mathcal{L}(x_j, y_j)}{\partial w_i} = x_{ji} - \frac{\partial}{\partial w_i} \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

$$= x_{ji} - \frac{1}{1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right)} \frac{\partial}{\partial w_i} \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

$$= x_{ji} - \frac{1}{1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right)} x_{ji} \exp \left(\sum_{i=1}^n w_i x_{ji} \right)$$

$$= x_{ji} - x_{ji} \frac{\exp \left(\sum_{i=1}^n w_i x_{ji} \right)}{1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right)}$$

deriv
of log

deriv
of exp

Logistic Regression

$$\mathcal{L}(x_j, y_j = +) = \log P(y_j = + | x_j) = \sum_{i=1}^n w_i x_{ji} - \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

$$\frac{\partial \mathcal{L}(x_j, y_j)}{\partial w_i} = x_{ji} - \frac{\partial}{\partial w_i} \log \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

$$= x_{ji} - \frac{1}{1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right)} \frac{\partial}{\partial w_i} \left(1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right) \right)$$

$$= x_{ji} - \frac{1}{1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right)} x_{ji} \exp \left(\sum_{i=1}^n w_i x_{ji} \right)$$

$$= x_{ji} - x_{ji} \frac{\exp \left(\sum_{i=1}^n w_i x_{ji} \right)}{1 + \exp \left(\sum_{i=1}^n w_i x_{ji} \right)} = x_{ji} (1 - P(y_j = + | x_j))$$

deriv
of log

deriv
of exp

Logistic Regression

- ▶ Recall that $y_j = 1$ for positive instances, $y_j = 0$ for negative instances.
- ▶ Gradient of w_i on positive example $= x_{ji}(y_j - P(y_j = + | x_j))$

Logistic Regression

- ▶ Recall that $y_j = 1$ for positive instances, $y_j = 0$ for negative instances.
- ▶ Gradient of w_i on positive example $= x_{ji}(y_j - P(y_j = + | x_j))$
 - If $P(+)$ is close to 1, make very little update
 - Otherwise make w_i look more like x_{ji} , which will increase $P(+)$

Logistic Regression

- ▶ Recall that $y_j = 1$ for positive instances, $y_j = 0$ for negative instances.
- ▶ Gradient of w_i on positive example $= x_{ji}(y_j - P(y_j = + | x_j))$
 - If $P(+)$ is close to 1, make very little update
 - Otherwise make w_i look more like x_{ji} , which will increase $P(+)$
- ▶ Gradient of w_i on negative example $= x_{ji}(-P(y_j = + | x_j))$

Logistic Regression

- ▶ Recall that $y_j = 1$ for positive instances, $y_j = 0$ for negative instances.
- ▶ Gradient of w_i on positive example $= x_{ji}(y_j - P(y_j = +|x_j))$
 - If $P(+)$ is close to 1, make very little update
 - Otherwise make w_i look more like x_{ji} , which will increase $P(+)$
- ▶ Gradient of w_i on negative example $= x_{ji}(-P(y_j = +|x_j))$
 - If $P(+)$ is close to 0, make very little update
 - Otherwise make w_i look less like x_{ji} , which will decrease $P(+)$
- ▶ Can combine these gradients as $x_j(y_j - P(y_j = 1|x_j))$

Regularization

Regularization

- ▶ Regularizing an objective can mean many things, including an L2-norm penalty to the weights:

$$\sum_{j=1}^m \mathcal{L}(x_j, y_j) - \lambda \|w\|_2^2$$

Regularization

- ▶ Regularizing an objective can mean many things, including an L2-norm penalty to the weights:

$$\sum_{j=1}^m \mathcal{L}(x_j, y_j) - \lambda \|w\|_2^2$$

- ▶ Keeping weights small can prevent overfitting

Regularization

- ▶ Regularizing an objective can mean many things, including an L2-norm penalty to the weights:

$$\sum_{j=1}^m \mathcal{L}(x_j, y_j) - \lambda \|w\|_2^2$$

- ▶ Keeping weights small can prevent overfitting
- ▶ For most of the NLP models we build, explicit regularization isn't necessary

Regularization

- ▶ Regularizing an objective can mean many things, including an L2-norm penalty to the weights:

$$\sum_{j=1}^m \mathcal{L}(x_j, y_j) - \lambda \|w\|_2^2$$

- ▶ Keeping weights small can prevent overfitting
- ▶ For most of the NLP models we build, explicit regularization isn't necessary
 - ▶ Early stopping

Regularization

- ▶ Regularizing an objective can mean many things, including an L2-norm penalty to the weights:

$$\sum_{j=1}^m \mathcal{L}(x_j, y_j) - \lambda \|w\|_2^2$$

- ▶ Keeping weights small can prevent overfitting
- ▶ For most of the NLP models we build, explicit regularization isn't necessary
 - ▶ Early stopping
 - ▶ Large numbers of sparse features are hard to overfit in a really bad way

Regularization

- ▶ Regularizing an objective can mean many things, including an L2-norm penalty to the weights:

$$\sum_{j=1}^m \mathcal{L}(x_j, y_j) - \lambda \|w\|_2^2$$

- ▶ Keeping weights small can prevent overfitting
- ▶ For most of the NLP models we build, explicit regularization isn't necessary
 - ▶ Early stopping
 - ▶ Large numbers of sparse features are hard to overfit in a really bad way
 - ▶ For neural networks: dropout and gradient clipping

Logistic Regression: Summary

► Model

$$P(y = +|x) = \frac{\exp(\sum_{i=1}^n w_i x_i)}{1 + \exp(\sum_{i=1}^n w_i x_i)}$$

Logistic Regression: Summary

► Model

$$P(y = +|x) = \frac{\exp(\sum_{i=1}^n w_i x_i)}{1 + \exp(\sum_{i=1}^n w_i x_i)}$$

► Inference

$\operatorname{argmax}_y P(y|x)$ fundamentally same as Naive Bayes

Logistic Regression: Summary

► Model

$$P(y = +|x) = \frac{\exp(\sum_{i=1}^n w_i x_i)}{1 + \exp(\sum_{i=1}^n w_i x_i)}$$

► Inference

$\operatorname{argmax}_y P(y|x)$ fundamentally same as Naive Bayes

$$P(y = 1|x) \geq 0.5 \Leftrightarrow w^\top x \geq 0$$

Logistic Regression: Summary

- ▶ Model

$$P(y = +|x) = \frac{\exp(\sum_{i=1}^n w_i x_i)}{1 + \exp(\sum_{i=1}^n w_i x_i)}$$

- ▶ Inference

$\operatorname{argmax}_y P(y|x)$ fundamentally same as Naive Bayes

$$P(y = 1|x) \geq 0.5 \Leftrightarrow w^\top x \geq 0$$

- ▶ Learning: gradient ascent on the (regularized) discriminative log-likelihood

Perceptron/SVM

Perceptron

- ▶ Simple error-driven learning approach similar to logistic regression

Perceptron

- ▶ Simple error-driven learning approach similar to logistic regression
- ▶ Decision rule: $w^\top x > 0$

Perceptron

- ▶ Simple error-driven learning approach similar to logistic regression
- ▶ Decision rule: $w^\top x > 0$
 - ▶ If incorrect: if positive, $w \leftarrow w + x$
 - if negative, $w \leftarrow w - x$

Perceptron

- ▶ Simple error-driven learning approach similar to logistic regression

- ▶ Decision rule: $w^\top x > 0$

- ▶ If incorrect: if positive, $w \leftarrow w + x$

- if negative, $w \leftarrow w - x$

Logistic Regression

$$w \leftarrow w + x(1 - P(y = 1|x))$$

$$w \leftarrow w - xP(y = 1|x)$$

Perceptron

- ▶ Simple error-driven learning approach similar to logistic regression

- ▶ Decision rule: $w^\top x > 0$

- ▶ If incorrect: if positive, $w \leftarrow w + x$

- if negative, $w \leftarrow w - x$

Logistic Regression


$$w \leftarrow w + x(1 - P(y = 1|x))$$

$$w \leftarrow w - xP(y = 1|x)$$

- ▶ Guaranteed to eventually separate the data if the data are separable


Support Vector Machines

- ▶ Many separating hyperplanes — is there a best one?



Support Vector Machines

- ▶ Many separating hyperplanes – is there a best one?



Support Vector Machines

Support Vector Machines

- ▶ Constraint formulation: find w via following quadratic program:

Support Vector Machines

- ▶ Constraint formulation: find w via following quadratic program:

Minimize $\|w\|_2^2$

Support Vector Machines

- ▶ Constraint formulation: find w via following quadratic program:

$$\text{Minimize } \|w\|_2^2$$

minimizing norm with
fixed margin \Leftrightarrow
maximizing margin

Support Vector Machines

- ▶ Constraint formulation: find w via following quadratic program:

Minimize $\|w\|_2^2$

s.t. $\forall j \quad w^\top x_j \geq 1 \text{ if } y_j = 1$

$w^\top x_j \leq -1 \text{ if } y_j = 0$

minimizing norm with
fixed margin \Leftrightarrow
maximizing margin

Support Vector Machines

- ▶ Constraint formulation: find w via following quadratic program:

Minimize $\|w\|_2^2$

s.t. $\forall j \quad w^\top x_j \geq 1 \text{ if } y_j = 1$

$w^\top x_j \leq -1 \text{ if } y_j = 0$

minimizing norm with
fixed margin \Leftrightarrow
maximizing margin

As a single constraint:

Support Vector Machines

- ▶ Constraint formulation: find w via following quadratic program:

$$\text{Minimize } \|w\|_2^2$$

$$\text{s.t. } \forall j \quad w^\top x_j \geq 1 \text{ if } y_j = 1$$

$$w^\top x_j \leq -1 \text{ if } y_j = 0$$

minimizing norm with
fixed margin \Leftrightarrow
maximizing margin

As a single constraint:

$$\forall j \quad (2y_j - 1)(w^\top x_j) \geq 1$$

Support Vector Machines

- ▶ Constraint formulation: find w via following quadratic program:

$$\text{Minimize } \|w\|_2^2$$

$$\text{s.t. } \forall j \quad w^\top x_j \geq 1 \text{ if } y_j = 1$$

$$w^\top x_j \leq -1 \text{ if } y_j = 0$$

minimizing norm with
fixed margin \Leftrightarrow
maximizing margin

As a single constraint:

$$\forall j \quad (2y_j - 1)(w^\top x_j) \geq 1$$

- ▶ Generally no solution (data is generally non-separable) – need slack!

N-Slack SVMs

N-Slack SVMs

$$\text{Minimize} \quad \lambda \|w\|_2^2 + \sum_{j=1}^m \xi_j$$

N-Slack SVMs

$$\begin{aligned} \text{Minimize} \quad & \lambda \|w\|_2^2 + \sum_{j=1}^m \xi_j \\ \text{s.t.} \quad & \forall j \quad (2y_j - 1)(w^\top x_j) \geq 1 - \xi_j \end{aligned}$$

N-Slack SVMs

$$\begin{aligned} \text{Minimize} \quad & \lambda \|w\|_2^2 + \sum_{j=1}^m \xi_j \\ \text{s.t.} \quad & \forall j \quad (2y_j - 1)(w^\top x_j) \geq 1 - \xi_j \quad \forall j \quad \xi_j \geq 0 \end{aligned}$$

N-Slack SVMs

$$\begin{aligned} \text{Minimize} \quad & \lambda \|w\|_2^2 + \sum_{j=1}^m \xi_j \\ \text{s.t.} \quad & \forall j \quad (2y_j - 1)(w^\top x_j) \geq 1 - \xi_j \quad \forall j \quad \xi_j \geq 0 \end{aligned}$$

- ▶ The ξ_j are a “fudge factor” to make all constraints satisfied

N-Slack SVMs

$$\begin{aligned} \text{Minimize} \quad & \lambda \|w\|_2^2 + \sum_{j=1}^m \xi_j \\ \text{s.t.} \quad & \forall j \quad (2y_j - 1)(w^\top x_j) \geq 1 - \xi_j \quad \forall j \quad \xi_j \geq 0 \end{aligned}$$

- ▶ The ξ_j are a “fudge factor” to make all constraints satisfied
- ▶ Take the gradient of the objective:

N-Slack SVMs

$$\begin{aligned} \text{Minimize} \quad & \lambda \|w\|_2^2 + \sum_{j=1}^m \xi_j \\ \text{s.t.} \quad & \forall j \quad (2y_j - 1)(w^\top x_j) \geq 1 - \xi_j \quad \forall j \quad \xi_j \geq 0 \end{aligned}$$

- ▶ The ξ_j are a “fudge factor” to make all constraints satisfied
- ▶ Take the gradient of the objective:

$$\frac{\partial}{\partial w_i} \xi_j = 0 \text{ if } \xi_j = 0$$

N-Slack SVMs

$$\begin{aligned} \text{Minimize} \quad & \lambda \|w\|_2^2 + \sum_{j=1}^m \xi_j \\ \text{s.t.} \quad & \forall j \quad (2y_j - 1)(w^\top x_j) \geq 1 - \xi_j \quad \forall j \quad \xi_j \geq 0 \end{aligned}$$

- ▶ The ξ_j are a “fudge factor” to make all constraints satisfied
- ▶ Take the gradient of the objective:

$$\frac{\partial}{\partial w_i} \xi_j = 0 \text{ if } \xi_j = 0 \quad \frac{\partial}{\partial w_i} \xi_j = (2y_j - 1)x_{ji} \text{ if } \xi_j > 0$$

N-Slack SVMs

$$\begin{aligned} \text{Minimize} \quad & \lambda \|w\|_2^2 + \sum_{j=1}^m \xi_j \\ \text{s.t.} \quad & \forall j \quad (2y_j - 1)(w^\top x_j) \geq 1 - \xi_j \quad \forall j \quad \xi_j \geq 0 \end{aligned}$$

- ▶ The ξ_j are a “fudge factor” to make all constraints satisfied
- ▶ Take the gradient of the objective:

$$\frac{\partial}{\partial w_i} \xi_j = 0 \text{ if } \xi_j = 0 \quad \frac{\partial}{\partial w_i} \xi_j = (2y_j - 1)x_{ji} \text{ if } \xi_j > 0$$
$$= x_{ji} \text{ if } y_j = 1, \quad -x_{ji} \text{ if } y_j = 0$$

N-Slack SVMs

$$\begin{aligned} \text{Minimize} \quad & \lambda \|w\|_2^2 + \sum_{j=1}^m \xi_j \\ \text{s.t.} \quad & \forall j \quad (2y_j - 1)(w^\top x_j) \geq 1 - \xi_j \quad \forall j \quad \xi_j \geq 0 \end{aligned}$$

- ▶ The ξ_j are a “fudge factor” to make all constraints satisfied
- ▶ Take the gradient of the objective:

$$\frac{\partial}{\partial w_i} \xi_j = 0 \text{ if } \xi_j = 0 \quad \frac{\partial}{\partial w_i} \xi_j = (2y_j - 1)x_{ji} \text{ if } \xi_j > 0$$
$$= x_{ji} \text{ if } y_j = 1, \quad -x_{ji} \text{ if } y_j = 0$$

- ▶ Looks like the perceptron! But updates more frequently

Gradients on Positive Examples

Logistic regression

$$x(1 - \text{logistic}(w^\top x))$$

Perceptron

$$x \text{ if } w^\top x < 0, \text{ else } 0$$

SVM (ignoring regularizer)

$$x \text{ if } w^\top x < 1, \text{ else } 0$$

Gradients on Positive Examples

Logistic regression


$$x(1 - \text{logistic}(w^\top x))$$

Perceptron

$$x \text{ if } w^\top x < 0, \text{ else } 0$$

SVM (ignoring regularizer)

$$x \text{ if } w^\top x < 1, \text{ else } 0$$



Gradients on Positive Examples

Logistic regression


$$x(1 - \text{logistic}(w^\top x))$$

Perceptron

$$x \text{ if } w^\top x < 0, \text{ else } 0$$

SVM (ignoring regularizer)

$$x \text{ if } w^\top x < 1, \text{ else } 0$$



Gradients on Positive Examples

Logistic regression


$$x(1 - \text{logistic}(w^\top x))$$

Perceptron

$$x \text{ if } w^\top x < 0, \text{ else } 0$$

SVM (ignoring regularizer)

$$x \text{ if } w^\top x < 1, \text{ else } 0$$



Gradients on Positive Examples

Logistic regression


$$x(1 - \text{logistic}(w^\top x))$$

Perceptron

$$x \text{ if } w^\top x < 0, \text{ else } 0$$

SVM (ignoring regularizer)

$$x \text{ if } w^\top x < 1, \text{ else } 0$$



Gradients on Positive Examples

Logistic regression


$$x(1 - \text{logistic}(w^\top x))$$

Perceptron

$$x \text{ if } w^\top x < 0, \text{ else } 0$$

SVM (ignoring regularizer)

$$x \text{ if } w^\top x < 1, \text{ else } 0$$



Gradients on Positive Examples

Logistic regression


$$x(1 - \text{logistic}(w^\top x))$$

Perceptron

$$x \text{ if } w^\top x < 0, \text{ else } 0$$

SVM (ignoring regularizer)

$$x \text{ if } w^\top x < 1, \text{ else } 0$$



*gradients are for maximizing things,
which is why they are flipped

Comparing Gradient Updates (Reference)

Logistic regression (unregularized)

$$x(y - P(y = 1|x)) = x(y - \text{logistic}(w^\top x))$$

$y = 1$ for pos,

0 for neg

Perceptron

$$(2y - 1)x \text{ if classified incorrectly}$$

0 else

SVM

$$(2y - 1)x \text{ if not classified correctly with margin of 1}$$

0 else

Optimization — next time...

- ▶ Range of techniques from simple gradient descent (works pretty well) to more complex methods (can work better)
- ▶ Most methods boil down to: take a gradient and a step size, apply the gradient update times step size, incorporate estimated curvature information to make the update more effective

Sentiment Analysis

this movie was great! would watch again

+

Sentiment Analysis

this movie was great! would watch again

+

the movie was gross and overwrought, but I liked it

+

this movie was not really very enjoyable

-

Sentiment Analysis

this movie was great! would watch again +

the movie was gross and overwrought, but I liked it +

this movie was not really very enjoyable —

- ▶ Bag-of-words doesn't seem sufficient (discourse structure, negation)

Sentiment Analysis

this movie was great! would watch again +

the movie was gross and overwrought, but I liked it +

this movie was not really very enjoyable -

- ▶ Bag-of-words doesn't seem sufficient (discourse structure, negation)
- ▶ There are some ways around this: extract bigram feature for “*not X*” for all X following the *not*

Sentiment Analysis

Sentiment Analysis

	Features	# of features	frequency or presence?	NB	ME	SVM
(1)	unigrams	16165	freq.	78.7	N/A	72.8
(2)	unigrams	"	pres.	81.0	80.4	82.9
(3)	unigrams+bigrams	32330	pres.	80.6	80.8	82.7
(4)	bigrams	16165	pres.	77.3	77.4	77.1
(5)	unigrams+POS	16695	pres.	81.5	80.4	81.9
(6)	adjectives	2633	pres.	77.0	77.7	75.1
(7)	top 2633 unigrams	2633	pres.	80.3	81.0	81.4
(8)	unigrams+position	22430	pres.	81.0	80.1	81.6

Sentiment Analysis

	Features	# of features	frequency or presence?	NB	ME	SVM
(1)	unigrams	16165	freq.	78.7	N/A	72.8
(2)	unigrams	"	pres.	81.0	80.4	82.9
(3)	unigrams+bigrams	32330	pres.	80.6	80.8	82.7
(4)	bigrams	16165	pres.	77.3	77.4	77.1
(5)	unigrams+POS	16695	pres.	81.5	80.4	81.9
(6)	adjectives	2633	pres.	77.0	77.7	75.1
(7)	top 2633 unigrams	2633	pres.	80.3	81.0	81.4
(8)	unigrams+position	22430	pres.	81.0	80.1	81.6

- ▶ Simple feature sets can do pretty well!

Sentiment Analysis

Sentiment Analysis

Method	RT-s	MPQA
MNB-uni	77.9	85.3
MNB-bi	79.0	86.3
SVM-uni	76.2	86.1
SVM-bi	77.7	<u>86.7</u>
NBSVM-uni	78.1	85.3
NBSVM-bi	<u>79.4</u>	86.3
RAE	76.8	85.7
RAE-pretrain	77.7	86.4
Voting-w/Rev.	63.1	81.7
Rule	62.9	81.8
BoF-noDic.	75.7	81.8
BoF-w/Rev.	76.4	84.1
Tree-CRF	77.3	86.1
BoWSVM	—	—

Sentiment Analysis

Method	RT-s	MPQA
MNB-uni	77.9	85.3
MNB-bi	79.0	86.3
SVM-uni	76.2	86.1
SVM-bi	77.7	<u>86.7</u>
NBSVM-uni	78.1	85.3
NBSVM-bi	<u>79.4</u>	86.3
RAE	76.8	85.7
RAE-pretrain	77.7	86.4
Voting-w/Rev.	63.1	81.7
Rule	62.9	81.8
BoF-noDic.	75.7	81.8
BoF-w/Rev.	76.4	84.1
Tree-CRF	77.3	86.1
BoWSVM	—	—

← Naive Bayes is doing well!

Sentiment Analysis

Method	RT-s	MPQA
MNB-uni	77.9	85.3
MNB-bi	79.0	86.3
SVM-uni	76.2	86.1
SVM-bi	77.7	<u>86.7</u>
NBSVM-uni	78.1	85.3
NBSVM-bi	<u>79.4</u>	86.3
RAE	76.8	85.7
RAE-pretrain	77.7	86.4
Voting-w/Rev.	63.1	81.7
Rule	62.9	81.8
BoF-noDic.	75.7	81.8
BoF-w/Rev.	76.4	84.1
Tree-CRF	77.3	86.1
BoWSVM	—	—

← Naive Bayes is doing well!

Ng and Jordan (2002) — NB
can be better for small data

Sentiment Analysis

Method	RT-s	MPQA
MNB-uni	77.9	85.3
MNB-bi	79.0	86.3
SVM-uni	76.2	86.1
SVM-bi	77.7	<u>86.7</u>
NBSVM-uni	78.1	85.3
NBSVM-bi	<u>79.4</u>	86.3
RAE	76.8	85.7
RAE-pretrain	77.7	86.4
Voting-w/Rev.	63.1	81.7
Rule	62.9	81.8
BoF-noDic.	75.7	81.8
BoF-w/Rev.	76.4	84.1
Tree-CRF	77.3	86.1
BoWSVM	—	—

← Naive Bayes is doing well!

Ng and Jordan (2002) — NB
can be better for small data

Before neural nets had taken off
— results weren't that great

Sentiment Analysis

Method	RT-s	MPQA
MNB-uni	77.9	85.3
MNB-bi	79.0	86.3
SVM-uni	76.2	86.1
SVM-bi	77.7	<u>86.7</u>
NBSVM-uni	78.1	85.3
NBSVM-bi	<u>79.4</u>	86.3
RAE	76.8	85.7
RAE-pretrain	77.7	86.4
Voting-w/Rev.	63.1	81.7
Rule	62.9	81.8
BoF-noDic.	75.7	81.8
BoF-w/Rev.	76.4	84.1
Tree-CRF	77.3	86.1
BoWSVM	—	—
Kim (2014) CNNs	81.5	89.5

← Naive Bayes is doing well!

Ng and Jordan (2002) — NB
can be better for small data

Before neural nets had taken off
— results weren't that great

Wang and Manning (2012)

Recap

Recap

► Logistic regression: $P(y = 1|x) = \frac{\exp(\sum_{i=1}^n w_i x_i)}{(1 + \exp(\sum_{i=1}^n w_i x_i))}$

Decision rule: $P(y = 1|x) \geq 0.5 \Leftrightarrow w^\top x \geq 0$

Gradient (unregularized): $x(y - P(y = 1|x))$

Recap

► Logistic regression: $P(y = 1|x) = \frac{\exp(\sum_{i=1}^n w_i x_i)}{(1 + \exp(\sum_{i=1}^n w_i x_i))}$

Decision rule: $P(y = 1|x) \geq 0.5 \Leftrightarrow w^\top x \geq 0$

Gradient (unregularized): $x(y - P(y = 1|x))$

► SVM:

Decision rule: $w^\top x \geq 0$

(Sub)gradient (unregularized): 0 if correct with margin of 1, else $x(2y - 1)$

Recap

Recap

- ▶ Logistic regression, SVM, and perceptron are closely related

Recap

- ▶ Logistic regression, SVM, and perceptron are closely related
- ▶ SVM and perceptron inference require taking maxes, logistic regression has a similar update but is “softer” due to its probabilistic nature

Recap

- ▶ Logistic regression, SVM, and perceptron are closely related
- ▶ SVM and perceptron inference require taking maxes, logistic regression has a similar update but is “softer” due to its probabilistic nature
- ▶ All gradient updates: “make it look more like the right thing and less like the wrong thing”