Classical detector clicks: thresholds, shared release and coincidence bounds

Independently prepared receivers with monotone responses to **fixed fractions of one common scalar pulse energy**, counted on the same full gate ensemble, obey $p_{12} \geq p_1 p_2$. This is the strongest exclusion below: saturation, unequal efficiencies and independent dark triggers preserve it. A passive barrier supplies discrete crossings but no universal threshold; a shared release supplies exclusive fringe-weighted records by changing the independence premise. Neither the exclusion nor these classical constructions selects physical $\hbar$ or reconstructs quantum states and instruments.

The proofs concern declared receiver models. They are written derivations with internal consistency checks, not independent peer review or experimental validation. The coincidence witness has established optical precedent; no literature novelty is claimed.

Independent monotone receivers

Preparation and all-gate probabilities

Fix a gate duration $T > 0$, settings and pulse shape. A random energy $E \geq 0$ reaches a passive splitter whose outputs are aE, bE, for fixed dimensionless $a, b > 0$, $a + b \leq 1$. A two-path interference output fits this model only when its fractions are fixed across the ensemble. Let $X, Y \in \{0, 1\}$ indicate at least one record in the gate. Assume measurable nondecreasing responses

$$f(E) = F_T(aE), \qquad g(E) = G_T(bE), \qquad 0 \leq f, g \leq 1,$$

and conditional factorization

$$\Pr(X = 1, Y = 1 \mid E) = f(E)g(E).$$

Independent local apparatus variables U, V, jointly independent of E, with $X = x(aE, U)$, $Y = y(bE, V)$ and monotone averaged responses suffice. Spatial separation alone does not give factorization: common readiness, reset memory or an unrecorded pulse shape can invalidate it. Independence between successive gates is unnecessary for the inequality, although relevant to finite-data error estimates.

All admitted gates, including empty gates and doubles, enter $p_1 = \mathbb{E}X$, $p_2 = \mathbb{E}Y$, $p_{12} = \mathbb{E}(XY)$. These are gate probabilities, not mean counts from a repeatedly firing receiver.

Covariance bound and sharp efficiency cost

For an independent copy E' of E, conditional factorization gives

$$p_{12} - p_1 p_2 = \frac{1}{2}\mathbb{E}[(f(E) - f(E'))(g(E) - g(E'))] \geq 0.$$

Monotonicity supplies the sign; boundedness removes any moment assumption on E. Equality holds exactly when the nonnegative product vanishes almost surely. Constant E gives equality; two strictly increasing responses on a nondegenerate energy law give strict inequality. Saturation can restore equality. For positive singles, $A = p_{12}/(p_1 p_2) \geq 1$; at zero singles use the covariance inequality, since A is undefined.

For example, $F_T(e) = 1 - e^{-\kappa_1 T e}$ and $G_T(e) = 1 - e^{-\kappa_2 T e}$, with κ_i in $(\text{energy}\,\text{time})^{-1}$, obey the bound without a weak-pulse approximation. Independent dark probabilities d_i replace these by $1 - (1 - d_i)e^{-\kappa_i T e}$ and preserve it. At fixed $E_0 > 0$ the two records are independent. Attenuation $E_0 \mapsto \eta^2 E_0$ sends no-dark singles and doubles to zero, while $A = 1$ for every $\eta > 0$.

In particular, $p_1, p_2 \geq s > 0$ requires $p_{12} \geq s^2$. More precisely, put $q = p_1 + p_2 - p_{12}$, $d = p_{12}$, $r = p_1/(p_1 + p_2) \in (0, 1)$ and $c_r = r(1 - r)$. Since $p_1 + p_2 = q + d$,

$$d \geq c_r(q + d)^2, \qquad d \geq \frac{1 - 2c_r q - \sqrt{1 - 4c_r q}}{2c_r}.$$

The second expression is the lower root of the first quadratic. It is sharp: constant independent responses $p_1 = rS$, $p_2 = (1-r)S$, with $S = (1 - \sqrt{1 - 4c_r q})/(2c_r)$, attain it. For $0 < q \leq 1$, $0 < S \leq 1/\max(r, 1 - r)$, so both responses are admissible. At $q = 0$ one simply has $d = 0$ and balance is undefined unless specified as a limit. Balanced channels satisfy

$$d \geq (1 - \sqrt{1 - q})^2.$$

Thus efficient balanced events require frequent doubles in this class. The trade-off is dimensionless and contains no energy gap or action observable.

How the independence inference fails

Fluctuating routing. At fixed $E_0 > 0$, route all energy to output 1 with probability r and to output 2 otherwise. Independent deterministic detectors with threshold $0 < \theta < E_0$ give $(p_1, p_2, p_{12}) = (r, 1 - r, 0)$. Their local responses remain monotone, but the inputs are no longer fixed fractions of the common scalar. Conditioning on the full routed input makes outputs deterministic and factorized. Mixing opposite bright/dark settings of a two-path network has the same issue. This is no model of a fixed-split single-photon experiment.

Correlated readiness. Keep both signals fixed above threshold and prepare $U = J, V = 1 - J$, where $\Pr(J = 1) = r$ and J is independent of the source. Let $X = U, Y = V$. The same exclusive singles occur without communication during the gate. Source independence and monotone local responses do not exclude this anticorrelated apparatus preparation.

Outcome-selected gates. Start with independent Bernoulli records of probability $p \in (0, 1)$ and retain only gates containing a record. Then

$$p_1' = p_2' = \frac{1}{2 - p}, \qquad p_{12}' = \frac{p}{2 - p}, \qquad A' = p(2 - p) < 1.$$

Selecting exactly one record makes the apparent double probability zero. The unselected A was one. A source-side herald is compatible with the theorem if monotonicity and factorization still hold within its ensemble. Correlation with E alone merely changes the energy law; selection of readiness requires a new check. Settings with different routing fractions must be tested separately.

A deficit of coincidences therefore refutes this joint premise package; it does not identify uniquely which premise failed. The CHSH treatment tests a different package: arbitrary shared readiness is allowed, but settings are independent and every gate has conditionally local outcomes. Its proof and supplied singlet comparison are retained separately because scalar monotonicity and independent preparation are absent there.

Passive thresholds and stored readiness

Complementary work outputs and the event regions

The mechanical interference calculation gives finite-pulse works

$$W_\pm = \frac{E}{2}(1 \pm z), \qquad -1 \leq z \leq 1,$$

where z is normalized overlap (a phase cosine for ideal coherent paths). A lossless accumulator starts at zero, $\dot{e}_i = P_i(t) \geq 0$, and a stipulated end-of-gate comparator records $C_i = \mathbf{1}_{W_i > \Delta}$,

$\Delta > 0$. It gives at most one event per gate; it supplies neither a permanent memory nor rearming dynamics. For $E > 0$,

$$C_+ = 1 \iff z > 2\Delta/E - 1, \qquad C_- = 1 \iff z < 1 - 2\Delta/E.$$

If $E \le \Delta$ nothing fires. For $\Delta < E < 2\Delta$, doubles are impossible but only $|z| > 2\Delta/E - 1$ gives a record. If $E > 2\Delta$, every overlap gives a record and $|z| < 1 - 2\Delta/E$ gives two. At $E = 2\Delta$ exactly one fires except at $z = 0$, where neither does; a non-strict comparator instead gives two at that point. No open energy range has exclusive, unit-efficiency events for every overlap. At balanced equal inputs, identical deterministic receiver states force identical records by exchange symmetry.

Random thresholds, asymmetric preparations or communication change these premises. Counts depend on the sampling law of z as well as the comparator; W_i/E is not automatically a Born probability. Removing misses or doubles changes the ensemble. Varying z here also changes routing, so the fixed-fraction theorem applies to each fixed overlap, not automatically to their mixture.

A conservative quartic barrier and reset accounting

A receiver with coordinate q, momentum p, mass M and potential

$$H_R = \frac{p^2}{2M} + U(q), \qquad U(q) = \Delta(1 - q^2/\ell^2)^2, \qquad M, \ell, \Delta > 0$$

has minima at $\pm\ell$ and a saddle of height Δ at zero. Start at $(-\ell, 0)$ and supply a positive impulse I. The deposited energy is $W = I^2/(2M)$, and the subsequent trajectory crosses zero precisely for $W > \Delta$. Equality approaches the saddle only asymptotically: near zero, $\dot{q} \simeq \sqrt{4\Delta/(M\ell^2)}|q|$, so travel time diverges logarithmically. A finite deadline supplies another receiver parameter. General forcing cannot be replaced by total work without checking direction and timing. Conservative crossing can later recross; a latch or capture needs additional dynamics and energy accounting.

Prepare instead $(q_0, 0)$, $-\ell < q_0 < 0$, with stored energy $e_0 = U(q_0)$. A positive impulse at this state crosses when $W > \Delta - e_0$. As $q_0 \uparrow 0$, the required signal tends to zero with M, ℓ, Δ fixed. This is readiness near an unstable state, supplied by preparation energy.

If a cycle captures the receiver at the right minimum at rest, restoring the ready state requires net work at least e_0 when the reset apparatus supplies all work and losses are nonnegative. Capture must account for $e_0 + W$. Recovering energy into another store can reduce external work only by including that store in the balance; full return of all stores leaves exported work and dissipation as the net supplied energy. No universal reset number follows. For a narrow-band pulse, E/ω is approximately its wave action; the threshold scales Δ/ω and $(\Delta - e_0)/\omega$ depend on frequency and readiness. Barrier energy times crossing time is another apparatus scale, with a separatrix divergence rather than a selected constant.

Exclusive shared release and causal timing

One release permission with supplied hazards

Store the two inputs $e_\pm = E(1 \pm z)/2$, $E > 0$. A ready state R has absorbing exits $C_\pm$ with rates $r_\pm = \alpha e_\pm$, where $\alpha > 0$ has units (energy time)$^{-1}$. The first exit consumes the only permission to release. This is an effective autonomous Markov receiver after preparation, not a microscopic Hamiltonian derivation. A central reservoir can lower its energy by $\Delta > 0$ on either exit, delivering that energy to the chosen output plus heat. The stored signal acts as a kinetic control and need not be the emitted energy. Reset replaces Δ or retrieves it from an included

store. Energy conservation permits this accounting but does not itself enforce the single-use state graph or linear rate law.

With $\Gamma = \alpha E$, integration of the exit flux gives

$$p_R(t) = e^{-\Gamma t}, \qquad p_\pm(t) = \frac{e_\pm}{E}(1 - e^{-\Gamma t}).$$

Doubles are impossible. Conditional on an event by any $t > 0$, or after indefinite waiting, the probabilities are $e_\pm/E = (1 \pm z)/2$. Prescribed hazards $\alpha_p e_\pm^p$, $p > 0$, would instead give $e_\pm^p/(e_+^p + e_-^p)$; exclusivity does not select linearity or quantum state structure.

Attenuating displacement by η scales energy by η^2. The conditional weights stay fixed, but efficiency by a fixed T becomes $1 - e^{-\alpha\eta^2 ET} \to 0$. Error tolerance $0 < \varepsilon < 1$ requires

$$E \geq \frac{\log(1/\varepsilon)}{\alpha T}, \qquad \frac{E}{\omega} \gtrsim \frac{\log(1/\varepsilon)}{\alpha T \omega}$$

for the narrow-band wave-action convention. At zero energy no event occurs; zero-signal and indefinite-wait limits do not commute.

Local firing followed by delayed inhibition

A co-located arbiter can access both inputs before release and send its output to a remote record after travel. It is not instantaneous inhibition between independently firing distant detectors. To model the latter, start independent Poisson clocks r_+, r_-; each site fires at most once and the first inhibits the other after delay $\delta > 0$. Memorylessness gives the eventual double-event probability

$$P_2 = \frac{r_+}{\Gamma}(1 - e^{-r_-\delta}) + \frac{r_-}{\Gamma}(1 - e^{-r_+\delta}).$$

It is positive when both rates are positive. In this architecture, separation d and inhibition speed at most c imply $\delta \geq d/c$. Balanced rates give $P_2 = 1 - e^{-\Gamma\delta/2}$. A first-event deadline T, no-first-event tolerance ε_0 and double tolerance ε_2 are compatible only if

$$\frac{\log(1/\varepsilon_0)}{T} \leq \Gamma \leq \frac{-2\log(1 - \varepsilon_2)}{\delta}.$$

Doubles here are counted through the entire inhibition window, including its part after T. Gate censoring changes the criterion. Central arbitration, prior correlated readiness or a different propagation law changes a premise; this timing bound is not a theorem about every classical receiver.

Source evidence

Grangier, Roger and Aspect, *EPL* **1**, 173–179 (1986), primary paper, DOI, supplies the established optical coincidence precedent. Extracted passages on pp. 174–175 describe gate-normalized probabilities and a semiclassical coincidence-product lower bound. Formula extraction was incomplete; exact source equations, experimental data and a full detector audit are not claimed. The monotone Bernoulli proof, sharp trade-off and countermodels above are derived under their displayed premises, not attributed as extensions proved in that paper.

Gillespie, *J. Phys. Chem.* **81**, 2340–2361 (1977), DOI, was checked at publisher-metadata level as the standard competing-hazard lead. The exponential survival and delay formulas here are direct calculations, not an imported microscopic receiver model. The B67 companion supplies the recorded operational-premise comparison. No exhaustive priority search or independent proof acceptance is implied.

Consequence for STATE

Clicks, exclusive fringe weights and a fixed-split coincidence exclusion have different premises. The retained passive-barrier and shared-release countermodels locate those differences explicitly. Further receiver tuning remains parked; any reliable-record floor needs a separately justified stability, retention and error law, and any identification with physical $\hbar$ needs dynamics and calibration beyond dimensionless event statistics. The independent-setting CHSH question retains its separate proof and supplied quantum comparison.