

Status	Finished
Started	Monday, 3 November 2025, 9:27 PM
Completed	Monday, 3 November 2025, 10:11 PM
Duration	44 mins 29 secs

Question **1**

Correct

The k-digit number N is an Armstrong number if and only if the k-th power of each digit sums to N.

Given a positive integer N, return true if and only if it is an Armstrong number.

Example 1:

Input:

153

Output:

true

Explanation:

153 is a 3-digit number, and $153 = 1^3 + 5^3 + 3^3$.

Example 2:

Input:

123

Output:

false

Explanation:

123 is a 3-digit number, and $123 \neq 1^3 + 2^3 + 3^3 = 36$.

Example 3:

Input:

1634

Output:

true

Note:

$1 \leq N \leq 10^8$

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 #include <math.h>
3 int main()
4 {
5     int n,sum=0,r,temp,d=0;
6     scanf("%d",&n);
7     temp=n;
8     while(temp!=0)
9     {
10         temp/=10;
11         d++;
12     }
13     temp=n;
14     while(temp!=0)
15     {
16         r=temp%10;
17         sum+=pow(r,d);
18         temp/=10;
19     }
20     if(sum==n)
21         printf("true");
22     else
23         printf("false");
24     return 0;
25 }
```



	Input	Expected	Got	
✓	153	true	true	✓
✓	123	false	false	✓

Passed all tests! ✓

Question **2**

Correct

Take a number, reverse it and add it to the original number until the obtained number is a palindrome.

Constraints $1 \leq \text{num} \leq 999999999$ **Sample Input 1**

32

Sample Output 1

55

For example:

Input	Result
32	55
1234	5555

Answer: (penalty regime: 0 %)

```
1  #include <stdio.h>
2  long reverse(long n)
3  {
4      long r=0;
5      while(n!=0)
6      {
7          r=r*10+n%10;
8          n/=10;
9      }
10     return r;
11 }
12 int isPalindrome(long n)
13 {
14     return n==reverse(n);
15 }
16 int main()
17 {
18     long n;
19     scanf("%ld",&n);
20     while(!isPalindrome(n))
21     {
22         n=n+reverse(n);
23     }
24     printf("%ld",n);
```

```
25 | return 0;  
26 | }
```



	Input	Expected	Got	
✓	32	55	55	✓
✓	1234	5555	5555	✓

Passed all tests! ✓



Question **3**

Correct

Maya, a student in an arts and crafts class, wants to create a pattern using stars (*) in a specific format. She plans to use a program to help her construct the pattern.

Write a program that takes an integer as input and constructs the following pattern using nested for loops.

Input: 5

Output:

```
*
* *
* * *
* * * *
* * * * *
* * * *
* * *
* *
*
```

Answer: (penalty regime: 0 %)

```
1  #include <stdio.h>
2  int main()
3  {
4      int n,i,j;
5      scanf("%d",&n);
6      for(i=1;i<=n;i++)
7      {
8          for(j=1;j<=i;j++)
9          {
10             printf("* ");
11          }
12          printf("\n");
13      }
14      for(i=n-1;i>=1;i--)
15      {
16          for(j=1;j<=i;j++)
17          {
18             printf("* ");
19          }
20          printf("\n");
21      }
22      return 0;
23 }
```



	Input	Expected	Got	
✓	5	<pre>* *</pre>	<pre>* *</pre>	✓

Passed all tests! ✓